Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Issue date: 12/3/2024



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : ALMOND & MARZIPAN CC-13091

UFI : WKT4-R272-200J-V3PM

Product code : CC-13091

Type of product : Perfumes, fragrances
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use

Industrial/Professional use spec : Industrial

For professional use only : Perfumes, fragrances

Use of the substance/mixture : Perfumes, frag Function or use category : Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Candle Craft Weiherwiese 10 65510 Idstein - Germany T 49-6126-9363 -0

info@candlecraft.de - www.candlecraft.de

1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China: +400-120-0751; Mexico: +01-800-099-0731;

Brazil: +0-800-591-6042; India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1 H317 Hazardous to the aquatic environment – Chronic Hazard, H412

Category 3

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP) : Warning

Contains : Aldehyde C-16; Eugenol; benzyl alcohol

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP) : H317 - May cause an allergic skin reaction.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P321 - Specific treatment (see supplemental first aid instruction on this label).

: For professional users only.

2.3. Other hazards

Extra phrases

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzaldehyde substance with national workplace exposure limit(s) (BG, FI, HU, LT, LV, PL)	CAS-No.: 100-52-7 EC-No.: 202-860-4 EC Index-No.: 605-012-00-5 REACH-no: 01-2119455540-	18 – 36	Acute Tox. 4 (Oral), H302
Resin acids and Rosin acids, hydrogenated, methyl esters	CAS-No.: 8050-15-5 EC-No.: 232-476-2	9.6 – 19.1	Aquatic Chronic 3, H412
Aldehyde C-16	CAS-No.: 77-83-8 EC-No.: 201-061-8 REACH-no: 01-2119967770- 28	2.6 – 5.2	Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Eugenol	CAS-No.: 97-53-0 EC-No.: 202-589-1 REACH-no: 01-2119971802- 33	1.3 – 2.5	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Ethyl vanillin	CAS-No.: 121-32-4 EC-No.: 204-464-7 REACH-no: 01-211958961-24	1 – 2	Eye Irrit. 2, H319
acetophenone substance with national workplace exposure limit(s) (BE, BG, DK, ES, FI, HU, IE, LT, LV, PL, PT, RO)	CAS-No.: 98-86-2 EC-No.: 202-708-7 EC Index-No.: 606-042-00-1 REACH-no: 01-2119533169- 37	0.8 – 1.6	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319
Allyl caproate	CAS-No.: 123-68-2 EC-No.: 204-642-4 REACH-no: 01-2119983573- 26	0.7 – 1.35	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Aquatic Acute 1, H400 Aquatic Chronic 3, H412

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-	0.5 – 1	Flam. Liq. 1, H224 Eye Irrit. 2, H319 STOT SE 3, H336
benzyl alcohol substance with national workplace exposure limit(s) (BG, CZ, DE, FI, LT, LV, PL, SI, CH)	CAS-No.: 100-51-6 EC-No.: 202-859-9 EC Index-No.: 603-057-00-5 REACH-no: 01-2119492630- 38	0.2 – 0.3	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
isobutyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR)	CAS-No.: 110-19-0 EC-No.: 203-745-1 EC Index-No.: 607-026-00-7	0.1 – 0.25	Flam. Liq. 2, H225 STOT SE 3, H336

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

First-aid measures after inhalation

First-aid measures after eye contact

First-aid measures after ingestion

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

: Remove person to fresh air and keep comfortable for breathing. Allow affected person to

breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all ex

: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash with plenty of water/.... Get medical advice/attention. Wash contaminated clothing before reuse. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.

: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.3. Advice for firefighters

Firefighting instructions

: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting

: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures

: Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures

: Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information

: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing dust/fume/gas/mist/vapours/spray. No open flames. No smoking. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures

: Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep only in the original container in a cool, well ventilated place away from : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Keep in fireproof place. Store in a well-ventilated place. Keep cool.

Incompatible products

: Strong bases. Strong acids.

Incompatible materials

: Sources of ignition. Direct sunlight. Heat sources.

Storage temperature

: 25 °C

Storage area

: Store in a well-ventilated place. Store away from heat.

Special rules on packaging Packaging materials

Store in a closed container.Do not store in corrodable metal.

Germany

Storage class (LGK, TRGS 510) : LGK 10 - Combustible liquids

12/3/2024 (Issue date) EN (English) 4/24

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Joint storage table : LCK 1

GK 1 LGK 2A LGK 2B LGK 3 LGK 4.1A LGK 4.2 LGK 5.1B LGK 4.1B LGK 4.3 LGK 5.1A LGK 5.1C LGK 5.2 LGK 6.1A LGK 6.1B LGK 6.1C LGK 6.1D LGK 6.2 LGK 7 LGK 8A LGK 8B LGK 12 LGK 10 LGK 11 LGK 13 LGK 10-13

Joint storage not permitted for : LGK 1, LGK 2A, LGK 5.1A, LGK 6.2, LGK 7

Joint storage with restrictions permitted for : LGK 4.1A, LGK 4.2, LGK 4.3, LGK 5.1B, LGK 5.1C, LGK 5.2

 $: \mathsf{LGK}\,\mathsf{2B}, \mathsf{LGK}\,\mathsf{3}, \mathsf{LGK}\,\mathsf{4.1B}, \mathsf{LGK}\,\mathsf{6.1A}, \mathsf{LGK}\,\mathsf{6.1B}, \mathsf{LGK}\,\mathsf{6.1C}, \mathsf{LGK}\,\mathsf{6.1D}, \mathsf{LGK}\,\mathsf{8A}, \mathsf{LGK}\,\mathsf{8B},$

LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13

Switzerland

Storage class (LK) : LK 10/12 - Liquids

7.3. Specific end use(s)

Joint storage permitted for

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

benzaldehyde (100-52-7)		
Bulgaria - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	4.4 mg/m³	
	1 ppm	
HTP (OEL C)	17.4 mg/m³	
	4 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³	
CK (OEL STEL)	10 mg/m³	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	10 mg/m³	
NDSCh (OEL STEL)	40 mg/m³	
isobutyl acetate (110-19-0)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	241 mg/m³ (Butyl acetates)	
	50 ppm (Butyl acetates)	
MAK (OEL STEL)	480 mg/m³ (Butyl acetate)	
	100 ppm (Butyl acetate)	

Safety Data Sheet

isobutyl acetate (110-19-0)		
Belgium - Occupational Exposure Limits		
OEL TWA	238 mg/m³	
	50 ppm	
OEL STEL	712 mg/m³	
	150 ppm	
Bulgaria - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
	50 ppm	
OEL STEL	723 mg/m³	
	150 ppm	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA)	241 mg/m³	
,	50 ppm	
KGVI (OEL STEL)	723 mg/m³	
Novi (GLZ GTZZ)	150 ppm	
Cyprus - Occupational Exposure Limits	Тоо ррш	
OEL TWA	241 mg/m³	
OLL TWA		
OFL OTFL	50 ppm	
OEL STEL	723 mg/m³	
	150 ppm	
Czech Republic - Occupational Exposure Limits	T	
PEL (OEL TWA)	241 mg/m³	
Denmark - Occupational Exposure Limits		
OEL TWA	241 mg/m³ (Butyl acetate, all isomers)	
	50 ppm (Butyl acetate, all isomers)	
OEL STEL	723 mg/m³	
	150 ppm	
Estonia - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
	50 ppm	
OEL STEL	723 mg/m³	
	150 ppm	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	240 mg/m³ (Butyl acetate)	
	50 ppm (Butyl acetate)	
HTP (OEL STEL)	725 mg/m³ (Butyl acetate)	
	150 ppm (Butyl acetate)	
France - Occupational Exposure Limits		
VME (OEL TWA)	241 mg/m³ (restrictive limit)	

Safety Data Sheet

VLE (OEL C/STEL) 723 m 150 p 150 p Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) 300 m BGW 62 pp value 62 pp Greece - Occupational Exposure Limits OEL TWA 241 m 50 pp	ng/m³
150 pp	opm (restrictive limit) Ing/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and values are observed) Ing/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW as are observed) Ing/m³ Ing/m³
Germany - Occupational Exposure Limits (TRGS 900) 300 n BGW 62 pp value	ng/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and values are observed) om (the risk of damage to the embryo or fetus can be excluded when AGW and BGW as are observed) om om om om om om
AGW (OEL TWA) 300 n BGW 62 pp value Greece - Occupational Exposure Limits OEL TWA 241 n 50 pp OEL STEL 723 n 150 p	my (the risk of damage to the embryo or fetus can be excluded when AGW and BGW as are observed) mg/m³ mg/m³
BGW 62 pp value	my (the risk of damage to the embryo or fetus can be excluded when AGW and BGW as are observed) mg/m³ mg/m³
value Greece - Occupational Exposure Limits OEL TWA 241 n 50 pp 50 pp OEL STEL 723 n 150 p 150 p	ng/m³
OEL TWA 241 n 50 pp OEL STEL 723 n 150 p	om ng/m³
DEL STEL 723 n 150 p	om ng/m³
OEL STEL 723 n 150 p	ng/m³
150 p	
	ррт
Hungary Occupational Exposure Limits	
Hungary - Occupational Exposure Limits	
AK (OEL TWA) 241 n	ng/m³
CK (OEL STEL) 723 n	ng/m³
OEL chemical category Sensi	itizer
Ireland - Occupational Exposure Limits	
OEL TWA 241 n	ng/m³
50 pp	om
OEL STEL 723 m	ng/m³ (calculated)
150 p	ppm (calculated)
Italy - Occupational Exposure Limits	
OEL TWA 241 n	ng/m³
50 pp	om
OEL STEL 723 n	ng/m³
150 p	ppm
Latvia - Occupational Exposure Limits	
OEL TWA 241 n	ng/m³
50 pp	om
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA) 241 n	ng/m³
50 pp	om
TPRV (OEL STEL) 723 n	ng/m³
150 p	ppm
Luxembourg - Occupational Exposure Limits	
OEL TWA 241 n	ng/m³
50 pp	om
OEL STEL 723 n	ng/m³
150 p	ppm

Safety Data Sheet

isobutyl acetate (110-19-0)		
Malta - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
	50 ppm	
OEL STEL	723 mg/m³	
	150 ppm	
Netherlands - Occupational Exposure Limits		
TGG-8u (OEL TWA)	241 mg/m³	
	50 ppm	
TGG-15min (OEL STEL)	723 mg/m³	
	150 ppm	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	240 mg/m³	
NDSCh (OEL STEL)	720 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	241 mg/m³ (indicative limit value)	
	50 ppm (indicative limit value)	
OEL STEL	723 mg/m³ (indicative limit value)	
	150 ppm (indicative limit value)	
Romania - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
	50 ppm	
OEL STEL	723 mg/m³	
	150 ppm	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA)	241 mg/m³	
	50 ppm	
NPHV (OEL C)	723 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
	50 ppm	
OEL STEL	723 mg/m³	
	150 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	241 mg/m³	
	50 ppm	
VLA-EC (OEL STEL)	723 mg/m³	
	150 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	241 mg/m³ (Butyl acetates)	

Safety Data Sheet

Mary Column Mary Colu	isobutyl acetate (110-19-0)			
United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) 724 mg/m² 150 ppm 724 mg/m² 150 ppm 150 ppm WEL STEL (OEL STEL) 993 mg/m² 187 ppm 187 ppm Norway - Occupational Exposure Limits 241 mg/m³ Kortidsverdi (OEL STEL) 223 mg/m² (value from the regulation) 150 ppm 150 ppm (value from the regulation) 150 ppm 150 ppm KZGW (OEL STEL) 720 mg/m³ 150 ppm 150 ppm KZGW (OEL STEL) 720 mg/m³ 150 ppm 150 ppm KZGW (OEL STEL) 150 ppm (Bulyl acetates, all isomers) ACGIH OEL TWA 50 ppm (Bulyl acetates, all isomers) ACGIH OEL TWA 50 ppm (Bulyl acetates, all isomers) EU - Indicative Occupational Exposure Limit (IOEL TWA) 150 ppm (Bulyl acetates, all isomers) IOEL TWA 1488 mg/m³ 100 ppm 1468 mg/m³ 100 ppm 1468 mg/m³ 100 ppm 1468 mg/m³ 100 ppm 1400 ppm Belgium - Occupational Exposure Limits		50 ppm (Butyl acetates)		
United Kingdom - Occupational Exposure Limits WEL STEL (OEL STEL) 903 mg/m² 187 ppm 187 ppm Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 241 mg/m² 50 ppm 723 mg/m² (value from the regulation) Kortideverdi (OEL STEL) 723 mg/m² (value from the regulation) Switzerland - Occupational Exposure Limits MAK (OEL TWA) 240 mg/m² 50 ppm 50 ppm KZGW (OEL STEL) 720 mg/m³ 150 ppm 150 ppm USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA 50 ppm (Butyl acetates, all isomers) ACGIH OEL STEL 150 ppm (Butyl acetates, all isomers) EU - Indicative Occupational Exposure Limit (IOEL TWA) 720 mg/m² Oppm Austria - Occupational Exposure Limits MAK (OEL TWA) 734 mg/m³ 200 ppm 400 ppm Belgium - Occupational Exposure Limits OEL TWA 734 mg/m³ OED ppm	KGV (OEL STEL)	723 mg/m³ (Butyl acetates)		
WEL TWA (OEL TWA) 724 mg/m³ 150 ppm 150 ppm WEL STEL (OEL STEL) 903 mg/m³ 187 ppm 187 ppm Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 241 mg/m³ 50 ppm 50 ppm Kortidoverdi (OEL STEL) 723 mg/m³ (value from the regulation) Switzerland - Occupational Exposure Limits MAK (OEL TWA) 240 mg/m³ 50 ppm 50 ppm KZGW (OEL STEL) 720 mg/m³ 50 ppm 720 mg/m³ 150 ppm 150 ppm USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA 50 ppm (Butyl acetates, all isomers) ACGIH OEL STEL 150 ppm (Butyl acetates, all isomers) EU - Indicative Occupational Exposure Limit (IOEL - USA) OP pm Indicative Occupational Exposure Limit (IOEL - USA) OP pm OP pm Austria - Occupational Exposure Limits MAK (OEL TWA) 734 mg/m³ <td< td=""><td></td><td>150 ppm (Butyl acetates)</td></td<>		150 ppm (Butyl acetates)		
150 ppm 150	United Kingdom - Occupational Exposure Limits			
WEL STEL (OEL STEL) 903 mg/m³ 187 ppm 187 ppm Norway - Occupational Exposure Limits 241 mg/m³ 60 ppm 50 ppm Kortidoverdi (OEL STEL) 723 mg/m³ (value from the regulation) Switzerland - Occupational Exposure Limits 240 mg/m³ MAK (OEL TWA) 240 mg/m³ 50 ppm KZGW (OEL STEL) 720 mg/m³ 150 ppm USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA 50 ppm (Butyl acetates, all isomers) ACGIH OEL TYA 50 ppm (Butyl acetates, all isomers) EU - Indicative Occupational Exposure Limit (IOEL) 10 ppm (Butyl acetates, all isomers) EU - Indicative Occupational Exposure Limit (IOEL) 1468 mg/m³ IOEL TWA 734 mg/m³ 400 ppm Austria - Occupational Exposure Limits MAK (OEL TWA) 734 mg/m³ 400 ppm Belgium - Occupational Exposure Limits OEL TWA 734 mg/m³ 200 ppm	WEL TWA (OEL TWA)	724 mg/m³		
Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 4241 mg/m³ 50 ppm Kortidsverdi (OEL STEL) 725 mg/m³ (value from the regulation) 150 ppm (value from the regulation) Switzerland - Occupational Exposure Limits MAK (OEL TWA) 240 mg/m³ 50 ppm KZGW (OEL STEL) 720 mg/m³ 150 ppm VSA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA 350 ppm (Butyl acetates, all isomers) ACGIH OEL TWA 4CGIH OEL TWA 50 ppm (Butyl acetates, all isomers) CUSA - ACGIH - Occupational Exposure Limits FUSA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA 4CGIH OEL TWA 50 ppm (Butyl acetates, all isomers) CUSA - ACGIH - Occupational Exposure Limit (IOEL) FUSA - A		150 ppm		
Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) Grenseverdi (OEL TWA) Evertidesverdi (OEL STEL) Evertidesverdi (O	WEL STEL (OEL STEL)	903 mg/m³		
Grenseverdi (OEL TWA) 241 mg/m³ 50 ppm 50 ppm Kortidsverdi (OEL STEL) 723 mg/m³ (value from the regulation) Switzerland - Occupational Exposure Limits 240 mg/m³ MAK (OEL TWA) 240 mg/m³ 50 ppm 50 ppm KZGW (OEL STEL) 720 mg/m³ 150 ppm 150 ppm USA - ACGIH - Occupational Exposure Limits 50 ppm (Butyl acetates, all isomers) ACGIH OEL TWA 50 ppm (Butyl acetates, all isomers) ACGIH OEL TWA 50 ppm (Butyl acetates, all isomers) EU - Indicative Occupational Exposure Limit (IOEL) OEL TWA 734 mg/m³ 200 ppm IOEL STEL 468 mg/m³ 400 ppm Austria - Occupational Exposure Limits MAK (OEL TWA) 734 mg/m³ 200 ppm MAK (OEL STEL) 1468 mg/m³ 400 ppm Belgium - Occupational Exposure Limits OEL TWA 734 mg/m³ 200 ppm		187 ppm		
So ppm So ppm Nortidisverdi (OEL STEL) 723 mg/m³ (value from the regulation) 150 ppm 150 ppm (Butyl acetates, all isomers) 150 ppm	Norway - Occupational Exposure Limits			
Kortidsverdi (OEL STEL) 723 mg/m³ (value from the regulation) Switzerland - Occupational Exposure Limits MAK (OEL TWA) 240 mg/m³ 50 ppm KZGW (OEL STEL) 720 mg/m³ 150 ppm USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA 50 ppm (Butyl acetates, all isomers) ACGIH OEL STEL 150 ppm (Butyl acetates, all isomers) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA 734 mg/m³ 200 ppm IOEL STEL 1468 mg/m³ 400 ppm AMK (OEL TWA) 734 mg/m³ 200 ppm MAK (OEL TWA) 734 mg/m³ 200 ppm MAK (OEL TWA) 734 mg/m³ 400 ppm MAK (OEL STEL) 1468 mg/m³ 400 ppm Belgium - Occupational Exposure Limits Belgium - Occupational Exposure Limits TAY mg/m³ 200 ppm MAK (OEL STEL) 734 mg/m³ 200 ppm Belgium - Occupational Exposure Limits FAY mg/m³ 200 ppm Belgium - Occupational Exposure Limits FAY mg/m³ 200 ppm	Grenseverdi (OEL TWA)	241 mg/m³		
Switzerland - Occupational Exposure Limits MAK (OEL TWA)		50 ppm		
Switzerland - Occupational Exposure Limits MAK (OEL TWA) 240 mg/m³ 50 ppm 720 mg/m³ 150 ppm 150 ppm USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA 50 ppm (Butyl acetates, all isomers) ACGIH OEL STEL 150 ppm (Butyl acetates, all isomers) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA 734 mg/m³ 10EL STEL 1468 mg/m³ 400 ppm Austria - Occupational Exposure Limits MAK (OEL TWA) 734 mg/m³ 200 ppm 400 ppm MAK (OEL STEL) 1468 mg/m³ 400 ppm 400 ppm Belgium - Occupational Exposure Limits 734 mg/m³ OEL TWA 734 mg/m³ 200 ppm 200 ppm	Korttidsverdi (OEL STEL)	723 mg/m³ (value from the regulation)		
MAK (OEL TWA) 240 mg/m³ 50 ppm 50 ppm KZGW (OEL STEL) 720 mg/m³ 150 ppm 150 ppm USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA 50 ppm (Butyl acetates, all isomers) ACGIH OEL STEL 150 ppm (Butyl acetates, all isomers) Ethyl acetate (141-78-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA 734 mg/m³ 1468 mg/m³ 400 ppm MAK (OEL TWA) 734 mg/m³ 200 ppm MAK (OEL STEL) 1468 mg/m³ Mak (OEL STEL) 1468 mg/m³ Belgium - Occupational Exposure Limits OEL TWA 734 mg/m³ 0 ppm		150 ppm (value from the regulation)		
KZGW (OEL STEL) 720 mg/m³ 150 ppm	Switzerland - Occupational Exposure Limits			
KZGW (OEL STEL) 720 mg/m³ 150 ppm 150 ppm USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA 50 ppm (Butyl acetates, all isomers) ACGIH OEL STEL 150 ppm (Butyl acetates, all isomers) ethyl acetate (141-78-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA 734 mg/m³ 200 ppm IOEL STEL 1468 mg/m³ 400 ppm Austria - Occupational Exposure Limits MAK (OEL TWA) 734 mg/m³ 200 ppm MAK (OEL STEL) 1468 mg/m³ 400 ppm Belgium - Occupational Exposure Limits OEL TWA 734 mg/m³ 200 ppm	MAK (OEL TWA)	240 mg/m³		
USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA ACGIH OEL STEL 50 ppm (Butyl acetates, all isomers) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA 734 mg/m³ 200 ppm IOEL STEL 1468 mg/m³ 400 ppm MAK (OEL TWA) 734 mg/m³ 200 ppm MAK (OEL STEL) 1468 mg/m³ 400 ppm MAK (OEL STEL) 1468 mg/m³ 400 ppm MAK (OEL STEL) 1468 mg/m³ 400 ppm Belgium - Occupational Exposure Limits Region - Occupational Exposure Limits Tyang/m³ 200 ppm		50 ppm		
USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA 50 ppm (Butyl acetates, all isomers) ACGIH OEL STEL 150 ppm (Butyl acetates, all isomers) ethyl acetate (141-78-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA 734 mg/m³ 200 ppm IOEL STEL 1468 mg/m³ Austria - Occupational Exposure Limits MAK (OEL TWA) 734 mg/m³ 200 ppm MAK (OEL STEL) 1468 mg/m³ 400 ppm Belgium - Occupational Exposure Limits OEL TWA 734 mg/m³ 200 ppm	KZGW (OEL STEL)	720 mg/m³		
ACGIH OEL TWA 50 ppm (Butyl acetates, all isomers) ACGIH OEL STEL 150 ppm (Butyl acetates, all isomers) ethyl acetate (141-78-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA 734 mg/m³ 200 ppm IOEL STEL 408 mg/m³ 400 ppm Austria - Occupational Exposure Limits MAK (OEL TWA) 734 mg/m³ 200 ppm MAK (OEL STEL) 1468 mg/m³ 400 ppm Belgium - Occupational Exposure Limits OEL TWA 734 mg/m³ 200 ppm		150 ppm		
ACGIH OEL STEL 150 ppm (Butyl acetates, all isomers) ethyl acetate (141-78-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA 734 mg/m³ 200 ppm IOEL STEL 4468 mg/m³ 400 ppm Austria - Occupational Exposure Limits MAK (OEL TWA) 734 mg/m³ 200 ppm MAK (OEL STEL) 468 mg/m³ 400 ppm Belgium - Occupational Exposure Limits OEL TWA 734 mg/m³ 200 ppm	USA - ACGIH - Occupational Exposure Limits			
ethyl acetate (141-78-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA 734 mg/m³ 200 ppm IOEL STEL 1468 mg/m³ 400 ppm Austria - Occupational Exposure Limits MAK (OEL TWA) 734 mg/m³ 200 ppm MAK (OEL STEL) 1468 mg/m³ 400 ppm Belgium - Occupational Exposure Limits OEL TWA 734 mg/m³ 200 ppm	ACGIH OEL TWA	50 ppm (Butyl acetates, all isomers)		
EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA 734 mg/m³ 200 ppm IOEL STEL 1468 mg/m³ Austria - Occupational Exposure Limits MAK (OEL TWA) 734 mg/m³ 200 ppm MAK (OEL STEL) 1468 mg/m³ 400 ppm Belgium - Occupational Exposure Limits OEL TWA 734 mg/m³ 200 ppm	ACGIH OEL STEL	150 ppm (Butyl acetates, all isomers)		
IOEL TWA 734 mg/m³ 200 ppm	ethyl acetate (141-78-6)			
200 ppm 200	EU - Indicative Occupational Exposure Limit (IOEL)			
IOEL STEL 1468 mg/m³ Austria - Occupational Exposure Limits 734 mg/m³ MAK (OEL TWA) 734 mg/m³ 200 ppm 1468 mg/m³ MAK (OEL STEL) 1468 mg/m³ 400 ppm 88elgium - Occupational Exposure Limits OEL TWA 734 mg/m³ 200 ppm	IOEL TWA	734 mg/m³		
Austria - Occupational Exposure Limits MAK (OEL TWA)		200 ppm		
Austria - Occupational Exposure Limits MAK (OEL TWA) 734 mg/m³ 200 ppm 1468 mg/m³ 400 ppm 400 ppm Belgium - Occupational Exposure Limits OEL TWA 734 mg/m³ 200 ppm	IOEL STEL	1468 mg/m³		
MAK (OEL TWA) 734 mg/m³ 200 ppm 200 ppm MAK (OEL STEL) 1468 mg/m³ 400 ppm Belgium - Occupational Exposure Limits OEL TWA 734 mg/m³ 200 ppm		400 ppm		
200 ppm 200 ppm	Austria - Occupational Exposure Limits			
MAK (OEL STEL) 1468 mg/m³ 400 ppm Belgium - Occupational Exposure Limits OEL TWA 734 mg/m³ 200 ppm	MAK (OEL TWA)	734 mg/m³		
Belgium - Occupational Exposure Limits OEL TWA 734 mg/m³ 200 ppm		200 ppm		
Belgium - Occupational Exposure Limits OEL TWA 734 mg/m³ 200 ppm	MAK (OEL STEL)	1468 mg/m³		
OEL TWA 734 mg/m³ 200 ppm		400 ppm		
200 ppm	Belgium - Occupational Exposure Limits	Belgium - Occupational Exposure Limits		
	OEL TWA	734 mg/m³		
OFL STEL 1468 mg/m³		200 ppm		
55	OEL STEL	1468 mg/m³		
400 ppm		400 ppm		
Bulgaria - Occupational Exposure Limits	Bulgaria - Occupational Exposure Limits			
OEL TWA 734 mg/m³	OEL TWA	734 mg/m³		

Safety Data Sheet

ethyl acetate (141-78-6)	
	200 ppm
OEL STEL	1468 mg/m³
	400 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	734 mg/m³
	200 ppm
KGVI (OEL STEL)	1468 mg/m³
	400 ppm
Cyprus - Occupational Exposure Limits	
OEL TWA	734 mg/m³
	200 ppm
OEL STEL	1468 mg/m³
	400 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	700 mg/m³
Denmark - Occupational Exposure Limits	
OEL TWA	540 mg/m³
	150 ppm
OEL STEL	1468 mg/m³
	400 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	500 mg/m³
	150 ppm
OEL STEL	1100 mg/m³
	300 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	730 mg/m³
	200 ppm
HTP (OEL STEL)	1470 mg/m³
	400 ppm
France - Occupational Exposure Limits	
VME (OEL TWA)	734 mg/m³ (restrictive limit)
	200 ppm (restrictive limit)
VLE (OEL C/STEL)	1468 mg/m³ (restrictive limit)
	400 ppm (restrictive limit)
Germany - Occupational Exposure Limits (TRGS 90	
AGW (OEL TWA)	730 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	200 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)

Safety Data Sheet

ethyl acetate (141-78-6)		
Gibraltar - Occupational Exposure Limits		
OEL TWA	200 mg/m³	
	734 ppm	
OEL STEL	400 mg/m³	
	1468 ppm	
Greece - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
	200 ppm	
OEL STEL	1468 mg/m³	
	400 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	734 mg/m³	
CK (OEL STEL)	1468 mg/m³	
OEL chemical category	Sensitizer	
Ireland - Occupational Exposure Limits	1	
OEL TWA	734 mg/m³	
	200 ppm	
OEL STEL	1468 mg/m³	
	400 ppm	
Italy - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
	200 ppm	
OEL STEL	1468 mg/m³	
	400 ppm	
Latvia - Occupational Exposure Limits		
OEL TWA	200 mg/m³	
	54 ppm	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	500 mg/m³	
	150 ppm	
NRV (OEL C)	1100 mg/m³	
	300 ppm	
Luxembourg - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
	200 ppm	
OEL STEL	1468 mg/m³	
	400 ppm	
Malta - Occupational Exposure Limits	1	
OEL TWA	734 mg/m³	
1	1	

Safety Data Sheet

ethyl acetate (141-78-6)		
	200 ppm	
OEL STEL	1468 mg/m³	
	400 ppm	
Netherlands - Occupational Exposure Limits		
TGG-8u (OEL TWA)	734 mg/m³	
	200 ppm	
TGG-15min (OEL STEL)	1468 mg/m³	
· · · ·	400 ppm	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	734 mg/m³	
NDSCh (OEL STEL)	1468 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	734 mg/m³ (indicative limit value)	
	200 ppm (indicative limit value)	
OEL STEL	1468 mg/m³ (indicative limit value)	
	400 ppm (indicative limit value)	
Romania - Occupational Exposure Limits	,	
OEL TWA	734 mg/m³	
	200 ppm	
OEL STEL	1468 mg/m³	
	400 ppm	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA)	734 mg/m³	
	200 ppm	
NPHV (OEL C)	1468 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
	200 ppm	
OEL STEL	1468 mg/m³	
	400 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	734 mg/m³	
	200 ppm	
VLA-EC (OEL STEL)	1468 mg/m³	
	400 ppm	
Sweden - Occupational Exposure Limits	1	
NGV (OEL TWA)	550 mg/m³	
	150 ppm	
KGV (OEL STEL)	1100 mg/m³	
	I	

Safety Data Sheet

ethyl acetate (141-78-6)		
	300 ppm	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	734 mg/m³	
	200 ppm	
WEL STEL (OEL STEL)	1468 mg/m³	
	400 ppm	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA)	734 mg/m³	
	200 ppm	
Korttidsverdi (OEL STEL)	1468 mg/m³ (value from the regulation)	
	400 ppm (value from the regulation)	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	730 mg/m³	
	200 ppm	
KZGW (OEL STEL)	1460 mg/m³	
	400 ppm	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	400 ppm	
benzyl alcohol (100-51-6)		
Bulgaria - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	40 mg/m³	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	45 mg/m³	
	10 ppm	
Germany - Occupational Exposure Limits (TRGS 900)		
AGW (OEL TWA)	22 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Chemical category	Skin notation	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
OEL chemical category	Skin notation	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	240 mg/m³	

Safety Data Sheet

benzyl alcohol (100-51-6)			
Slovenia - Occupational Exposure Limits			
OEL TWA	22 mg/m³		
	5 ppm		
OEL STEL	44 mg/m³		
	10 ppm		
OEL chemical category	Potential for cutaneous absorption		
Switzerland - Occupational Exposure Limits			
MAK (OEL TWA)	22 mg/m³ (aerosol, vapour)		
	5 ppm (aerosol, vapour)		
OEL chemical category	Skin notation		
acetophenone (98-86-2)			
Belgium - Occupational Exposure Limits			
OEL TWA	50 mg/m³		
	10 ppm		
Bulgaria - Occupational Exposure Limits			
OEL TWA	5 mg/m³		
Denmark - Occupational Exposure Limits			
OEL TWA	49 mg/m³		
	10 ppm		
OEL STEL	98 mg/m³		
	20 ppm		
Finland - Occupational Exposure Limits			
HTP (OEL TWA)	25 mg/m³		
	5 ppm		
Hungary - Occupational Exposure Limits			
AK (OEL TWA)	50 mg/m³		
Ireland - Occupational Exposure Limits	Ireland - Occupational Exposure Limits		
OEL TWA	49 mg/m³		
	10 ppm		
OEL STEL	147 mg/m³ (calculated)		
	30 ppm (calculated)		
Latvia - Occupational Exposure Limits			
OEL TWA	5 mg/m³		
Lithuania - Occupational Exposure Limits			
IPRV (OEL TWA)	5 mg/m³		
OEL chemical category	Skin notation		
Poland - Occupational Exposure Limits			
NDS (OEL TWA)	50 mg/m³		
NDSCh (OEL STEL)	100 mg/m³		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

acetophenone (98-86-2)		
Portugal - Occupational Exposure Limits		
OEL TWA	10 ppm	
Romania - Occupational Exposure Limits		
OEL TWA	100 mg/m³	
	20 ppm	
OEL STEL	200 mg/m³	
	41 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	50 mg/m³	
	10 ppm	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	10 ppm	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):





8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Conforms to standard.

Odour : characteristic.
Odour threshold : Not available
Melting point : Not applicable
Freezing point : Not available
Boiling point : Not available

Flammability : Not applicable, Combustible liquid

Lower explosion limit : Not available
Upper explosion limit : Not available
Flash point : 70 °C
Auto-ignition temperature : Not available
Decomposition temperature : Not available
pH : Not available
Viscosity, kinematic : Not available

Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available : Not available

Vapour pressure : 0.071380572 mm Hg (calculated value)

Vapour pressure at 50°C : Not available
Density : Not available
Relative density : Not available
Relative vapour density at 20°C : Not available
Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 40.75 % (calculated value)(CARB VOC) (%w/w)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Combustible liquid. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (inhalation)	Not classified	
benzaldehyde (100-52-7)		
LD50 oral rat	1292 mg/kg (Source: JAPAN_GHS)	
LD50 dermal rabbit	> 1250 mg/kg (Source: JAPAN_GHS)	
LC50 Inhalation - Rat	< 5 mg/l/4h	
Ethyl vanillin (121-32-4)		
LD50 oral rat	1590 mg/kg (Source: NLM_CIP)	
LD50 oral	3000 mg/kg bodyweight	
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)	
Aldehyde C-16 (77-83-8)		
LD50 oral rat	5470 mg/kg (Source: NLM_CIP)	
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)	
Resin acids and Rosin acids, hydrogenated, n	nethyl esters (8050-15-5)	
LD50 oral rat	> 2000 mg/kg (Source: ECHA)	
LD50 dermal rabbit	> 10000 mg/kg (Source: ECHA_API)	
Eugenol (97-53-0)		
LD50 oral rat	1930 mg/kg (Source: NZ_CCID)	
LD50 oral	2500 mg/kg bodyweight	
LC50 Inhalation - Rat	> 2.58 mg/l/4h	
isobutyl acetate (110-19-0)		
LD50 oral rat	15400 mg/kg (Source: JAPAN_GHS)	
LD50 dermal rabbit	> 17400 mg/kg (Source: NLM_CIP)	
Allyl caproate (123-68-2)		
LD50 oral	218 mg/kg	
LD50 dermal rabbit	820 mg/kg (Source: ECHA_API)	
LD50 dermal	300 mg/kg	
ethyl acetate (141-78-6)		
LD50 oral rat	5620 mg/kg (Source: NLM_CIP)	
LD50 dermal rabbit	> 18000 mg/kg (Source: JAPAN_GHS)	
LC50 Inhalation - Rat [ppm]	4000 ppm/4h	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

benzyl alcohol (100-51-6)		
LD50 oral rat	1230 mg/kg (Source: NLM_CIP)	
LD50 oral	1570 mg/kg	
acetophenone (98-86-2)		
LD50 oral rat	2081 mg/kg (Source: ECHA_API)	
LD50 oral	500 mg/kg bodyweight	
LD50 dermal rat	3300 mg/kg (Source: ECHA_API)	
LC50 Inhalation - Rat	> 2.13 mg/l (Exposure time: 8 h Source: CHEMVIEW)	
Skin corrosion/irritation	: Not classified	
Serious eye damage/irritation	: Not classified	
Respiratory or skin sensitisation	: May cause an allergic skin reaction.	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Eugenol (97-53-0)		
IARC group	3 - Not classifiable	
Reproductive toxicity	: Not classified	
STOT-single exposure	: Not classified	
isobutyl acetate (110-19-0)		
STOT-single exposure	May cause drowsiness or dizziness.	
ethyl acetate (141-78-6)		
STOT-single exposure	May cause drowsiness or dizziness.	
STOT-repeated exposure	: Not classified	
Aspiration hazard	: Not classified	

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

: Harmful to aquatic life with long lasting effects. Ecology - general : Not classified

Hazardous to the aquatic environment, short-term

: Harmful to aquatic life with long lasting effects. Hazardous to the aquatic environment, long-term

(chronic)	
benzaldehyde (100-52-7)	
LC50 - Fish [1]	10.6 – 11.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: EPA)
LC50 - Fish [2]	12.69 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: IUCLID)
Ethyl vanillin (121-32-4)	
LC50 - Fish [1]	81.4 – 94.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Aldehyde C-16 (77-83-8)		
LC50 - Fish [1]	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static] Source: ECHA)	
Eugenol (97-53-0)		
LC50 - Fish [1]	13 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)	
isobutyl acetate (110-19-0)		
LC50 - Fish [1]	17 mg/l (Exposure time: 96 h - Species: Oryzias latipes Source: ECHA)	
Allyl caproate (123-68-2)		
LC50 - Fish [1]	0.117 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)	
ethyl acetate (141-78-6)		
LC50 - Fish [1]	220 – 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
LC50 - Fish [2]	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: IUCLID)	
EC50 - Crustacea [1]	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
benzyl alcohol (100-51-6)		
LC50 - Fish [1]	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)	
LC50 - Fish [2]	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)	
EC50 - Crustacea [1]	23 mg/l (Exposure time: 48 h - Species: water flea)	
acetophenone (98-86-2)		
LC50 - Fish [1]	162 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
LC50 - Fish [2]	155 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)	

12.2. Persistence and degradability

ALMOND & MADZIDAN CO 40004		
ALMOND & MARZIPAN CC-13091		
Persistence and degradability	Not established.	
benzaldehyde (100-52-7)		
Persistence and degradability	Rapidly degradable	
Ethyl vanillin (121-32-4)		
Persistence and degradability	Rapidly degradable	
Aldehyde C-16 (77-83-8)		
Persistence and degradability	Rapidly degradable	
Resin acids and Rosin acids, hydrogenated, methyl esters (8050-15-5)		
Persistence and degradability	Rapidly degradable	
Eugenol (97-53-0)		
Persistence and degradability	Rapidly degradable	
isobutyl acetate (110-19-0)		
Persistence and degradability	Rapidly degradable	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Allyl caproate (123-68-2)	
Persistence and degradability	Rapidly degradable
ethyl acetate (141-78-6)	
Persistence and degradability	Rapidly degradable
benzyl alcohol (100-51-6)	
Persistence and degradability	Rapidly degradable
acetophenone (98-86-2)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

ALMOND & MARZIPAN CC-13091		
Bioaccumulative potential	Not established.	
benzaldehyde (100-52-7)		
BCF - Fish [1]	(no significant bioaccumulation)	
Partition coefficient n-octanol/water (Log Pow)	1.4 (at 25 °C)	
Ethyl vanillin (121-32-4)		
Partition coefficient n-octanol/water (Log Pow)	1.61 (at 25 °C)	
Aldehyde C-16 (77-83-8)		
Partition coefficient n-octanol/water (Log Pow)	2.4 (at 25 °C (cis isomer)	
Resin acids and Rosin acids, hydrogenated, n	nethyl esters (8050-15-5)	
Partition coefficient n-octanol/water (Log Pow)	6.4 – 7.6 (at pH 6)	
Eugenol (97-53-0)		
Partition coefficient n-octanol/water (Log Pow)	1.83 (at 30 °C (at pH 5.5)	
isobutyl acetate (110-19-0)		
BCF - Fish [1]	(no significant bioconcentration)	
Partition coefficient n-octanol/water (Log Pow)	2.3 (at 25 °C (at pH 7)	
Allyl caproate (123-68-2)		
Partition coefficient n-octanol/water (Log Pow)	3.191 (at 20 °C (at pH 5)	
ethyl acetate (141-78-6)		
BCF - Fish [1]	(30 dimensionless)	
Partition coefficient n-octanol/water (Log Pow)	0.73 (at 20 °C (at pH 7)	
benzyl alcohol (100-51-6)		
Partition coefficient n-octanol/water (Log Pow)	1.05	
acetophenone (98-86-2)		
Partition coefficient n-octanol/water (Log Pow)	1.63 – 1.65	

12.4. Mobility in soil

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information

: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

Product/Packaging disposal recommendations

Ecological information HP Code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with local/national laws and regulations.
- : Avoid release to the environment.
- : HP6 "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.

 ${\sf HP4}$ - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	14.1. UN number or ID number			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping	14.2. UN proper shipping name			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	isobutyl acetate ; ethyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	ALMOND & MARZIPAN CC-13091; benzaldehyde; Aldehyde C-16; Eugenol; isobutyl acetate; Allyl caproate; ethyl acetate; benzyl alcohol; acetophenone	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	ALMOND & MARZIPAN CC-13091; Aldehyde C- 16; Resin acids and Rosin acids, hydrogenated, methyl esters; Allyl caproate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	isobutyl acetate ; ethyl acetate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

VOC Directive (2004/42)

VOC content : 40.75 % (calculated value)(CARB VOC) (%w/w)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases		
Code	Description	
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide	

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(3) - hazardous for aquatic organisms, may have longterm hazardous effects in aquatic

environment

SZW-lijst van kankerverwekkende stoffen : Resin acids and Rosin acids, hydrogenated, methyl esters is listed

SZW-lijst van mutagene stoffen : Resin acids and Rosin acids, hydrogenated, methyl esters is listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – : None of the components are listed Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Class for fire hazard : Class III-1
Store unit : 50 liter

Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines

for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.