Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Issue date: 10/28/2024 Version: 1.0



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : FIRE ROASTED CHESTNUT CC-13094 10% in DPG

Product code : CC-13094_10%
Type of product : Perfumes, Fragrances

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial

For professional use only : Perfumes, Fragrances

Use of the substance/mixture : Perfumes, Fragran Function or use category : Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Candle Craft Weiherwiese 10 65510 Idstein - Germany T 49-6126-9363 -0

info@candlecraft.de - www.candlecraft.de

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitization, Category 1 H317 Hazardous to the aquatic environment – Chronic Hazard H412

Category 3

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) : Warning

Contains : CINNAMAL; Heliotropine; 1,2-Cyclopentanedione, 3-methyl-

Hazard statements (CLP) : H317 - May cause an allergic skin reaction.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

P302+P352 - IF ON SKIN: Wash with plenty of water.

P321 - Specific treatment (see supplemental first aid instruction on this label).

Extra phrases : Restricted to professional users.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371- 33	4 – 8.005	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
CINNAMAL	CAS-No.: 104-55-2 EC-No.: 203-213-9 EC Index-No.: 606-155-00-6 REACH-no: 01-2119935242-	0.3 – 0.6	Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 Aquatic Chronic 3, H412
Heliotropine	CAS-No.: 120-57-0 EC-No.: 204-409-7 REACH-no: 01-2119983608- 21	0.15 – 0.3	Skin Sens. 1B, H317
1,2-Cyclopentanedione, 3-methyl-	CAS-No.: 765-70-8 EC-No.: 212-154-8	0.1 – 0.19	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317
benzaldehyde substance with national workplace exposure limit(s) (BG, FI, HU, LT, LV, PL)	CAS-No.: 100-52-7 EC-No.: 202-860-4 EC Index-No.: 605-012-00-5 REACH-no: 01-2119455540-	0.01 – 0.025	Acute Tox. 4 (Oral), H302
1,2-Propanediol substance with national workplace exposure limit(s) (GB, HR, IE, LT, LV, PL, NO)	CAS-No.: 57-55-6 EC-No.: 200-338-0 REACH-no: 01-2119456809- 23	0.01 – 0.02425	Not classified
isopentyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, DE, DK, EE, ES, FI, FR, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2 REACH-no: 01-2119548408- 32	0.01 – 0.01	Flam. Liq. 3, H226

Full text of H- and EUH-statements: see section 16

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water,

followed by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

persists

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

10/28/2024 (Issue date) EN (English US) 3/17

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep only in the original container in a cool, well ventilated place away from : Keep

container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

Germany

Storage class (LGK, TRGS 510)

Joint storage table

: LGK 12 - Non-combustible liquids

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for

Joint storage with restrictions permitted for

Joint storage permitted for

: LGK 1, LGK 6.2, LGK 7 : LGK 4.1A, LGK 4.3, LGK 5.1C

: LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A,

LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK

10-13

Switzerland

Storage class (LK) : LK 10/12 - Liquids

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

benzaldehyde (100-52-7)		
Bulgaria - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	4.4 mg/m³	
	1 ppm	
HTP (OEL C)	17.4 mg/m³	
	4 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³	
CK (OEL STEL)	10 mg/m³	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	

Safety Data Sheet

benzaldehyde (100-52-7)		
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	10 mg/m³	
NDSCh (OEL STEL)	40 mg/m³	
1,2-Propanediol (57-55-6)		
Croatia - Occupational Exposure Limits		
GVI (OEL TWA)	474 mg/m³ (total vapor and particles) 10 mg/m³ (particles)	
	150 ppm	
Ireland - Occupational Exposure Limits		
OEL TWA	10 mg/m³ (particulates) 470 mg/m³ (total vapour and particulates)	
	150 ppm (total vapour and particulates)	
OEL STEL	1410 mg/m³ (calculated-particulates) 30 mg/m³ (calculated)	
	450 ppm (calculated-total vapour and particulates)	
Latvia - Occupational Exposure Limits		
OEL TWA	7 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	7 mg/m³	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	100 mg/m³ (vapor and inhalable fraction)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	474 mg/m³ (total vapour and particulates) 10 mg/m³ (particulates)	
	150 ppm (total vapour and particulates)	
WEL STEL (OEL STEL)	1422 mg/m³ (calculated-total vapour and particulates) 30 mg/m³ (calculated-particulate)	
	450 ppm (calculated-total vapour and particulates)	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA)	79 mg/m³	
	25 ppm	
Korttidsverdi (OEL STEL)	118.5 mg/m³ (value calculated)	
	37.5 ppm (value calculated)	
isopentyl acetate (123-92-2)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	270 mg/m³	
	50 ppm	
IOEL STEL	540 mg/m³	

Safety Data Sheet

isopentyl acetate (123-92-2)		
	100 ppm	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	270 mg/m³ (Pentyl acetate (all isomers))	
	50 ppm (Pentyl acetate (all isomers))	
MAK (OEL STEL)	540 mg/m³ (Pentylacetate)	
	100 ppm (Pentylacetate)	
Belgium - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Bulgaria - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA)	270 mg/m³	
	50 ppm	
KGVI (OEL STEL)	540 mg/m³	
	100 ppm	
Cyprus - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Denmark - Occupational Exposure Limits		
OEL TWA	271 mg/m³ (Amyl acetate, all isomers)	
	50 ppm (Amyl acetate, all isomers)	
OEL STEL	540 mg/m³	
	100 ppm	
Estonia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	270 mg/m³ (Pentyl acetate)	
	50 ppm (Pentyl acetate)	

Safety Data Sheet

isopentyl acetate (123-92-2)		
HTP (OEL STEL)	540 mg/m³	
	100 ppm	
France - Occupational Exposure Limits		
VME (OEL TWA)	270 mg/m³ (restrictive limit)	
	50 ppm (restrictive limit)	
VLE (OEL C/STEL)	540 mg/m³ (restrictive limit)	
	100 ppm (restrictive limit)	
Germany - Occupational Exposure Limits (TRG	iS 900)	
AGW (OEL TWA)	270 mg/m³	
	50 ppm	
Gibraltar - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Greece - Occupational Exposure Limits		
OEL TWA	530 mg/m³	
	100 ppm	
OEL STEL	800 mg/m³	
	150 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	270 mg/m³	
CK (OEL STEL)	540 mg/m³	
Ireland - Occupational Exposure Limits		
OEL TWA	260 mg/m³	
	50 ppm	
OEL STEL	520 mg/m³	
	100 ppm	
Italy - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Latvia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	270 mg/m³	
	50 ppm	
	· I	

Safety Data Sheet

isopentyl acetate (123-92-2)		
TPRV (OEL STEL)	540 mg/m³	
	100 ppm	
Luxembourg - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Malta - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Netherlands - Occupational Exposure Limits		
TGG-15min (OEL STEL)	530 mg/m³	
	98.1 ppm	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	250 mg/m³	
NDSCh (OEL STEL)	500 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	270 mg/m³ (indicative limit value)	
	50 ppm (indicative limit value (Pentyl acetate, all isomers)	
OEL STEL	540 mg/m³ (indicative limit value)	
	100 ppm (indicative limit value)	
Romania - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA)	270 mg/m³	
	50 ppm	
NPHV (OEL C)	540 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	270 mg/m³ (indicative limit value)	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

isopentyl acetate (123-92-2)		
	50 ppm (indicative limit value)	
VLA-EC (OEL STEL)	540 mg/m³	
	100 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	270 mg/m³ (Pentyl acetates)	
	50 ppm (Pentyl acetates)	
KGV (OEL STEL)	540 mg/m³ (Pentyl acetates)	
	100 ppm (Pentyl acetates)	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA)	260 mg/m³	
	50 ppm	
Korttidsverdi (OEL STEL)	325 mg/m³ (value calculated)	
	75 ppm (value calculated)	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	260 mg/m³ (Pentyl acetate all isomers)	
	50 ppm (Pentyl acetate all isomers)	
KZGW (OEL STEL)	260 mg/m³ (Pentyl acetate all isomers)	
	50 ppm (Pentyl acetate all isomers)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	50 ppm (Pentyl acetate, all isomers)	
ACGIH OEL STEL	100 ppm (Pentyl acetate, all isomers)	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses

8.2.2.2. Skin protection

Hand protection:

Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

: Conforms to standard. Color

Odor characteristic. Odor threshold Not available Melting point Not available Freezing point Not available Boiling point Not available Flammability : Non flammable. Lower explosion limit : Not available Upper explosion limit : Not available Flash point : > 93 °C Auto-ignition temperature : Not available : Not available Decomposition temperature : Not available рΗ : Not available Viscosity, kinematic Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available : Not available Vapor pressure Vapor pressure at 50°C : Not available

Density : Not available Relative density : Not available Relative vapor density at 20°C : Not available Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10/28/2024 (Issue date) EN (English US) 10/17

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

Additional information

Serious eye damage/irritation

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (innaiation)	Not classified	
benzyl benzoate (120-51-4)		
LD50 oral rat	> 2000 mg/kg (Source: ECHA_API)	
LD50 oral	1160 mg/kg body weight	
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)	
CINNAMAL (104-55-2)		
LD50 oral rat	2220 mg/kg (Source: NLM_CIP)	
LD50 oral	2220 mg/kg	
LD50 dermal rabbit	1260 mg/kg (Source: EPA_HPV)	
Heliotropine (120-57-0)		
LD50 oral rat	2700 mg/kg (Source: NLM_CIP)	
LD50 oral	2700 mg/kg body weight	
LD50 dermal rat	> 5000 mg/kg (Source: ECHA_API)	
1,2-Cyclopentanedione, 3-methyl- (765-70-8)		
LD50 oral	1067 mg/kg body weight	
benzaldehyde (100-52-7)		
LD50 oral rat	1292 mg/kg (Source: JAPAN_GHS)	
LD50 dermal rabbit	> 1250 mg/kg (Source: JAPAN_GHS)	
LC50 Inhalation - Rat	< 5 mg/l/4h	
1,2-Propanediol (57-55-6)		
LD50 oral rat	20 g/kg (Source: NLM_CIP)	
LD50 dermal rabbit	20800 mg/kg (Source: NLM_CIP)	
Skin corrosion/irritation :	Not classified	

10/28/2024 (Issue date) EN (English US) 11/17

: Not classified

: Based on available data, the classification criteria are not met

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Additional information : Based on available data, the classification criteria are not met Respiratory or skin sensitization : May cause an allergic skin reaction. Additional information : Based on available data, the classification criteria are not met Germ cell mutagenicity Additional information : Based on available data, the classification criteria are not met Carcinogenicity : Not classified : Based on available data, the classification criteria are not met Additional information Reproductive toxicity : Not classified Additional information : Based on available data, the classification criteria are not met STOT-single exposure Not classified : Based on available data, the classification criteria are not met Additional information STOT-repeated exposure : Not classified Additional information : Based on available data, the classification criteria are not met

: Not classified

benzyl benzoate (120-51-4)	
Viscosity, kinematic 7.456 mm²/s	
Heliotropine (120-57-0)	
Viscosity, kinematic	Not applicable

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Aspiration hazard

Additional information

Potential Adverse human health effects and

: Based on available data, the classification criteria are not met

: Based on available data, the classification criteria are not met

symptoms

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term

(acute)

Hazardous to the aquatic environment, long-term

: Not classified

: Harmful to aquatic life with long lasting effects.

(chronic)

(Chronic)	
benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
NOEC (chronic)	0.168 mg/l
Heliotropine (120-57-0)	
LC50 - Fish [1]	2.5 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static] Source: ECHA)
benzaldehyde (100-52-7)	
LC50 - Fish [1]	10.6 – 11.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: EPA)
LC50 - Fish [2]	12.69 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: IUCLID)
1,2-Propanediol (57-55-6)	
LC50 - Fish [1]	51600 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: IUCLID)
LC50 - Fish [2]	41 – 47 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

Safety Data Sheet

1,2-Propanediol (57-55-6)		
EC50 96h - Algae [1]	19000 mg/l (Species: Pseudokirchneriella subcapitata)	
12.2. Persistence and degradability		
FIRE ROASTED CHESTNUT CC-13094 10% in	n DPG	
Persistence and degradability	Not established.	
benzyl benzoate (120-51-4)		
Persistence and degradability	May cause long-term adverse effects in the environment.	
CINNAMAL (104-55-2)		
Persistence and degradability	Rapidly degradable	
Heliotropine (120-57-0)		
Persistence and degradability	Rapidly degradable	
1,2-Cyclopentanedione, 3-methyl- (765-70-8)		
Persistence and degradability	Rapidly degradable	
benzaldehyde (100-52-7)		
Persistence and degradability	Rapidly degradable	
1,2-Propanediol (57-55-6)		
Persistence and degradability	Rapidly degradable	
isopentyl acetate (123-92-2)		
Persistence and degradability	Rapidly degradable	
12.3. Bioaccumulative potential		
FIRE ROASTED CHESTNUT CC-13094 10% in DPG		
Bioaccumulative potential	Not established.	
benzyl benzoate (120-51-4)		
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)	
Bioaccumulative potential	Not established.	

FIRE ROASTED CHESTNUT CC-13094 10% in DPG			
Bioaccumulative potential	Not established.		
benzyl benzoate (120-51-4)			
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)		
Bioaccumulative potential	Not established.		
CINNAMAL (104-55-2)			
Partition coefficient n-octanol/water (Log Pow)	2.1065 (at 25 °C)		
Heliotropine (120-57-0)			
Partition coefficient n-octanol/water (Log Pow)	1.2 (at 35 °C)		
benzaldehyde (100-52-7)			
BCF - Fish [1]	(no significant bioaccumulation)		
Partition coefficient n-octanol/water (Log Pow)	1.4 (at 25 °C)		
1,2-Propanediol (57-55-6)			
BCF - Fish [1]	(1 dimensionless)		
Partition coefficient n-octanol/water (Log Pow)	-1.07 (at 20.5 °C (at pH >=6.2-<=6.4)		

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

isopentyl acetate (123-92-2)		
	Partition coefficient n-octanol/water (Log Pow)	2.7 (at 35 °C)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations

Ecological information

HP code

: Dispose in a safe manner in accordance with local/national regulations.

Avoid release to the environment.

: HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one

or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID		
14.1. UN number or ID number						
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
14.2. UN proper shipping name						
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
14.3. Transport hazard class(es)						
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
14.4. Packing group						
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
14.5. Environmental hazards						
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
No supplementary information available						

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)			
Reference code	Applicable on	Entry title or description	
3(a)	isopentyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	
3(b)	FIRE ROASTED CHESTNUT CC-13094 10% in DPG; benzyl benzoate; CINNAMAL; benzaldehyde	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	
3(c)	FIRE ROASTED CHESTNUT CC-13094 10% in DPG; benzyl benzoate; CINNAMAL	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	
40.	isopentyl acetate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.		Category, Subcategory	Threshold	Annex
Piperonal		120-57-0	2932 93 00	Category 1		Annex I

15.1.2. National regulations

France

Professional diseases		
Code	Description	
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide	

Germany

Water hazard class (WGK) : WGK 2, sign

List of sensitizing substances (TRGS 907)

Hazardous Incident Ordinance (12. BImSchV)

: WGK 2, significant hazardous to water (Classification according to AwSV, Annex 1).

: Contains sensitizing substances according TRGS 907.

: Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic

environment

SZW-lijst van kankerverwekkende stoffen

SZW-lijst van mutagene stoffen

SZW-lijst van reprotoxische stoffen – Borstvoeding

SZW-lijst van reprotoxische stoffen -

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen - Ontwikkeling

None of the components are listed
None of the components are listed
None of the components are listed

None of the components are listed

: None of the components are listed

Denmark

Classification remarks

Danish National Regulations

: Emergency management guidelines for the storage of flammable liquids must be followed

Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and

amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-phrases:	
Acute Tox. 4 (Dermal) Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard Category 2

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Full text of H- and EUH-phrases:		
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard Category 3	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 3	Flammable liquids Category 3	
H226	Flammable liquid and vapor.	
H302	Harmful if swallowed.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H400	Very toxic to aquatic life.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Skin Irrit. 2	Skin corrosion/irritation Category 2	
Skin Sens. 1	Skin sensitization, Category 1	
Skin Sens. 1A	Skin sensitization, Category 1A	
Skin Sens. 1B	Skin sensitization, Category 1B	

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.