## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Issue date: 12/2/2024 Version: 1.0



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

: SWEATER WEATHER CC-13119 10% in DPG Product name

Product code : CC-13119\_10% Type of product : Perfumes, fragrances

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial

For professional use only

Use of the substance/mixture : Perfumes, fragrances Function or use category : Odour agents

#### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Candle Craft Weiherwiese 10 65510 Idstein - Germany T 49-6126-9363 -0

info@candlecraft.de - www.candlecraft.de

#### 1.4. Emergency telephone number

No additional information available

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazardous to the aquatic environment - Chronic Hazard, H412

Category 3

Full text of H- and EUH-statements: see section 16

#### Adverse physicochemical, human health and environmental effects

No additional information available

## 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP)

Hazard statements (CLP) : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P273 - Avoid release to the environment.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

**EUH-statements** : EUH208 - Contains Patchouli oil, Hexyl cinnamic aldehyde, Linalool, (R)-p-mentha-1,8-

diene; d-limonene. May produce an allergic reaction.

Extra phrases : For professional users only.

#### 2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

## **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Not applicable

## 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ACETYL HEXAMETHYL TETRALIN	CAS-No.: 21145-77-7 EC-No.: 244-240-6	0.12 – 0.24	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Patchouli oil	CAS-No.: 8014-09-3 EC-No.: 616-944-7 EC Index-No.: 616-944-7	0.11 – 0.22	Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Hexyl cinnamic aldehyde	CAS-No.: 101-86-0 EC-No.: 202-983-3 REACH-no: 01-2119533092- 50	0.1 – 0.19526	Skin Sens. 1, H317 Aquatic Chronic 2, H411
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016-	0.07191258 – 0.14012887	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran; galaxolide; (HHCB)	CAS-No.: 1222-05-5 EC-No.: 214-946-9 EC Index-No.: 603-212-00-7 REACH-no: 01-2119488227-	0.06 – 0.125	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
(R)-p-mentha-1,8-diene; d-limonene substance with national workplace exposure limit(s) (DE, ES, FI, SI, NO, CH)	CAS-No.: 5989-27-5 EC-No.: 205-341-0 EC Index-No.: 601-096-00-2 REACH-no: 01-2119493353-	0.0551228 – 0.1135142	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
benzyl alcohol substance with national workplace exposure limit(s) (BG, CZ, DE, FI, LT, LV, PL, SI, CH)	CAS-No.: 100-51-6 EC-No.: 202-859-9 EC Index-No.: 603-057-00-5 REACH-no: 01-2119492630-	0.01 – 0.01069	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
.betaPinene substance with national workplace exposure limit(s) (BE, EE, ES, LT, PT, SE, NO)	CAS-No.: 127-91-3 EC-No.: 204-872-5	0.0007651 – 0.00114765	Flam. Liq. 3, H226
Alcohol C-10 substance with national workplace exposure limit(s) (BG, DE, LT, LV, RO, CH)	CAS-No.: 112-30-1 EC-No.: 203-956-9	0 – 0.00056	Aquatic Chronic 3, H412
Benzyl acetate substance with national workplace exposure limit(s) (BE, DK, ES, IE, LT, LV, PT, RO)	CAS-No.: 140-11-4 EC-No.: 205-399-7 REACH-no: 01-2119638272- 42	0 – 0.00018	Aquatic Chronic 3, H412
Aldehyde C-6 substance with national workplace exposure limit(s) (FI, PL)	CAS-No.: 66-25-1 EC-No.: 200-624-5	0 – 0.00014	Flam. Liq. 3, H226

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
isopentyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, DE, DK, EE, ES, FI, FR, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2 REACH-no: 01-2119548408- 32	0 – 0.00003	Flam. Liq. 3, H226
citral substance with national workplace exposure limit(s) (BE, ES, IE, PL, PT)	CAS-No.: 5392-40-5 EC-No.: 226-394-6 EC Index-No.: 605-019-00-3 REACH-no: 01-2119462829- 23	0 – 0.0000204	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
benzaldehyde substance with national workplace exposure limit(s) (BG, FI, HU, LT, LV, PL)	CAS-No.: 100-52-7 EC-No.: 202-860-4 EC Index-No.: 605-012-00-5 REACH-no: 01-2119455540-	0 - 0.00002	Acute Tox. 4 (Oral), H302
Caproic acid substance with national workplace exposure limit(s) (BG, LT, LV)	CAS-No.: 142-62-1 EC-No.: 205-550-7	0 – 0.00001	Eye Dam. 1, H318 Skin Corr. 1C, H314
Toluene substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3	0.00000008 - 0.00000012	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of H- and EUH-statements: see section 16

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water,

followed by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

persists.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

## 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

12/2/2024 (Issue date) EN (English) 3/31

#### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

#### 5.2. Special hazards arising from the substance or mixture

No additional information available

#### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

**Emergency procedures** : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Methods for cleaning up

Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Section 8. Exposure controls and personal protection.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Wash hands and other exposed areas with mild soap and water before eating, drinking or Precautions for safe handling

smoking and when leaving work. Provide good ventilation in process area to prevent

formation of vapour.

## 7.2. Conditions for safe storage, including any incompatibilities

: Keep only in the original container in a cool, well ventilated place away from : Keep Storage conditions

container closed when not in use.

Incompatible products : Strong bases. Strong acids. Incompatible materials Sources of ignition. Direct sunlight.

Germany

Storage class (LGK, TRGS 510) : LGK 12 - Non-combustible liquids

Joint storage table

LGK 1 LGK 2A I GK 2B LGK 3 LGK 4.1A LGK 4.1B LGK 5.1B LGK 4.2 LGK 4.3 **LGK 5.1A** LGK 6.1A LGK 6.1B LGK 6.1C LGK 5.10 LGK 5.2 LGK 6.1D LGK 6.2 LGK 7 LGK 8A LGK 8B LGK 12 LGK 11 **LGK 13** LGK 10 LGK 10-13

Joint storage not permitted for : LGK 1, LGK 6.2, LGK 7 : LGK 4.1A, LGK 4.3, LGK 5.1C

Joint storage with restrictions permitted for

LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A, Joint storage permitted for LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13

12/2/2024 (Issue date) EN (English) 4/31

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

#### **Switzerland**

Storage class (LK) : LK 10/12 - Liquids

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

### 8.1.1 National occupational exposure and biological limit values

(R)-p-mentha-1,8-diene; d-limonene (5989-27	7-5)
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	140 mg/m³
	25 ppm
HTP (OEL STEL)	280 mg/m³
	50 ppm
Germany - Occupational Exposure Limits (TRGS 9	900)
AGW (OEL TWA)	28 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	Skin notation, Skin sensitization
Slovenia - Occupational Exposure Limits	
OEL TWA	28 mg/m³
	5 ppm
OEL STEL	112 mg/m³
	20 ppm
OEL chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	168 mg/m³
	30 ppm
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	140 mg/m³
	25 ppm
Korttidsverdi (OEL STEL)	175 mg/m³ (value calculated)
	37.5 ppm (value calculated)
OEL chemical category	Allergenic substance
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	40 mg/m³
	7 ppm
KZGW (OEL STEL)	80 mg/m³

12/2/2024 (Issue date) EN (English) 5/31

## Safety Data Sheet

(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)		
	14 ppm	
OEL chemical category	Sensitizer	
Toluene (108-88-3)		
EU - Indicative Occupational Exposure Limit (IOE	L)	
IOEL TWA	192 mg/m³	
	50 ppm	
IOEL STEL	384 mg/m³	
	100 ppm	
Remark	Possibility of significant uptake through the skin	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	190 mg/m³	
	50 ppm	
MAK (OEL STEL)	380 mg/m³	
	100 ppm	
OEL chemical category	Skin notation	
Belgium - Occupational Exposure Limits		
OEL TWA	77 mg/m³	
	20 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Skin, Skin notation	
Bulgaria - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
Bulgaria - Biological limit values		
BLV	1.6 mmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of exposure or end of work shift	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA)	192 mg/m³	
	50 ppm	
KGVI (OEL STEL)	384 mg/m³	
	100 ppm	
OEL chemical category	Skin notation	

## Safety Data Sheet

Toluene (108-88-3)	
Croatia - Biological limit values	
BLV	1 mg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of the work shift 20 ppm Parameter: Toluene - Medium: final exhaled air - Sampling time: during exposure 2.5 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine) 1 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine)
Cyprus - Occupational Exposure Limits	·
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposur	e Limits
PEL (OEL TWA)	200 mg/m³
OEL chemical category	Potential for cutaneous absorption
Czech Republic - Biological limit values	
BLV	1.6 μmol/mmol Creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1000 μmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.) 1.5 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1600 mg/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.)
Denmark - Occupational Exposure Limit	s
OEL TWA	94 mg/m³
	25 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	81 mg/m³

## Safety Data Sheet

Toluene (108-88-3)	
	25 ppm
HTP (OEL STEL)	380 mg/m³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Finland - Biological limit values	
BLV	500 nmol/L Parameter: Toluene - Medium: blood - Sampling time: in the morning after a working day
France - Occupational Exposure Limits	
VME (OEL TWA)	76.8 mg/m³ (restrictive limit)
	20 ppm (restrictive limit)
VLE (OEL C/STEL)	384 mg/m³ (restrictive limit)
	100 ppm (restrictive limit)
OEL chemical category	Reproductive Toxin category 2, Risk of cutaneous absorption
France - Biological limit values	
BLV	20 μg/l Parameter: Toluene - Medium: blood - Sampling time: end of workweek (Semi-quantitative (ambiguous interpretation)) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (per the Authority, the values for this substance must be decided and/or determined on a case by case basis. Guidance for the calculation of and interpretation of values is provided in the source)
Germany - Occupational Exposure Limits (The	RGS 900)
AGW (OEL TWA)	190 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	50 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	Skin notation
Germany - Biological limit values (TRGS 903	)
Biological limit value	600 μg/l Parameter: Toluene - Medium: whole blood - Sampling time: immediately after exposure 75 μg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: for long-term exposures: at the end of the shift after several shifts 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: end of shift
Gibraltar - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
Greece - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³

## Safety Data Sheet

Toluene (108-88-3)		
	100 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	190 mg/m³	
CK (OEL STEL)	384 mg/m³	
OEL chemical category	Potential for cutaneous absorption	
Ireland - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Potential for cutaneous absorption	
Italy - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Latvia - Occupational Exposure Limits		
OEL TWA	50 mg/m³	
	14 ppm	
OEL chemical category	skin - potential for cutaneous exposure	
Latvia - Biological Exposure Indices		
BEI	1.6 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: end of shift	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	192 mg/m³	
	50 ppm	
TPRV (OEL STEL)	384 mg/m³	
	100 ppm	
OEL chemical category	Reproductive toxin, Skin notation	
Luxembourg - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Possibility of significant uptake through the skin	
Malta - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	

## Safety Data Sheet

Toluene (108-88-3)		
	100 ppm	
OEL chemical category	Possibility of significant uptake through the skin	
Netherlands - Occupational Exposure Limits		
TGG-8u (OEL TWA)	150 mg/m³	
	39 ppm	
TGG-15min (OEL STEL)	384 mg/m³	
	100 ppm	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	100 mg/m³	
NDSCh (OEL STEL)	200 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	192 mg/m³ (indicative limit value)	
	50 ppm (indicative limit value)	
OEL STEL	384 mg/m³ (indicative limit value)	
	100 ppm (indicative limit value)	
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure indicative limit value	
Romania - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Skin notation	
Romania - Biological limit values		
BLV	2 g/l Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 3 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA)	192 mg/m³	
	50 ppm	
NPHV (OEL C)	384 mg/m³ (also biological monitoring considered)	
OEL chemical category	Potential for cutaneous absorption	
Slovakia - Biological limit values		
BLV	600 μg/l Parameter: Toluene - Medium: blood - Sampling time: end of exposure or work shift	
	1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: after all work shifts (for long-term exposure)     1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of exposure or work shift     2401 mg/g creatinine Parameter: Hippuric acid - Sampling time: end of exposure or work shift	
Slovenia - Occupational Exposure Limits	1	
OEL TWA	192 mg/m³	

## Safety Data Sheet

Toluene (108-88-3)	
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Category 2, Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	192 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)
VLA-EC (OEL STEL)	384 mg/m³
	100 ppm
OEL chemical category	skin - potential for cutaneous absorption
Spain - Biological limit values	
BLV	0.6 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift 0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: start of last shift of workweek 0.08 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	192 mg/m³
	50 ppm
KGV (OEL STEL)	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limit	s
WEL TWA (OEL TWA)	191 mg/m³
	50 ppm
WEL STEL (OEL STEL)	384 mg/m³
	100 ppm
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	94 mg/m³
	25 ppm
Korttidsverdi (OEL STEL)	141 mg/m³ (value calculated)
	37.5 ppm (value calculated)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	190 mg/m³
	50 ppm
KZGW (OEL STEL)	760 mg/m³
	200 ppm
	Skin notation, Category 2 reproductive toxin

## Safety Data Sheet

Toluene (108-88-3)	
Switzerland - BAT	
BAT	600 μg/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 6.48 μmol/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 2 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 0.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 4.62 μmol/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 75 μg/l Parameter: Toluol - Medium: urine - Sampling time: end of shift
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	20 ppm
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 0.3 mg/g creatinine Parameter: o-Cresol with hydrolysis - Medium: urine - Sampling time: end of shift (background)
.betaPinene (127-91-3)	
Belgium - Occupational Exposure Limits	
OEL TWA	20 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	150 mg/m³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
	25 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
OEL STEL	300 mg/m³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
	50 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	150 mg/m³
	25 ppm
TPRV (OEL STEL)	300 mg/m³
	50 ppm
Portugal - Occupational Exposure Limits	
OEL TWA	20 ppm (Turpentine and selected Monoterpenes)
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	113 mg/m³
	20 ppm
OEL chemical category	Sensitizer

## Safety Data Sheet

.betaPinene (127-91-3)			
Sweden - Occupational Exposure Limits			
NGV (OEL TWA)	150 mg/m³		
	25 ppm		
KGV (OEL STEL)	300 mg/m³		
	50 ppm		
OEL chemical category	Sensitizer		
Norway - Occupational Exposure Limits			
Grenseverdi (OEL TWA)	140 mg/m³		
	25 ppm		
Korttidsverdi (OEL STEL)	175 mg/m³ (value calculated)		
	37.5 ppm (value calculated)		
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA	20 ppm (Turpentine and selected Monoterpenes)		
ACGIH chemical category	Not Classifiable as a Human Carcinogen, dermal sensitizer		
benzyl alcohol (100-51-6)			
Bulgaria - Occupational Exposure Limits			
OEL TWA	5 mg/m³		
Czech Republic - Occupational Exposure Limits			
PEL (OEL TWA)	40 mg/m³		
Finland - Occupational Exposure Limits			
HTP (OEL TWA)	45 mg/m³		
	10 ppm		
Germany - Occupational Exposure Limits (TRGS 90	00)		
AGW (OEL TWA)	22 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)		
	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)		
Chemical category	Skin notation		
Latvia - Occupational Exposure Limits			
OEL TWA	5 mg/m³		
Lithuania - Occupational Exposure Limits	Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³		
OEL chemical category	Skin notation		
Poland - Occupational Exposure Limits			
NDS (OEL TWA)	240 mg/m³		
Slovenia - Occupational Exposure Limits			
OEL TWA	22 mg/m³		
	5 ppm		
OEL STEL	44 mg/m³		

## Safety Data Sheet

benzyl alcohol (100-51-6)		
	10 ppm	
OEL chemical category	Potential for cutaneous absorption	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	22 mg/m³ (aerosol, vapour)	
	5 ppm (aerosol, vapour)	
OEL chemical category	Skin notation	
citral (5392-40-5)		
Belgium - Occupational Exposure Limits		
OEL TWA	32 mg/m³ (vapor and aerosol)	
	5 ppm (vapor and aerosol)	
OEL chemical category	Skin	
Ireland - Occupational Exposure Limits		
OEL TWA	5 ppm	
OEL STEL	15 ppm (calculated)	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	27 mg/m³	
NDSCh (OEL STEL)	54 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	5 ppm (inhalable fraction; vapor)	
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	5 ppm (inhalable fraction and vapor)	
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 ppm (inhalable fraction and vapor)	
ACGIH chemical category	Not Classifiable as a Human Carcinogen, Skin - potential significant contribution to overall exposure by the cutaneous route, dermal sensitizer	
Alcohol C-10 (112-30-1)		
Bulgaria - Occupational Exposure Limits		
OEL TWA	10 mg/m³	
Germany - Occupational Exposure Limits (TRGS 900)		
AGW (OEL TWA)	66 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
	10 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Latvia - Occupational Exposure Limits		
OEL TWA	10 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	10 mg/m³	

## Safety Data Sheet

Alcohol C-10 (112-30-1)		
Romania - Occupational Exposure Limits		
OEL TWA	100 mg/m³	
	15 ppm	
OEL STEL	200 mg/m³	
	30 ppm	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	66 mg/m³ (aerosol, vapour)	
	10 ppm (aerosol, vapour)	
KZGW (OEL STEL)	66 mg/m³ (aerosol, vapour)	
	10 ppm (aerosol, vapour)	
Benzyl acetate (140-11-4)		
Belgium - Occupational Exposure Limits		
OEL TWA	62 mg/m³	
	10 ppm	
Denmark - Occupational Exposure Limits		
OEL TWA	61 mg/m³	
	10 ppm	
OEL STEL	122 mg/m³	
	20 ppm	
Ireland - Occupational Exposure Limits		
OEL TWA	10 ppm	
OEL STEL	30 ppm (calculated)	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	10 ppm	
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen	
Romania - Occupational Exposure Limits		
OEL TWA	50 mg/m³	
	8 ppm	
OEL STEL	80 mg/m³	
	13 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	62 mg/m³	
	10 ppm	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	10 ppm	

## Safety Data Sheet

Benzyl acetate (140-11-4)		
ACGIH chemical category	Not Classifiable as a Human Carcinogen	
Aldehyde C-6 (66-25-1)		
Finland - Occupational Exposure Limits		
HTP (OEL STEL)	42 mg/m³	
	10 ppm	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	40 mg/m³	
NDSCh (OEL STEL)	80 mg/m³	
isopentyl acetate (123-92-2)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	270 mg/m³	
	50 ppm	
IOEL STEL	540 mg/m³	
	100 ppm	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	270 mg/m³ (Pentyl acetate (all isomers))	
	50 ppm (Pentyl acetate (all isomers))	
MAK (OEL STEL)	540 mg/m³ (Pentylacetate)	
	100 ppm (Pentylacetate)	
Belgium - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Bulgaria - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA)	270 mg/m³	
	50 ppm	
KGVI (OEL STEL)	540 mg/m³	
	100 ppm	
Cyprus - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	

## Safety Data Sheet

isopentyl acetate (123-92-2)		
	100 ppm	
Denmark - Occupational Exposure Limits		
OEL TWA	271 mg/m³ (Amyl acetate, all isomers)	
	50 ppm (Amyl acetate, all isomers)	
OEL STEL	540 mg/m³	
	100 ppm	
Estonia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	270 mg/m³ (Pentyl acetate)	
	50 ppm (Pentyl acetate)	
HTP (OEL STEL)	540 mg/m³	
	100 ppm	
France - Occupational Exposure Limits		
VME (OEL TWA)	270 mg/m³ (restrictive limit)	
	50 ppm (restrictive limit)	
VLE (OEL C/STEL)	540 mg/m³ (restrictive limit)	
	100 ppm (restrictive limit)	
Germany - Occupational Exposure Limits (TRGS 9	00)	
AGW (OEL TWA)	270 mg/m³	
	50 ppm	
Gibraltar - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Greece - Occupational Exposure Limits		
OEL TWA	530 mg/m³	
	100 ppm	
OEL STEL	800 mg/m³	
	150 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	270 mg/m³	
CK (OEL STEL)	540 mg/m³	
Ireland - Occupational Exposure Limits		
OEL TWA	260 mg/m³	

## Safety Data Sheet

isopentyl acetate (123-92-2)			
	50 ppm		
OEL STEL	520 mg/m³		
	100 ppm		
Italy - Occupational Exposure Limits			
OEL TWA	270 mg/m³		
	50 ppm		
OEL STEL	540 mg/m³		
	100 ppm		
Latvia - Occupational Exposure Limits			
OEL TWA	270 mg/m³		
	50 ppm		
Lithuania - Occupational Exposure Limits			
IPRV (OEL TWA)	270 mg/m³		
	50 ppm		
TPRV (OEL STEL)	540 mg/m³		
	100 ppm		
Luxembourg - Occupational Exposure Limits			
OEL TWA	270 mg/m³		
	50 ppm		
OEL STEL	540 mg/m³		
	100 ppm		
Malta - Occupational Exposure Limits			
OEL TWA	270 mg/m³		
	50 ppm		
OEL STEL	540 mg/m³		
	100 ppm		
Netherlands - Occupational Exposure Limits			
TGG-15min (OEL STEL)	530 mg/m³		
	98.1 ppm		
Poland - Occupational Exposure Limits			
NDS (OEL TWA)	250 mg/m³		
NDSCh (OEL STEL)	500 mg/m³		
Portugal - Occupational Exposure Limits			
OEL TWA	270 mg/m³ (indicative limit value)		
	50 ppm (indicative limit value (Pentyl acetate, all isomers)		
OEL STEL	540 mg/m³ (indicative limit value)		
	100 ppm (indicative limit value)		
Romania - Occupational Exposure Limits			
Momania - Occupational Exposure Limits			

## Safety Data Sheet

isopentyl acetate (123-92-2)		
	50 ppm	
	540 mg/m³	
	100 ppm	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA)	270 mg/m³	
	50 ppm	
NPHV (OEL C)	540 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	270 mg/m³ (indicative limit value)	
	50 ppm (indicative limit value)	
VLA-EC (OEL STEL)	540 mg/m³	
	100 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	270 mg/m³ (Pentyl acetates)	
	50 ppm (Pentyl acetates)	
KGV (OEL STEL)	540 mg/m³ (Pentyl acetates)	
	100 ppm (Pentyl acetates)	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA)	260 mg/m³	
	50 ppm	
Korttidsverdi (OEL STEL)	325 mg/m³ (value calculated)	
	75 ppm (value calculated)	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	260 mg/m³ (Pentyl acetate all isomers)	
	50 ppm (Pentyl acetate all isomers)	
KZGW (OEL STEL)	260 mg/m³ (Pentyl acetate all isomers)	
	50 ppm (Pentyl acetate all isomers)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	50 ppm (Pentyl acetate, all isomers)	
ACGIH OEL STEL	100 ppm (Pentyl acetate, all isomers)	
benzaldehyde (100-52-7)		
Bulgaria - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
	<u> </u>	

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

benzaldehyde (100-52-7)		
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	4.4 mg/m³	
	1 ppm	
HTP (OEL C)	17.4 mg/m³	
	4 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³	
CK (OEL STEL)	10 mg/m³	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	10 mg/m³	
NDSCh (OEL STEL)	40 mg/m³	
Caproic acid (142-62-1)		
Bulgaria - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

No additional information available

## 8.1.5. Control banding

No additional information available

#### 8.2. Exposure controls

## 8.2.1. Appropriate engineering controls

No additional information available

## 8.2.2. Personal protection equipment

#### Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



#### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

#### 8.2.2.1. Eye and face protection

#### Eye protection:

Chemical goggles or safety glasses

#### 8.2.2.2. Skin protection

#### Hand protection:

Wear protective gloves.

#### 8.2.2.3. Respiratory protection

#### Respiratory protection:

Wear appropriate mask

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

#### Other information:

Do not eat, drink or smoke during use.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Conforms to standard.

Odour characteristic. Odour threshold Not available Melting point Not available Freezing point Not available Boiling point Not available Flammability : Non flammable. Lower explosion limit : Not available Upper explosion limit : Not available Flash point : > 93 °C Auto-ignition temperature : Not available : Not available Decomposition temperature : Not available рΗ : Not available Viscosity, kinematic Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available : Not available Vapour pressure Vapour pressure at 50°C : Not available Density : Not available Relative density : Not available

#### 9.2. Other information

Particle characteristics

Relative vapour density at 20°C

## 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No additional information available

: Not available

: Not applicable

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

#### 10.2. Chemical stability

Not established.

#### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

#### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (inhalation) :	Not classified	
ACETYL HEXAMETHYL TETRALIN (21145-77-7)		
LD50 oral rat	570 mg/kg (Source: NLM_CIP)	
LD50 oral	1000 mg/kg bodyweight	
LD50 dermal rabbit	> 5 g/kg (Source: NLM_HSDB)	
Patchouli oil (8014-09-3)		
LD50 oral rat	> 5 g/kg (Source: NLM_CIP)	
Hexyl cinnamic aldehyde (101-86-0)		
LD50 oral rat	3100 mg/kg (Source: NLM_CIP)	
LD50 oral	3100 mg/kg bodyweight	
LD50 dermal rabbit	> 3000 mg/kg (Source: EPA_HPV)	
LC50 Inhalation - Rat	> 5 mg/l/4h	
Linalool (78-70-6)		
LD50 oral	2790 mg/kg	
1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran; galaxolide; (HHCB) (1222-05-5)		
LD50 oral rat	> 3250 mg/kg (Source: CHEMVIEW)	
LD50 dermal rabbit	> 3250 mg/kg (Source: CHEMVIEW)	
LC50 Inhalation - Rat	> 5.04 mg/l/4h	
(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)		
LD50 oral rat	4400 mg/kg (Source: CHEMVIEW)	
LD50 dermal rabbit	> 5 g/kg (Source: CHEMVIEW)	
Toluene (108-88-3)		
LD50 oral rat	2600 mg/kg (Source: JAPAN_GHS)	

## Safety Data Sheet

Toluene (108-88-3)	
LD50 dermal rabbit	12000 mg/kg (Source: JAPAN_GHS)
LC50 Inhalation - Rat	12.5 mg/l/4h
.betaPinene (127-91-3)	
LD50 oral rat	> 5000 mg/kg (Source: EPA_HPV)
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)
benzyl alcohol (100-51-6)	
LD50 oral rat	1230 mg/kg (Source: NLM_CIP)
LD50 oral	1570 mg/kg
citral (5392-40-5)	
LD50 oral rat	4960 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	2250 mg/kg (Source: NLM_CIP)
Alcohol C-10 (112-30-1)	
LD50 oral rat	4720 mg/kg (Source: NZ_CCID)
LD50 dermal rat	> 5000 mg/kg (Source: ECHA_API)
LC50 Inhalation - Rat	> 71 mg/l (Exposure time: 1 h Source: ECHA_API)
Benzyl acetate (140-11-4)	
LD50 oral rat	2490 mg/kg (Source: JAPAN_GHS)
LD50 oral	2490 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: JAPAN_GHS)
Aldehyde C-6 (66-25-1)	
LD50 oral rat	4890 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 8100 mg/kg (Source: ECHA_API)
benzaldehyde (100-52-7)	
LD50 oral rat	1292 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	> 1250 mg/kg (Source: JAPAN_GHS)
LC50 Inhalation - Rat	< 5 mg/l/4h
Caproic acid (142-62-1)	
LD50 oral rat	3 g/kg (Source: NLM_HSDB)
LD50 oral	4000 mg/kg bodyweight
LD50 dermal rabbit	630 mg/kg (Source: NLM_HSDB)
	Not classified  Based on available data, the classification criteria are not met
Serious eye damage/irritation :	Not classified
	Based on available data, the classification criteria are not met  Not classified
	Based on available data, the classification criteria are not met
	Not classified
	Based on available data, the classification criteria are not met  Not classified
	Based on available data, the classification criteria are not met

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)		
IARC group	3 - Not classifiable	
Toluene (108-88-3)		
IARC group	3 - Not classifiable	
Benzyl acetate (140-11-4)		
IARC group	3 - Not classifiable	
Reproductive toxicity :	Not classified	
Additional information :	Based on available data, the classification criteria are not met	
STOT-single exposure :	Not classified	
	Based on available data, the classification criteria are not met	
Additional information .	Dased on available data, the dassilication chiena are not met	
Toluene (108-88-3)		
STOT-single exposure	May cause drowsiness or dizziness.	
STOT-repeated exposure :	Not classified	
Additional information :	Based on available data, the classification criteria are not met	
Toluene (108-88-3)		
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
Aspiration hazard :	Not classified	
Additional information :	Based on available data, the classification criteria are not met	
(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)		
Hydrocarbon	Yes	
Toluene (108-88-3)		
Hydrocarbon	Yes	
.betaPinene (127-91-3)		
Hydrocarbon	Yes	

### 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

No additional information available

#### 11.2.2. Other information

Potential adverse human health effects and symptoms

: Based on available data, the classification criteria are not met

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Harmful to aquatic life with long lasting effects.

(chronic)

(Chronic)		
Linalool (78-70-6)		
EC50 96h - Algae [1]	88.3 mg/l (Species: Desmodesmus subspicatus)	
1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran; galaxolide; (HHCB) (1222-05-5)		
LC50 - Fish [1]	0.452 mg/l Wolf, 1996d-27682	
LC50 - Other aquatic organisms [1]	> 0.14 mg/l REACH DOSSIER Pimephales promelas	

## Safety Data Sheet

1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran; galaxolide; (HHCB) (1222-05-5)		
EC50 - Crustacea [2]	260 μg/l REACH Dossier	
EC50 - Other aquatic organisms [1]	0.131 mg/l REACH Dossier	
(R)-p-mentha-1,8-diene; d-limonene (5989-27-	5)	
LC50 - Fish [1]	0.619 – 0.796 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
LC50 - Fish [2]	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: EPA)	
Toluene (108-88-3)		
LC50 - Fish [1]	15.22 – 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
LC50 - Fish [2]	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)	
EC50 - Crustacea [1]	5.46 – 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
EC50 - Crustacea [2]	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 72h - Algae [1]	12.5 mg/l (Species: Pseudokirchneriella subcapitata [static])	
EC50 96h - Algae [1]	> 433 mg/l (Species: Pseudokirchneriella subcapitata)	
benzyl alcohol (100-51-6)		
LC50 - Fish [1]	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)	
LC50 - Fish [2]	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)	
EC50 - Crustacea [1]	23 mg/l (Exposure time: 48 h - Species: water flea)	
citral (5392-40-5)		
EC50 - Crustacea [1]	7 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 72h - Algae [1]	16 mg/l (Species: Desmodesmus subspicatus)	
EC50 96h - Algae [1]	19 mg/l (Species: Desmodesmus subspicatus)	
Alcohol C-10 (112-30-1)		
LC50 - Fish [1]	2.2 – 2.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
LC50 - Fish [2]	4.12 – 6.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)	
EC50 - Crustacea [1]	3 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
Aldehyde C-6 (66-25-1)		
LC50 - Fish [1]	12 – 16.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
benzaldehyde (100-52-7)		
LC50 - Fish [1]	10.6 – 11.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: EPA)	
LC50 - Fish [2]	12.69 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: IUCLID)	
Caproic acid (142-62-1)	Caproic acid (142-62-1)	
LC50 - Fish [1]	306 – 334 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
LC50 - Fish [2]	88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)	

## Safety Data Sheet

12.2. Persistence and degradability		
SWEATER WEATHER CC-13119 10% in DPG		
Persistence and degradability	Not established.	
ACETYL HEXAMETHYL TETRALIN (21145-77-	7)	
Persistence and degradability	Rapidly degradable	
Patchouli oil (8014-09-3)		
Persistence and degradability	Rapidly degradable	
Hexyl cinnamic aldehyde (101-86-0)		
Persistence and degradability	Rapidly degradable	
Linalool (78-70-6)		
Persistence and degradability	Rapidly degradable	
1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylin	ndeno[5,6-c]pyran; galaxolide; (HHCB) (1222-05-5)	
Persistence and degradability	Rapidly degradable	
(R)-p-mentha-1,8-diene; d-limonene (5989-27-5	5)	
Persistence and degradability	Rapidly degradable	
Toluene (108-88-3)		
Persistence and degradability	Rapidly degradable	
.betaPinene (127-91-3)		
Persistence and degradability	Rapidly degradable	
benzyl alcohol (100-51-6)		
Persistence and degradability	Rapidly degradable	
citral (5392-40-5)		
Persistence and degradability	Rapidly degradable	
Alcohol C-10 (112-30-1)		
Persistence and degradability	Rapidly degradable	
Benzyl acetate (140-11-4)		
Persistence and degradability	Rapidly degradable	
Aldehyde C-6 (66-25-1)		
Persistence and degradability	Rapidly degradable	
isopentyl acetate (123-92-2)		
Persistence and degradability	Rapidly degradable	
benzaldehyde (100-52-7)		
Persistence and degradability	Rapidly degradable	
Caproic acid (142-62-1)		
Persistence and degradability	Rapidly degradable	

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

## 12.3. Bioaccumulative potential

SWEATER WEATHER CC-13119 10% in DPG  Bioaccumulative potential Not established.  ACETYL HEXAMETHYL TETRALIN (21145-77-7)  Partition coefficient n-octanol/water (Log Pow) 5.7 (at 24 °C)			
ACETYL HEXAMETHYL TETRALIN (21145-77-7)			
Partition coefficient proctangl/water (Log Pow) 5.7 (at 24 °C)			
3.7 (at 24 G)			
1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran; galaxolide; (HHCB) (1222-05-5)			
BCF - Fish [1] (1618 dimensionless (whole body w.w.)			
Partition coefficient n-octanol/water (Log Pow) 5.3 (at 25 °C (at pH 7)			
(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)			
Partition coefficient n-octanol/water (Log Pow) 4.38 (at 37 °C (at pH 7.2)			
Toluene (108-88-3)			
Partition coefficient n-octanol/water (Log Pow) 2.73 (at 20 °C (at pH 7)			
benzyl alcohol (100-51-6)			
Partition coefficient n-octanol/water (Log Pow) 1.05			
citral (5392-40-5)			
Partition coefficient n-octanol/water (Log Pow) 2.76 (at 25 °C)			
Alcohol C-10 (112-30-1)			
Partition coefficient n-octanol/water (Log Pow) 4.5 (at 25 °C (at pH 6)			
Benzyl acetate (140-11-4)			
Partition coefficient n-octanol/water (Log Pow) 1.96 (at 25 °C (at pH 7)			
Aldehyde C-6 (66-25-1)			
Partition coefficient n-octanol/water (Log Pow) 2.3 (at 25 °C (at pH 5)			
isopentyl acetate (123-92-2)			
Partition coefficient n-octanol/water (Log Pow) 2.7 (at 35 °C)			
benzaldehyde (100-52-7)			
BCF - Fish [1] (no significant bioaccumulation)			
Partition coefficient n-octanol/water (Log Pow) 1.4 (at 25 °C)			
Caproic acid (142-62-1)			
Partition coefficient n-octanol/water (Log Pow) 1.88			

## 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

## 12.6. Endocrine disrupting properties

No additional information available

## 12.7. Other adverse effects

Additional information : Avoid release to the environment.

12/2/2024 (Issue date) EN (English) 27/31

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product/Packaging disposal recommendations

**Ecological information** 

**HP Code** 

- : Dispose in a safe manner in accordance with local/national regulations.
- : Avoid release to the environment.
- : HP14 "Ecotoxic:" waste which presents or may present immediate or delayed risks for one

or more sectors of the environment

## **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID number					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.2. UN proper shipping name					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.3. Transport hazard class(es)					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.4. Packing group					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.5. Environmental hazards					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
No supplementary information available					

## 14.6. Special precautions for user

#### **Overland transport**

Not applicable

#### Transport by sea

Not applicable

#### Air transport

Not applicable

#### **Inland waterway transport**

Not applicable

#### Rail transport

Not applicable

#### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

#### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

#### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

#### **REACH Annex XVII (Restriction List)**

EU restriction list (REACH Annex XVII)			
Reference code	Applicable on	Entry title or description	
3(a)	(R)-p-mentha-1,8-diene; d-limonene; Toluene; .betaPinene; Aldehyde C-6; isopentyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	
3(b)	Patchouli oil; Hexyl cinnamic aldehyde; Linalool; (R)-p-mentha-1,8-diene; d-limonene; Toluene; benzyl alcohol; citral; benzaldehyde; Caproic acid	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	
3(c)	SWEATER WEATHER CC-13119 10% in DPG; Patchouli oil; Hexyl cinnamic aldehyde; 1,3,4,6,7,8-hexahydro- 4,6,6,7,8,8- hexamethylindeno[5,6- c]pyran; galaxolide; (HHCB); (R)-p-mentha- 1,8-diene; d-limonene; Alcohol C-10; Benzyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	
40.	(R)-p-mentha-1,8-diene; d-limonene; Toluene; .betaPinene; Aldehyde C-6; isopentyl acetate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	
48.	Toluene	Toluene	

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

## **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

#### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

#### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

#### **Drug Precursors Regulation (273/2004)**

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Toluene		108-88-3	2902 30 00	Category 3		Annex I

#### 15.1.2. National regulations

#### **France**

Occupational diseases		
Code	Description	
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them	
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide	

#### Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

**Netherlands** 

ABM category : A(3) - hazardous for aquatic organisms, may have longterm hazardous effects in aquatic

environment

SZW-lijst van kankerverwekkende stoffen

SZW-lijst van mutagene stoffen

SZW-lijst van reprotoxische stoffen – Borstvoeding

SZW-lijst van reprotoxische stoffen -

Vruchtbaarheid

Classification remarks

**Danish National Regulations** 

**Denmark** 

SZW-lijst van reprotoxische stoffen – Ontwikkeling

None of the components are listedNone of the components are listed

None of the components are listedNone of the components are listed

: Toluene is listed

the product

#### ....

No chemical safety assessment has been carried out

## 15.2. Chemical safety assessment

#### **SECTION 16: Other information**

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances

and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and

: Emergency management guidelines for the storage of flammable liquids must be followed

: Pregnant/breastfeeding women working with the product must not be in direct contact with

amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:		
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	

12/2/2024 (Issue date) EN (English) 30/31

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Full text of H- and EUI	H-statements:
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains Patchouli oil, Hexyl cinnamic aldehyde, Linalool, (R)-p-mentha-1,8-diene; d-limonene. May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.