

WHITE SANDALWOOD CC-13211 10% in DPG



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Issue date: 6/25/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : WHITE SANDALWOOD CC-13211 10% in DPG
Product code : CC-13211_10%
Type of product : Perfumes, Fragrances

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial
For professional use only
Use of the substance/mixture : Perfumes, Fragrances
Function or use category : Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Candle Craft
Weiherwiese 10
65510 Idstein - Germany
T 49-6126-9363 -0
info@candlecraft.de - www.candlecraft.de

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitization, Category 1 H317
Hazardous to the aquatic environment – Chronic Hazard H411
Category 2

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

GHS09

Signal word (CLP) :

Warning

Contains :

1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone

Hazard statements (CLP) :

H317 - May cause an allergic skin reaction.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

WHITE SANDALWOOD CC-13211 10% in DPG

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P321 - Specific treatment (see supplemental first aid instruction on this label).

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	2.905 – 4.905	Not classified
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone	CAS-No.: 54464-57-2 EC-No.: 259-174-3 REACH-no: 01-2119489989-04	0.78 – 1.56	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 1, H410
Sandal Mysore Core	CAS-No.: 28219-60-5 EC-No.: 248-907-2	0.3275 – 0.655	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran, galaxolide, (HHCB)	CAS-No.: 1222-05-5 EC-No.: 214-946-9 EC Index-No.: 603-212-00-7 REACH-no: 01-2119488227-29	0.264 – 0.528	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
ACETYL HEXAMETHYL TETRALIN	CAS-No.: 21145-77-7 EC-No.: 244-240-6	0.1 – 0.2	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
benzyl alcohol substance with national workplace exposure limit(s) (BG, CZ, DE, FI, LT, LV, PL, SI, CH)	CAS-No.: 100-51-6 EC-No.: 202-859-9 EC Index-No.: 603-057-00-5 REACH-no: 01-2119492630-38	0.0225 – 0.045	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Carbitol substance with national workplace exposure limit(s) (AT, DE, EE, SE, SI, CH)	CAS-No.: 111-90-0 EC-No.: 203-919-7 REACH-no: 01-2119475105-42	0.01265775 – 0.0253155	Not classified

Full text of H- and EUH-statements: see section 16

WHITE SANDALWOOD CC-13211 10% in DPG

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
-------------------------	--

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

WHITE SANDALWOOD CC-13211 10% in DPG

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.
Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.

Germany

Storage class (LGK, TRGS 510) : LGK 12 - Non-combustible liquids

Joint storage table :

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for : LGK 1, LGK 6.2, LGK 7

Joint storage with restrictions permitted for : LGK 4.1A, LGK 4.3, LGK 5.1C

Joint storage permitted for : LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13

Switzerland

Storage class (LK) : LK 10/12 - Liquids

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Dipropylene glycol monomethyl ether (34590-94-8)

EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	308 mg/m ³
	50 ppm
Remark	Possibility of significant uptake through the skin

Austria - Occupational Exposure Limits

MAK (OEL TWA)	307 mg/m ³ (mixed isomers)
	50 ppm (mixed isomers)
MAK (OEL STEL)	614 mg/m ³ (isomers mixtures)
	100 ppm (isomers mixtures)

OEL chemical category : skin notation

Belgium - Occupational Exposure Limits

OEL TWA	308 mg/m ³
---------	-----------------------

WHITE SANDALWOOD CC-13211 10% in DPG

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
	50 ppm
OEL chemical category	Skin, skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	308 mg/m ³
	50 ppm
OEL chemical category	skin notation
Cyprus - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	270 mg/m ³
OEL chemical category	Potential for cutaneous absorption
Denmark - Occupational Exposure Limits	
OEL TWA	309 mg/m ³
	50 ppm
OEL STEL	618 mg/m ³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	310 mg/m ³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
France - Occupational Exposure Limits	
VME (OEL TWA)	308 mg/m ³ (restrictive limit)
	50 ppm (restrictive limit)
OEL chemical category	Risk of cutaneous absorption
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	310 mg/m ³ (isomer mixture)
	50 ppm (isomer mixture)
Gibraltar - Occupational Exposure Limits	
OEL TWA	308 mg/m ³

WHITE SANDALWOOD CC-13211 10% in DPG

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
	50 ppm
OEL chemical category	skin notation
Greece - Occupational Exposure Limits	
OEL TWA	600 mg/m ³
	100 ppm
OEL STEL	900 mg/m ³
	150 ppm
OEL chemical category	skin - potential for cutaneous absorption
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	308 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ ((2-Methoxymethylethoxy)propanol)
	50 ppm ((2-Methoxymethylethoxy)propanol)
OEL STEL	924 mg/m ³ (calculated (2-(2-Methoxypropoxy)-1-propanol)
	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ (1-(3-Methoxypropoxy)propan-1-ol)
	50 ppm (1-(3-Methoxypropoxy)propan-1-ol)
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	skin - potential for cutaneous exposure
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	300 mg/m ³ (2-(2-Methoxypropoxy)-propanol)
	50 ppm (2-(2-Methoxypropoxy)-propanol)
TPRV (OEL STEL)	450 mg/m ³ (2-(2-Methoxypropoxy)-propanol)
	75 ppm (2-(2-Methoxypropoxy)-propanol)
OEL chemical category	skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin

WHITE SANDALWOOD CC-13211 10% in DPG

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	300 mg/m ³
	48.7 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m ³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
NDSCh (OEL STEL)	480 mg/m ³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
Portugal - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
OEL STEL	150 ppm
OEL chemical category	skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	skin notation
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	308 mg/m ³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
Slovenia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL STEL	308 mg/m ³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	308 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
OEL chemical category	skin - potential for cutaneous absorption
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	300 mg/m ³
	50 ppm
KGV (OEL STEL)	450 mg/m ³
	75 ppm
OEL chemical category	skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	308 mg/m ³
	50 ppm

WHITE SANDALWOOD CC-13211 10% in DPG

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
WEL STEL (OEL STEL)	924 mg/m ³ (calculated)
	150 ppm (calculated)
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	300 mg/m ³
	50 ppm
Korttidsverdi (OEL STEL)	375 mg/m ³ (value calculated)
	75 ppm (value calculated)
OEL chemical category	skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	300 mg/m ³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
KZGW (OEL STEL)	300 mg/m ³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	50 ppm (Dipropylene glycol methyl ether)
benzyl alcohol (100-51-6)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	40 mg/m ³
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	45 mg/m ³
	10 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	22 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	skin notation
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m ³
OEL chemical category	skin notation
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m ³
Slovenia - Occupational Exposure Limits	
OEL TWA	22 mg/m ³

WHITE SANDALWOOD CC-13211 10% in DPG

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

benzyl alcohol (100-51-6)	
	5 ppm
OEL STEL	44 mg/m ³
	10 ppm
OEL chemical category	Potential for cutaneous absorption
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	22 mg/m ³ (aerosol, vapour)
	5 ppm (aerosol, vapour)
OEL chemical category	skin notation
Carbitol (111-90-0)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	35 mg/m ³
	6 ppm
MAK (OEL STEL)	140 mg/m ³
	24 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	50.1 mg/m ³
	10 ppm
OEL chemical category	skin notation
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	35 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	6 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Slovenia - Occupational Exposure Limits	
OEL TWA	35 mg/m ³
	6 ppm
OEL STEL	70 mg/m ³
	12 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	80 mg/m ³
	15 ppm
KGV (OEL STEL)	170 mg/m ³
	30 ppm
OEL chemical category	skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	50 mg/m ³ (aerosol, inhalable dust, vapour)
KZGW (OEL STEL)	100 mg/m ³ (aerosol, inhalable dust, vapour)

8.1.2. Recommended monitoring procedures

No additional information available

WHITE SANDALWOOD CC-13211 10% in DPG

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses

8.2.2.2. Skin protection

Hand protection:

Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Standard.
Odor	: characteristic.
Odor threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 93 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available

WHITE SANDALWOOD CC-13211 10% in DPG

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapor pressure	: Not available
Vapor pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapor density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Dipropylene glycol monomethyl ether (34590-94-8)

LD50 oral rat	5.35 g/kg (Source: NLM_HSDB)
LD50 dermal rabbit	9500 mg/kg (Source: NLM_CIP)

1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran, galaxolide, (HHCB) (1222-05-5)

LD50 oral rat	> 3250 mg/kg (Source: CHEMVIEW)
LD50 dermal rabbit	> 3250 mg/kg (Source: CHEMVIEW)
LC50 Inhalation - Rat	> 5.04 mg/l/4h

ACETYL HEXAMETHYL TETRALIN (21145-77-7)

LD50 oral rat	570 mg/kg (Source: NLM_CIP)
---------------	-----------------------------

WHITE SANDALWOOD CC-13211 10% in DPG

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ACETYL HEXAMETHYL TETRALIN (21145-77-7)	
LD50 oral	1000 mg/kg body weight
LD50 dermal rabbit	> 5 g/kg (Source: NLM_HSDB)
benzyl alcohol (100-51-6)	
LD50 oral rat	1230 mg/kg (Source: NLM_CIP)
LD50 oral	1570 mg/kg
Carbitol (111-90-0)	
LD50 oral rat	10502 mg/kg (Source: OECD_SIDS)
LD50 dermal rabbit	9143 mg/kg (Source: OECD_SIDS)
LC50 Inhalation - Rat	> 5240 mg/m ³ (Exposure time: 4 h Source: NLM_CIP)

Skin corrosion/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified
Additional information	: Based on available data, the classification criteria are not met

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

Dipropylene glycol monomethyl ether (34590-94-8)	
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)
1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran, galaxolide, (HHCb) (1222-05-5)	
LC50 - Fish [1]	0.452 mg/l Wolf, 1996d-27682

WHITE SANDALWOOD CC-13211 10% in DPG

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran, galaxolide, (HHCB) (1222-05-5)	
LC50 - Other aquatic organisms [1]	> 0.14 mg/l REACH DOSSIER Pimephales promelas
EC50 - Crustacea [2]	260 µg/l REACH Dossier
EC50 - Other aquatic organisms [1]	0.131 mg/l REACH Dossier
benzyl alcohol (100-51-6)	
LC50 - Fish [1]	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
LC50 - Fish [2]	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
EC50 - Crustacea [1]	23 mg/l (Exposure time: 48 h - Species: water flea)
Carbitol (111-90-0)	
LC50 - Fish [1]	10000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
LC50 - Fish [2]	19100 – 23900 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through] Source: EPA)
EC50 - Crustacea [1]	3940 – 4670 mg/l (Exposure time: 48 h - Species: Daphnia magna)
12.2. Persistence and degradability	
WHITE SANDALWOOD CC-13211 10% in DPG	
Persistence and degradability	Not established.
Dipropylene glycol monomethyl ether (34590-94-8)	
Persistence and degradability	Rapidly degradable
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone (54464-57-2)	
Persistence and degradability	Rapidly degradable
Sandal Mysore Core (28219-60-5)	
Persistence and degradability	Rapidly degradable
1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran, galaxolide, (HHCB) (1222-05-5)	
Persistence and degradability	Rapidly degradable
ACETYL HEXAMETHYL TETRALIN (21145-77-7)	
Persistence and degradability	Rapidly degradable
benzyl alcohol (100-51-6)	
Persistence and degradability	Rapidly degradable
Carbitol (111-90-0)	
Persistence and degradability	Rapidly degradable
12.3. Bioaccumulative potential	
WHITE SANDALWOOD CC-13211 10% in DPG	
Bioaccumulative potential	Not established.
Dipropylene glycol monomethyl ether (34590-94-8)	
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7)
1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran, galaxolide, (HHCB) (1222-05-5)	
BCF - Fish [1]	(1618 dimensionless (whole body w.w.)

WHITE SANDALWOOD CC-13211 10% in DPG

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran, galaxolide, (HHCB) (1222-05-5)

Partition coefficient n-octanol/water (Log Pow) 5.3 (at 25 °C (at pH 7))

ACETYL HEXAMETHYL TETRALIN (21145-77-7)

Partition coefficient n-octanol/water (Log Pow) 5.7 (at 24 °C)

benzyl alcohol (100-51-6)

Partition coefficient n-octanol/water (Log Pow) 1.05

Carbitol (111-90-0)

Partition coefficient n-octanol/water (Log Pow) -0.8

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecological information : Avoid release to the environment.
HP code : HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.
HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information






In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER)	Environmentally hazardous substance, liquid, n.o.s. (ISO E SUPER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER)
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (ISO E SUPER), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER), 9, III

WHITE SANDALWOOD CC-13211 10% in DPG



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.3. Transport hazard class(es)				
9	9	9	9	9
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: M6
Special provision (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90
Orange plates	:  
Tunnel restriction code (ADR)	: -
EAC	: •3Z

Transport by sea

Special provision (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-F
Stowage category (IMDG)	: A

Air transport

PCA Excepted quantities (IATA)	: E1
--------------------------------	------

WHITE SANDALWOOD CC-13211 10% in DPG

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provision (IATA)	: A97, A158, A197, A215
ERG code (IATA)	: 9L

Inland waterway transport

Classification code (ADN)	: M6
Special provision (ADN)	: 274, 335, 375, 601
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: M6
Special provision (RID)	: 274, 335, 375, 601
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBV
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Special provisions for carriage - Loading, unloading and handling (RID)	: CW13, CW31
Colis express (express parcels) (RID)	: CE8
Hazard identification number (RID)	: 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	WHITE SANDALWOOD CC-13211 10% in DPG ; 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8-tetramethyl-2-naphthalenyl)ethanone ; Sandal Mysore Core ; benzyl alcohol	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

WHITE SANDALWOOD CC-13211 10% in DPG

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(c)	WHITE SANDALWOOD CC-13211 10% in DPG ; 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone ; Sandal Mysore Core ; 1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran, galaxolide, (HHCB)	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

REACH Annex XIV (Authorisation List)

Contains no REACH Annex XIV substances.

REACH Candidate List (SVHC)

Contains no REACH candidate substance

PIC Regulation (Prior Informed Consent)

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Ozone Regulation (1005/2009)

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

Explosives Precursors Regulation (2019/1148)

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Drug Precursors Regulation (273/2004)

Contains no substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

15.1.2. National regulations

France

Professional diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 2, significant hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

WHITE SANDALWOOD CC-13211 10% in DPG

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Netherlands

ABM category	: A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment
SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: None of the components are listed

Denmark

Classification remarks	: Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Other information	: None.

Full text of H- and EUH-phrases:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.