

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Type 16 - DiJad CC-16039 10% in DPG  
Product code : CC-16039\_10%  
Type of product : Perfumes, fragrances

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial  
For professional use only  
Use of the substance/mixture : Perfumes, fragrances  
Function or use category : Odour agents

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Candle Craft  
Weiherrwiese 10  
65510 Idstein - Germany  
T 49-6126-9363 -0  
info@candlecraft.de - www.candlecraft.de

#### 1.4. Emergency telephone number

No additional information available

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412  
Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP) : -  
Hazard statements (CLP) : H412 - Harmful to aquatic life with long lasting effects.  
Precautionary statements (CLP) : P273 - Avoid release to the environment.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.  
EUH-statements : EUH208 - Contains Ethyl linalool, Hexyl cinnamic aldehyde, Helional, Benzyl salicylate. May produce an allergic reaction.  
Extra phrases : For professional users only.

#### 2.3. Other hazards

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371-33	3.76 – 7.5272	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Ethyl linalool	CAS-No.: 10339-55-6 EC-No.: 233-732-6 REACH-no: 01-2119969272-32	0.11 – 0.21	Eye Irrit. 2, H319 Skin Sens. 1B, H317
Hexyl cinnamic aldehyde	CAS-No.: 101-86-0 EC-No.: 202-983-3 REACH-no: 01-2119533092-50	0.07 – 0.13	Skin Sens. 1, H317 Aquatic Chronic 2, H411
2-phenoxyethanol substance with national workplace exposure limit(s) (AT, DE, FI, PL, SI, CH)	CAS-No.: 122-99-6 EC-No.: 204-589-7 EC Index-No.: 603-098-00-9 REACH-no: 01-2119488943-21	0.05 – 0.105	Acute Tox. 4 (Oral), H302 STOT SE 3, H335 Eye Dam. 1, H318
Helional	CAS-No.: 1205-17-0 EC-No.: 214-881-6 REACH-no: 01-2120740119-58	0.05 – 0.105	Skin Sens. 1B, H317 Repr. 2, H361 Aquatic Chronic 2, H411
Benzyl salicylate	CAS-No.: 118-58-1 EC-No.: 204-262-9 EC Index-No.: 607-754-00-5 REACH-no: 01-2119969442-31	0.05 – 0.10003	Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Benzyl acetate substance with national workplace exposure limit(s) (BE, DK, ES, IE, LT, LV, PT, RO)	CAS-No.: 140-11-4 EC-No.: 205-399-7 REACH-no: 01-2119638272-42	0.03 – 0.055	Aquatic Chronic 3, H412
Carbitol substance with national workplace exposure limit(s) (AT, DE, EE, SE, SI, CH)	CAS-No.: 111-90-0 EC-No.: 203-919-7 REACH-no: 01-2119475105-42	0.007233 – 0.014466	Not classified
ethyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-46	0 – 0.005	Flam. Liq. 1, H224 Eye Irrit. 2, H319 STOT SE 3, H336
Alcohol C-10 substance with national workplace exposure limit(s) (BG, DE, LT, LV, RO, CH)	CAS-No.: 112-30-1 EC-No.: 203-956-9	0 – 0.00014	Aquatic Chronic 3, H412

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Aldehyde C-6 substance with national workplace exposure limit(s) (FI, PL)	CAS-No.: 66-25-1 EC-No.: 200-624-5	0 – 0.00004	Flam. Liq. 3, H226

Full text of H- and EUH-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
------------------	--

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

No additional information available

#### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

##### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.  
Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Section 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.  
Incompatible products : Strong bases. Strong acids.  
Incompatible materials : Sources of ignition. Direct sunlight.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

2-phenoxyethanol (122-99-6)	
<b>Austria - Occupational Exposure Limits</b>	
MAK (OEL TWA)	110 mg/m <sup>3</sup>
MAK (OEL TWA) [ppm]	20 ppm
MAK (OEL STEL)	110 mg/m <sup>3</sup>
MAK (OEL STEL) [ppm]	20 ppm
OEL C	110 mg/m <sup>3</sup>
OEL C	20 ppm
<b>Finland - Occupational Exposure Limits</b>	
HTP (OEL TWA) [1]	110 mg/m <sup>3</sup>
HTP (OEL TWA) [2]	20 ppm
HTP (OEL STEL)	290 mg/m <sup>3</sup>
HTP (OEL STEL) [ppm]	50 ppm
OEL chemical category	Potential for cutaneous absorption
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
AGW (OEL TWA) [1]	5.7 mg/m <sup>3</sup> (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
AGW (OEL TWA) [2]	1 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>2-phenoxyethanol (122-99-6)</b>	
<b>Poland - Occupational Exposure Limits</b>	
NDS (OEL TWA)	230 mg/m <sup>3</sup>
<b>Slovenia - Occupational Exposure Limits</b>	
OEL TWA	5.7 mg/m <sup>3</sup>
OEL TWA	1 ppm
OEL STEL	5.7 mg/m <sup>3</sup>
OEL STEL	1 ppm
<b>Switzerland - Occupational Exposure Limits</b>	
MAK (OEL TWA) [1]	110 mg/m <sup>3</sup> (aerosol, vapour)
MAK (OEL TWA) [2]	20 ppm (aerosol, vapour)
KZGW (OEL STEL)	110 mg/m <sup>3</sup> (aerosol, vapour)
KZGW (OEL STEL) [ppm]	20 ppm (aerosol, vapour)
<b>Benzyl acetate (140-11-4)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
OEL TWA	62 mg/m <sup>3</sup>
OEL TWA	10 ppm
<b>Denmark - Occupational Exposure Limits</b>	
OEL TWA [1]	61 mg/m <sup>3</sup>
OEL TWA [2]	10 ppm
OEL STEL	122 mg/m <sup>3</sup>
OEL STEL	20 ppm
<b>Ireland - Occupational Exposure Limits</b>	
OEL TWA [2]	10 ppm
OEL STEL	30 ppm (calculated)
<b>Latvia - Occupational Exposure Limits</b>	
OEL TWA	5 mg/m <sup>3</sup>
<b>Lithuania - Occupational Exposure Limits</b>	
IPRV (OEL TWA)	5 mg/m <sup>3</sup>
<b>Portugal - Occupational Exposure Limits</b>	
OEL TWA	10 ppm
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen
<b>Romania - Occupational Exposure Limits</b>	
OEL TWA	50 mg/m <sup>3</sup>
OEL TWA	8 ppm
OEL STEL	80 mg/m <sup>3</sup>
OEL STEL	13 ppm
<b>Spain - Occupational Exposure Limits</b>	
VLA-ED (OEL TWA) [1]	62 mg/m <sup>3</sup>
VLA-ED (OEL TWA) [2]	10 ppm

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>Benzyl acetate (140-11-4)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA [ppm]	10 ppm
ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>Carbitol (111-90-0)</b>	
<b>Austria - Occupational Exposure Limits</b>	
MAK (OEL TWA)	35 mg/m <sup>3</sup>
MAK (OEL TWA) [ppm]	6 ppm
MAK (OEL STEL)	140 mg/m <sup>3</sup>
MAK (OEL STEL) [ppm]	24 ppm
<b>Estonia - Occupational Exposure Limits</b>	
OEL TWA	50.1 mg/m <sup>3</sup>
OEL TWA	10 ppm
OEL chemical category	Skin notation
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
AGW (OEL TWA) [1]	35 mg/m <sup>3</sup> (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
AGW (OEL TWA) [2]	6 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
<b>Slovenia - Occupational Exposure Limits</b>	
OEL TWA	35 mg/m <sup>3</sup>
OEL TWA	6 ppm
OEL STEL	70 mg/m <sup>3</sup>
OEL STEL	12 ppm
<b>Sweden - Occupational Exposure Limits</b>	
NGV (OEL TWA)	80 mg/m <sup>3</sup>
NGV (OEL TWA) [ppm]	15 ppm
KTV (OEL STEL)	170 mg/m <sup>3</sup>
KTV (OEL STEL) [ppm]	30 ppm
OEL chemical category	Skin notation
<b>Switzerland - Occupational Exposure Limits</b>	
MAK (OEL TWA) [1]	50 mg/m <sup>3</sup> (aerosol, inhalable dust, vapour)
KZGW (OEL STEL)	100 mg/m <sup>3</sup> (aerosol, inhalable dust, vapour)
<b>ethyl acetate (141-78-6)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
IOEL TWA	734 mg/m <sup>3</sup>
IOEL TWA [ppm]	200 ppm
IOEL STEL	1468 mg/m <sup>3</sup>
IOEL STEL [ppm]	400 ppm

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ethyl acetate (141-78-6)	
<b>Austria - Occupational Exposure Limits</b>	
MAK (OEL TWA)	734 mg/m <sup>3</sup>
MAK (OEL TWA) [ppm]	200 ppm
MAK (OEL STEL)	1468 mg/m <sup>3</sup>
MAK (OEL STEL) [ppm]	400 ppm
<b>Belgium - Occupational Exposure Limits</b>	
OEL TWA	734 mg/m <sup>3</sup>
OEL TWA	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL	400 ppm
<b>Bulgaria - Occupational Exposure Limits</b>	
OEL TWA	734 mg/m <sup>3</sup>
OEL TWA	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL	400 ppm
<b>Croatia - Occupational Exposure Limits</b>	
GVI (OEL TWA) [1]	734 mg/m <sup>3</sup>
GVI (OEL TWA) [2]	200 ppm
KGVI (OEL STEL)	1468 mg/m <sup>3</sup>
KGVI (OEL STEL) [ppm]	400 ppm
<b>Cyprus - Occupational Exposure Limits</b>	
OEL TWA	734 mg/m <sup>3</sup>
OEL TWA	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL	400 ppm
<b>Czech Republic - Occupational Exposure Limits</b>	
PEL (OEL TWA)	700 mg/m <sup>3</sup>
<b>Denmark - Occupational Exposure Limits</b>	
OEL TWA [1]	540 mg/m <sup>3</sup>
OEL TWA [2]	150 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL	400 ppm
<b>Estonia - Occupational Exposure Limits</b>	
OEL TWA	500 mg/m <sup>3</sup>
OEL TWA	150 ppm
OEL STEL	1100 mg/m <sup>3</sup>
OEL STEL	300 ppm
<b>Finland - Occupational Exposure Limits</b>	
HTP (OEL TWA) [1]	730 mg/m <sup>3</sup>

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>ethyl acetate (141-78-6)</b>	
HTP (OEL TWA) [2]	200 ppm
HTP (OEL STEL)	1470 mg/m <sup>3</sup>
HTP (OEL STEL) [ppm]	400 ppm
<b>France - Occupational Exposure Limits</b>	
VME (OEL TWA)	734 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	200 ppm
VLE (OEL C/STEL)	1468 mg/m <sup>3</sup> (restrictive limit)
VLE (OEL C/STEL) [ppm]	400 ppm (restrictive limit)
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
AGW (OEL TWA) [1]	730 mg/m <sup>3</sup> (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
AGW (OEL TWA) [2]	200 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
<b>Gibraltar - Occupational Exposure Limits</b>	
OEL TWA	200 mg/m <sup>3</sup>
OEL TWA	734 ppm
OEL STEL	400 mg/m <sup>3</sup>
OEL STEL	1468 ppm
<b>Greece - Occupational Exposure Limits</b>	
OEL TWA	734 mg/m <sup>3</sup>
OEL TWA	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL	400 ppm
<b>Hungary - Occupational Exposure Limits</b>	
AK (OEL TWA)	734 mg/m <sup>3</sup>
CK (OEL STEL)	1468 mg/m <sup>3</sup>
OEL chemical category	Sensitizer
<b>Ireland - Occupational Exposure Limits</b>	
OEL TWA [1]	734 mg/m <sup>3</sup>
OEL TWA [2]	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL	400 ppm
<b>Italy - Occupational Exposure Limits</b>	
OEL TWA	734 mg/m <sup>3</sup>
OEL TWA	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL	400 ppm
<b>Latvia - Occupational Exposure Limits</b>	
OEL TWA	200 mg/m <sup>3</sup>
OEL TWA	54 ppm

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>ethyl acetate (141-78-6)</b>	
<b>Lithuania - Occupational Exposure Limits</b>	
IPRV (OEL TWA)	500 mg/m <sup>3</sup>
IPRV (OEL TWA) [ppm]	150 ppm
NRV (OEL C)	1100 mg/m <sup>3</sup>
NRV (OEL C) [ppm]	300 ppm
<b>Luxembourg - Occupational Exposure Limits</b>	
OEL TWA	734 mg/m <sup>3</sup>
OEL TWA	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL	400 ppm
<b>Malta - Occupational Exposure Limits</b>	
OEL TWA	734 mg/m <sup>3</sup>
OEL TWA	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL	400 ppm
<b>Netherlands - Occupational Exposure Limits</b>	
TGG-8u (OEL TWA)	734 mg/m <sup>3</sup>
TGG-8u (OEL TWA) [ppm]	200 ppm
TGG-15min (OEL STEL)	1468 mg/m <sup>3</sup>
TGG-15min (OEL STEL) [ppm]	400 ppm
<b>Poland - Occupational Exposure Limits</b>	
NDS (OEL TWA)	734 mg/m <sup>3</sup>
NDSCh (OEL STEL)	1468 mg/m <sup>3</sup>
<b>Portugal - Occupational Exposure Limits</b>	
OEL TWA	734 mg/m <sup>3</sup> (indicative limit value)
OEL TWA	200 ppm (indicative limit value)
OEL STEL	1468 mg/m <sup>3</sup> (indicative limit value)
OEL STEL	400 ppm (indicative limit value)
<b>Romania - Occupational Exposure Limits</b>	
OEL TWA	734 mg/m <sup>3</sup>
OEL TWA	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL	400 ppm
<b>Slovakia - Occupational Exposure Limits</b>	
NPHV (OEL TWA) [1]	734 mg/m <sup>3</sup>
NPHV (OEL TWA) [2]	200 ppm
NPHV (OEL C)	1100 mg/m <sup>3</sup>
<b>Slovenia - Occupational Exposure Limits</b>	
OEL TWA	734 mg/m <sup>3</sup>

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>ethyl acetate (141-78-6)</b>	
OEL TWA	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL	400 ppm
<b>Spain - Occupational Exposure Limits</b>	
VLA-ED (OEL TWA) [1]	734 mg/m <sup>3</sup>
VLA-ED (OEL TWA) [2]	200 ppm
VLA-EC (OEL STEL)	1468 mg/m <sup>3</sup>
VLA-EC (OEL STEL) [ppm]	400 ppm
<b>Sweden - Occupational Exposure Limits</b>	
NGV (OEL TWA)	550 mg/m <sup>3</sup>
NGV (OEL TWA) [ppm]	150 ppm
KTV (OEL STEL)	1100 mg/m <sup>3</sup>
KTV (OEL STEL) [ppm]	300 ppm
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA) [1]	734 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	1468 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	400 ppm
<b>Norway - Occupational Exposure Limits</b>	
Grenseverdi (OEL TWA) [1]	734 mg/m <sup>3</sup>
Grenseverdi (OEL TWA) [2]	200 ppm
Korttidsverdi (OEL STEL)	1468 mg/m <sup>3</sup> (value from the regulation)
Korttidsverdi (OEL STEL) [ppm]	400 ppm (value from the regulation)
<b>Switzerland - Occupational Exposure Limits</b>	
MAK (OEL TWA) [1]	730 mg/m <sup>3</sup>
MAK (OEL TWA) [2]	200 ppm
KZGW (OEL STEL)	1460 mg/m <sup>3</sup>
KZGW (OEL STEL) [ppm]	400 ppm
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA [ppm]	400 ppm
<b>Alcohol C-10 (112-30-1)</b>	
<b>Bulgaria - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup>
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
AGW (OEL TWA) [1]	66 mg/m <sup>3</sup> (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
AGW (OEL TWA) [2]	10 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Alcohol C-10 (112-30-1)	
<b>Latvia - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup>
<b>Lithuania - Occupational Exposure Limits</b>	
IPRV (OEL TWA)	10 mg/m <sup>3</sup>
<b>Romania - Occupational Exposure Limits</b>	
OEL TWA	100 mg/m <sup>3</sup>
OEL TWA	15 ppm
OEL STEL	200 mg/m <sup>3</sup>
OEL STEL	30 ppm
<b>Switzerland - Occupational Exposure Limits</b>	
MAK (OEL TWA) [1]	66 mg/m <sup>3</sup> (aerosol, vapour)
MAK (OEL TWA) [2]	10 ppm (aerosol, vapour)
KZGW (OEL STEL)	66 mg/m <sup>3</sup> (aerosol, vapour)
KZGW (OEL STEL) [ppm]	10 ppm (aerosol, vapour)
<b>Aldehyde C-6 (66-25-1)</b>	
<b>Finland - Occupational Exposure Limits</b>	
HTP (OEL STEL)	42 mg/m <sup>3</sup>
HTP (OEL STEL) [ppm]	10 ppm
<b>Poland - Occupational Exposure Limits</b>	
NDS (OEL TWA)	40 mg/m <sup>3</sup>
NDSch (OEL STEL)	80 mg/m <sup>3</sup>

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

No additional information available

### 8.2.2. Personal protection equipment

**Personal protective equipment:**

Avoid all unnecessary exposure.

**Personal protective equipment symbol(s):**



# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 8.2.2.1. Eye and face protection

**Eye protection:**

Chemical goggles or safety glasses

### 8.2.2.2. Skin protection

**Hand protection:**

Wear protective gloves.

### 8.2.2.3. Respiratory protection

**Respiratory protection:**

Wear appropriate mask

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

**Other information:**

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Standard.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 93 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Not established.

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### benzyl benzoate (120-51-4)

LD50 oral rat	500 mg/kg (Source: NLM_CIP)
LD50 oral	1160 mg/kg bodyweight
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)

#### Ethyl linalool (10339-55-6)

LD50 oral	5000 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)

#### Hexyl cinnamic aldehyde (101-86-0)

LD50 oral rat	3100 mg/kg (Source: NLM_CIP)
LD50 oral	3100 mg/kg bodyweight
LD50 dermal rabbit	> 3000 mg/kg (Source: EPA_HPVS)
LC50 Inhalation - Rat	> 5 mg/l/4h

#### 2-phenoxyethanol (122-99-6)

LD50 oral rat	1850 mg/kg (Source: EU_CLH)
LD50 oral	1394 mg/kg bodyweight
LD50 dermal rabbit	5 ml/kg (Source: NLM_CIP)
LC50 Inhalation - Rat	> 0.057 mg/l (Exposure time: 8 h Source: EU_CLH)

#### Helional (1205-17-0)

LD50 dermal rabbit	> 2000 mg/kg (Source: ECHA_API)
--------------------	---------------------------------

#### Benzyl salicylate (118-58-1)

LD50 oral rat	2227 mg/kg (Source: NLM_CIP)
LD50 oral	2200 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)

#### Benzyl acetate (140-11-4)

LD50 oral rat	2490 mg/kg (Source: JAPAN_GHS)
---------------	--------------------------------

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>Benzyl acetate (140-11-4)</b>	
LD50 oral	2490 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: JAPAN_GHS)
<b>Carbitol (111-90-0)</b>	
LD50 oral rat	10502 mg/kg (Source: OECD_SIDS)
LD50 dermal rabbit	9143 mg/kg (Source: OECD_SIDS)
LC50 Inhalation - Rat	> 5240 mg/m <sup>3</sup> (Exposure time: 4 h Source: NLM_CIP)
<b>ethyl acetate (141-78-6)</b>	
LD50 oral rat	5620 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 18000 mg/kg (Source: JAPAN_GHS)
LC50 Inhalation - Rat [ppm]	4000 ppm/4h
<b>Alcohol C-10 (112-30-1)</b>	
LD50 oral rat	4720 mg/kg (Source: NZ_CCID)
LD50 dermal rabbit	3560 mg/kg (Source: NLM_CIP)
<b>Aldehyde C-6 (66-25-1)</b>	
LD50 oral rat	4890 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 8100 mg/kg (Source: ECHA_API)
Skin corrosion/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Respiratory or skin sensitisation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
<b>Benzyl acetate (140-11-4)</b>	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
<b>2-phenoxyethanol (122-99-6)</b>	
STOT-single exposure	May cause respiratory irritation.
<b>ethyl acetate (141-78-6)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified
Additional information	: Based on available data, the classification criteria are not met
<b>benzyl benzoate (120-51-4)</b>	
Viscosity, kinematic	7.456 mm <sup>2</sup> /s
Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 12: Ecological information

#### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

##### benzyl benzoate (120-51-4)

LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
NOEC (chronic)	0.168 mg/l

##### Ethyl linalool (10339-55-6)

LC50 - Fish [1]	24 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
-----------------	---

##### 2-phenoxyethanol (122-99-6)

LC50 - Fish [1]	337 – 352 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	366 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: IUCLID)
EC50 - Crustacea [1]	> 500 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	> 500 mg/l (Species: Desmodesmus subspicatus)

##### Benzyl salicylate (118-58-1)

LC50 - Fish [1]	1.03 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
-----------------	---

##### Carbitol (111-90-0)

LC50 - Fish [1]	10000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
LC50 - Fish [2]	19100 – 23900 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through] Source: EPA)
EC50 - Crustacea [1]	3940 – 4670 mg/l (Exposure time: 48 h - Species: Daphnia magna)

##### ethyl acetate (141-78-6)

LC50 - Fish [1]	220 – 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: IUCLID)
EC50 - Crustacea [1]	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

##### Alcohol C-10 (112-30-1)

LC50 - Fish [1]	2.2 – 2.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	4.12 – 6.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
EC50 - Crustacea [1]	3 mg/l (Exposure time: 48 h - Species: Daphnia magna)

##### Aldehyde C-6 (66-25-1)

LC50 - Fish [1]	12 – 16.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
-----------------	--

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 12.2. Persistence and degradability

#### Type 16 - DiJad CC-16039 10% in DPG

Persistence and degradability	Not established.
-------------------------------	------------------

#### benzyl benzoate (120-51-4)

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

### 12.3. Bioaccumulative potential

#### Type 16 - DiJad CC-16039 10% in DPG

Bioaccumulative potential	Not established.
---------------------------	------------------

#### benzyl benzoate (120-51-4)

Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)
---	-----------------

Bioaccumulative potential	Not established.
---------------------------	------------------

#### Ethyl linalool (10339-55-6)

Partition coefficient n-octanol/water (Log Pow)	3.3 (at 20 °C)
---	----------------

#### 2-phenoxyethanol (122-99-6)

Partition coefficient n-octanol/water (Log Pow)	1.107
---	-------

#### Helional (1205-17-0)

Partition coefficient n-octanol/water (Log Pow)	2.4 (at 25 °C)
---	----------------

#### Benzyl salicylate (118-58-1)

Partition coefficient n-octanol/water (Log Pow)	4
---	---

#### Benzyl acetate (140-11-4)

Partition coefficient n-octanol/water (Log Pow)	1.96 (at 25 °C (at pH 7))
---	---------------------------

#### Carbitol (111-90-0)

Partition coefficient n-octanol/water (Log Pow)	-0.8
---	------

#### ethyl acetate (141-78-6)

BCF - Fish [1]	(30 dimensionless)
----------------	--------------------

Partition coefficient n-octanol/water (Log Pow)	0.73 (at 20 °C (at pH 7))
---	---------------------------

#### Alcohol C-10 (112-30-1)

Partition coefficient n-octanol/water (Log Pow)	4.5 (at 25 °C (at pH 6))
---	--------------------------

#### Aldehyde C-6 (66-25-1)

Partition coefficient n-octanol/water (Log Pow)	2.3 (at 25 °C (at pH 5))
---	--------------------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Additional information : Avoid release to the environment.

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.
HP Code	: HP3 - "Flammable:" <ul style="list-style-type: none"><li>– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point &gt; 55 °C and ≤ 75 °C;</li><li>– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;</li><li>– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;</li><li>– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;</li><li>– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;</li><li>– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.</li></ul>
	HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

#### 14.6. Special precautions for user

##### Overland transport

Not applicable

##### Transport by sea

Not applicable

##### Air transport

Not applicable

##### Inland waterway transport

Not applicable

##### Rail transport

Not applicable

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	ethyl acetate ; Aldehyde C-6	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	benzyl benzoate ; Ethyl linalool ; Hexyl cinnamic aldehyde ; 2-phenoxyethanol ; Helional ; Benzyl salicylate ; ethyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Type 16 - DiJad CC-16039 10% in DPG ; benzyl benzoate ; Hexyl cinnamic aldehyde ; Helional ; Benzyl salicylate ; Benzyl acetate ; Alcohol C-10	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	ethyl acetate ; Aldehyde C-6	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

##### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

##### Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 15.1.2. National regulations

#### France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

#### Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Storage class (LGK, TRGS 510) : LGK 12 - Non-combustible liquids.

Joint storage table :

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for : LGK 1, LGK 6.2, LGK 7.

Joint storage with restrictions permitted for : LGK 4.1A, LGK 4.3, LGK 5.1C.

Joint storage permitted for : LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13.

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

#### Netherlands

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen –

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

#### Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Pregnant/breastfeeding women working with the product must not be in direct contact with the product

#### Switzerland

Storage class (LK) : LK 10/12 - Liquids

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

### Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
---------------------	-----------------------------------

# Type 16 - DiJad CC-16039 10% in DPG

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
EUH208	Contains Ethyl linalool, Hexyl cinnamic aldehyde, Helional, Benzyl salicylate. May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
H224	Extremely flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.