SEAWEED & JUNIPER CC-16046

Safety Data Sheet

Issue date: 1/25/2021 Revision date: 10/6/2026 Supersedes version of: 2/21/2022 Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Mixture
Product name	:	SEAWEED & JUNIPER CC-16046
UFI	:	S4C0-64XU-V007-NW7V
Product code	:	CC-16046
Type of product	:	Perfumes, fragrances
Product group	:	Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	:	Industrial use,Professional use
Industrial/Professional use spec	:	Industrial For professional use only
Use of the substance/mixture	:	Perfumes, fragrances
Function or use category	:	Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Candle Craft
Weiherwiese 10
65510 Idstein - Germany
T 49-6126-9363 -0
info@candlecraft.de - www.candlecraft.de

1.4. Emergency telephone number

Emergency number	:	06126-9363-0

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Reproductive toxicity, Category 2	H361
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07 GHS08 GHS09

Signal word (CLP)	:	Warning
Contains	:	Cyclamal; Citronellol Pure; d-Limonene; Nopyl acetate; Linalool; Benzyl salicylate; Geranyl acetate; 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone; Eugenol; Amyl cinnamic aldehyde; Hexyl cinnamic aldehyde; Veratryl aldehyde (Veratraldehyde); Aldehyde C-12; Melonal
Hazard statements (CLP)	:	H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H361 - Suspected of damaging fertility or the unborn child. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	:	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Cyclamal	CAS-No.: 103-95-7 EC-No.: 203-161-7 REACH-no: 01-2119970582-32	3.4 – 6.8486	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Repr. 2, H361 Aquatic Chronic 2, H411
Citronellol Pure	CAS-No.: 106-22-9 EC-No.: 203-375-0 REACH-no: 01-2119453995-23	3.300015 – 6.64103113	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Verdyl acetate	CAS-No.: 5413-60-5 EC-No.: 226-501-6	3.2 – 6.3643	Aquatic Chronic 3, H412
Methyl ionone (gamma) (Fragrance)	CAS-No.: 127-42-4 EC-No.: 204-842-1 REACH-no: 01-2119471581-35	2.8 – 5.6726	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Methyl ionone (mixture of isomers)	CAS-No.: 1335-46-2 EC-No.: 215-635-0	2.8 – 5.6726	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Benzyl acetate substance with national workplace exposure limit(s) (BE, DK, ES, IE, LT, LV, PT, RO)	CAS-No.: 140-11-4 EC-No.: 205-399-7 REACH-no: 01-2119638272-42	2.7 – 5.3959	Aquatic Chronic 3, H412

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
(R)-p-mentha-1,8-diene; d-limonene substance with national workplace exposure limit(s) (DE, ES, FI, SI, NO, CH)	CAS-No.: 5989-27-5 EC-No.: 205-341-0 EC Index-No.: 601-096-00-2 REACH-no: 01-2119493353-35	2.6 – 5.1191	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Verdox	CAS-No.: 88-41-5 EC-No.: 201-828-7 REACH-no: 01-2119970713-33	2.518291 – 5.1139432	Aquatic Chronic 2, H411
Nopyl acetate	CAS-No.: 128-51-8 EC-No.: 204-891-9	2.4 – 4.7041	Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Phenylethyl alcohol	CAS-No.: 60-12-8 EC-No.: 200-456-2 REACH-no: 01-2119963921-31	2.3 – 4.5657	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319
Dihydromyrcenol	CAS-No.: 18479-58-8 EC-No.: 242-362-4 REACH-no: 01-2119457274-37	2.2 – 4.4965	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336
2(3H)-Furanone, 5-heptyldihydro-	CAS-No.: 104-67-6 EC-No.: 203-225-4 REACH-no: 01-2119959333-34	1.8 – 3.5972	Aquatic Chronic 3, H412
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016-42	1.8 – 3.5972	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
tetrahydro-2-isobutyl-4-methylpyran-4-ol, mixed isomers (cis and trans)	CAS-No.: 63500-71-0 EC-No.: 405-040-6 EC Index-No.: 603-101-00-3 REACH-no: 01-000015458-64	0.65 – 2.6979	Eye Irrit. 2, H319
Benzyl salicylate	CAS-No.: 118-58-1 EC-No.: 204-262-9 EC Index-No.: 607-754-00-5 REACH-no: 01-2119969442-31	1.3 – 2.6979	Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Geranyl acetate	CAS-No.: 105-87-3 EC-No.: 203-341-5 REACH-no: 01-2119973480-35	1.2 – 2.4904	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone	CAS-No.: 54464-57-2 EC-No.: 259-174-3 REACH-no: 01-2119489989-04	1.2 – 2.4212	Aquatic Chronic 1, H410 Skin Irrit. 2, H315 Skin Sens. 1B, H317
1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran; galaxolide; (HHCB)	CAS-No.: 1222-05-5 EC-No.: 214-946-9 EC Index-No.: 603-212-00-7 REACH-no: 01-2119488227-29	0.715357 – 1.5424784	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Eugenol	CAS-No.: 97-53-0 EC-No.: 202-589-1 REACH-no: 01-2119971802-33	0.8 – 1.5219	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Amyl cinnamic aldehyde	CAS-No.: 122-40-7 EC-No.: 204-541-5	0.7 – 1.3836	Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Hexyl cinnamic aldehyde	CAS-No.: 101-86-0 EC-No.: 202-983-3 REACH-no: 01-2119533092-50	0.40074 – 0.764984	Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Aldehyde C-12	CAS-No.: 112-54-9 EC-No.: 203-983-6	0.2 – 0.3459	Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Melonal	CAS-No.: 106-72-9 EC-No.: 203-427-2	0.1 – 0.2767	Skin Sens. 1B, H317
Anisic aldehyde	CAS-No.: 123-11-5 EC-No.: 204-602-6 REACH-no: 01-2119977101-43	0.084 – 0.174328	Repr. 2, H361 Aquatic Chronic 3, H412
Veratryl aldehyde (Veratraldehyde)	CAS-No.: 120-14-9 EC-No.: 204-373-2	0.075 – 0.15565	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317
hexan-1-ol substance with national workplace exposure limit(s) (DE, RO, SI)	CAS-No.: 111-27-3 EC-No.: 203-852-3 EC Index-No.: 603-059-00-6 REACH-no: 01-2119487967-12	0.00212 – 0.0093541	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Irrit. 2, H319
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	0.000762 – 0.001581404	Not classified
Toluene substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3	≤ 0.000018678	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Allow the victim to rest. Allow affected person to breathe fresh air.

First-aid measures after skin contact : If skin irritation occurs: Get medical advice/attention. Wash with plenty of water/…. Wash contaminated clothing before reuse. Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label). If skin irritation or rash occurs:

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Obtain emergency medical attention. Rinse mouth. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Suspected of damaging fertility or the unborn child.

Symptoms/effects after inhalation : May cause an allergic skin reaction.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction. Causes skin irritation.

Symptoms/effects after eye contact : Eye irritation. Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Sand. Foam. Dry powder. Carbon dioxide. Water spray.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Notify authorities if liquid enters sewers or public waters. Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Store away from other materials. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

Exposure controls and personal protection. See Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid breathing dust/fume/gas/mist/vapours/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep only in the original container in a cool, well-ventilated place away from:

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

Storage temperature : 25 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container.

Packaging materials : Do not store in corrodable metal.

Switzerland

Storage class (LK) : LK 6.1 - Toxic materials

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Benzyl acetate (140-11-4)	
Belgium - Occupational Exposure Limits	
OEL TWA	62 mg/m³
	10 ppm
Denmark - Occupational Exposure Limits	
OEL TWA	61 mg/m³
	10 ppm
OEL STEL	122 mg/m³
	20 ppm
Ireland - Occupational Exposure Limits	
OEL TWA	10 ppm
OEL STEL	30 ppm (calculated)
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m³
Portugal - Occupational Exposure Limits	
OEL TWA	10 ppm

Benzyl acetate (140-11-4)	
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen
Romania - Occupational Exposure Limits	
OEL TWA	50 mg/m³
	8 ppm
OEL STEL	80 mg/m³
	13 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	62 mg/m³
	10 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	10 ppm
ACGIH® chemical category	Not Classifiable as a Human Carcinogen

(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)	
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	140 mg/m³
	25 ppm
HTP (OEL STEL)	280 mg/m³
	50 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	28 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	Skin notation, Skin sensitization
Slovenia - Occupational Exposure Limits	
OEL TWA	28 mg/m³
	5 ppm
OEL STEL	112 mg/m³
	20 ppm
OEL chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	168 mg/m³
	30 ppm
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	140 mg/m³
	25 ppm
Korttidsverdi (OEL STEL)	175 mg/m³ (value calculated)
	37.5 ppm (value calculated)

(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)	
OEL chemical category	Allergenic substance
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	40 mg/m³
	7 ppm
KZGW (OEL STEL)	80 mg/m³
	14 ppm
OEL chemical category	Sensitizer

Toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	192 mg/m³
	50 ppm
IOEL STEL	384 mg/m³
	100 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	190 mg/m³
	50 ppm
MAK (OEL STEL)	380 mg/m³
	100 ppm
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	77 mg/m³
	20 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin, Skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
Bulgaria - Biological limit values	
BLV	1.6 mmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of exposure or end of work shift
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	192 mg/m³
	50 ppm
KGVI (OEL STEL)	384 mg/m³
	100 ppm

Toluene (108-88-3)	
OEL chemical category	Skin notation
Croatia - Biological limit values	
BLV	1 mg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of the work shift 20 ppm Parameter: Toluene - Medium: final exhaled air - Sampling time: during exposure 2.5 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine) 1 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine)
Cyprus - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	200 mg/m³
OEL chemical category	Potential for cutaneous absorption
Czech Republic - Biological limit values	
BLV	1.6 µmol/mmol Creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1000 µmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.) 1.5 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1600 mg/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.)
Denmark - Occupational Exposure Limits	
OEL TWA	94 mg/m³
	25 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin notation

Toluene (108-88-3)	
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	81 mg/m³
	25 ppm
HTP (OEL STEL)	380 mg/m³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Finland - Biological limit values	
BLV	500 nmol/L Parameter: Toluene - Medium: blood - Sampling time: in the morning after a working day
France - Occupational Exposure Limits	
VLEP 8h (OEL TWA)	76.8 mg/m³ (restrictive limit)
	20 ppm (restrictive limit)
VLEP CT (OEL STEL)	384 mg/m³ (restrictive limit)
	100 ppm (restrictive limit)
OEL chemical category	Reproductive Toxin category 2, Risk of cutaneous absorption
France - Biological limit values	
BLV	20 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of workweek (Semi-quantitative (ambiguous interpretation)) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (per the Authority, the values for this substance must be decided and/or determined on a case by case basis. Guidance for the calculation of and interpretation of values is provided in the source)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	190 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	50 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	Skin notation
Germany - Biological limit values (TRGS 903)	
Biological limit value	600 µg/l Parameter: Toluene - Medium: whole blood - Sampling time: immediately after exposure 75 µg/l Parameter: Toluene - Medium: urine - Sampling time: end of exposure or shift 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: at the end of the shift, in case of long-term exposure after several previous shifts
Gibraltar - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
Greece - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³

Toluene (108-88-3)	
	100 ppm
OEL chemical category	skin - potential for cutaneous absorption
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	190 mg/m³
CK (OEL STEL)	384 mg/m³
OEL chemical category	Potential for cutaneous absorption
Ireland - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	50 mg/m³
	14 ppm
OEL chemical category	skin - potential for cutaneous exposure
Latvia - Biological Exposure Indices	
BEI	600 µg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of exposure (for assessment of long-term exposure, samples are taken at the end of a shift after several previous shifts) 75 µg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift (for assessment of long-term exposure, samples are taken at the end of a shift after several previous shifts) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: at the end of exposure or shift (after hydrolysis)
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	192 mg/m³
	50 ppm
TPRV (OEL STEL)	384 mg/m³
	100 ppm
OEL chemical category	Reproductive toxin, Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Possibility of significant uptake through the skin

Toluene (108-88-3)	
Malta - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	150 mg/m³
	39 ppm
TGG-15min (OEL STEL)	384 mg/m³
	100 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	100 mg/m³
NDSCh (OEL STEL)	200 mg/m³
Portugal - Occupational Exposure Limits	
OEL TWA	192 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)
OEL STEL	384 mg/m³ (indicative limit value)
	100 ppm (indicative limit value)
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
Romania - Biological limit values	
BLV	2 g/l Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 3 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	192 mg/m³
	50 ppm
NPHV (OEL C)	384 mg/m³ (also biological monitoring considered)
OEL chemical category	Potential for cutaneous absorption

Toluene (108-88-3)	
Slovakia - Biological limit values	
BLV	600 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of exposure or work shift 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: after all work shifts (for long-term exposure) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of exposure or work shift 2401 mg/g creatinine Parameter: Hippuric acid - Sampling time: end of exposure or work shift
Slovenia - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Category 2, Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	192 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)
VLA-EC (OEL STEL)	384 mg/m³
	100 ppm
OEL chemical category	skin - potential for cutaneous absorption
Spain - Biological limit values	
BLV	0.6 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift 0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: start of last shift of workweek 0.08 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	192 mg/m³
	50 ppm
KGV (OEL STEL)	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	191 mg/m³
	50 ppm
WEL STEL (OEL STEL)	384 mg/m³
	100 ppm
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	94 mg/m³
	25 ppm
Korttidsverdi (OEL STEL)	141 mg/m³ (value calculated)

Toluene (108-88-3)	
	37.5 ppm (value calculated)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	190 mg/m³
	50 ppm
KZGW (OEL STEL)	760 mg/m³
	200 ppm
OEL chemical category	Skin notation, Category 2 reproductive toxin
Switzerland - BAT	
BAT	600 µg/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 6.48 µmol/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 2 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 0.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 4.62 µmol/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 75 µg/l Parameter: Toluol - Medium: urine - Sampling time: end of shift
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	20 ppm
ACGIH® chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 0.3 mg/g creatinine Parameter: o-Cresol with hydrolysis - Medium: urine - Sampling time: end of shift (background)

Dipropylene glycol monomethyl ether (34590-94-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	308 mg/m³
	50 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	307 mg/m³ (mixed isomers)
	50 ppm (mixed isomers)
MAK (OEL STEL)	614 mg/m³ (isomers mixtures)
	100 ppm (isomers mixtures)
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Skin, Skin notation

Dipropylene glycol monomethyl ether (34590-94-8)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	308 mg/m³
	50 ppm
OEL chemical category	Skin notation
Cyprus - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	270 mg/m³
OEL chemical category	Potential for cutaneous absorption
Denmark - Occupational Exposure Limits	
OEL TWA	309 mg/m³
	50 ppm
OEL STEL	618 mg/m³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	310 mg/m³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
France - Occupational Exposure Limits	
VLEP 8h (OEL TWA)	308 mg/m³ (restrictive limit)
	50 ppm (restrictive limit)
OEL chemical category	Risk of cutaneous absorption
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	310 mg/m³ (isomer mixture)
	50 ppm (isomer mixture)
Gibraltar - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Skin notation

Dipropylene glycol monomethyl ether (34590-94-8)	
Greece - Occupational Exposure Limits	
OEL TWA	600 mg/m³
	100 ppm
OEL STEL	900 mg/m³
	150 ppm
OEL chemical category	skin - potential for cutaneous absorption
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	308 mg/m³
Ireland - Occupational Exposure Limits	
OEL TWA	308 mg/m³ ((2-Methoxymethylethoxy)-1-propanol)
	50 ppm ((2-Methoxymethylethoxy)-1-propanol)
OEL STEL	924 mg/m³ (calculated (2-Methoxymethylethoxy)-1-propanol)
	150 ppm (calculated (2-Methoxymethylethoxy)-1-propanol)
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	skin - potential for cutaneous exposure
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	300 mg/m³ (2-(2-Methoxypropoxy)-propanol)
	50 ppm (2-(2-Methoxypropoxy)-propanol)
TPRV (OEL STEL)	450 mg/m³ (2-(2-Methoxypropoxy)-propanol)
	75 ppm (2-(2-Methoxypropoxy)-propanol)
OEL chemical category	Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	300 mg/m³
	48.7 ppm

Dipropylene glycol monomethyl ether (34590-94-8)	
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
NDSCh (OEL STEL)	480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
Portugal - Occupational Exposure Limits	
OEL TWA	308 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)
OEL STEL	150 ppm
OEL chemical category	skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Skin notation
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	308 mg/m³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
Slovenia - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL STEL	308 mg/m³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	308 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)
OEL chemical category	skin - potential for cutaneous absorption
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	300 mg/m³
	50 ppm
KGV (OEL STEL)	450 mg/m³
	75 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	308 mg/m³
	50 ppm
WEL STEL (OEL STEL)	924 mg/m³ (calculated)
	150 ppm (calculated)
WEL chemical category	Potential for cutaneous absorption

Dipropylene glycol monomethyl ether (34590-94-8)	
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	300 mg/m³
	50 ppm
Korttidsverdi (OEL STEL)	375 mg/m³ (value calculated)
	75 ppm (value calculated)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	300 mg/m³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
KZGW (OEL STEL)	300 mg/m³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	50 ppm (Dipropylene glycol methyl ether)

hexan-1-ol (111-27-3)	
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	105 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed (long-chain Alcohols)
	25 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed (long-chain Alcohols)
Romania - Occupational Exposure Limits	
OEL TWA	150 mg/m³
	36 ppm
OEL STEL	250 mg/m³
	60 ppm
Slovenia - Occupational Exposure Limits	
OEL TWA	210 mg/m³
	50 ppm
OEL STEL	210 mg/m³
	50 ppm

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:
Avoid all unnecessary exposure.
Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:
Chemical goggles or safety glasses

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:
Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.
Other information:
Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	light yellow. amber.
Odour	:	characteristic.
Odour threshold	:	No data available
pH	:	No data available
Relative evaporation rate (butylacetate=1)	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	91 °C
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Flammability (solid, gas)	:	Not applicable,Non flammable.
Vapour pressure	:	0.003420017 mm Hg (calculated value)
Relative vapour density at 20°C	:	No data available
Relative density	:	≈ 0.96
Solubility	:	No data available
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Viscosity, kinematic	:	No data available

Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

9.2. Other information

VOC content : 20.65338836 % (calculated value)(CARB VOC) (%w/w)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Extremely high or low temperatures. Direct sunlight.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Carbon dioxide. fume. Carbon monoxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Cyclamal (103-95-7)	
LD50 oral rat	3810 mg/kg (Source: NLM_CIP)
LD50 oral	3810 mg/kg
LD50 dermal rat	> 5000 mg/kg (Source: ECHA_API)

Citronellol Pure (106-22-9)	
LD50 oral rat	3450 mg/kg (Source: NLM_CIP)
LD50 oral	3450 mg/kg
LD50 dermal rabbit	2650 mg/kg (Source: EPA_HPV)
LD50 dermal	2650 mg/kg

Verdyl acetate (5413-60-5)	
LD50 oral	2750 mg/kg
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)

Methyl ionone (mixture of isomers) (1335-46-2)	
LD50 oral rat	> 5000 mg/kg

Methyl ionone (mixture of isomers) (1335-46-2)	
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)

Benzyl acetate (140-11-4)	
LD50 oral rat	2490 mg/kg (Source: JAPAN_GHS)
LD50 oral	2490 mg/kg
LD50 dermal rabbit	> 5000 mg/kg (Source: JAPAN_GHS)

(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)	
LD50 oral rat	4400 mg/kg (Source: CHEMVIEW)
LD50 dermal rabbit	> 5 g/kg (Source: CHEMVIEW)

Verdox (88-41-5)	
LD50 oral rat	4600 mg/kg (Source: NLM_CIP)
LD50 oral	4600 mg/kg

Nopyl acetate (128-51-8)	
LD50 oral rat	3 g/kg (Source: NLM_CIP)
LD50 oral	2991 mg/kg

Phenylethyl alcohol (60-12-8)	
LD50 oral rat	1609 mg/kg (Source: EPA_HPV)
LD50 oral	1610 mg/kg
LD50 dermal rabbit	2535 mg/kg (Source: EPA_HPV)
LC50 Inhalation - Rat	> 4.63 mg/l/4h

Dihydromyrcenol (18479-58-8)	
LD50 oral rat	3600 mg/kg (Source: NLM_CIP)
LD50 oral	3020 mg/kg
LD50 dermal rabbit	> 5 g/kg (Source: CHEMVIEW)

2(3H)-Furanone, 5-heptyldihydro- (104-67-6)	
LD50 oral rat	18500 mg/kg (Source: NLM_CIP)
LD50 dermal rat	> 2000 mg/kg (Source: ECHA)

Linalool (78-70-6)	
LD50 oral rat	2790 mg/kg (Source: NLM_CIP)
LD50 oral	2790 mg/kg
LD50 dermal rabbit	5610 mg/kg (Source: ECHA_API)

tetrahydro-2-isobutyl-4-methylpyran-4-ol, mixed isomers (cis and trans) (63500-71-0)	
LD50 dermal rabbit	> 2000 mg/kg (Source: ECHA_API)

Benzyl salicylate (118-58-1)	
LD50 oral rat	2227 mg/kg (Source: NLM_CIP)
LD50 oral	2227 mg/kg
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)

Geranyl acetate (105-87-3)	
LD50 oral rat	6330 mg/kg (Source: NLM_CIP)

Eugenol (97-53-0)	
LD50 oral rat	1930 mg/kg (Source: NZ_CCID)
LD50 oral	2500 mg/kg bodyweight
LC50 Inhalation - Rat	> 2.58 mg/l/4h

1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran; galaxolide; (HHCB) (1222-05-5)	
LD50 oral rat	> 3250 mg/kg (Source: CHEMVIEW)
LD50 dermal rabbit	> 3250 mg/kg (Source: CHEMVIEW)
LC50 Inhalation - Rat	> 5.04 mg/l/4h

Amyl cinnamic aldehyde (122-40-7)	
LD50 oral rat	3730 mg/kg (Source: CHEMVIEW)
LD50 dermal rabbit	> 2000 mg/kg (Source: CHEMVIEW)

Hexyl cinnamic aldehyde (101-86-0)	
LD50 oral rat	3100 mg/kg (Source: NLM_CIP)
LD50 oral	3100 mg/kg
LD50 dermal rabbit	> 3000 mg/kg (Source: EPA_HPV)
LC50 Inhalation - Rat	> 5 mg/l/4h

Anisic aldehyde (123-11-5)	
LD50 oral rat	3210 mg/kg (Source: ECHA)
LD50 oral	3210 mg/kg
LD50 dermal rabbit	> 5000 mg/kg (Source: EPA_HPV)
LC50 Inhalation - Rat	> 0.32 mg/l (Exposure time: 7 h Source: ECHA)

Veratryl aldehyde (Veratraldehyde) (120-14-9)	
LD50 oral rat	2 g/kg (Source: NLM_CIP)
LD50 oral	2000 mg/kg

Toluene (108-88-3)	
LD50 oral rat	5000 mg/kg (Source: NLM_HSDB)
LD50 dermal rabbit	12000 mg/kg (Source: JAPAN_GHS)
LC50 Inhalation - Rat	12.5 mg/l/4h

Dipropylene glycol monomethyl ether (34590-94-8)	
LD50 oral rat	5.35 g/kg (Source: NLM_HSDB)
LD50 dermal rabbit	9500 mg/kg (Source: NLM_CIP)

Aldehyde C-12 (112-54-9)	
LD50 oral rat	23 g/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 2000 mg/kg (Source: ECHA_API)

Melonal (106-72-9)	
LD50 oral rat	> 5 g/kg (Source: NLM_CIP)

hexan-1-ol (111-27-3)	
LD50 oral rat	3210 mg/kg (Source: OECD_SIDS)
LD50 dermal rabbit	1500 – 2000 mg/kg (Source: OECD_SIDS)
LD50 dermal	1750 mg/kg
LC50 Inhalation - Rat	> 21 mg/l (Exposure time: 1 h Source: OECD_SIDS)

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Additional information : Based on available data, the classification criteria are not met
Carcinogenicity : Not classified
Additional information : Based on available data, the classification criteria are not met

Benzyl acetate (140-11-4)	
IARC group	3 - Not classifiable

(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)	
IARC group	3 - Not classifiable

Eugenol (97-53-0)	
IARC group	3 - Not classifiable

Toluene (108-88-3)	
IARC group	3 - Not classifiable

Reproductive toxicity : Suspected of damaging fertility or the unborn child.
STOT-single exposure : Not classified
Additional information : Based on available data, the classification criteria are not met

Dihydromyrcenol (18479-58-8)	
STOT-single exposure	May cause drowsiness or dizziness.

Toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified
Additional information : Based on available data, the classification criteria are not met

Toluene (108-88-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified
Additional information : Based on available data, the classification criteria are not met

(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)	
Hydrocarbon	Yes

Toluene (108-88-3)	
Hydrocarbon	Yes

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Ecology - water	:	Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short–term (acute)	:	Not classified
Hazardous to the aquatic environment, long–term (chronic)	:	Toxic to aquatic life with long lasting effects.

Methyl ionone (mixture of isomers) (1335-46-2)	
LC50 - Fish [1]	2.3 mg/l (Exposure time: 96 h - Species: Danio rerio [static] Source: ECHA)

(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)	
LC50 - Fish [1]	0.619 – 0.796 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: EPA)

Phenylethyl alcohol (60-12-8)	
EC50 - Crustacea [1]	287.17 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	490 mg/l (Species: Desmodesmus subspicatus)

2(3H)-Furanone, 5-heptyldihydro- (104-67-6)	
LC50 - Fish [1]	569 mg/l 96 h
EC50 - Crustacea [1]	5.85 mg/l 48 h
EC50 - Other aquatic organisms [1]	5.94 mg/l 72 h

Linalool (78-70-6)	
LC50 - Fish [1]	27.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: ECHA)
EC50 - Crustacea [1]	20 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 96h - Algae [1]	88.3 mg/l (Species: Desmodesmus subspicatus)

Benzyl salicylate (118-58-1)	
LC50 - Fish [1]	1.03 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)

Eugenol (97-53-0)	
LC50 - Fish [1]	13 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)

1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran; galaxolide; (HHCB) (1222-05-5)	
LC50 - Fish [1]	0.452 mg/l Wolf, 1996d-27682
LC50 - Other aquatic organisms [1]	> 0.14 mg/l REACH DOSSIER Pimephales promelas
EC50 - Crustacea [2]	260 µg/l REACH Dossier
EC50 - Other aquatic organisms [1]	0.131 mg/l REACH Dossier

Toluene (108-88-3)	
LC50 - Fish [1]	15.22 – 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
EC50 - Crustacea [1]	5.46 – 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 - Crustacea [2]	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	12.5 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 96h - Algae [1]	> 433 mg/l (Species: Pseudokirchneriella subcapitata)

Dipropylene glycol monomethyl ether (34590-94-8)	
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

Dipropylene glycol monomethyl ether (34590-94-8)	
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)
hexan-1-ol (111-27-3)	
LC50 - Fish [1]	89.7 – 106 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	144 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static] Source: IUCLID)

12.2. Persistence and degradability

SEAWEED & JUNIPER CC-16046	
Persistence and degradability	May cause long-term adverse effects in the environment.
Cyclamal (103-95-7)	
Persistence and degradability	Not established.
Citronellol Pure (106-22-9)	
Persistence and degradability	Rapidly degradable
Verdyl acetate (5413-60-5)	
Persistence and degradability	Rapidly degradable
Methyl ionone (gamma) (127-42-4)	
Persistence and degradability	Rapidly degradable
Methyl ionone (mixture of isomers) (1335-46-2)	
Persistence and degradability	Rapidly degradable
Benzyl acetate (140-11-4)	
Persistence and degradability	Rapidly degradable
(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)	
Persistence and degradability	Rapidly degradable
Verdox (88-41-5)	
Persistence and degradability	Rapidly degradable
Nopyl acetate (128-51-8)	
Persistence and degradability	Rapidly degradable
Phenylethyl alcohol (60-12-8)	
Persistence and degradability	Rapidly degradable
Dihydromyrcenol (18479-58-8)	
Persistence and degradability	Rapidly degradable
2(3H)-Furanone, 5-heptyldihydro- (104-67-6)	
Persistence and degradability	Rapidly degradable
Linalool (78-70-6)	
Persistence and degradability	Rapidly degradable
tetrahydro-2-isobutyl-4-methylpyran-4-ol, mixed isomers (cis and trans) (63500-71-0)	
Persistence and degradability	Rapidly degradable

Benzyl salicylate (118-58-1)	
Persistence and degradability	Rapidly degradable

Geranyl acetate (105-87-3)	
Persistence and degradability	Rapidly degradable

1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone (54464-57-2)	
Persistence and degradability	Rapidly degradable

Eugenol (97-53-0)	
Persistence and degradability	Rapidly degradable

1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran; galaxolide; (HHCB) (1222-05-5)	
Persistence and degradability	Rapidly degradable

Amyl cinnamic aldehyde (122-40-7)	
Persistence and degradability	Rapidly degradable

Hexyl cinnamic aldehyde (101-86-0)	
Persistence and degradability	Rapidly degradable

Anisic aldehyde (123-11-5)	
Persistence and degradability	Rapidly degradable

Veratryl aldehyde (Veratraldehyde) (120-14-9)	
Persistence and degradability	Rapidly degradable

Toluene (108-88-3)	
Persistence and degradability	Rapidly degradable

Dipropylene glycol monomethyl ether (34590-94-8)	
Persistence and degradability	Rapidly degradable

Aldehyde C-12 (112-54-9)	
Persistence and degradability	Rapidly degradable

Melonal (106-72-9)	
Persistence and degradability	Rapidly degradable

hexan-1-ol (111-27-3)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

SEAWEED & JUNIPER CC-16046	
Bioaccumulative potential	Not established.

Cyclamal (103-95-7)	
Partition coefficient n-octanol/water (Log Pow)	3.4 (at 35 °C)
Bioaccumulative potential	Not established.

Citronellol Pure (106-22-9)	
Partition coefficient n-octanol/water (Log Pow)	3.41 (at 25 °C)

Verdyl acetate (5413-60-5)	
Partition coefficient n-octanol/water (Log Pow)	4.2 (at 30 °C (at pH 5.92)
Methyl ionone (mixture of isomers) (1335-46-2)	
Partition coefficient n-octanol/water (Log Pow)	(>4.5 - <5 - at 23 °C (at pH 6.2)
Benzyl acetate (140-11-4)	
Partition coefficient n-octanol/water (Log Pow)	1.96 (at 25 °C (at pH 7)
(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)	
Partition coefficient n-octanol/water (Log Pow)	4.38 (at 37 °C (at pH 7.2)
Phenylethyl alcohol (60-12-8)	
Partition coefficient n-octanol/water (Log Pow)	1.36 (at 20 °C (at pH 7)
Dihydromyrcenol (18479-58-8)	
Partition coefficient n-octanol/water (Log Pow)	3.25 (at 40 °C (at pH 7)
2(3H)-Furanone, 5-heptyldihydro- (104-67-6)	
Partition coefficient n-octanol/water (Log Pow)	3.6 (at 25 °C)
Linalool (78-70-6)	
Partition coefficient n-octanol/water (Log Pow)	2.9 (at 20 °C (at pH 7)
tetrahydro-2-isobutyl-4-methylpyran-4-ol, mixed isomers (cis and trans) (63500-71-0)	
Partition coefficient n-octanol/water (Log Pow)	1.65 (at 23 °C (at pH >6.09-<6.74)
Benzyl salicylate (118-58-1)	
Partition coefficient n-octanol/water (Log Pow)	4
Geranyl acetate (105-87-3)	
Partition coefficient n-octanol/water (Log Pow)	4.04
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone (54464-57-2)	
Partition coefficient n-octanol/water (Log Pow)	5.65 (at 30°C)
Eugenol (97-53-0)	
Partition coefficient n-octanol/water (Log Pow)	1.83 (at 30 °C (at pH 5.5)
1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran; galaxolide; (HHCB) (1222-05-5)	
BCF - Fish [1]	(1618 dimensionless (whole body w.w.)
Partition coefficient n-octanol/water (Log Pow)	5.3 (at 25 °C (at pH 7)
Amyl cinnamic aldehyde (122-40-7)	
Partition coefficient n-octanol/water (Log Pow)	2.498 (at 25 °C (at pH 6.2)
Anisic aldehyde (123-11-5)	
Partition coefficient n-octanol/water (Log Pow)	1.56 (at 25 °C (at pH >7.9-<8.25)
Veratryl aldehyde (Veratraldehyde) (120-14-9)	
Partition coefficient n-octanol/water (Log Pow)	0.8 (at 25 °C)
Toluene (108-88-3)	
Partition coefficient n-octanol/water (Log Pow)	2.73 (at 20 °C (at pH 7)

Dipropylene glycol monomethyl ether (34590-94-8)	
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7)

Aldehyde C-12 (112-54-9)	
Partition coefficient n-octanol/water (Log Pow)	4.9 (at 35 °C)

Melonal (106-72-9)	
Partition coefficient n-octanol/water (Log Pow)	3.4 (at 35 °C (at pH 7)

hexan-1-ol (111-27-3)	
Partition coefficient n-octanol/water (Log Pow)	1.8

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Cyclamal (103-95-7)	
Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with local/national laws and regulations.

Ecological waste information : Avoid release to the environment.

HP Code : HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.
HP10 - "Toxic for reproduction:" waste which has adverse effects on sexual function and fertility in adult males and females, as well as developmental toxicity in the offspring.
HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (HEXYL SALICYLATE)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (HEXYL SALICYLATE)	Environmentally hazardous substance, liquid, n.o.s. (HEXYL SALICYLATE)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (HEXYL SALICYLATE)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (HEXYL SALICYLATE)

ADR	IMDG	IATA	ADN	RID
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (HEXYL SALICYLATE), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (HEXYL SALICYLATE), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (HEXYL SALICYLATE), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (HEXYL SALICYLATE), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (HEXYL SALICYLATE), 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : M6
Special provisions (ADR) : 274, 335, 375, 601, 650
Limited quantities (ADR) : 5l
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions (ADR) : TP1, TP29
Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading and handling (ADR) : CV13
Hazard identification number (Kemler No.) : 90
Orange plates :



Tunnel restriction code (ADR) : -
EAC code : •3Z

Transport by sea

Special provisions (IMDG) : 274, 335, 375, 969
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : LP01, P001
Special packing provisions (IMDG) : PP1

IBC packing instructions (IMDG)	:	IBC03
Tank instructions (IMDG)	:	T4
Tank special provisions (IMDG)	:	TP1, TP29
EmS-No. (Fire)	:	F-A
EmS-No. (Spillage)	:	S-F
Stowage category (IMDG)	:	A

Air transport

PCA Excepted quantities (IATA)	:	E1
PCA Limited quantities (IATA)	:	Y964
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	964
PCA max net quantity (IATA)	:	450L
CAO packing instructions (IATA)	:	964
CAO max net quantity (IATA)	:	450L
Special provisions (IATA)	:	A97, A158, A197, A215
ERG code (IATA)	:	9L

Inland waterway transport

Classification code (ADN)	:	M6
Special provisions (ADN)	:	274, 335, 375, 601, 650
Limited quantities (ADN)	:	5 L
Excepted quantities (ADN)	:	E1
Carriage permitted (ADN)	:	T
Equipment required (ADN)	:	PP
Number of blue cones/lights (ADN)	:	0

Rail transport

Classification code (RID)	:	M6
Special provisions (RID)	:	274, 335, 375, 601, 650
Limited quantities (RID)	:	5L
Excepted quantities (RID)	:	E1
Packing instructions (RID)	:	P001, IBC03, LP01, R001
Special packing provisions (RID)	:	PP1
Mixed packing provisions (RID)	:	MP19
Portable tank and bulk container instructions (RID)	:	T4
Portable tank and bulk container special provisions (RID)	:	TP1, TP29
Tank codes for RID tanks (RID)	:	LGBV
Transport category (RID)	:	3
Special provisions for carriage – Packages (RID)	:	W12
Special provisions for carriage - Loading, unloading and handling (RID)	:	CW13, CW31
Colis express (express parcels) (RID)	:	CE8
Hazard identification number (RID)	:	90

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	**Applicable on**	**Entry title or description**
3(a)	d-Limonene ; Toluene ; Hexyl alcohol	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	SEAWEED & JUNIPER CC-16046 ; Cyclamal ; Citronellol Pure ; Methyl ionone (gamma) ; Methyl ionone (mixture of isomers) ; d-Limonene ; Nopyl acetate ; Phenylethyl alcohol ; Dihydromyrcenol ; Linalool ; Florol ; Benzyl salicylate ; Geranyl acetate ; 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone ; Eugenol ; Amyl cinnamic aldehyde ; Hexyl cinnamic aldehyde ; Anisic aldehyde ; Toluene ; Aldehyde C-12 ; Melonal ; Hexyl alcohol	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	SEAWEED & JUNIPER CC-16046 ; Cyclamal ; Verdyl acetate ; Methyl ionone (gamma) ; Benzyl acetate ; d-Limonene ; Verdox ; Nopyl acetate ; Aldehyde C-14 ; Benzyl salicylate ; Geranyl acetate ; 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone ; Hexamethylindanopyran ; Amyl cinnamic aldehyde ; Hexyl cinnamic aldehyde ; Anisic aldehyde ; Aldehyde C-12	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
48.	Toluene	Toluene

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 20.65338836 % (calculated value)(CARB VOC) (%w/w)

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Toluene		108-88-3	2902 30 00	Category 3		Annex I

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

VOC ordinance (ChemVOCFarbV) : VOC content : 20.65338836 % (calculated value)(CARB VOC) (%w/w)

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG). Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Major Accidents Ordinance (12. BImSchV) : Is not subject to the Major Accidents Ordinance (12. BImSchV)

Netherlands

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment

SZW List of Carcinogenic Substances : None of the components are listed

SZW List of Mutagenic Substances : None of the components are listed

SZW List of Reprotoxic Substances – Breastfeeding : None of the components are listed

SZW List of Reprotoxic Substances – Fertility : None of the components are listed

SZW List of Reprotoxic Substances – Development : Toluene is listed

Denmark

Class for fire hazard : Class III-1

Store unit : 50 liter

Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with it.
If an employee is pregnant or breastfeeding and the person in question uses or is exposed to this product at work, the employer must always carry out a risk assessment of the work. The assessment must both deal with the dangerousness of the impact and its strength and duration. The employer's decision that a pregnant or lactating woman can perform a specific work task must therefore be made in the context of her specific working conditions. See also WEA-Guideline A.1.8-7 on the working environment of pregnant and breastfeeding workers.

Poland

Polish National Regulations : Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).
Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).
The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).
Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).
Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).
Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).
The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488)
Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended).
Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).
ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)
Regulation of the Minister of Health of 25 August 2015 on the method of marking places, pipelines, and containers and tanks used for storing or containing hazardous substances or hazardous mixtures (J.o.L. 2015, item 1368 as amended)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level

Abbreviations and acronyms:	
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstracts Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1

Full text of H- and EUH-statements:	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.