Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : BANANA CREME CC-16055 10%

Product code : CC-16055_10%
Type of product : Perfumes, fragrances

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial

For professional use only : Perfumes, fragrances

Use of the substance/mixture : Perfumes, fragram Function or use category : Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Candle Craft Weiherwiese 10 65510 Idstein - Germany T 49-6126-9363 -0

info@candlecraft.de - www.candlecraft.de

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP) : -

Hazard statements (CLP) : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P273 - Avoid release to the environment.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

EUH208 - Contains d-Limonene. May produce an allergic reaction.

Extra phrases : For professional users only.

2.3. Other hazards

EUH-statements

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

EN (English) 1/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371- 33	3.86 – 7.72	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Isoamyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, DE, DK, EE, ES, FI, FR, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, TR); substance with a Community workplace exposure limit	CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2 REACH-no: 01-2119548408- 32	0.12 – 0.235	Flam. Liq. 3, H226
d-Limonene substance with national workplace exposure limit(s) (DE, ES, FI, SI, NO, CH)	CAS-No.: 5989-27-5 EC-No.: 205-341-0 EC Index-No.: 601-096-00-2 REACH-no: 01-2119493353- 35	0.09 – 0.18	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Hexamethylindanopyran	CAS-No.: 1222-05-5 EC-No.: 214-946-9 EC Index-No.: 603-212-00-7 REACH-no: 01-2119488227-	0.06 – 0.11	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Benzyl acetate substance with national workplace exposure limit(s) (BE, DK, ES, IE, LT, LV, PT, RO)	CAS-No.: 140-11-4 EC-No.: 205-399-7 REACH-no: 01-2119638272- 42	0.03 – 0.065	Aquatic Chronic 3, H412
Isobutyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH)	CAS-No.: 110-19-0 EC-No.: 203-745-1 EC Index-No.: 607-026-00-7	0.03 – 0.06	Flam. Liq. 2, H225 STOT SE 3, H336
1,2-Propanediol substance with national workplace exposure limit(s) (GB, HR, IE, LT, LV, PL, NO)	CAS-No.: 57-55-6 EC-No.: 200-338-0 REACH-no: 01-2119456809- 23	0.01 – 0.016	Not classified
Ethyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-	0.01 – 0.015	Flam. Liq. 1, H224 Eye Irrit. 2, H319 STOT SE 3, H336
Isovaleraldehyde substance with national workplace exposure limit(s) (AT, DE, LT, SI)	CAS-No.: 590-86-3 EC-No.: 209-691-5	0.01 – 0.01	Flam. Liq. 2, H225 Eye Irrit. 2, H319 Skin Sens. 1B, H317 STOT SE 3, H335 Aquatic Chronic 2, H411

EN (English) 2/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Butyric acid substance with national workplace exposure limit(s) (BG, LT, LV, RO)	CAS-No.: 107-92-6 EC-No.: 203-532-3 EC Index-No.: 607-135-00-X	0 – 0.005	Skin Corr. 1B, H314

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water,

followed by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

persists.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

EN (English) 3/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep only in the original container in a cool, well ventilated place away from : Keep

container closed when not in use.Strong bases. Strong acids.

Incompatible products Incompatible materials

: Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Isoamyl acetate (123-92-2)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	270 mg/m³	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	540 mg/m³	
IOEL STEL [ppm]	100 ppm	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	270 mg/m³ (Pentyl acetate (all isomers))	
MAK (OEL TWA) [ppm]	50 ppm (Pentyl acetate (all isomers))	
MAK (OEL STEL)	540 mg/m³ (Pentylacetate)	
MAK (OEL STEL) [ppm]	100 ppm (Pentylacetate)	
Belgium - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Bulgaria - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	

EN (English) 4/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Isoamyl acetate (123-92-2)		
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA) [1]	270 mg/m³	
GVI (OEL TWA) [2]	50 ppm	
KGVI (OEL STEL)	540 mg/m³	
KGVI (OEL STEL) [ppm]	100 ppm	
Cyprus - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	271 mg/m³ (Amyl acetate, all isomers)	
OEL TWA [2]	50 ppm (Amyl acetate, all isomers)	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Estonia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Finland - Occupational Exposure Limits		
HTP (OEL TWA) [1]	270 mg/m³ (Pentyl acetate)	
HTP (OEL TWA) [2]	50 ppm (Pentyl acetate)	
HTP (OEL STEL)	540 mg/m³	
HTP (OEL STEL) [ppm]	100 ppm	
France - Occupational Exposure Limits		
VME (OEL TWA)	270 mg/m³ (restrictive limit)	
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)	
VLE (OEL C/STEL)	540 mg/m³ (restrictive limit)	
VLE (OEL C/STEL) [ppm]	100 ppm (restrictive limit)	
Germany - Occupational Exposure Limits (TRGS 900)		
AGW (OEL TWA) [1]	270 mg/m³	
AGW (OEL TWA) [2]	50 ppm	
Gibraltar - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	

EN (English) 5/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Isoamyl acetate (123-92-2)		
OEL STEL [ppm]	100 ppm	
Greece - Occupational Exposure Limits		
OEL TWA	530 mg/m³	
OEL TWA [ppm]	100 ppm	
OEL STEL	800 mg/m³	
OEL STEL [ppm]	150 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	270 mg/m³	
CK (OEL STEL)	540 mg/m³	
Ireland - Occupational Exposure Limits		
OEL TWA [1]	260 mg/m³	
OEL TWA [2]	50 ppm	
OEL STEL	520 mg/m³	
OEL STEL [ppm]	100 ppm	
Italy - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Latvia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	270 mg/m ³	
IPRV (OEL TWA) [ppm]	50 ppm	
TPRV (OEL STEL)	540 mg/m³	
TPRV (OEL STEL) [ppm]	100 ppm	
Luxembourg - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Malta - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Netherlands - Occupational Exposure Limits		
TGG-15min (OEL STEL)	530 mg/m³	

EN (English) 6/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Isoamyl acetate (123-92-2)		
TGG-15min (OEL STEL) [ppm]	98.1 ppm	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	250 mg/m³	
NDSCh (OEL STEL)	500 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	270 mg/m³ (indicative limit value)	
OEL TWA [ppm]	50 ppm (indicative limit value (Pentyl acetate, all isomers)	
OEL STEL	540 mg/m³ (indicative limit value)	
OEL STEL [ppm]	100 ppm (indicative limit value)	
Romania - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA) [1]	270 mg/m³	
NPHV (OEL TWA) [2]	50 ppm	
NPHV (OEL C)	540 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	270 mg/m³ (indicative limit value)	
VLA-ED (OEL TWA) [2]	50 ppm (indicative limit value)	
VLA-EC (OEL STEL)	540 mg/m³	
VLA-EC (OEL STEL) [ppm]	100 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	270 mg/m³ (Pentyl acetates)	
NGV (OEL TWA) [ppm]	50 ppm (Pentyl acetates)	
KTV (OEL STEL)	540 mg/m³ (Pentyl acetates)	
KTV (OEL STEL) [ppm]	100 ppm (Pentyl acetates)	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	260 mg/m³	
Grenseverdi (OEL TWA) [2]	50 ppm	
Korttidsverdi (OEL STEL)	325 mg/m³ (value calculated)	
Korttidsverdi (OEL STEL) [ppm]	75 ppm (value calculated)	

EN (English) 7/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Isoamyl acetate (123-92-2)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	50 ppm (Pentyl acetate, all isomers)	
ACGIH OEL STEL [ppm]	100 ppm (Pentyl acetate, all isomers)	
d-Limonene (5989-27-5)		
Finland - Occupational Exposure Limits		
HTP (OEL TWA) [1]	140 mg/m³	
HTP (OEL TWA) [2]	25 ppm	
HTP (OEL STEL)	280 mg/m³	
HTP (OEL STEL) [ppm]	50 ppm	
Germany - Occupational Exposure Limits (TRGS 90	0)	
AGW (OEL TWA) [1]	28 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
AGW (OEL TWA) [2]	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Chemical category	Skin notation, Skin sensitization	
Slovenia - Occupational Exposure Limits		
OEL TWA	28 mg/m³	
OEL TWA [ppm]	5 ppm	
OEL STEL	112 mg/m³	
OEL STEL [ppm]	20 ppm	
OEL chemical category	Potential for cutaneous absorption	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	168 mg/m³	
VLA-ED (OEL TWA) [2]	30 ppm	
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	140 mg/m³	
Grenseverdi (OEL TWA) [2]	25 ppm	
Korttidsverdi (OEL STEL)	175 mg/m³ (value calculated)	
Korttidsverdi (OEL STEL) [ppm]	37.5 ppm (value calculated)	
OEL chemical category	Allergenic substance	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA) [1]	40 mg/m³	
MAK (OEL TWA) [2]	7 ppm	
KZGW (OEL STEL)	80 mg/m³	
KZGW (OEL STEL) [ppm]	14 ppm	
OEL chemical category	Sensitizer	

EN (English) 8/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Benzyl acetate (140-11-4)		
Belgium - Occupational Exposure Limits		
OEL TWA	62 mg/m³	
OEL TWA [ppm]	10 ppm	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	61 mg/m³	
OEL TWA [2]	10 ppm	
OEL STEL	122 mg/m³	
OEL STEL [ppm]	20 ppm	
Ireland - Occupational Exposure Limits		
OEL TWA [2]	10 ppm	
OEL STEL [ppm]	30 ppm (calculated)	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA [ppm]	10 ppm	
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen	
Romania - Occupational Exposure Limits		
OEL TWA	50 mg/m³	
OEL TWA [ppm]	8 ppm	
OEL STEL	80 mg/m³	
OEL STEL [ppm]	13 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	62 mg/m³	
VLA-ED (OEL TWA) [2]	10 ppm	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	10 ppm	
ACGIH chemical category	Not Classifiable as a Human Carcinogen	
Isobutyl acetate (110-19-0)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	241 mg/m³ (Butyl acetates)	
MAK (OEL TWA) [ppm]	50 ppm (Butyl acetates)	
MAK (OEL STEL)	480 mg/m³ (Butyl acetate)	
MAK (OEL STEL) [ppm]	100 ppm (Butyl acetate)	
Belgium - Occupational Exposure Limits		
OEL TWA	238 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	712 mg/m³	

EN (English) 9/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Isobutyl acetate (110-19-0)		
OEL STEL [ppm]	150 ppm	
Bulgaria - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA) [1]	241 mg/m³	
GVI (OEL TWA) [2]	50 ppm	
KGVI (OEL STEL)	723 mg/m³	
KGVI (OEL STEL) [ppm]	150 ppm	
Cyprus - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	241 mg/m³	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	241 mg/m³ (Butyl acetate, all isomers)	
OEL TWA [2]	50 ppm (Butyl acetate, all isomers)	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Estonia - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Finland - Occupational Exposure Limits		
HTP (OEL TWA) [1]	240 mg/m³ (Butyl acetate)	
HTP (OEL TWA) [2]	50 ppm (Butyl acetate)	
HTP (OEL STEL)	725 mg/m³ (Butyl acetate)	
HTP (OEL STEL) [ppm]	150 ppm (Butyl acetate)	
France - Occupational Exposure Limits		
VME (OEL TWA)	241 mg/m³ (restrictive limit)	
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)	
VLE (OEL C/STEL)	723 mg/m³ (restrictive limit)	
VLE (OEL C/STEL) [ppm]	150 ppm (restrictive limit)	

EN (English) 10/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Isobutyl acetate (110-19-0)		
Germany - Occupational Exposure Limits (TRGS 900)		
AGW (OEL TWA) [1]	300 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
AGW (OEL TWA) [2]	62 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Greece - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	241 mg/m³	
CK (OEL STEL)	723 mg/m³	
OEL chemical category	Sensitizer	
Ireland - Occupational Exposure Limits		
OEL TWA [1]	241 mg/m³	
OEL TWA [2]	50 ppm	
OEL STEL	723 mg/m³ (calculated)	
OEL STEL [ppm]	150 ppm (calculated)	
Italy - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Latvia - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	241 mg/m³	
IPRV (OEL TWA) [ppm]	50 ppm	
TPRV (OEL STEL)	723 mg/m³	
TPRV (OEL STEL) [ppm]	150 ppm	
Luxembourg - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Malta - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	

EN (English) 11/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Isobutyl acetate (110-19-0)		
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Netherlands - Occupational Exposure Limits		
TGG-8u (OEL TWA)	241 mg/m³	
TGG-8u (OEL TWA) [ppm]	50 ppm	
TGG-15min (OEL STEL)	723 mg/m³	
TGG-15min (OEL STEL) [ppm]	150 ppm	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	240 mg/m³	
NDSCh (OEL STEL)	720 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	241 mg/m³ (indicative limit value)	
OEL TWA [ppm]	50 ppm (indicative limit value)	
OEL STEL	723 mg/m³ (indicative limit value)	
OEL STEL [ppm]	150 ppm (indicative limit value)	
Romania - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA) [1]	480 mg/m³	
NPHV (OEL TWA) [2]	100 ppm	
NPHV (OEL C)	700 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	241 mg/m³	
VLA-ED (OEL TWA) [2]	50 ppm	
VLA-EC (OEL STEL)	723 mg/m³	
VLA-EC (OEL STEL) [ppm]	150 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	241 mg/m³ (Butyl acetates)	
NGV (OEL TWA) [ppm]	50 ppm (Butyl acetates)	
KTV (OEL STEL)	723 mg/m³ (Butyl acetates)	
KTV (OEL STEL) [ppm]	150 ppm (Butyl acetates)	

EN (English) 12/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Isobutyl acetate (110-19-0)		
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	724 mg/m³	
WEL TWA (OEL TWA) [2]	150 ppm	
WEL STEL (OEL STEL)	903 mg/m³	
WEL STEL (OEL STEL) [ppm]	187 ppm	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	241 mg/m³	
Grenseverdi (OEL TWA) [2]	50 ppm	
Korttidsverdi (OEL STEL)	723 mg/m³ (value from the regulation)	
Korttidsverdi (OEL STEL) [ppm]	150 ppm (value from the regulation)	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA) [1]	240 mg/m³	
MAK (OEL TWA) [2]	50 ppm	
KZGW (OEL STEL)	720 mg/m³	
KZGW (OEL STEL) [ppm]	150 ppm	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	50 ppm (Butyl acetates, all isomers)	
ACGIH OEL STEL [ppm]	150 ppm (Butyl acetates, all isomers)	
1,2-Propanediol (57-55-6)		
Croatia - Occupational Exposure Limits		
GVI (OEL TWA) [1]	474 mg/m³ (total vapor and particles) 10 mg/m³ (particles)	
GVI (OEL TWA) [2]	150 ppm	
Ireland - Occupational Exposure Limits		
OEL TWA [1]	10 mg/m³ (particulates) 470 mg/m³ (total vapour and particulates)	
OEL TWA [2]	150 ppm (total vapour and particulates)	
OEL STEL	1410 mg/m³ (calculated-particulates) 30 mg/m³ (calculated)	
OEL STEL [ppm]	450 ppm (calculated-total vapour and particulates)	
Latvia - Occupational Exposure Limits		
OEL TWA	7 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	7 mg/m³	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	100 mg/m³ (vapor and inhalable fraction)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	474 mg/m³ (total vapour and particulates) 10 mg/m³ (particulates)	
WEL TWA (OEL TWA) [2]	150 ppm (total vapour and particulates)	

EN (English) 13/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

1,2-Propanectiol (57-55-6) WEL STEL (CEL STEL) [ppm] 1422 mg/m² (calculated-particulates) WEL STEL (CEL STEL) [ppm] 450 ppm (calculated-particulates) Norway - Occupational Exposure Limits 78 mg/m² Geneaeverd (CEL TWA) [1] 25 ppm Kortidoverdi (OEL STEL) (ppm] 37.5 ppm (value calculated) Kortidoverdi (OEL STEL) (ppm] 37.5 ppm (value calculated) Kortidoverdi (OEL STEL) (ppm] 37.5 ppm (value calculated) Ethyl accutate (141-78-6) ************************************				
Kel STEL (plam) 30 mg/m² (calculated-porticulates) Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) (1) 79 mg/m² Grenseverdi (OEL TWA) (2) 25 ppm Kortidoverdi (OEL STEL) (plom) 118.5 mg/m² (value calculated) Kortidoverdi (OEL STEL) (plom) 75.5 ppm (value calculated) Ethyl accetate (141-78-6) Ethyl accetate (141-78-6) EU-Indicative Occupational Exposure Limit (OEL*) Indicative Occupational Exposure Limit (OEL*) OEL TWA (plom) OEL STEL (plom) 200 ppm OEL STEL (plom) Mak (Sel E TWA) 734 mg/m² MAK (OEL TWA) (plom) 744 mg/m² MAK (OEL TWA) (plom) 400 ppm Austria - Occupational Exposure Limits OEL TWA OEL TWA (plom) 734 mg/m² OEL TWA (plom) 400 ppm OEL STEL (plom) 400 ppm OEL TWA (plom) 200 ppm </td <td colspan="4">1,2-Propanediol (57-55-6)</td>	1,2-Propanediol (57-55-6)			
Norway - Occupational Exposure Limits 79 mg/m² 79	WEL STEL (OEL STEL)			
Grenseverd (OEL TWA) [1] 78 mg/m² Grenseverd (OEL TWA) [2] 28 ppm Kortidsverd (OEL STEL) 118 s mg/m² (value calculated) Kortidsverd (OEL STEL) [ppm] 37.5 ppm (value calculated) Ethyl accutate (141-78-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA 734 mg/m² IOEL TWA [ppm] 200 ppm IOEL STEL [ppm] 406 ppm MAK (OEL TWA) 734 mg/m² MAK (OEL TWA) [ppm] 200 ppm MAK (OEL STEL) [ppm] 406 ppm MAK (OEL STEL) [ppm] 200 ppm MAK (OEL STEL) [ppm] 200 ppm MAK (OEL STEL) [ppm] 200 ppm OEL TWA [ppm] A 34 mg/m² <th colsp<="" td=""><td>WEL STEL (OEL STEL) [ppm]</td><td>450 ppm (calculated-total vapour and particulates)</td></th>	<td>WEL STEL (OEL STEL) [ppm]</td> <td>450 ppm (calculated-total vapour and particulates)</td>	WEL STEL (OEL STEL) [ppm]	450 ppm (calculated-total vapour and particulates)	
Grenseverdi (OEL TWA) [2] 25 ppm Kortidosverdi (OEL STEL) (ppm) 37.5 ppm (value calculated) Ethylacotate (141-78-6) EU - Indicative Occupational Exposure Limit (IOEL**) IOEL TWA 734 mg/m² IOEL TWA (ppm) 200 ppm IOEL STEL (ppm) 400 ppm Austria - Occupational Exposure Limits 734 mg/m² MAK (OEL TWA) (ppm) 200 ppm MAK (OEL TWA) (ppm) 200 ppm MAK (OEL TWA) (ppm) 200 ppm MAK (OEL STEL) (ppm) 400 ppm Belgium - Occupational Exposure Limits 734 mg/m² OEL TWA (ppm) 200 ppm Belgium - Occupational Exposure Limits 734 mg/m² OEL TWA (ppm) 200 ppm OEL TWA (ppm) 200 ppm OEL STEL (ppm) 400 ppm Bulgaria - Occupational Exposure Limits 734 mg/m² OEL TWA (ppm) 200 ppm OEL TWA (ppm) 200 ppm OEL TWA (ppm) 400 ppm OEL TWA (ppm) 200 ppm OEL TWA (ppm) 400 ppm Croatia - Occupational Expos	Norway - Occupational Exposure Limits			
Korttidsverdi (OEL STEL) [pm] 118.5 mg/m² (value calculated) Ethyl acetate (141-78-6) EU -Indicative Occupational Exposure Limit (IOEL*) IOEL TWA 734 mg/m² IOEL TWA [pm] 200 ppm IOEL STEL 1468 mg/m² IOEL STEL [pm] 400 ppm Austra - Occupational Exposure Limits Wargim² MAK (OEL TWA) 734 mg/m² MAK (OEL TWA) [pm] 200 ppm MAK (OEL TWA) [pm] 400 ppm MAK (OEL STEL) [pm] 400 ppm Belgium - Occupational Exposure Limits Variance OEL TWA 734 mg/m² OEL TWA [pm] 200 ppm OEL STEL [pm] 400 ppm Bulgaria - Occupational Exposure Limits Variance OEL STEL [pm] 400 ppm Bulgaria - Occupational Exposure Limits Variance OEL TWA [pm] 200 ppm OEL STEL [pm] 400 ppm Couts - Occupational Exposure Limits Varianc	Grenseverdi (OEL TWA) [1]	79 mg/m³		
Kortidosverdi (OEL STEL) (ppm) 37.5 ppm (value calculated) Ethyl accetate (141-78-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA 734 mg/m² IOEL TWA (ppm) 200 ppm OEL STEL 1468 mg/m² IOEL STEL (ppm) 400 ppm Austria - Occupational Exposure Limits T34 mg/m² MAK (OEL TWA) 734 mg/m² MAK (OEL STEL) (ppm) 400 ppm MAK (OEL STEL) (ppm) 400 ppm Belgium - Occupational Exposure Limits T04 mg/m² OEL TWA (ppm) 200 ppm OEL TWA (ppm) 200 ppm OEL STEL (ppm) 400 ppm OEL STEL (ppm) 400 ppm OEL STEL (ppm) 400 ppm OEL STEL (ppm) 200 ppm OEL STEL (ppm) 400 ppm OEL TWA (ppm) 200 ppm OEL STEL (ppm) 400 ppm Coptia STEL (ppm) <td< td=""><td>Grenseverdi (OEL TWA) [2]</td><td>25 ppm</td></td<>	Grenseverdi (OEL TWA) [2]	25 ppm		
Ethyl acetate (141-78-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA	Korttidsverdi (OEL STEL)	118.5 mg/m³ (value calculated)		
EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA Fight 734 mg/m³ IOEL TWA Fight 794 mg/m³ IOEL STEL 1488 mg/m³ 794 mg/m³ IOEL STEL 1488 mg/m³ 794 mg/m² 794 mg/m³ IOEL STEL 797 mg/m³ 794 mg/m³	Korttidsverdi (OEL STEL) [ppm]	37.5 ppm (value calculated)		
COEL TWA FORM TAY May	Ethyl acetate (141-78-6)			
COEL TWA (ppm) 200 ppm COEL STEL 1468 mg/m² COEL STEL (ppm) 400 ppm COEL	EU - Indicative Occupational Exposure Limit (IOEL)			
Total	IOEL TWA	734 mg/m³		
Austria - Occupational Exposure Limits	IOEL TWA [ppm]	200 ppm		
Austria - Occupational Exposure Limits MAK (OEL TWA) [ppm] 200 ppm MAK (OEL STEL) 1468 mg/m³ MAK (OEL STEL) [ppm] 400 ppm Belgium - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA 734 mg/m³ OEL STEL 1468 mg/m³ OEL STEL 1468 mg/m³ OEL STEL 169 mg 400 ppm Bulgaria - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA 734 mg/m³ OEL TWA 734 mg/m³ OEL TWA 734 mg/m³ OEL STEL 1468 mg/m³ OEL STEL 160 pm] 400 ppm Croatia - Occupational Exposure Limits GVI (OEL TWA) [1] 734 mg/m³ GVI (OEL TWA) [2] 200 ppm KGVI (OEL STEL) 1468 mg/m³ KGVI (OEL STEL) 1468 mg/m³ Cyprus - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³ OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³	IOEL STEL	1468 mg/m³		
MAK (OEL TWA) [ppm] 200 ppm MAK (OEL STEL) [1488 mg/m² 400 ppm Belgium - Occupational Exposure Limits OEL TWA [ppm] 200 ppm OEL TWA [ppm] 200 ppm OEL STEL [1468 mg/m² 400 ppm Bulgaria - Occupational Exposure Limits OEL TWA [200 ppm 400 ppm OEL STEL [200 ppm 400 ppm OEL STEL [200 ppm 400 ppm OEL STEL [200 ppm 400 ppm OEL TWA [200 ppm 400 ppm OEL TWA [200 ppm 400 ppm OEL TWA [200 ppm 400 ppm OEL STEL [200 ppm 400 ppm OEL STEL [200 ppm 400 ppm OEL STEL [200 ppm 400 ppm Croatia - Occupational Exposure Limits OFL STEL [200 ppm 400 ppm Croatia - Occupational Exposure Limits OFL [200 ppm 400 ppm Croatia - Occupational Exposure Limits OFL [200 ppm 400 ppm Croatia - Occupational Exposure Limits OFL [200 ppm 400 ppm Croatia - Occupational Exposure Limits OFL [200 ppm 400 ppm Croatia - Occupational Exposure Limits OFL [200 ppm 400 ppm Croatia - Occupational Exposure Limits OFL [200 ppm 400 ppm Croatia - Occupational Exposure Limits OFL [200 ppm 400 ppm Croatia - Occupational Exposure Limits OFL [200 ppm 400 ppm Croatia - Occupational Exposure Limits OFL [200 ppm 400 ppm Croatia - Occupational Exposure Limits OFL [200 ppm 400 ppm Croatia - Occupational Exposure Limits OFL [200 ppm 400 ppm Croatia - Occupational Exposure Limits OFL [200 ppm 400 ppm OFL [200 ppm 400 ppm	IOEL STEL [ppm]	400 ppm		
MAK (OEL TWA) [ppm] 200 ppm MAK (OEL STEL) 1488 mg/m² MAK (OEL STEL) [ppm] 400 ppm Belgium - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL STEL 1488 mg/m³ OEL STEL [ppm] 400 ppm Bulgaria - Occupational Exposure Limits OEL TWA [ppm] 200 ppm OEL STEL [ppm] 400 ppm OEL STEL [ppm] 200 ppm OEL STEL [ppm] 400 ppm CEL TWA [ppm] 200 ppm OEL STEL [ppm] 400 ppm Croatia - Occupational Exposure Limits GVI (OEL TWA) [1] 734 mg/m³ GVI (OEL TWA) [2] 200 ppm KGVI (OEL STEL) 1468 mg/m³ KGVI (OEL STEL) 1468 mg/m³ Cyrus - Occupational Exposure Limits Cyrus - Occupational Exposure Limits Cyrus - Occupational Exposure Limits OEL TWA [1] 734 mg/m³ GVI (OEL STEL) 1468 mg/m³ KGVI (OEL STEL) [ppm] 400 ppm Cyprus - Occupational Exposure Limits OEL TWA [1] 734 mg/m³ OEL TWA [1] 400 ppm Cyprus - Occupational Exposure Limits OEL TWA [1] 734 mg/m³	Austria - Occupational Exposure Limits			
MAK (OEL STEL) [ppm] 400 ppm Belgium - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³ OEL STEL [ppm] 400 ppm Bulgaria - Occupational Exposure Limits OEL TWA [ppm] 200 ppm OEL STEL [ppm] 400 ppm DEL STEL [ppm] 200 ppm OEL STEL [ppm] 200 ppm OEL STEL [ppm] 400 ppm COEL TWA [ppm] 200 ppm OEL STEL [ppm] 400 ppm Croatia - Occupational Exposure Limits GVI (OEL TWA) [1] 734 mg/m³ GVI (OEL TWA) [2] 200 ppm KGVI (OEL STEL) 1468 mg/m³ KGVI (OEL STEL) 1468 mg/m³ Cyrus - Occupational Exposure Limits OEL TWA [ppm] 400 ppm Cyprus - Occupational Exposure Limits OEL TWA [ppm] 200 ppm OEL STEL [ppm] 4468 mg/m³	MAK (OEL TWA)	734 mg/m³		
MAK (OEL STEL) [ppm]	MAK (OEL TWA) [ppm]	200 ppm		
Del TWA	MAK (OEL STEL)	1468 mg/m³		
OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³ OEL STEL [ppm] 400 ppm Bulgaria - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³ OEL STEL [ppm] 400 ppm Croatia - Occupational Exposure Limits GVI (OEL TWA) [1] 734 mg/m³ GVI (OEL STEL) 1468 mg/m³ KGVI (OEL STEL) [ppm] 400 ppm Cyprus - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL TWA [ppm] 200 ppm OEL TWA [ppm] 200 ppm	MAK (OEL STEL) [ppm]	400 ppm		
OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³ OEL STEL [ppm] 400 ppm Bulgaria - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³ OEL STEL [ppm] 400 ppm Croatia - Occupational Exposure Limits GVI (OEL TWA) [1] 734 mg/m³ GVI (OEL STEL) 1468 mg/m³ KGVI (OEL STEL) [ppm] 400 ppm Cyprus - Occupational Exposure Limits OEL TWA [ppm] 200 ppm	Belgium - Occupational Exposure Limits			
OEL STEL 1468 mg/m³ OEL STEL [ppm] 400 ppm Bulgaria - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³ OEL STEL [ppm] 400 ppm Croatia - Occupational Exposure Limits GVI (OEL TWA) [1] 734 mg/m³ GVI (OEL TWA) [2] 200 ppm KGVI (OEL STEL) 1468 mg/m³ KGVI (OEL STEL) [ppm] 400 ppm Cyprus - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³	OEL TWA	734 mg/m³		
OEL STEL [ppm] 400 ppm Bulgaria - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³ OEL STEL [ppm] 400 ppm Croatia - Occupational Exposure Limits GVI (OEL TWA) [1] 734 mg/m³ GVI (OEL STEL) 1468 mg/m³ KGVI (OEL STEL) [ppm] 400 ppm Cyprus - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³	OEL TWA [ppm]	200 ppm		
Del TWA 734 mg/m³ 200 ppm 20	OEL STEL	1468 mg/m³		
OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³ OEL STEL [ppm] 400 ppm Croatia - Occupational Exposure Limits GVI (OEL TWA) [1] 734 mg/m³ GVI (OEL TWA) [2] 200 ppm KGVI (OEL STEL) 1468 mg/m³ KGVI (OEL STEL) [ppm] 400 ppm Cyprus - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³	OEL STEL [ppm]	400 ppm		
OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³ OEL STEL [ppm] 400 ppm Croatia - Occupational Exposure Limits GVI (OEL TWA) [1] 734 mg/m³ GVI (OEL TWA) [2] 200 ppm KGVI (OEL STEL) 1468 mg/m³ KGVI (OEL STEL) [ppm] 400 ppm Cyprus - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL TWA [ppm] 200 ppm OEL TWA [ppm] 200 ppm	Bulgaria - Occupational Exposure Limits			
OEL STEL OEL STEL [ppm] 400 ppm Croatia - Occupational Exposure Limits GVI (OEL TWA) [1] GVI (OEL TWA) [2] KGVI (OEL STEL) 1468 mg/m³ KGVI (OEL STEL) 1468 mg/m³ KGVI (OEL STEL) [ppm] 400 ppm Cyprus - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³	OEL TWA	734 mg/m³		
OEL STEL [ppm] 400 ppm Croatia - Occupational Exposure Limits GVI (OEL TWA) [1] 734 mg/m³ GVI (OEL TWA) [2] 200 ppm KGVI (OEL STEL) 1468 mg/m³ KGVI (OEL STEL) [ppm] 400 ppm Cyprus - Occupational Exposure Limits OEL TWA [ppm] 200 ppm OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³	OEL TWA [ppm]	200 ppm		
Croatia - Occupational Exposure Limits GVI (OEL TWA) [1] 734 mg/m³ GVI (OEL TWA) [2] 200 ppm KGVI (OEL STEL) 1468 mg/m³ KGVI (OEL STEL) [ppm] 400 ppm Cyprus - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³	OEL STEL	1468 mg/m³		
GVI (OEL TWA) [1] 734 mg/m³ GVI (OEL TWA) [2] 200 ppm KGVI (OEL STEL) 1468 mg/m³ KGVI (OEL STEL) [ppm] 400 ppm Cyprus - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³	OEL STEL [ppm]	400 ppm		
GVI (OEL TWA) [2] 200 ppm KGVI (OEL STEL) 1468 mg/m³ KGVI (OEL STEL) [ppm] 400 ppm Cyprus - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³	Croatia - Occupational Exposure Limits			
KGVI (OEL STEL) 1468 mg/m³ KGVI (OEL STEL) [ppm] 400 ppm Cyprus - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³	GVI (OEL TWA) [1]	734 mg/m³		
KGVI (OEL STEL) [ppm] 400 ppm Cyprus - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³	GVI (OEL TWA) [2]	200 ppm		
Cyprus - Occupational Exposure Limits OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³	KGVI (OEL STEL)	1468 mg/m³		
OEL TWA 734 mg/m³ OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³	KGVI (OEL STEL) [ppm]	400 ppm		
OEL TWA [ppm] 200 ppm OEL STEL 1468 mg/m³	Cyprus - Occupational Exposure Limits			
OEL STEL 1468 mg/m³	OEL TWA	734 mg/m³		
	OEL TWA [ppm]	200 ppm		
OEL STEL [ppm] 400 ppm	OEL STEL	1468 mg/m³		
	OEL STEL [ppm]	400 ppm		

EN (English) 14/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Czech Republic - Occupational Exposure Limits PEL (OEL TWA) 700 mg/m³ Denmark - Occupational Exposure Limits OEL TWA [1] 540 mg/m³ OEL TWA [2] 150 ppm OEL STEL 1468 mg/m³ OEL STEL [ppm] 400 ppm Estonia - Occupational Exposure Limits	
Denmark - Occupational Exposure Limits OEL TWA [1] 540 mg/m³ OEL TWA [2] 150 ppm OEL STEL 1468 mg/m³ OEL STEL [ppm] 400 ppm	
OEL TWA [1] 540 mg/m³ OEL TWA [2] 150 ppm OEL STEL 1468 mg/m³ OEL STEL [ppm] 400 ppm	
OEL TWA [2] 150 ppm OEL STEL 1468 mg/m³ OEL STEL [ppm] 400 ppm	
OEL STEL 1468 mg/m³ OEL STEL [ppm] 400 ppm	
OEL STEL [ppm] 400 ppm	
Estonia - Occupational Exposure Limits	
OEL TWA 500 mg/m³	
OEL TWA [ppm] 150 ppm	
OEL STEL 1100 mg/m³	
OEL STEL [ppm] 300 ppm	
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1] 730 mg/m ³	
HTP (OEL TWA) [2] 200 ppm	
HTP (OEL STEL) 1470 mg/m³	
HTP (OEL STEL) [ppm] 400 ppm	
France - Occupational Exposure Limits	
VME (OEL TWA) 734 mg/m³	
VME (OEL TWA) [ppm] 200 ppm	
VLE (OEL C/STEL) 1468 mg/m³ (restrictive limit)	
VLE (OEL C/STEL) [ppm] 400 ppm (restrictive limit)	
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1] 730 mg/m³ (the risk of damage to the embryo or fetus can be BGW values are observed)	excluded when AGW and
AGW (OEL TWA) [2] 200 ppm (the risk of damage to the embryo or fetus can be ex BGW values are observed)	cluded when AGW and
Gibraltar - Occupational Exposure Limits	
OEL TWA 200 mg/m³	
OEL TWA [ppm] 734 ppm	
OEL STEL 400 mg/m³	
OEL STEL [ppm] 1468 ppm	
Greece - Occupational Exposure Limits	
OEL TWA 734 mg/m³	
OEL TWA [ppm] 200 ppm	
OEL STEL 1468 mg/m³	
OEL STEL [ppm] 400 ppm	
Hungary - Occupational Exposure Limits	
AK (OEL TWA) 734 mg/m³	
CK (OEL STEL) 1468 mg/m³	

EN (English) 15/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Ethyl acetate (141-78-6)		
OEL chemical category	Sensitizer	
Ireland - Occupational Exposure Limits		
OEL TWA [1]	734 mg/m³	
OEL TWA [2]	200 ppm	
OEL STEL	1468 mg/m³	
OEL STEL [ppm]	400 ppm	
Italy - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
OEL TWA [ppm]	200 ppm	
OEL STEL	1468 mg/m³	
OEL STEL [ppm]	400 ppm	
Latvia - Occupational Exposure Limits		
OEL TWA	200 mg/m³	
OEL TWA [ppm]	54 ppm	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	500 mg/m³	
IPRV (OEL TWA) [ppm]	150 ppm	
NRV (OEL C)	1100 mg/m³	
NRV (OEL C) [ppm]	300 ppm	
Luxembourg - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
OEL TWA [ppm]	200 ppm	
OEL STEL	1468 mg/m³	
OEL STEL [ppm]	400 ppm	
Malta - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
OEL TWA [ppm]	200 ppm	
OEL STEL	1468 mg/m³	
OEL STEL [ppm]	400 ppm	
Netherlands - Occupational Exposure Limits		
TGG-8u (OEL TWA)	734 mg/m³	
TGG-8u (OEL TWA) [ppm]	200 ppm	
TGG-15min (OEL STEL)	1468 mg/m³	
TGG-15min (OEL STEL) [ppm]	400 ppm	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	734 mg/m³	
NDSCh (OEL STEL)	1468 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	734 mg/m³ (indicative limit value)	

EN (English) 16/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Ethyl acetate (141-78-6)		
OEL TWA [ppm]	200 ppm (indicative limit value)	
OEL STEL	1468 mg/m³ (indicative limit value)	
OEL STEL [ppm]	400 ppm (indicative limit value)	
Romania - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
OEL TWA [ppm]	200 ppm	
OEL STEL	1468 mg/m³	
OEL STEL [ppm]	400 ppm	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA) [1]	734 mg/m³	
NPHV (OEL TWA) [2]	200 ppm	
NPHV (OEL C)	1100 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
OEL TWA [ppm]	200 ppm	
OEL STEL	1468 mg/m³	
OEL STEL [ppm]	400 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	734 mg/m³	
VLA-ED (OEL TWA) [2]	200 ppm	
VLA-EC (OEL STEL)	1468 mg/m³	
VLA-EC (OEL STEL) [ppm]	400 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	550 mg/m³	
NGV (OEL TWA) [ppm]	150 ppm	
KTV (OEL STEL)	1100 mg/m³	
KTV (OEL STEL) [ppm]	300 ppm	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	734 mg/m³	
WEL TWA (OEL TWA) [2]	200 ppm	
WEL STEL (OEL STEL)	1468 mg/m³	
WEL STEL (OEL STEL) [ppm]	400 ppm	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	734 mg/m³	
Grenseverdi (OEL TWA) [2]	200 ppm	
Korttidsverdi (OEL STEL)	1468 mg/m³ (value from the regulation)	
Korttidsverdi (OEL STEL) [ppm]	400 ppm (value from the regulation)	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA) [1]	730 mg/m³	

EN (English) 17/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Ethyl acetate (141-78-6)		
MAK (OEL TWA) [2]	200 ppm	
KZGW (OEL STEL)	1460 mg/m³	
KZGW (OEL STEL) [ppm]	400 ppm	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	400 ppm	
Isovaleraldehyde (590-86-3)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	39 mg/m³	
MAK (OEL TWA) [ppm]	10 ppm	
MAK (OEL STEL)	39 mg/m³	
MAK (OEL STEL) [ppm]	10 ppm	
OEL C	39 mg/m³	
OEL C [ppm]	10 ppm	
Germany - Occupational Exposure Limits (TRGS 900)		
AGW (OEL TWA) [1]	39 mg/m³	
AGW (OEL TWA) [2]	10 ppm	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	10 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	39 mg/m³	
OEL TWA [ppm]	10 ppm	
OEL STEL	39 mg/m³	
OEL STEL [ppm]	10 ppm	
Butyric acid (107-92-6)		
Bulgaria - Occupational Exposure Limits		
OEL TWA	10 mg/m³	
Latvia - Occupational Exposure Limits		
OEL TWA	10 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	10 mg/m³	
Romania - Occupational Exposure Limits		
OEL TWA	15 mg/m³	
OEL TWA [ppm]	4 ppm	
OEL STEL	30 mg/m³	
OEL STEL [ppm]	8 ppm	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

EN (English) 18/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses

8.2.2.2. Skin protection

Hand protection:

Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Physical state

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

: Liquid

Colour : Standard. Odour characteristic. Odour threshold No data available : No data available Relative evaporation rate (butylacetate=1) : No data available Melting point : No data available : No data available Freezing point : No data available Boiling point : > 93 °C Flash point

: No data available Auto-ignition temperature : No data available Decomposition temperature Flammability (solid, gas) : Non flammable. Vapour pressure : No data available Relative vapour density at 20°C : No data available Relative density : No data available Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available

EN (English) 19/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

Benzyl benzoate (120-51-4)		
LD50 oral rat	500 mg/kg (Source: NLM_CIP)	
LD50 oral	1160 mg/kg bodyweight	
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)	
d-Limonene (5989-27-5)		
LD50 oral rat	4400 mg/kg (Source: CHEMVIEW)	
LD50 dermal rabbit	> 5 g/kg (Source: CHEMVIEW)	
Hexamethylindanopyran (1222-05-5)		
LD50 oral rat	> 3250 mg/kg (Source: CHEMVIEW)	
LD50 dermal rabbit	> 3250 mg/kg (Source: CHEMVIEW)	
Benzyl acetate (140-11-4)		
LD50 oral rat	2490 mg/kg (Source: JAPAN_GHS)	
LD50 oral	2490 mg/kg bodyweight	

EN (English) 20/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Benzyl acetate (140-11-4)	
LD50 dermal rabbit	> 5000 mg/kg (Source: JAPAN_GHS)
Isobutyl acetate (110-19-0)	
LD50 oral rat	15400 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	> 17400 mg/kg (Source: NLM_CIP)
1,2-Propanediol (57-55-6)	
LD50 oral rat	20 g/kg (Source: NLM_CIP)
LD50 dermal rabbit	20800 mg/kg (Source: NLM_CIP)
Ethyl acetate (141-78-6)	
LD50 oral rat	5620 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 18000 mg/kg (Source: JAPAN_GHS)
LC50 Inhalation - Rat [ppm]	4000 ppm/4h
Isovaleraldehyde (590-86-3)	
LD50 oral rat	5600 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	2730 mg/kg (Source: NLM_CIP)
LD50 dermal	2534 mg/kg bodyweight
LC50 Inhalation - Rat	42.7 mg/l/4h
Butyric acid (107-92-6)	
LD50 oral rat	2 g/kg (Source: NLM_CIP)
LD50 oral	1630 mg/kg bodyweight
LD50 dermal rabbit	530 mg/kg (Source: NLM_HSDB)
	Not classified
	Based on available data, the classification criteria are not met Not classified
· · ·	Based on available data, the classification criteria are not met
. ,	Not classified
	Based on available data, the classification criteria are not met
3 ,	Not classified Based on available data, the classification criteria are not met
	Not classified
	Based on available data, the classification criteria are not met
d-Limonene (5989-27-5)	
IARC group	3 - Not classifiable
Benzyl acetate (140-11-4)	
IARC group	3 - Not classifiable
	Not classified
	Based on available data, the classification criteria are not met
3 - 1 - 1 - 1 - 1	Not classified Based on available data, the classification criteria are not met
Isobutyl acetate (110-19-0)	Dasco on available data, the diassilication differed die not met
STOT-single exposure	May cause drowsiness or dizziness.
Ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.

EN (English) 21/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Isovaleraldehyde (590-86-3)		
STOT-single exposure	May cause respiratory irritation.	
STOT-repeated exposure	: Not classified	
Additional information	: Based on available data, the classification criteria are not met	
Aspiration hazard	: Not classified	
Additional information	: Based on available data, the classification criteria are not met	
Benzyl benzoate (120-51-4)		
Viscosity, kinematic	7.456 mm²/s	
Potential adverse human health effects and	: Based on available data, the classification criteria are not met	
symptoms		

SECTION 12: Ecological information

40		_			
46	1		av		T 1/
- 1 4	78 1	. То	$\mathbf{J}\mathbf{\Lambda}$	ıv	LV

Hazardous to the aquatic environment, short-term : Not classified

Hazardous to the aquatic environment, long-term : Harmful to aquatic life with long lasting effects.

(chronic)

Benzyl benzoate (120-51-4)		
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)	
NOEC (chronic)	0.168 mg/l	
d-Limonene (5989-27-5)		
LC50 - Fish [1]	0.619 – 0.796 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
LC50 - Fish [2]	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: EPA)	
Hexamethylindanopyran (1222-05-5)		
LC50 - Fish [1]	0.452 mg/l Wolf, 1996d-27682	
LC50 - Other aquatic organisms [1]	> 0.14 mg/l REACH DOSSIER Pimephales promelas	
EC50 - Crustacea [2]	260 μg/l REACH Dossier	
EC50 - Other aquatic organisms [1]	0.131 mg/l REACH Dossier	
Isobutyl acetate (110-19-0)		
LC50 - Fish [1]	17 mg/l (Exposure time: 96 h - Species: Oryzias latipes Source: ECHA)	
1,2-Propanediol (57-55-6)		
LC50 - Fish [1]	51600 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: IUCLID)	
LC50 - Fish [2]	41 – 47 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)	
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
EC50 96h - Algae [1]	19000 mg/l (Species: Pseudokirchneriella subcapitata)	
Ethyl acetate (141-78-6)		
LC50 - Fish [1]	220 – 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
LC50 - Fish [2]	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: IUCLID)	
EC50 - Crustacea [1]	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	

EN (English) 22/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Isovaleraldehyde (590-86-3)			
LC50 - Fish [1]	2.98 – 3.54 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)		
EC50 - Crustacea [1]	177 mg/l (Exposure time: 48 h - Species: Daphnia magna)		
EC50 72h - Algae [1]	80 mg/l (Species: Desmodesmus subspicatus)		
EC50 96h - Algae [1]	78 mg/l (Species: Desmodesmus subspicatus)		
Butyric acid (107-92-6)			
EC50 72h - Algae [1]	46.7 mg/l (Species: Desmodesmus subspicatus)		
12.2. Persistence and degradability			
BANANA CREME CC-16055 10%			
Persistence and degradability	Not established.		
Benzyl benzoate (120-51-4)			
Persistence and degradability	May cause long-term adverse effects in the environment.		
12.3. Bioaccumulative potential			
BANANA CREME CC-16055 10%			
Bioaccumulative potential	Not established.		
Benzyl benzoate (120-51-4)			
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)		
Bioaccumulative potential	Not established.		
Isoamyl acetate (123-92-2)			
Partition coefficient n-octanol/water (Log Pow)	2.7 (at 35 °C)		
d-Limonene (5989-27-5)			
Partition coefficient n-octanol/water (Log Pow)	4.38 (at 37 °C (at pH 7.2)		
Hexamethylindanopyran (1222-05-5)			
BCF - Fish [1]	(1618 dimensionless (whole body w.w.)		
Partition coefficient n-octanol/water (Log Pow)	5.3 (at 25 °C (at pH 7)		
Benzyl acetate (140-11-4)			
Partition coefficient n-octanol/water (Log Pow)	1.96 (at 25 °C (at pH 7)		
Isobutyl acetate (110-19-0)			
BCF - Fish [1]	(no significant bioconcentration)		
Partition coefficient n-octanol/water (Log Pow)	2.3 (at 25 °C (at pH 7)		
1,2-Propanediol (57-55-6)			
BCF - Fish [1]	(1 dimensionless)		
Partition coefficient n-octanol/water (Log Pow)	-1.07 (at 20.5 °C (at pH >=6.2-<=6.4)		
Ethyl acetate (141-78-6)			
BCF - Fish [1]	(30 dimensionless)		
Partition coefficient n-octanol/water (Log Pow)	0.73 (at 20 °C (at pH 7)		

EN (English) 23/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Isovaleraldehyde (590-86-3)	
Partition coefficient n-octanol/water (Log Pow) 1.5 (at 25 °C (at pH 7)	
Butyric acid (107-92-6)	
Partition coefficient n-octanol/water (Log Pow)	1.1 (at 25 °C (at pH 3)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations Ecology - waste materials HP Code

- : Dispose in a safe manner in accordance with local/national regulations.
- : Avoid release to the environment.
- : HP3 "Flammable:"
 - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
 - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
 - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
 - flammable gaseous waste: gaseous waste which is flammable in air at 20 $^{\circ}\text{C}$ and a standard pressure of 101.3 kPa;
 - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
 - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number	14.1. UN number			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shippin	g name			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

EN (English) 24/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REA	EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description	
3(a)	Isoamyl acetate ; d- Limonene ; Isobutyl acetate ; Ethyl acetate ; Isovaleraldehyde	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	
3(b)	Benzyl benzoate ; d- Limonene ; Isobutyl acetate ; Ethyl acetate ; Isovaleraldehyde ; Butyric acid	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	
3(c)	BANANA CREME CC- 16055 10%; Benzyl benzoate; d-Limonene; Hexamethylindanopyran; Benzyl acetate; Isovaleraldehyde	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	
40.	Isoamyl acetate ; d- Limonene ; Isobutyl acetate ; Ethyl acetate ; Isovaleraldehyde	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

EN (English) 25/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases		
Code	Description	
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide	

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Storage class (LGK, TRGS 510) : LGK 12 - Non-combustible liquids.

Joint storage table : LGK 12 - Non-combustible liquids.

	LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
	LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
ı	LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
	LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
	LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for : LGK 1, LGK 6.2, LGK 7.

Joint storage with restrictions permitted for : LGK 4.1A, LGK 4.3, LGK 5.1C.

Joint storage permitted for : LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK

10-13.

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic

environn

SZW-lijst van kankerverwekkende stoffen : None of the components are listed SZW-lijst van mutagene stoffen : None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed SZW-lijst van reprotoxische stoffen – : None of the components are listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

EN (English) 26/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Switzerland

Storage class (LK) : LK 10/12 - Liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and

amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUF	Full text of H- and EUH-statements:		
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4		
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1		
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1		
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2		
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3		
Asp. Tox. 1	Aspiration hazard, Category 1		
EUH208	Contains d-Limonene. May produce an allergic reaction.		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Liq. 1	Flammable liquids, Category 1		
Flam. Liq. 2	Flammable liquids, Category 2		
Flam. Liq. 3	Flammable liquids, Category 3		
H224	Extremely flammable liquid and vapour.		
H225	Highly flammable liquid and vapour.		
H226	Flammable liquid and vapour.		
H302	Harmful if swallowed.		
H304	May be fatal if swallowed and enters airways.		
H314	Causes severe skin burns and eye damage.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H319	Causes serious eye irritation.		
H335	May cause respiratory irritation.		
H336	May cause drowsiness or dizziness.		
H400	Very toxic to aquatic life.		
H410	Very toxic to aquatic life with long lasting effects.		
H411	Toxic to aquatic life with long lasting effects.		
H412	Harmful to aquatic life with long lasting effects.		
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B		
Skin Irrit. 2	Skin corrosion/irritation, Category 2		
Skin Sens. 1B	Skin sensitisation, category 1B		

EN (English) 27/28

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

EN (English) 28/28