

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form	: Mixture
Product name	: Bourbon
UFI	: A5TC-W3C0-300C-UFCH
Product code	: CC-16088
Type of product	: Perfumes, fragrances
Product group	: Trade product

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Main use category	: Industrial use, Professional use
Industrial/Professional use spec	: For professional use only Industrial
Use of the substance/mixture	: Perfumes, fragrances
Function or use category	: Odour agents

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet**

Candle Craft  
Weiherwiese 10  
65510 Idstein - Germany  
T 49-6126-9363 -0  
info@candlecraft.de - www.candlecraft.de

**1.4. Emergency telephone number**

Emergency number	: 1-800-255-3924; +01-813-248-0585; China: +400-120-0751; Mexico: +01-800-099-0731; Brazil: +0-800-591-6042; India: +000-800-100-4086
------------------	--

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Acute toxicity (oral), Category 4	H302
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411
Full text of H-statements: see section 16	

**Adverse physicochemical, human health and environmental effects**

Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Toxic to aquatic life with long lasting effects.

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP)



# Bourbon CC-16088

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Signal word (CLP)	: Danger
Contains	: Eugenol; Balsam oil, Peru; Coumarin crystals; Benzyl benzoate; Geraniol
Hazard statements (CLP)	: H302 - Harmful if swallowed. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P301+P312 - IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371-33	56.75 – 76.75	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Geraniol	CAS-No.: 106-24-1 EC-No.: 203-377-1 EC Index-No.: 603-241-00-5 REACH-no: 01-2119552430-49	5.5 – 11	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317
Oenanthic ether (Ethyl heptanoate)	CAS-No.: 106-30-9 EC-No.: 203-382-9	1.8 – 3.6	Flam. Liq. 3, H226 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Hexamethylindanopyran	CAS-No.: 1222-05-5 EC-No.: 214-946-9 EC Index-No.: 603-212-00-7 REACH-no: 01-2119488227-29	0.9 – 1.8	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Ethyl acetate substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-46	0.5 – 1	Flam. Liq. 1, H224 Eye Irrit. 2, H319 STOT SE 3, H336
Eugenol	CAS-No.: 97-53-0 EC-No.: 202-589-1 REACH-no: 01-2119971802-33	0.375 – 0.75	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317

# Bourbon CC-16088

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Cedarwood oil, Texas	CAS-No.: 68990-83-0 EC-No.: 294-461-7;614-888-8	0.35 – 0.7	Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Coumarin crystals	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756-26	0.25 – 0.5	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Balsam oil, Peru	CAS-No.: 8007-00-9 EC-No.: 232-352-8	0.15 – 0.3	Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Rose oxide	CAS-No.: 16409-43-1 EC-No.: 240-457-5	0.05 – 0.1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

# Bourbon CC-16088

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.  
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1. National occupational exposure and biological limit values

Ethyl acetate (141-78-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	734 mg/m <sup>3</sup>
IOEL TWA [ppm]	200 ppm
IOEL STEL	1468 mg/m <sup>3</sup>
IOEL STEL [ppm]	400 ppm
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	734 mg/m <sup>3</sup>
MAK (OEL TWA) [ppm]	200 ppm

# Bourbon CC-16088

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethyl acetate (141-78-6)	
MAK (OEL STEL)	1468 mg/m <sup>3</sup>
MAK (OEL STEL) [ppm]	400 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	734 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL [ppm]	400 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	734 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL [ppm]	400 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	734 mg/m <sup>3</sup>
GVI (OEL TWA) [2]	200 ppm
KGVI (OEL STEL)	1468 mg/m <sup>3</sup>
KGVI (OEL STEL) [ppm]	400 ppm
Cyprus - Occupational Exposure Limits	
OEL TWA	734 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL [ppm]	400 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	700 mg/m <sup>3</sup>
Denmark - Occupational Exposure Limits	
OEL TWA [1]	540 mg/m <sup>3</sup>
OEL TWA [2]	150 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	500 mg/m <sup>3</sup>
OEL TWA [ppm]	150 ppm
OEL STEL	1100 mg/m <sup>3</sup>
OEL STEL [ppm]	300 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	730 mg/m <sup>3</sup>
HTP (OEL TWA) [2]	200 ppm
HTP (OEL STEL)	1470 mg/m <sup>3</sup>
HTP (OEL STEL) [ppm]	400 ppm
France - Occupational Exposure Limits	
VME (OEL TWA)	1400 mg/m <sup>3</sup>

# Bourbon CC-16088

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethyl acetate (141-78-6)	
VME (OEL TWA) [ppm]	400 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	730 mg/m <sup>3</sup> (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
AGW (OEL TWA) [2]	200 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Gibraltar - Occupational Exposure Limits	
OEL TWA	200 mg/m <sup>3</sup>
OEL TWA [ppm]	734 ppm
OEL STEL	400 mg/m <sup>3</sup>
OEL STEL [ppm]	1468 ppm
Greece - Occupational Exposure Limits	
OEL TWA	734 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL [ppm]	400 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	734 mg/m <sup>3</sup>
CK (OEL STEL)	1468 mg/m <sup>3</sup>
Chemical category	Sensitizer
Ireland - Occupational Exposure Limits	
OEL TWA [1]	734 mg/m <sup>3</sup>
OEL TWA [2]	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL [ppm]	400 ppm
Italy - Occupational Exposure Limits	
OEL TWA	734 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL [ppm]	400 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	200 mg/m <sup>3</sup>
OEL TWA [ppm]	54 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	500 mg/m <sup>3</sup>
IPRV (OEL TWA) [ppm]	150 ppm
NRV (OEL C)	1100 mg/m <sup>3</sup>
NRV (OEL C) [ppm]	300 ppm
Luxembourg - Occupational Exposure Limits	
OEL STEL	1468 mg/m <sup>3</sup>

# Bourbon CC-16088

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethyl acetate (141-78-6)	
OEL STEL [ppm]	400 ppm
Malta - Occupational Exposure Limits	
OEL TWA	734 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL [ppm]	400 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	734 mg/m <sup>3</sup>
TGG-15min (OEL STEL)	1468 mg/m <sup>3</sup>
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	734 mg/m <sup>3</sup>
NDSch (OEL STEL)	1468 mg/m <sup>3</sup>
Portugal - Occupational Exposure Limits	
OEL TWA	734 mg/m <sup>3</sup> (indicative limit value)
OEL TWA [ppm]	200 ppm (indicative limit value)
OEL STEL	1468 mg/m <sup>3</sup> (indicative limit value)
OEL STEL [ppm]	400 ppm (indicative limit value)
Romania - Occupational Exposure Limits	
OEL TWA	400 mg/m <sup>3</sup>
OEL TWA [ppm]	111 ppm
OEL STEL	500 mg/m <sup>3</sup>
OEL STEL [ppm]	139 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	734 mg/m <sup>3</sup>
NPHV (OEL TWA) [2]	200 ppm
NPHV (OEL C)	1100 mg/m <sup>3</sup>
Slovenia - Occupational Exposure Limits	
OEL TWA	734 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL [ppm]	400 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	734 mg/m <sup>3</sup>
VLA-ED (OEL TWA) [2]	200 ppm
VLA-EC (OEL STEL)	1468 mg/m <sup>3</sup>
VLA-EC (OEL STEL) [ppm]	400 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	550 mg/m <sup>3</sup>
NGV (OEL TWA) [ppm]	150 ppm

# Bourbon CC-16088

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethyl acetate (141-78-6)	
KTV (OEL STEL)	1100 mg/m <sup>3</sup>
KTV (OEL STEL) [ppm]	300 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	734 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	1468 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	400 ppm
Norway - Occupational Exposure Limits	
Grønseverdi (OEL TWA) [1]	734 mg/m <sup>3</sup>
Grønseverdi (OEL TWA) [2]	200 ppm
Korttidsverdi (OEL STEL)	1468 mg/m <sup>3</sup> (value from the regulation)
Korttidsverdi (OEL STEL) [ppm]	400 ppm (value from the regulation)
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	730 mg/m <sup>3</sup>
MAK (OEL TWA) [2]	200 ppm
KZGW (OEL STEL)	1460 mg/m <sup>3</sup>
KZGW (OEL STEL) [ppm]	400 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	400 ppm

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses



# Bourbon CC-16088

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 8.2.2.2. Skin protection

#### Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Protective gloves

### 8.2.2.3. Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light yellow. amber.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 77.2 °C (closed cup) ASTM D7094
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: $\approx 1.07$
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

# Bourbon CC-16088

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### Bourbon CC-16088

ATE CLP (oral)	630.915 mg/kg bodyweight
----------------	--------------------------

#### Ethyl acetate (141-78-6)

LD50 oral rat	5620 mg/kg
---------------	------------

LD50 dermal rabbit	> 18000 mg/kg
--------------------	---------------

LC50 Inhalation - Rat [ppm]	4000 ppm/4h
-----------------------------	-------------

#### Oenanthic ether (Ethyl heptanoate) (106-30-9)

LD50 oral rat	> 34640 mg/kg
---------------	---------------

#### Eugenol (97-53-0)

LD50 oral rat	1930 mg/kg
---------------	------------

LD50 oral	2500 mg/kg bodyweight
-----------	-----------------------

#### Hexamethylindanopyran (1222-05-5)

LD50 oral rat	> 3250 mg/kg
---------------	--------------

LD50 dermal rabbit	> 3250 mg/kg
--------------------	--------------

#### Coumarin crystals (91-64-5)

LD50 oral rat	> 5000 mg/kg
---------------	--------------

LD50 oral	500 mg/kg bodyweight
-----------	----------------------

LD50 dermal rat	293 mg/kg
-----------------	-----------

#### Benzyl benzoate (120-51-4)

LD50 oral rat	500 mg/kg
---------------	-----------

LD50 oral	1500 mg/kg bodyweight
-----------	-----------------------

LD50 dermal rabbit	4000 mg/kg
--------------------	------------

LD50 dermal	4000 mg/kg bodyweight
-------------	-----------------------

#### Geraniol (106-24-1)

LD50 oral rat	3600 mg/kg
---------------	------------

LD50 oral	3600 mg/kg bodyweight
-----------	-----------------------

LD50 dermal rabbit	> 5 g/kg
--------------------	----------

# Bourbon CC-16088

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Rose oxide (16409-43-1)	
LD50 oral rat	4300 mg/kg
LD50 oral	4300 mg/kg bodyweight
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Eugenol (97-53-0)	
IARC group	3 - Not classifiable
Coumarin crystals (91-64-5)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
Ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Balsam oil, Peru (8007-00-9)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

Ethyl acetate (141-78-6)	
LC50 - Fish [1]	220 – 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 - Crustacea [1]	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
Eugenol (97-53-0)	
LC50 - Fish [1]	13 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])
Hexamethylindanopyran (1222-05-5)	
LC50 - Fish [1]	0.452 mg/l Wolf, 1996d-27682
LC50 - Other aquatic organisms [1]	> 0.14 mg/l REACH DOSSIER Pimephales promelas
EC50 - Crustacea [2]	260 µg/l REACH Dossier
EC50 - Other aquatic organisms [1]	0.131 mg/l REACH Dossier
Benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])
NOEC (chronic)	0.168 mg/l

# Bourbon CC-16088

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Geraniol (106-24-1)

LC50 - Fish [1]	22 mg/l (Exposure time: 96 h - Species: Danio rerio [static])
-----------------	---

### 12.2. Persistence and degradability

#### Cedarwood oil, Texas (68990-83-0)

Persistence and degradability	Not established.
-------------------------------	------------------

#### Benzyl benzoate (120-51-4)

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

### 12.3. Bioaccumulative potential

#### Ethyl acetate (141-78-6)

BCF - Fish [1]	30
----------------	----

Partition coefficient n-octanol/water (Log Pow)	0.6
---	-----

#### Cedarwood oil, Texas (68990-83-0)

Bioaccumulative potential	Not established.
---------------------------	------------------

#### Benzyl benzoate (120-51-4)

Partition coefficient n-octanol/water (Log Pow)	4
---	---

Bioaccumulative potential	Not established.
---------------------------	------------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

### 14.1. UN number

UN-No. (ADR)	: UN 3082
UN-No. (IMDG)	: UN 3082
UN-No. (IATA)	: UN 3082
UN-No. (ADN)	: Not regulated
UN-No. (RID)	: Not regulated

### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Proper Shipping Name (IMDG)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Proper Shipping Name (IATA)	: Environmentally hazardous substance, liquid, n.o.s.

# Bourbon CC-16088

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Proper Shipping Name (ADN)	: Not regulated
Proper Shipping Name (RID)	: Not regulated
Transport document description (ADR)	: UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III, (-)
Transport document description (IMDG)	: UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III, MARINE POLLUTANT
Transport document description (IATA)	: UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Benzyl Benzoate), 9, III

### 14.3. Transport hazard class(es)


#### ADR

Transport hazard class(es) (ADR)	: 9
Danger labels (ADR)	: 9



#### IMDG

Transport hazard class(es) (IMDG)	: 9
Danger labels (IMDG)	: 9



#### IATA

Transport hazard class(es) (IATA)	: 9
Danger labels (IATA)	: 9



#### ADN

Transport hazard class(es) (ADN)	: Not regulated
----------------------------------	-----------------

#### RID

Transport hazard class(es) (RID)	: Not regulated
----------------------------------	-----------------

### 14.4. Packing group

Packing group (ADR)	: III
Packing group (IMDG)	: III
Packing group (IATA)	: III
Packing group (ADN)	: Not regulated
Packing group (RID)	: Not regulated

### 14.5. Environmental hazards

Dangerous for the environment	: Yes
Marine pollutant	: Yes
Other information	: No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601

# Bourbon CC-16088

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90
Orange plates	:



Tunnel restriction code (ADR)	: -
EAC code	: •3Z

### Transport by sea

Special provisions (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-F
Stowage category (IMDG)	: A

### Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provisions (IATA)	: A97, A158, A197, A215
ERG code (IATA)	: 9L

### Inland waterway transport

Not regulated

### Rail transport

Not regulated

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

# Bourbon CC-16088

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3(a)	Ethyl acetate ; Oenanthic ether (Ethyl heptanoate)
3(b)	Bourbon CC-16088 ; Ethyl acetate ; Eugenol ; Balsam oil, Peru ; Cedarwood oil, Texas ; Benzyl benzoate ; Geraniol ; Rose oxide
3(c)	Bourbon CC-16088 ; Oenanthic ether (Ethyl heptanoate) ; Balsam oil, Peru ; Hexamethylindanopyran ; Cedarwood oil, Texas ; Benzyl benzoate
40.	Ethyl acetate ; Oenanthic ether (Ethyl heptanoate)

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

##### 15.1.2. National regulations

France	
Occupational diseases	
Code	Description
RG 65	Eczematiform lesions of allergic mechanism
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamide; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

##### Germany

- Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)  
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)
- Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)
- Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

##### Netherlands

- SZW-lijst van kankerverwekkende stoffen : Balsam oil, Peru, Cedarwood oil, Texas are listed
- SZW-lijst van mutagene stoffen : Balsam oil, Peru is listed
- SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

##### Denmark

- Class for fire hazard : Class III-1
- Store unit : 50 liter
- Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed
- Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

##### Switzerland

- Storage class (LK) : LK 8 - Corrosive materials

# Bourbon CC-16088

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

#### Abbreviations and acronyms

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties



# Bourbon CC-16088

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H224	Extremely flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet (SDS), EU

# Bourbon CC-16088

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

---

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.