Pina Colada CC-16090

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 5/20/2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Mixture
Product name	:	Pina Colada CC-16090
UFI	:	PPTF-3309-N009-76XS
Product code	:	CC-16090
Type of product	:	Perfumes, Fragrances
Product group	:	Finished Good

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec	:	For professional use only Industrial
Use of the substance/mixture	:	Perfumes, Fragrances
Function or use category	:	Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Candle Craft
Weiherwiese 10
65510 Idstein - Germany
T 49-6126-9363 -0
info@candlecraft.de - www.candlecraft.de

Emergency number	:	06126-9363-0

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral) Category 4	H302
Skin sensitization, Category 1	H317
Hazardous to the aquatic environment - Chronic Hazard Category 2	H411

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Harmful if swallowed. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07 GHS09

Signal word (CLP)	:	Warning
Contains	:	Benzyl benzoate; 2-Hydroxybenzoic acid, benzyl ester; Coumarin crystals; Hexyl cinnamic aldehyde; Heliotropine crystals; Linalool; Vertenex

Hazard statements (CLP) : H302 - Harmful if swallowed.
H317 - May cause an allergic skin reaction.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371-33	35.87 – 71.74	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Coumarin crystals	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756-26	2.2 – 4.4	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Sens. 1, H317 Aquatic Chronic 2, H411
2-Hydroxybenzoic acid, benzyl ester	CAS-No.: 118-58-1 EC-No.: 204-262-9 REACH-no: 01-2119969442-31	1.5 – 3	Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Allyl caproate	CAS-No.: 123-68-2 EC-No.: 204-642-4 REACH-no: 01-2119983573-26	0.35 – 0.7	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Heliotropine crystals	CAS-No.: 120-57-0 EC-No.: 204-409-7 REACH-no: 01-2119983608-21	0.15 – 0.3	Skin Sens. 1B, H317
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016-42	0.1 – 0.2	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Isoamyl acetate substance with a Community workplace exposure limit	CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2 REACH-no: 01-2119548408-32	0.075 – 0.15	Flam. Liq. 3, H226

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Allyl heptanoate	CAS-No.: 142-19-8 EC-No.: 205-527-1 REACH-no: 01-2119488961-23	0.075 – 0.15	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Hexyl cinnamic aldehyde	CAS-No.: 101-86-0 EC-No.: 202-983-3 REACH-no: 01-2119533092-50	0.05 – 0.1	Skin Sens. 1, H317 Aquatic Chronic 2, H411
ACETYL HEXAMETHYL TETRALIN	CAS-No.: 21145-77-7 EC-No.: 244-240-6	0.05 – 0.1	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Vertenex	CAS-No.: 32210-23-4 EC-No.: 250-954-9 REACH-no: 01-2119976286-24	0.05 – 0.1	Skin Sens. 1B, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center/doctor/physician if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Rinse mouth. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.
Storage temperature : 25 °C
Storage area : Store in a well-ventilated place. Store away from heat.
Special rules on packaging : Store in a closed container.
Packaging materials : Do not store in corrodable metal.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

Isoamyl acetate (123-92-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	270 mg/m³
IOEL TWA [ppm]	50 ppm
IOEL STEL	540 mg/m³
IOEL STEL [ppm]	100 ppm

Isoamyl acetate (123-92-2)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	270 mg/m³ (Pentyl acetate (all isomers))
MAK (OEL TWA) [ppm]	50 ppm (Pentyl acetate (all isomers))
MAK (OEL STEL)	540 mg/m³ (Pentylacetate)
MAK (OEL STEL) [ppm]	100 ppm (Pentylacetate)
Belgium - Occupational Exposure Limits	
OEL TWA	270 mg/m³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m³
OEL STEL [ppm]	100 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	270 mg/m³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m³
OEL STEL [ppm]	100 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	270 mg/m³
GVI (OEL TWA) [2]	50 ppm
KGVI (OEL STEL)	540 mg/m³
KGVI (OEL STEL) [ppm]	100 ppm
Cyprus - Occupational Exposure Limits	
OEL TWA	270 mg/m³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m³
OEL STEL [ppm]	100 ppm
Denmark - Occupational Exposure Limits	
OEL TWA [1]	271 mg/m³ (Amyl acetate, all isomers)
OEL TWA [2]	50 ppm (Amyl acetate, all isomers)
Estonia - Occupational Exposure Limits	
OEL TWA	270 mg/m³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m³
OEL STEL [ppm]	100 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	270 mg/m³ (Pentyl acetate)
HTP (OEL TWA) [2]	50 ppm (Pentyl acetate)
HTP (OEL STEL)	540 mg/m³
HTP (OEL STEL) [ppm]	100 ppm

Isoamyl acetate (123-92-2)	
France - Occupational Exposure Limits	
VME (OEL TWA)	270 mg/m³ (restrictive limit)
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)
VLE (OEL C/STEL)	540 mg/m³ (restrictive limit)
VLE (OEL C/STEL) [ppm]	100 ppm (restrictive limit)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	270 mg/m³
AGW (OEL TWA) [2]	50 ppm
Gibraltar - Occupational Exposure Limits	
OEL TWA	270 mg/m³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m³
OEL STEL [ppm]	100 ppm
Greece - Occupational Exposure Limits	
OEL TWA	530 mg/m³
OEL TWA [ppm]	100 ppm
OEL STEL	800 mg/m³
OEL STEL [ppm]	150 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	270 mg/m³
CK (OEL STEL)	540 mg/m³
Ireland - Occupational Exposure Limits	
OEL TWA [1]	260 mg/m³
OEL TWA [2]	50 ppm
OEL STEL	520 mg/m³
OEL STEL [ppm]	100 ppm
Italy - Occupational Exposure Limits	
OEL TWA	270 mg/m³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m³
OEL STEL [ppm]	100 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	270 mg/m³
OEL TWA [ppm]	50 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	270 mg/m³
IPRV (OEL TWA) [ppm]	50 ppm
TPRV (OEL STEL)	540 mg/m³
TPRV (OEL STEL) [ppm]	100 ppm

Isoamyl acetate (123-92-2)	
Luxembourg - Occupational Exposure Limits	
OEL TWA	270 mg/m³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m³
OEL STEL [ppm]	100 ppm
Malta - Occupational Exposure Limits	
OEL TWA	270 mg/m³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m³
OEL STEL [ppm]	100 ppm
Netherlands - Occupational Exposure Limits	
MAC-15 (OEL STEL)	530 mg/m³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	250 mg/m³
NDSCh (OEL STEL)	500 mg/m³
Portugal - Occupational Exposure Limits	
OEL TWA	270 mg/m³ (indicative limit value)
OEL TWA [ppm]	50 ppm (indicative limit value)
OEL STEL	540 mg/m³ (indicative limit value)
OEL STEL [ppm]	100 ppm (indicative limit value, regulated under Pentyl acetate, all isomers)
Romania - Occupational Exposure Limits	
OEL TWA	270 mg/m³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m³
OEL STEL [ppm]	100 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	270 mg/m³
NPHV (OEL TWA) [2]	50 ppm
NPHV (OEL C)	540 mg/m³
Slovenia - Occupational Exposure Limits	
OEL TWA	270 mg/m³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m³
OEL STEL [ppm]	100 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	270 mg/m³ (indicative limit value)
VLA-ED (OEL TWA) [2]	50 ppm (indicative limit value)
VLA-EC (OEL STEL)	540 mg/m³
VLA-EC (OEL STEL) [ppm]	100 ppm

Isoamyl acetate (123-92-2)	
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	270 mg/m³ (Pentyl acetates)
NGV (OEL TWA) [ppm]	50 ppm (Pentyl acetates)
KTV (OEL STEL)	540 mg/m³ (Pentyl acetates)
KTV (OEL STEL) [ppm]	100 ppm (Pentyl acetates)
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	260 mg/m³
Grenseverdi (OEL TWA) [2]	50 ppm
Korttidsverdi (OEL STEL)	325 mg/m³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	75 ppm (value calculated)
Turkey - Occupational Exposure Limits	
OEL TWA	270 mg/m³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m³
OEL STEL [ppm]	100 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	50 ppm (Pentyl acetate, all isomers)
ACGIH OEL STEL [ppm]	100 ppm (Pentyl acetate, all isomers)

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:
Safety glasses

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Color	:	light yellow. amber.
Odor	:	characteristic.
Odor threshold	:	No data available
pH	:	No data available
Relative evaporation rate (butyl acetate=1)	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	> 93 °C (closed cup) ASTM D7094
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Flammability (solid, gas)	:	Not applicable
Vapor pressure	:	No data available
Relative vapor density at 20 °C	:	No data available
Relative density	:	≈ 1.13
Solubility	:	No data available
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Explosion limits	:	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Pina Colada CC-16090	
ATE CLP (oral)	510.256 mg/kg body weight

Allyl caproate (123-68-2)	
LD50 oral	300 mg/kg body weight
LD50 dermal rabbit	820 mg/kg
LD50 dermal	300 mg/kg body weight
LC50 Inhalation - Rat (Vapours)	3 mg/l/4h

Allyl heptanoate (142-19-8)	
LD50 oral rat	500 mg/kg
LD50 oral	218 mg/kg body weight
LD50 dermal rabbit	810 mg/kg
LD50 dermal	810 mg/kg body weight

Benzyl benzoate (120-51-4)	
LD50 oral rat	500 mg/kg
LD50 oral	1500 mg/kg body weight
LD50 dermal rabbit	4000 mg/kg
LD50 dermal	4000 mg/kg body weight

2-Hydroxybenzoic acid, benzyl ester (118-58-1)	
LD50 oral rat	2227 mg/kg
LD50 oral	2200 mg/kg body weight
LD50 dermal rabbit	> 5000 mg/kg

Coumarin crystals (91-64-5)	
LD50 oral rat	> 5000 mg/kg
LD50 oral	500 mg/kg body weight
LD50 dermal rat	293 mg/kg

Hexyl cinnamic aldehyde (101-86-0)	
LD50 oral rat	3100 mg/kg
LD50 oral	3100 mg/kg body weight
LD50 dermal rabbit	> 3000 mg/kg

Hexyl cinnamic aldehyde (101-86-0)	
LC50 Inhalation - Rat	> 5 mg/l/4h

Heliotropine crystals (120-57-0)	
LD50 oral rat	2700 mg/kg
LD50 oral	2700 mg/kg body weight
LD50 dermal rat	> 5000 mg/kg

Linalool (78-70-6)	
LD50 oral	2790 mg/kg body weight

ACETYL HEXAMETHYL TETRALIN (21145-77-7)	
LD50 oral rat	570 mg/kg
LD50 oral	1000 mg/kg body weight
LD50 dermal rabbit	> 5 g/kg

Vertenex (32210-23-4)	
LD50 oral rat	5 g/kg
LD50 oral	3370 mg/kg body weight
LD50 dermal rabbit	> 5000 mg/kg

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Coumarin crystals (91-64-5)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

Allyl caproate (123-68-2)	
LC50 - Fish [1]	0.117 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])

Benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])
NOEC (chronic)	0.168 mg/l

2-Hydroxybenzoic acid, benzyl ester (118-58-1)	
LC50 - Fish [1]	1.03 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])

Heliotropine crystals (120-57-0)	
LC50 - Fish [1]	2.5 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static])

Linalool (78-70-6)	
EC50 96h - Algae [1]	88.3 mg/l (Species: Desmodesmus subspicatus)

Vertenex (32210-23-4)	
LC50 - Fish [1]	8.6 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])

12.2. Persistence and degradability

Benzyl benzoate (120-51-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

Benzyl benzoate (120-51-4)	
Partition coefficient n-octanol/water (Log Pow)	4
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number

UN-No. (ADR) : UN 3082
UN-No. (IMDG) : UN 3082
UN-No. (IATA) : UN 3082
UN-No. (ADN) : UN 3082
UN-No. (RID) : Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s.
Proper Shipping Name (ADN) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Proper Shipping Name (RID) : Not applicable
Transport document description (ADR) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III, (-)

Transport document description (IMDG)	:	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III, MARINE POLLUTANT
Transport document description (IATA)	:	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Benzyl Benzoate), 9, III
Transport document description (ADN)	:	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 9
Hazard labels (ADR) : 9

:



IMDG

Transport hazard class(es) (IMDG) : 9
Hazard labels (IMDG) : 9

:



IATA

Transport hazard class(es) (IATA) : 9
Hazard labels (IATA) : 9

:



ADN

Transport hazard class(es) (ADN) : 9
Hazard labels (ADN) : 9

:



RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR)	:	III
Packing group (IMDG)	:	III
Packing group (IATA)	:	III
Packing group (ADN)	:	III
Packing group (RID)	:	Not applicable

14.5. Environmental hazards

Dangerous for the environment	:	Yes
Marine pollutant	:	Yes
Other information	:	No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR)	:	M6
Special provision (ADR)	:	274, 335, 375, 601
Limited quantities (ADR)	:	5l
Excepted quantities (ADR)	:	E1
Packing instructions (ADR)	:	P001, IBC03, LP01, R001
Special packing provisions (ADR)	:	PP1
Mixed packing provisions (ADR)	:	MP19
Portable tank and bulk container instructions (ADR)	:	T4
Portable tank and bulk container special provisions (ADR)	:	TP1, TP29
Tank code (ADR)	:	LGBV
Vehicle for tank carriage	:	AT
Transport category (ADR)	:	3
Special provisions for carriage - Packages (ADR)	:	V12
Special provisions for carriage - Loading, unloading and handling (ADR)	:	CV13
Hazard identification number (Kemler No.)	:	90
Orange plates	:	
Tunnel restriction code (ADR)	:	-
EAC	:	•3Z

Transport by sea

Special provision (IMDG)	:	274, 335, 969
Limited quantities (IMDG)	:	5 L
Excepted quantities (IMDG)	:	E1
Packing instructions (IMDG)	:	LP01, P001
Packing provisions (IMDG)	:	PP1
IBC packing instructions (IMDG)	:	IBC03
Tank instructions (IMDG)	:	T4
Tank special provisions (IMDG)	:	TP2, TP29
EmS-No. (Fire)	:	F-A
EmS-No. (Spillage)	:	S-F
Stowage category (IMDG)	:	A

Air transport

PCA Excepted quantities (IATA)	:	E1
PCA Limited quantities (IATA)	:	Y964
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	964
PCA max net quantity (IATA)	:	450L
CAO packing instructions (IATA)	:	964
CAO max net quantity (IATA)	:	450L
Special provision (IATA)	:	A97, A158, A197
ERG code (IATA)	:	9L

Inland waterway transport

Classification code (ADN)	:	M6
Special provision (ADN)	:	274, 335, 375, 601
Limited quantities (ADN)	:	5 L
Excepted quantities (ADN)	:	E1
Carriage permitted (ADN)	:	T
Equipment required (ADN)	:	PP
Number of blue cones/lights (ADN)	:	0

Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)	
Reference code	**Applicable on**
3(a)	Isoamyl acetate
3(b)	Pina Colada CC-16090 ; Allyl caproate ; Allyl heptanoate ; Benzyl benzoate ; 2-Hydroxybenzoic acid, benzyl ester ; Hexyl cinnamic aldehyde ; Linalool ; Vertenex
3(c)	Pina Colada CC-16090 ; Allyl caproate ; Allyl heptanoate ; Benzyl benzoate ; 2-Hydroxybenzoic acid, benzyl ester ; Hexyl cinnamic aldehyde
40.	Isoamyl acetate

Contains no REACH candidate substance
Contains no REACH Annex XIV substances.
Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.
Contains no substance(s) subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

Germany

Water hazard class (WGK) : WGK 2, significant hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

Storage class (LK) : LK 10/12 - Liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate

Abbreviations and acronyms	
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-phrases	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1

Full text of H- and EUH-phrases	
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids Category 3
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1B	Skin sensitization, Category 1B
H226	Flammable liquid and vapor.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.