

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 9/19/2023



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : ACAI BERRY BOOST CC-16315
UFI : GEQT-A9UY-S00H-259G
Product code : CC-16315
Type of product : Perfumes, fragrances
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use
Industrial/Professional use spec : Industrial
For professional use only
Use of the substance/mixture : Perfumes, fragrances
Function or use category : Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Candle Craft
Weiherwiese 10
65510 Idstein - Germany
T 49-6126-9363 -0
info@candlecraft.de - www.candlecraft.de

1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China: +400-120-0751; Mexico: +01-800-099-0731;
Brazil: +0-800-591-6042; India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 1 H318
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Causes skin irritation. Causes serious eye damage. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS05

GHS07

GHS09

Signal word (CLP) :

Danger

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Contains	: Hexyl salicylate; Iso E Super; Hexyl cinnamic aldehyde; Linalool; CUPRESSUS FUNEBRIS WOOD OIL; Linalyl acetate; d-Limonene; Citral; Orange oil ; Helional; Geraniol; Nerol; Aldehyde C-16; Triplal (Vertocitral); Patchouli oil; Geranyl acetate; delta-Damascone
Hazard statements (CLP)	: H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P302+P352 - IF ON SKIN: Wash with plenty of water.
Extra phrases	: For professional users only.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-Isobutyl-4-methyltetrahydro-2H-pyran-4-ol	CAS-No.: 63500-71-0 EC-No.: 405-040-6 EC Index-No.: 603-101-00-3 REACH-no: 01-000015458-64	2 – 7.612	Eye Irrit. 2, H319
Benzyl acetate substance with national workplace exposure limit(s) (BE, DK, ES, IE, LT, LV, PT, RO)	CAS-No.: 140-11-4 EC-No.: 205-399-7 REACH-no: 01-2119638272-42	3.8 – 7.5	Aquatic Chronic 3, H412
Iso E Super	CAS-No.: 54464-57-2 EC-No.: 259-174-3 REACH-no: 01-2119489989-04	3.3 – 6.5	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 1, H410
Hexyl cinnamic aldehyde	CAS-No.: 101-86-0 EC-No.: 202-983-3 REACH-no: 01-2119533092-50	2.5 – 5	Skin Sens. 1, H317 Aquatic Chronic 2, H411
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016-42	2 – 3.9	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
CUPRESSUS FUNEBRIS WOOD OIL	CAS-No.: 85085-29-6 EC-No.: 285-360-9	1.8 – 3.6	Skin Corr. 1, H314 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Verdorex	CAS-No.: 88-41-5 EC-No.: 201-828-7 REACH-no: 01-2119970713-33	1.5 – 3	Aquatic Chronic 2, H411
Dihydromyrcenol	CAS-No.: 18479-58-8 EC-No.: 242-362-4 REACH-no: 01-2119457274-37	1.3 – 2.6	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Hexamethylindanopyran	CAS-No.: 1222-05-5 EC-No.: 214-946-9 EC Index-No.: 603-212-00-7 REACH-no: 01-2119488227-29	1.3 – 2.5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Linalyl acetate	CAS-No.: 115-95-7 EC-No.: 204-116-4 REACH-no: 01-2119454789-19	1.2 – 2.4	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
d-Limonene substance with national workplace exposure limit(s) (DE, ES, FI, SI, NO, CH)	CAS-No.: 5989-27-5 EC-No.: 205-341-0 EC Index-No.: 601-096-00-2 REACH-no: 01-2119493353-35	1.1 – 2.2	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Citral substance with national workplace exposure limit(s) (BE, ES, IE, PL, PT)	CAS-No.: 5392-40-5 EC-No.: 226-394-6 EC Index-No.: 605-019-00-3 REACH-no: 01-2119462829-23	1 – 2	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Hexyl salicylate	CAS-No.: 6259-76-3 EC-No.: 228-408-6	0.438 – 1.5435	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Orange oil	CAS-No.: 8008-57-9 EC-No.: 232-433-8 REACH-no: 01-2119493353-35	0.8 – 1.5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Aldehyde C-14	CAS-No.: 104-67-6 EC-No.: 203-225-4 REACH-no: 01-2119959333-34	0.6 – 1.2	Aquatic Chronic 3, H412
Helional	CAS-No.: 1205-17-0 EC-No.: 214-881-6 REACH-no: 01-2120740119-58	0.6 – 1.1	Skin Sens. 1B, H317 Repr. 2, H361 Aquatic Chronic 2, H411

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Aldehyde C-16	CAS-No.: 77-83-8 EC-No.: 201-061-8 REACH-no: 01-2119967770-28	0.4 – 0.8	Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371-33	0.4 – 0.704	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Triplal (Vertocitral)	CAS-No.: 68039-49-6 EC-No.: 268-264-1	0.3 – 0.50775	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Patchouli oil	CAS-No.: 8014-09-3 EC Index-No.: 616-944-7	0.3 – 0.5	Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Allyl caproate	CAS-No.: 123-68-2 EC-No.: 204-642-4 REACH-no: 01-2119983573-26	0.3 – 0.5	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Geraniol	CAS-No.: 106-24-1 EC-No.: 203-377-1 EC Index-No.: 603-241-00-5 REACH-no: 01-2119552430-49	0.24 – 0.48	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317
Geranyl acetate	CAS-No.: 105-87-3 EC-No.: 203-341-5 REACH-no: 01-2119973480-35	0.2 – 0.35	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Nerol	CAS-No.: 106-25-2 EC-No.: 203-378-7	0.16 – 0.32	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Ethyl alcohol substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SI, SK, NO, CH)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5	0.1 – 0.2495	Flam. Liq. 2, H225
1,2-Propanediol substance with national workplace exposure limit(s) (GB, HR, IE, LT, LV, PL, NO)	CAS-No.: 57-55-6 EC-No.: 200-338-0 REACH-no: 01-2119456809-23	0.1 – 0.247	Not classified
delta-Damascone	CAS-No.: 57378-68-4 EC-No.: 260-709-8	0.1 – 0.2	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 1, H410
decyl alcohol substance with national workplace exposure limit(s) (BG, DE, LT, LV, RO, CH)	CAS-No.: 112-30-1 EC-No.: 203-956-9	0 – 0.0448	Aquatic Chronic 3, H412

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
.beta.-Pinene substance with national workplace exposure limit(s) (BE, EE, ES, LT, PT, SE, NO)	CAS-No.: 127-91-3 EC-No.: 204-872-5	≤ 0.0225	Flam. Liq. 3, H226
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	≤ 0.0186	Not classified
Aldehyde C-6 substance with national workplace exposure limit(s) (FI, PL)	CAS-No.: 66-25-1 EC-No.: 200-624-5	0 – 0.0112	Flam. Liq. 3, H226
.alpha.-Pinene substance with national workplace exposure limit(s) (BE, EE, ES, LT, PT, SE, NO)	CAS-No.: 80-56-8 EC-No.: 201-291-9	≤ 0.0015	Flam. Liq. 3, H226
Caproic acid substance with national workplace exposure limit(s) (BG, LT, LV)	CAS-No.: 142-62-1 EC-No.: 205-550-7	0 – 0.0006	Eye Dam. 1, H318 Skin Corr. 1C, H314
CAFFEINE substance with national workplace exposure limit(s) (BG, LT, LV)	CAS-No.: 58-08-2 EC-No.: 200-362-1 EC Index-No.: 613-086-00-5	0 – 0.0003	Acute Tox. 4 (Oral), H302
Butyric acid substance with national workplace exposure limit(s) (BG, LT, LV, RO)	CAS-No.: 107-92-6 EC-No.: 203-532-3 EC Index-No.: 607-135-00-X	0 – 0.0002	Skin Corr. 1B, H314

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash with plenty of water/.... Get medical advice/attention. Wash contaminated clothing before reuse. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: If eye irritation persists: Get medical advice/attention. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Suspected of damaging fertility or the unborn child. Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. No open flames. No smoking. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Keep in fireproof place. Store in a well-ventilated place. Keep cool.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Storage temperature : 25 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container.

Packaging materials : Do not store in corrodable metal.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Benzyl acetate (140-11-4)	
Belgium - Occupational Exposure Limits	
OEL TWA	62 mg/m ³
OEL TWA [ppm]	10 ppm
Denmark - Occupational Exposure Limits	
OEL TWA [1]	61 mg/m ³
OEL TWA [2]	10 ppm
OEL STEL	122 mg/m ³
OEL STEL [ppm]	20 ppm
Ireland - Occupational Exposure Limits	
OEL TWA [2]	10 ppm
OEL STEL [ppm]	30 ppm (calculated)
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA [ppm]	10 ppm
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen
Romania - Occupational Exposure Limits	
OEL TWA	50 mg/m ³
OEL TWA [ppm]	8 ppm
OEL STEL	80 mg/m ³

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzyl acetate (140-11-4)	
OEL STEL [ppm]	13 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	62 mg/m ³
VLA-ED (OEL TWA) [2]	10 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	10 ppm
ACGIH chemical category	Not Classifiable as a Human Carcinogen
d-Limonene (5989-27-5)	
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	140 mg/m ³
HTP (OEL TWA) [2]	25 ppm
HTP (OEL STEL)	280 mg/m ³
HTP (OEL STEL) [ppm]	50 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	28 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
AGW (OEL TWA) [2]	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	Skin notation, Skin sensitization
Slovenia - Occupational Exposure Limits	
OEL TWA	28 mg/m ³
OEL TWA [ppm]	5 ppm
OEL STEL	112 mg/m ³
OEL STEL [ppm]	20 ppm
OEL chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	168 mg/m ³
VLA-ED (OEL TWA) [2]	30 ppm
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grønseverdi (OEL TWA) [1]	140 mg/m ³
Grønseverdi (OEL TWA) [2]	25 ppm
Korttidsverdi (OEL STEL)	175 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	37.5 ppm (value calculated)
OEL chemical category	Allergenic substance
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	40 mg/m ³
MAK (OEL TWA) [2]	7 ppm
KZGW (OEL STEL)	80 mg/m ³

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

d-Limonene (5989-27-5)	
KZGW (OEL STEL) [ppm]	14 ppm
OEL chemical category	Sensitizer
Citral (5392-40-5)	
Belgium - Occupational Exposure Limits	
OEL TWA	32 mg/m ³ (vapor and aerosol)
OEL TWA [ppm]	5 ppm (vapor and aerosol)
OEL chemical category	Skin
Ireland - Occupational Exposure Limits	
OEL TWA [2]	5 ppm
OEL STEL [ppm]	15 ppm (calculated)
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	27 mg/m ³
NDSch (OEL STEL)	54 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA [ppm]	5 ppm (inhalable fraction; vapor)
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [2]	5 ppm (inhalable fraction and vapor)
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	5 ppm (inhalable fraction and vapor)
ACGIH chemical category	Not Classifiable as a Human Carcinogen, Skin - potential significant contribution to overall exposure by the cutaneous route, dermal sensitizer
Ethyl alcohol (64-17-5)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	1900 mg/m ³
MAK (OEL TWA) [ppm]	1000 ppm
MAK (OEL STEL)	3800 mg/m ³
MAK (OEL STEL) [ppm]	2000 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	1907 mg/m ³
OEL TWA [ppm]	1000 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	1000 mg/m ³
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	1900 mg/m ³
GVI (OEL TWA) [2]	1000 ppm

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethyl alcohol (64-17-5)	
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	1000 mg/m ³
Denmark - Occupational Exposure Limits	
OEL TWA [1]	1900 mg/m ³
OEL TWA [2]	1000 ppm
OEL STEL	3800 mg/m ³
OEL STEL [ppm]	2000 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	1000 mg/m ³
OEL TWA [ppm]	500 ppm
OEL STEL	1900 mg/m ³
OEL STEL [ppm]	1000 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	1900 mg/m ³
HTP (OEL TWA) [2]	1000 ppm
HTP (OEL STEL)	2500 mg/m ³
HTP (OEL STEL) [ppm]	1300 ppm
France - Occupational Exposure Limits	
VME (OEL TWA)	1900 mg/m ³
VME (OEL TWA) [ppm]	1000 ppm
VLE (OEL C/STEL)	9500 mg/m ³
VLE (OEL C/STEL) [ppm]	5000 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	380 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
AGW (OEL TWA) [2]	200 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Greece - Occupational Exposure Limits	
OEL TWA	1900 mg/m ³
OEL TWA [ppm]	1000 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	1900 mg/m ³
CK (OEL STEL)	3800 mg/m ³
Ireland - Occupational Exposure Limits	
OEL STEL [ppm]	1000 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	1000 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	1000 mg/m ³
IPRV (OEL TWA) [ppm]	500 ppm

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethyl alcohol (64-17-5)	
TPRV (OEL STEL)	1900 mg/m ³
TPRV (OEL STEL) [ppm]	1000 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	260 mg/m ³
TGG-8u (OEL TWA) [ppm]	137 ppm
TGG-15min (OEL STEL)	1900 mg/m ³
TGG-15min (OEL STEL) [ppm]	1000 ppm
MAC chemical category	Skin notation
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	1900 mg/m ³
Portugal - Occupational Exposure Limits	
OEL STEL [ppm]	1000 ppm
OEL chemical category	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
Romania - Occupational Exposure Limits	
OEL TWA	1900 mg/m ³
OEL TWA [ppm]	1000 ppm
OEL STEL	9500 mg/m ³
OEL STEL [ppm]	5000 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	960 mg/m ³
NPHV (OEL TWA) [2]	500 ppm
NPHV (OEL C)	1920 mg/m ³
Slovenia - Occupational Exposure Limits	
OEL TWA	960 mg/m ³
OEL TWA [ppm]	500 ppm
OEL STEL	1920 mg/m ³
OEL STEL [ppm]	1000 ppm
Spain - Occupational Exposure Limits	
VLA-EC (OEL STEL)	1910 mg/m ³
VLA-EC (OEL STEL) [ppm]	1000 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	1000 mg/m ³
NGV (OEL TWA) [ppm]	500 ppm
KTV (OEL STEL)	1900 mg/m ³
KTV (OEL STEL) [ppm]	1000 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	1920 mg/m ³
WEL TWA (OEL TWA) [2]	1000 ppm
WEL STEL (OEL STEL)	5760 mg/m ³ (calculated)

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethyl alcohol (64-17-5)	
WEL STEL (OEL STEL) [ppm]	3000 ppm (calculated)
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	950 mg/m ³
Grenseverdi (OEL TWA) [2]	500 ppm
Korttidsverdi (OEL STEL)	1187.5 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	625 ppm (value calculated)
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	960 mg/m ³
MAK (OEL TWA) [2]	500 ppm
KZGW (OEL STEL)	1920 mg/m ³
KZGW (OEL STEL) [ppm]	1000 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL STEL [ppm]	1000 ppm
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
1,2-Propanediol (57-55-6)	
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	474 mg/m ³ (total vapor and particles) 10 mg/m ³ (particles)
GVI (OEL TWA) [2]	150 ppm
Ireland - Occupational Exposure Limits	
OEL TWA [1]	10 mg/m ³ (particulates) 470 mg/m ³ (total vapour and particulates)
OEL TWA [2]	150 ppm (total vapour and particulates)
OEL STEL	1410 mg/m ³ (calculated-particulates) 30 mg/m ³ (calculated)
OEL STEL [ppm]	450 ppm (calculated-total vapour and particulates)
Latvia - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	7 mg/m ³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	100 mg/m ³ (vapor and inhalable fraction)
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	474 mg/m ³ (total vapour and particulates) 10 mg/m ³ (particulates)
WEL TWA (OEL TWA) [2]	150 ppm (total vapour and particulates)
WEL STEL (OEL STEL)	1422 mg/m ³ (calculated-total vapour and particulates) 30 mg/m ³ (calculated-particulate)
WEL STEL (OEL STEL) [ppm]	450 ppm (calculated-total vapour and particulates)

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1,2-Propanediol (57-55-6)	
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	79 mg/m ³
Grenseverdi (OEL TWA) [2]	25 ppm
Korttidsverdi (OEL STEL)	118.5 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	37.5 ppm (value calculated)
.beta.-Pinene (127-91-3)	
Belgium - Occupational Exposure Limits	
OEL TWA [ppm]	20 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	150 mg/m ³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
OEL TWA [ppm]	25 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
OEL STEL	300 mg/m ³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
OEL STEL [ppm]	50 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	150 mg/m ³
IPRV (OEL TWA) [ppm]	25 ppm
TPRV (OEL STEL)	300 mg/m ³
TPRV (OEL STEL) [ppm]	50 ppm
Portugal - Occupational Exposure Limits	
OEL TWA [ppm]	20 ppm (Turpentine and selected Monoterpenes)
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	113 mg/m ³
VLA-ED (OEL TWA) [2]	20 ppm
OEL chemical category	Sensitizer
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	150 mg/m ³
NGV (OEL TWA) [ppm]	25 ppm
KTV (OEL STEL)	300 mg/m ³
KTV (OEL STEL) [ppm]	50 ppm
OEL chemical category	Sensitizer
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	140 mg/m ³
Grenseverdi (OEL TWA) [2]	25 ppm
Korttidsverdi (OEL STEL)	175 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	37.5 ppm (value calculated)

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

.beta.-Pinene (127-91-3)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	20 ppm (Turpentine and selected Monoterpenes)
ACGIH chemical category	Not Classifiable as a Human Carcinogen, dermal sensitizer
.alpha.-Pinene (80-56-8)	
Belgium - Occupational Exposure Limits	
OEL TWA [ppm]	20 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	150 mg/m ³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
OEL TWA [ppm]	25 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
OEL STEL	300 mg/m ³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
OEL STEL [ppm]	50 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	150 mg/m ³
IPRV (OEL TWA) [ppm]	25 ppm
TPRV (OEL STEL)	300 mg/m ³
TPRV (OEL STEL) [ppm]	50 ppm
Portugal - Occupational Exposure Limits	
OEL TWA [ppm]	20 ppm (Turpentine and selected Monoterpenes)
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	113 mg/m ³
VLA-ED (OEL TWA) [2]	20 ppm
OEL chemical category	Sensitizer
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	150 mg/m ³
NGV (OEL TWA) [ppm]	25 ppm
KTV (OEL STEL)	300 mg/m ³
KTV (OEL STEL) [ppm]	50 ppm
OEL chemical category	Sensitizer
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	140 mg/m ³
Grenseverdi (OEL TWA) [2]	25 ppm
Korttidsverdi (OEL STEL)	175 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	37.5 ppm (value calculated)
OEL chemical category	Skin notation

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

.alpha.-Pinene (80-56-8)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	20 ppm (Turpentine and selected Monoterpenes)
ACGIH chemical category	Not Classifiable as a Human Carcinogen, dermal sensitizer
Dipropylene glycol monomethyl ether (34590-94-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	308 mg/m ³
IOEL TWA [ppm]	50 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	307 mg/m ³ (mixed isomers)
MAK (OEL TWA) [ppm]	50 ppm (mixed isomers)
MAK (OEL STEL)	614 mg/m ³ (isomers mixtures)
MAK (OEL STEL) [ppm]	100 ppm (isomers mixtures)
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Skin, Skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	308 mg/m ³
GVI (OEL TWA) [2]	50 ppm
OEL chemical category	Skin notation
Cyprus - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	270 mg/m ³
OEL chemical category	Potential for cutaneous absorption
Denmark - Occupational Exposure Limits	
OEL TWA [1]	309 mg/m ³
OEL TWA [2]	50 ppm
OEL STEL	618 mg/m ³
OEL STEL [ppm]	100 ppm
OEL chemical category	Potential for cutaneous absorption

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
Estonia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	310 mg/m ³
HTP (OEL TWA) [2]	50 ppm
OEL chemical category	Potential for cutaneous absorption
France - Occupational Exposure Limits	
VME (OEL TWA)	308 mg/m ³ (restrictive limit)
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)
OEL chemical category	Risk of cutaneous absorption
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	310 mg/m ³ (isomer mixture)
AGW (OEL TWA) [2]	50 ppm (isomer mixture)
Gibraltar - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Skin notation
Greece - Occupational Exposure Limits	
OEL TWA	600 mg/m ³
OEL TWA [ppm]	100 ppm
OEL STEL	900 mg/m ³
OEL STEL [ppm]	150 ppm
OEL chemical category	skin - potential for cutaneous absorption
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	308 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA [1]	308 mg/m ³ ((2-Methoxymethylethoxy)propanol)
OEL TWA [2]	50 ppm ((2-Methoxymethylethoxy)propanol)
OEL STEL	924 mg/m ³ (calculated (2-(2-Methoxypropoxy)-1-propanol)
OEL STEL [ppm]	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
OEL TWA [ppm]	50 ppm
OEL chemical category	skin - potential for cutaneous exposure
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	300 mg/m ³ (2-(2-Methoxypropoxy)-propanol)
IPRV (OEL TWA) [ppm]	50 ppm (2-(2-Methoxypropoxy)-propanol)
TPRV (OEL STEL)	450 mg/m ³ (2-(2-Methoxypropoxy)-propanol)
TPRV (OEL STEL) [ppm]	75 ppm (2-(2-Methoxypropoxy)-propanol)
OEL chemical category	Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	300 mg/m ³
TGG-8u (OEL TWA) [ppm]	48.7 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m ³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
NDSch (OEL STEL)	480 mg/m ³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
Portugal - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ (indicative limit value)
OEL TWA [ppm]	50 ppm (indicative limit value)
OEL STEL [ppm]	150 ppm
OEL chemical category	skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Skin notation
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	308 mg/m ³
NPHV (OEL TWA) [2]	50 ppm
OEL chemical category	Potential for cutaneous absorption
Slovenia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
OEL STEL	308 mg/m ³
OEL STEL [ppm]	50 ppm
OEL chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	308 mg/m ³ (indicative limit value)
VLA-ED (OEL TWA) [2]	50 ppm (indicative limit value)
OEL chemical category	skin - potential for cutaneous absorption
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	300 mg/m ³
NGV (OEL TWA) [ppm]	50 ppm
KTV (OEL STEL)	450 mg/m ³
KTV (OEL STEL) [ppm]	75 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	308 mg/m ³
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	924 mg/m ³ (calculated)
WEL STEL (OEL STEL) [ppm]	150 ppm (calculated)
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grænseverdi (OEL TWA) [1]	300 mg/m ³
Grænseverdi (OEL TWA) [2]	50 ppm
Korttidsverdi (OEL STEL)	375 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	75 ppm (value calculated)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	300 mg/m ³ (aerosol, vapour)
MAK (OEL TWA) [2]	50 ppm (aerosol, vapour)
KZGW (OEL STEL)	300 mg/m ³ (aerosol, vapour)
KZGW (OEL STEL) [ppm]	50 ppm (aerosol, vapour)
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	50 ppm (Dipropylene glycol methyl ether)
decyl alcohol (112-30-1)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	66 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

decyl alcohol (112-30-1)	
AGW (OEL TWA) [2]	10 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Latvia - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	10 mg/m ³
Romania - Occupational Exposure Limits	
OEL TWA	100 mg/m ³
OEL TWA [ppm]	15 ppm
OEL STEL	200 mg/m ³
OEL STEL [ppm]	30 ppm
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	66 mg/m ³ (aerosol, vapour)
MAK (OEL TWA) [2]	10 ppm (aerosol, vapour)
KZGW (OEL STEL)	66 mg/m ³ (aerosol, vapour)
KZGW (OEL STEL) [ppm]	10 ppm (aerosol, vapour)
Aldehyde C-6 (66-25-1)	
Finland - Occupational Exposure Limits	
HTP (OEL STEL)	42 mg/m ³
HTP (OEL STEL) [ppm]	10 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	40 mg/m ³
NDSch (OEL STEL)	80 mg/m ³
Caproic acid (142-62-1)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m ³
CAFFEINE (58-08-2)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	0.5 mg/m ³
Latvia - Occupational Exposure Limits	
OEL TWA	0.5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	0.5 mg/m ³ (base)

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Butyric acid (107-92-6)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Latvia - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	10 mg/m ³
Romania - Occupational Exposure Limits	
OEL TWA	15 mg/m ³
OEL TWA [ppm]	4 ppm
OEL STEL	30 mg/m ³
OEL STEL [ppm]	8 ppm

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Conforms to standard. light yellow. amber.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable, Combustible liquid
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 87 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Combustible liquid. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Benzyl acetate (140-11-4)	
LD50 oral rat	2490 mg/kg (Source: JAPAN_GHS)
LD50 oral	2490 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: JAPAN_GHS)
Hexyl salicylate (6259-76-3)	
LD50 oral rat	> 5 g/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)
2-Isobutyl-4-methyltetrahydro-2H-pyran-4-ol (63500-71-0)	
LD50 dermal rabbit	> 2000 mg/kg (Source: ECHA_API)
Hexyl cinnamic aldehyde (101-86-0)	
LD50 oral rat	3100 mg/kg (Source: NLM_CIP)
LD50 oral	3100 mg/kg bodyweight
LD50 dermal rabbit	> 3000 mg/kg (Source: EPA_HPVS)
LC50 Inhalation - Rat	> 5 mg/l/4h
Linalool (78-70-6)	
LD50 oral	2790 mg/kg bodyweight
Verdox (88-41-5)	
LD50 oral rat	4600 mg/kg (Source: NLM_CIP)
LD50 oral	4600 mg/kg bodyweight
Dihydromyrcenol (18479-58-8)	
LD50 oral rat	3600 mg/kg (Source: NLM_CIP)
LD50 oral	3600 mg/kg bodyweight
LD50 dermal rabbit	> 5 g/kg (Source: CHEMVIEW)
Hexamethylindanopyran (1222-05-5)	
LD50 oral rat	> 3250 mg/kg (Source: CHEMVIEW)
LD50 dermal rabbit	> 3250 mg/kg (Source: CHEMVIEW)
Linalyl acetate (115-95-7)	
LD50 oral rat	14550 mg/kg (Source: EPA_HPVS)
LD50 dermal rabbit	> 5000 mg/kg (Source: EPA_HPVS)

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

d-Limonene (5989-27-5)	
LD50 oral rat	4400 mg/kg (Source: CHEMVIEW)
LD50 dermal rabbit	> 5 g/kg (Source: CHEMVIEW)
Citral (5392-40-5)	
LD50 oral rat	4960 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	2250 mg/kg (Source: NLM_CIP)
Orange oil (8008-57-9)	
LD50 oral rat	4400 mg/kg (Source: NZ_CCID)
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)
Aldehyde C-14 (104-67-6)	
LD50 oral rat	18500 mg/kg (Source: NLM_CIP)
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)
Helional (1205-17-0)	
LD50 dermal rabbit	> 2000 mg/kg (Source: ECHA_API)
Geraniol (106-24-1)	
LD50 oral rat	3600 mg/kg (Source: NLM_CIP)
LD50 oral	3600 mg/kg bodyweight
LD50 dermal rabbit	> 5 g/kg (Source: NLM_CIP)
Nerol (106-25-2)	
LD50 oral rat	4500 mg/kg (Source: NLM_CIP)
LD50 oral	4500 mg/kg bodyweight
LD50 dermal rabbit	> 5 g/kg (Source: NLM_CIP)
Aldehyde C-16 (77-83-8)	
LD50 oral rat	5470 mg/kg (Source: NLM_CIP)
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)
Benzyl benzoate (120-51-4)	
LD50 oral rat	500 mg/kg (Source: NLM_CIP)
LD50 oral	1160 mg/kg bodyweight
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)
Triplal (Vertocitral) (68039-49-6)	
LD50 oral	3900 mg/kg bodyweight
Patchouli oil (8014-09-3)	
LD50 oral rat	> 5 g/kg (Source: NLM_CIP)
Allyl caproate (123-68-2)	
LD50 oral	300 mg/kg bodyweight
LD50 dermal rabbit	820 mg/kg (Source: ECHA_API)
LD50 dermal	300 mg/kg bodyweight
LC50 Inhalation - Rat (Vapours)	3 mg/l/4h

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Geranyl acetate (105-87-3)	
LD50 oral rat	6330 mg/kg (Source: NLM_CIP)
Ethyl alcohol (64-17-5)	
LD50 oral rat	7060 mg/kg (Source: NLM_CIP)
LC50 Inhalation - Rat	133.8 mg/l/4h
1,2-Propanediol (57-55-6)	
LD50 oral rat	20 g/kg (Source: NLM_CIP)
LD50 dermal rabbit	20800 mg/kg (Source: NLM_CIP)
delta-Damascone (57378-68-4)	
LD50 oral	1400 mg/kg bodyweight
.beta.-Pinene (127-91-3)	
LD50 oral rat	> 5000 mg/kg (Source: EPA_HPVS)
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)
.alpha.-Pinene (80-56-8)	
LD50 oral rat	3700 mg/kg (Source: NLM_CIP)
LD50 oral	500 mg/kg bodyweight
LD50 dermal rat	> 5000 mg/kg (Source: CHEMVIEW)
Dipropylene glycol monomethyl ether (34590-94-8)	
LD50 oral rat	5.35 g/kg (Source: NLM_HSDB)
LD50 dermal rabbit	9500 mg/kg (Source: NLM_CIP)
decyl alcohol (112-30-1)	
LD50 oral rat	4720 mg/kg (Source: NZ_CCID)
LD50 dermal rabbit	3560 mg/kg (Source: NLM_CIP)
Aldehyde C-6 (66-25-1)	
LD50 oral rat	4890 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 8100 mg/kg (Source: ECHA_API)
Caproic acid (142-62-1)	
LD50 oral rat	3 g/kg (Source: NLM_HSDB)
LD50 oral	4000 mg/kg bodyweight
LD50 dermal rabbit	630 mg/kg (Source: NLM_HSDB)
CAFFEINE (58-08-2)	
LD50 oral rat	367.7 mg/kg (Source: OECD_SIDS)
LD50 oral	370 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)
LC50 Inhalation - Rat	4.94 mg/l/4h
Butyric acid (107-92-6)	
LD50 oral rat	2 g/kg (Source: NLM_CIP)
LD50 oral	1630 mg/kg bodyweight

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Butyric acid (107-92-6)	
LD50 dermal rabbit	530 mg/kg (Source: NLM_HSDB)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Benzyl acetate (140-11-4)	
IARC group	3 - Not classifiable
d-Limonene (5989-27-5)	
IARC group	3 - Not classifiable
CAFFEINE (58-08-2)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Orange oil (8008-57-9)	
Hydrocarbon	Yes
Benzyl benzoate (120-51-4)	
Viscosity, kinematic	7.456 mm ² /s

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

Linalool (78-70-6)	
EC50 96h - Algae [1]	88.3 mg/l (Species: Desmodemus subspicatus)
Hexamethylindanopyran (1222-05-5)	
LC50 - Fish [1]	0.452 mg/l Wolf, 1996d-27682
LC50 - Other aquatic organisms [1]	> 0.14 mg/l REACH DOSSIER Pimephales promelas
EC50 - Crustacea [2]	260 µg/l REACH Dossier
EC50 - Other aquatic organisms [1]	0.131 mg/l REACH Dossier

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Linalyl acetate (115-95-7)	
LC50 - Fish [1]	11 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [flow-through] Source: ECHA)
d-Limonene (5989-27-5)	
LC50 - Fish [1]	0.619 – 0.796 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: EPA)
Citral (5392-40-5)	
EC50 - Crustacea [1]	7 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	16 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [1]	19 mg/l (Species: Desmodesmus subspicatus)
Aldehyde C-14 (104-67-6)	
LC50 - Fish [1]	569 mg/l 96 h
EC50 - Crustacea [1]	5.85 mg/l 48 h
EC50 - Other aquatic organisms [1]	5.94 mg/l 72 h
Geraniol (106-24-1)	
LC50 - Fish [1]	22 mg/l (Exposure time: 96 h - Species: Danio rerio [static] Source: ECHA)
Nerol (106-25-2)	
LC50 - Fish [1]	20.3 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
Aldehyde C-16 (77-83-8)	
LC50 - Fish [1]	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static] Source: ECHA)
Benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
NOEC (chronic)	0.168 mg/l
Allyl caproate (123-68-2)	
LC50 - Fish [1]	0.117 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
Ethyl alcohol (64-17-5)	
LC50 - Fish [2]	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
EC50 - Crustacea [1]	9268 – 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Crustacea [2]	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
1,2-Propanediol (57-55-6)	
LC50 - Fish [1]	51600 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: IUCLID)
LC50 - Fish [2]	41 – 47 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 96h - Algae [1]	19000 mg/l (Species: Pseudokirchneriella subcapitata)
.alpha.-Pinene (80-56-8)	
LC50 - Fish [1]	0.28 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: IUCLID)
EC50 - Crustacea [1]	41 mg/l (Exposure time: 48 h - Species: Daphnia magna)

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)
decyl alcohol (112-30-1)	
LC50 - Fish [1]	2.2 – 2.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	4.12 – 6.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
EC50 - Crustacea [1]	3 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Aldehyde C-6 (66-25-1)	
LC50 - Fish [1]	12 – 16.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
Caproic acid (142-62-1)	
LC50 - Fish [1]	306 – 334 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
CAFFEINE (58-08-2)	
LC50 - Fish [1]	151 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
Butyric acid (107-92-6)	
EC50 72h - Algae [1]	46.7 mg/l (Species: Desmodesmus subspicatus)
12.2. Persistence and degradability	
ACAI BERRY BOOST CC-16315	
Persistence and degradability	Not established.
Benzyl benzoate (120-51-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.
12.3. Bioaccumulative potential	
ACAI BERRY BOOST CC-16315	
Bioaccumulative potential	Not established.
Benzyl acetate (140-11-4)	
Partition coefficient n-octanol/water (Log Pow)	1.96 (at 25 °C (at pH 7))
Hexyl salicylate (6259-76-3)	
Partition coefficient n-octanol/water (Log Pow)	5.5 (at 30 °C (at pH 7))
2-Isobutyl-4-methyltetrahydro-2H-pyran-4-ol (63500-71-0)	
Partition coefficient n-octanol/water (Log Pow)	1.65 (at 23 °C (at pH >6.09-<6.74))
Dihydromyrcenol (18479-58-8)	
Partition coefficient n-octanol/water (Log Pow)	3.25 (at 40 °C (at pH 7))
Hexamethylindanopyran (1222-05-5)	
BCF - Fish [1]	(1618 dimensionless (whole body w.w.))

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hexamethylindanopyran (1222-05-5)	
Partition coefficient n-octanol/water (Log Pow)	5.3 (at 25 °C (at pH 7)
Linalyl acetate (115-95-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 (at 25 °C)
d-Limonene (5989-27-5)	
Partition coefficient n-octanol/water (Log Pow)	4.38 (at 37 °C (at pH 7.2)
Citral (5392-40-5)	
Partition coefficient n-octanol/water (Log Pow)	2.76 (at 25 °C)
Aldehyde C-14 (104-67-6)	
Partition coefficient n-octanol/water (Log Pow)	3.6 (at 25 °C)
Helional (1205-17-0)	
Partition coefficient n-octanol/water (Log Pow)	2.4 (at 25 °C)
Geraniol (106-24-1)	
Partition coefficient n-octanol/water (Log Pow)	2.6 (at 25 °C)
Nerol (106-25-2)	
Partition coefficient n-octanol/water (Log Pow)	2.76 (at 30 °C (at pH 6.5)
Aldehyde C-16 (77-83-8)	
Partition coefficient n-octanol/water (Log Pow)	2.4 (at 25 °C (cis isomer)
Benzyl benzoate (120-51-4)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)
Bioaccumulative potential	Not established.
Allyl caproate (123-68-2)	
Partition coefficient n-octanol/water (Log Pow)	3.191 (at 20 °C (at pH 5)
Geranyl acetate (105-87-3)	
Partition coefficient n-octanol/water (Log Pow)	4.04
Ethyl alcohol (64-17-5)	
Partition coefficient n-octanol/water (Log Pow)	-0.35 (at 24 °C (at pH 7.4)
1,2-Propanediol (57-55-6)	
BCF - Fish [1]	(1 dimensionless)
Partition coefficient n-octanol/water (Log Pow)	-1.07 (at 20.5 °C (at pH >=6.2-<=6.4)
.alpha.-Pinene (80-56-8)	
Partition coefficient n-octanol/water (Log Pow)	4.1
Dipropylene glycol monomethyl ether (34590-94-8)	
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7)
decyl alcohol (112-30-1)	
Partition coefficient n-octanol/water (Log Pow)	4.5 (at 25 °C (at pH 6)

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Aldehyde C-6 (66-25-1)	
Partition coefficient n-octanol/water (Log Pow)	2.3 (at 25 °C (at pH 5))
Caproic acid (142-62-1)	
Partition coefficient n-octanol/water (Log Pow)	1.88
CAFFEINE (58-08-2)	
Partition coefficient n-octanol/water (Log Pow)	-0.091 (at 23 °C)
Butyric acid (107-92-6)	
Partition coefficient n-octanol/water (Log Pow)	1.1 (at 25 °C (at pH 3))

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with local/national laws and regulations.
Ecology - waste materials	: Avoid release to the environment.
HP Code	: HP3 - "Flammable:" <ul style="list-style-type: none">– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
	HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.
	HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Iso E Super)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Iso E Super)	Environmentally hazardous substance, liquid, n.o.s. (Iso E Super)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Iso E Super)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Iso E Super)
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Iso E Super), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Iso E Super), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Iso E Super), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Iso E Super), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Iso E Super), 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : M6
 Special provisions (ADR) : 274, 335, 375, 601
 Limited quantities (ADR) : 5L
 Excepted quantities (ADR) : E1
 Packing instructions (ADR) : P001, IBC03, LP01, R001
 Special packing provisions (ADR) : PP1
 Mixed packing provisions (ADR) : MP19
 Portable tank and bulk container instructions (ADR) : T4
 Portable tank and bulk container special provisions (ADR) : TP1, TP29
 Tank code (ADR) : LGBV
 Vehicle for tank carriage : AT
 Transport category (ADR) : 3
 Special provisions for carriage - Packages (ADR) : V12
 Special provisions for carriage - Loading, unloading and handling (ADR) : CV13
 Hazard identification number (Kemler No.) : 90
 Orange plates :



ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Tunnel restriction code (ADR) : -
EAC code : •3Z

Transport by sea

Special provisions (IMDG) : 274, 335, 969
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : LP01, P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-F
Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L
Special provisions (IATA) : A97, A158, A197, A215
ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M6
Special provisions (ADN) : 274, 335, 375, 601
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T
Equipment required (ADN) : PP
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : M6
Special provisions (RID) : 274, 335, 375, 601
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions (RID) : TP1, TP29
Tank codes for RID tanks (RID) : LGBV
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31
Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	d-Limonene ; Orange oil ; Ethyl alcohol ; .beta.-Pinene ; .alpha.-Pinene ; Aldehyde C-6	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	ACAI BERRY BOOST CC-16315 ; Hexyl salicylate ; 2-Isobutyl-4-methyltetrahydro-2H-pyran-4-ol ; Iso E Super ; Hexyl cinnamic aldehyde ; Linalool ; CUPRESSUS FUNEBRIS WOOD OIL ; Dihydromyrcenol ; Linalyl acetate ; d-Limonene ; Citral ; Orange oil ; Helional ; Geraniol ; Nerol ; Aldehyde C-16 ; Benzyl benzoate ; Triplal (Vertocitral) ; Allyl caproate ; Geranyl acetate ; delta-Damascone ; Caproic acid ; CAFFEINE ; Butyric acid	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	ACAI BERRY BOOST CC-16315 ; Benzyl acetate ; Hexyl salicylate ; Iso E Super ; Hexyl cinnamic aldehyde ; CUPRESSUS FUNEBRIS WOOD OIL ; Verdox ; Hexamethylindanopyran ; d-Limonene ; Orange oil ; Aldehyde C-14 ; Helional ; Aldehyde C-16 ; Benzyl benzoate ; Triplal (Vertocitral) ; Allyl caproate ; Geranyl acetate ; delta-Damascone ; decyl alcohol	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	d-Limonene ; Orange oil ; Ethyl alcohol ; .beta.-Pinene ; .alpha.-Pinene ; Aldehyde C-6	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK)

: WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Storage class (LGK, TRGS 510)

: LGK 10 - Combustible liquids.

Joint storage table

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for

: LGK 1, LGK 2A, LGK 5.1A, LGK 6.2, LGK 7.

Joint storage with restrictions permitted for

: LGK 4.1A, LGK 4.2, LGK 4.3, LGK 5.1B, LGK 5.1C, LGK 5.2.

Joint storage permitted for

: LGK 2B, LGK 3, LGK 4.1B, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13.

Hazardous Incident Ordinance (12. BImSchV)

: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category

: A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment

SZW-lijst van kankerverwekkende stoffen

: CUPRESSUS FUNEBRIS WOOD OIL, Orange oil, Triplal (Vertocitral), Ethyl alcohol are listed

SZW-lijst van mutagene stoffen

: CUPRESSUS FUNEBRIS WOOD OIL, Orange oil, Triplal (Vertocitral) are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding

: Ethyl alcohol is listed

SZW-lijst van reprotoxische stoffen –

: Ethyl alcohol is listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling

: Ethyl alcohol is listed

Denmark

Class for fire hazard

: Class III-1

Store unit

: 50 liter

Classification remarks

: Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

Storage class (LK) : LK 10/12 - Liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Other information : None.

Full text of H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H361	Suspected of damaging fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

ACAI BERRY BOOST CC-16315

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1	Skin corrosion/irritation, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.