Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : LAVENDER GELATO CC-16354 10% in DPG

Product code : CC-16354_10%

Type of product : Perfumes, Fragrances

Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use

Industrial/Professional use spec : Industrial

For professional use only : Perfumes, Fragrances

Function or use category : Odour agents

1.2.2. Uses advised against

Use of the substance/mixture

No additional information available

1.3. Details of the supplier of the safety data sheet

Candle Craft
Weiherwiese 10
65510 Idstein - Germany
T 49-6126-9363 -0

info@candlecraft.de - www.candlecraft.de

1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731;

Brazil: +0-800-591-6042; India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitization, Category 1 H317 Hazardous to the aquatic environment – Chronic Hazard H412

Category 3

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Precautionary statements (CLP)

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) : Warning

Contains : Benzyl salicylate; Iso E Super; Lavandin abrialis oil; Linalyl acetate; Linalool

Hazard statements (CLP) : H317 - May cause an allergic skin reaction.

H412 - Harmful to aquatic life with long lasting effects.

: P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 - Contaminated work clothing should not be allowed out of the workplace.

11/29/2023 (Issue date) EN (English US) 1/17

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P321 - Specific treatment (see supplemental first aid instruction on this label).

Extra phrases : Restricted to professional users.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371- 33	2.17 – 4.34	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Iso E Super	CAS-No.: 54464-57-2 EC-No.: 259-174-3 REACH-no: 01-2119489989- 04	0.5 – 1	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 1, H410
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016-	0.25 – 0.5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Benzyl salicylate	CAS-No.: 118-58-1 EC-No.: 204-262-9 EC Index-No.: 607-754-00-5 REACH-no: 01-2119969442- 31	0.1 – 0.2	Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Benzyl acetate substance with national workplace exposure limit(s) (BE, DK, ES, IE, LT, LV, PT, RO)	CAS-No.: 140-11-4 EC-No.: 205-399-7 REACH-no: 01-2119638272- 42	0.1 – 0.2	Aquatic Chronic 3, H412
Lavandin abrialis oil	CAS-No.: 8022-15-9 EC-No.: 617-009-6	0.05 – 0.1	Eye Irrit. 2, H319 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Linalyl acetate	CAS-No.: 115-95-7 EC-No.: 204-116-4 REACH-no: 01-2119454789- 19	0.05 – 0.1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
isopentyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, DE, DK, EE, ES, FI, FR, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, TR); substance with a Community workplace exposure limit	CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2 REACH-no: 01-2119548408- 32	0.02 – 0.045	Flam. Liq. 3, H226
citral substance with national workplace exposure limit(s) (BE, ES, IE, PL, PT)	CAS-No.: 5392-40-5 EC-No.: 226-394-6 EC Index-No.: 605-019-00-3 REACH-no: 01-2119462829- 23	0.02 – 0.045	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical
	advice (show the label where possible).

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash skin with plenty of water. Take off contaminated

followed by warm water rinse. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes.

Avoid breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew

with proper protection. For further information refer to section 8: "Exposure

controls/personal protection".

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or

diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash

contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep

container closed when not in use. Store in a well-ventilated place. Keep cool.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

Storage temperature : 25 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container.

Packaging materials : Do not store in corrodable metal.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

11/29/2023 (Issue date) EN (English US) 4/17





isopentyl acetate (123-92-2)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	270 mg/m³	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	540 mg/m³	
IOEL STEL [ppm]	100 ppm	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	270 mg/m³ (Pentyl acetate (all isomers))	
MAK (OEL TWA) [ppm]	50 ppm (Pentyl acetate (all isomers))	
MAK (OEL STEL)	540 mg/m³ (Pentylacetate)	
MAK (OEL STEL) [ppm]	100 ppm (Pentylacetate)	
Belgium - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Bulgaria - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA) [1]	270 mg/m³	
GVI (OEL TWA) [2]	50 ppm	
KGVI (OEL STEL)	540 mg/m³	
KGVI (OEL STEL) [ppm]	100 ppm	
Cyprus - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	271 mg/m³ (Amyl acetate, all isomers)	
OEL TWA [2]	50 ppm (Amyl acetate, all isomers)	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Estonia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	






isopentyl acetate (123-92-2)		
OEL STEL	100 ppm	
Finland - Occupational Exposure Limits		
HTP (OEL TWA) [1]	270 mg/m³ (Pentyl acetate)	
HTP (OEL TWA) [2]	50 ppm (Pentyl acetate)	
HTP (OEL STEL)	540 mg/m³	
HTP (OEL STEL) [ppm]	100 ppm	
France - Occupational Exposure Limits		
VME (OEL TWA)	270 mg/m³ (restrictive limit)	
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)	
VLE (OEL C/STEL)	540 mg/m³ (restrictive limit)	
VLE (OEL C/STEL) [ppm]	100 ppm (restrictive limit)	
Germany - Occupational Exposure Limits (TRGS 90	00)	
AGW (OEL TWA) [1]	270 mg/m³	
AGW (OEL TWA) [2]	50 ppm	
Gibraltar - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Greece - Occupational Exposure Limits		
OEL TWA	530 mg/m³	
OEL TWA	100 ppm	
OEL STEL	800 mg/m³	
OEL STEL	150 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	270 mg/m³	
CK (OEL STEL)	540 mg/m³	
Ireland - Occupational Exposure Limits		
OEL TWA [1]	260 mg/m³	
OEL TWA [2]	50 ppm	
OEL STEL	520 mg/m³	
OEL STEL	100 ppm	
Italy - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Latvia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	






CEL TWA	isopentyl acetate (123-92-2)		
IPRV (OEL TWA) 270 mg/m² 50 ppm	OEL TWA	50 ppm	
IFRV (OEL TWA) [ppm]	Lithuania - Occupational Exposure Limits		
TPRV (OEL STEL) 540 mg/m² 100 ppm 100	IPRV (OEL TWA)	270 mg/m³	
TPRV (OEL STEL) [ppm] 100 ppm	IPRV (OEL TWA) [ppm]	50 ppm	
Luxembourg - Occupational Exposure Limits	TPRV (OEL STEL)	540 mg/m³	
OEL TWA 270 mg/m² OEL STEL 50 ppm OEL STEL 540 mg/m² OEL STEL 100 ppm Malta - Occupational Exposure Limits 270 mg/m² OEL TWA 50 ppm OEL STEL 540 mg/m² OEL STEL 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL STEL) NDS (OEL STEL) 500 mg/m² Portugal - Occupational Exposure Limits 250 mg/m² OEL TWA 270 mg/m² (indicative limit value) OEL TWA 50 ppm (indicative limit value) OEL STEL 540 mg/m² (indicative limit value) OEL STEL 540 mg/m² (indicative limit value) OEL STEL 50 ppm (indicative limit value) OEL TWA 270 mg/m² OEL TWA 50 ppm OEL TWA (SI TWA) [1] 270 mg/m² <td>TPRV (OEL STEL) [ppm]</td> <td>100 ppm</td>	TPRV (OEL STEL) [ppm]	100 ppm	
OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Malta - Occupational Exposure Limits OEL TWA OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) NDS (OEL TWA) 250 mg/m³ NDS (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits 270 mg/m³ (indicative limit value) OEL TWA 250 ppm (indicative limit value) OEL STEL 540 mg/m³ (indicative limit value) OEL STEL 540 mg/m³ (indicative limit value) OEL STEL 540 mg/m³ (indicative limit value) OEL STEL 100 ppm (indicative limit value) OEL STEL 540 mg/m³ OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ OEL T	Luxembourg - Occupational Exposure Limits		
OEL STEL 540 mg/m³ OEL STEL 100 ppm Malta - Occupational Exposure Limits 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits 500 mg/m³ NDS (OEL TWA) 250 mg/m³ NDS (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits 270 mg/m³ (indicative limit value) OEL TWA 270 mg/m³ (indicative limit value) OEL STEL 540 mg/m³ (indicative limit value) OEL STEL 540 mg/m³ (indicative limit value) OEL STEL 100 ppm (indicative limit value) OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] <td>OEL TWA</td> <td>270 mg/m³</td>	OEL TWA	270 mg/m³	
OEL STEL 100 ppm Malta - Occupational Exposure Limits 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits 550 mg/m³ NDS (OEL TWA) 250 mg/m³ NDS (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits 270 mg/m³ (indicative limit value) OEL TWA 270 mg/m³ (indicative limit value) OEL STEL 540 mg/m³ (indicative limit value) OEL STEL 540 mg/m³ (indicative limit value) OEL STEL 100 ppm (indicative limit value) OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL TWA 50 ppm NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] 50 ppm NPHV (OEL C) 540 mg/m³ Slovenia - O	OEL TWA	50 ppm	
Matta - Occupational Exposure Limits	OEL STEL	540 mg/m³	
OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) 530 mg/m³ TGG-15min (OEL STEL) (ppm) 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCN (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) OEL TWA 50 ppm (indicative limit value) OEL STEL 540 mg/m³ (indicative limit value) OEL STEL 100 ppm (indicative limit value) OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 50 ppm NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] 50 ppm	OEL STEL	100 ppm	
OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) 530 mg/m³ TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits 270 mg/m³ (indicative limit value) OEL TWA 50 ppm (indicative limit value) (Pentyl acetate, all isomers) OEL STEL 540 mg/m³ (indicative limit value) OEL STEL 100 ppm (indicative limit value) OEL STEL 100 ppm (indicative limit value) OEL TWA 50 ppm OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ OEL STEL 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] 50 ppm NPHV (OEL C) 540 mg/m³ Slovenia - Occupational Exposure Limits 270 mg/m³	Malta - Occupational Exposure Limits		
DEL STEL S40 mg/m³ 100 ppm 1	OEL TWA	270 mg/m³	
OEL STEL 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) 530 mg/m³ TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m² NDSCh (OEL STEL) 500 mg/m² Portugal - Occupational Exposure Limits 270 mg/m² (indicative limit value) OEL TWA 50 ppm (indicative limit value) (Pentyl acetate, all isomers) OEL STEL 540 mg/m² (indicative limit value) OEL STEL 100 ppm (indicative limit value) OEL TWA 270 mg/m³ OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ OEL STEL 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] 50 ppm NPHV (OEL C) 540 mg/m³ Slovenia - Occupational Exposure Limits 270 mg/m³	OEL TWA	50 ppm	
Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL)	OEL STEL	540 mg/m³	
TGG-15min (OEL STEL) 530 mg/m³ TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) OEL TWA 50 ppm (indicative limit value) OEL STEL 540 mg/m³ (indicative limit value) OEL STEL 100 ppm (indicative limit value) Romania - Occupational Exposure Limits 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ COL STEL 540 mg/m³ Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] 50 ppm NPHV (OEL C) 540 mg/m³ Slovenia - Occupational Exposure Limits Slovania - Occupational Exposure Limits OEL TWA 270 mg/m³	OEL STEL	100 ppm	
TGG-15min (OEL STEL) [ppm] 98.1 ppm	Netherlands - Occupational Exposure Limits		
Poland - Occupational Exposure Limits NDS (OEL TWA) DSCh (OEL STEL) Fortugal - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) OEL TWA 50 ppm (indicative limit value) OEL STEL 540 mg/m³ (indicative limit value) OEL STEL 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL TWA 550 ppm OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] 50 ppm NPHV (OEL TWA) [2] 50 ppm NPHV (OEL TWA) [2] Slovenia - Occupational Exposure Limits OEL TWA 270 mg/m³	TGG-15min (OEL STEL)	530 mg/m³	
NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) OEL TWA 50 ppm (indicative limit value) (Pentyl acetate, all isomers) OEL STEL 540 mg/m³ (indicative limit value) OEL STEL 100 ppm (indicative limit value) Romania - Occupational Exposure Limits 50 ppm OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] 50 ppm NPHV (OEL TWA) [2] 50 ppm NPHV (OEL C) 540 mg/m³ Slovenia - Occupational Exposure Limits OEL TWA 270 mg/m³	TGG-15min (OEL STEL) [ppm]	98.1 ppm	
NDSCh (OEL STEL) Portugal - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) OEL TWA 50 ppm (indicative limit value (Pentyl acetate, all isomers) OEL STEL 540 mg/m³ (indicative limit value) OEL STEL 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Stovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] NPHV (OEL TWA) [2] Stovenia - Occupational Exposure Limits OEL TWA 270 mg/m³ Stovenia - Occupational Exposure Limits OEL TWA 270 mg/m³	Poland - Occupational Exposure Limits		
Portugal - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) OEL TWA 50 ppm (indicative limit value) OEL STEL 540 mg/m³ (indicative limit value) OEL STEL 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ OEL STEL 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] NPHV (OEL TWA) [2] NPHV (OEL TWA) [3] Slovenia - Occupational Exposure Limits OEL TWA 270 mg/m³ Slovenia - Occupational Exposure Limits	NDS (OEL TWA)	250 mg/m³	
OEL TWA 270 mg/m³ (indicative limit value) OEL TWA 50 ppm (indicative limit value (Pentyl acetate, all isomers) OEL STEL 540 mg/m³ (indicative limit value) OEL STEL 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] 50 ppm NPHV (OEL TWA) [2] 50 ppm NPHV (OEL C) 540 mg/m³ Slovenia - Occupational Exposure Limits OEL TWA 270 mg/m³	NDSCh (OEL STEL)	500 mg/m³	
OEL TWA 50 ppm (indicative limit value (Pentyl acetate, all isomers) OEL STEL 540 mg/m³ (indicative limit value) OEL STEL 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ OEL STEL 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] 50 ppm NPHV (OEL C) 540 mg/m³ Slovenia - Occupational Exposure Limits OEL TWA 270 mg/m³	Portugal - Occupational Exposure Limits		
OEL STEL 540 mg/m³ (indicative limit value) OEL STEL 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] 50 ppm NPHV (OEL TWA) [2] 50 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [2] 50 ppm NPHV (OEL TWA) [2] 50 ppm Slovenia - Occupational Exposure Limits OEL TWA 270 mg/m³	OEL TWA	270 mg/m³ (indicative limit value)	
OEL STEL 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] 50 ppm NPHV (OEL C) 540 mg/m³ Slovenia - Occupational Exposure Limits OEL TWA 270 mg/m³	OEL TWA	50 ppm (indicative limit value (Pentyl acetate, all isomers)	
Romania - Occupational Exposure Limits 270 mg/m³	OEL STEL	540 mg/m³ (indicative limit value)	
OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] 50 ppm NPHV (OEL C) 540 mg/m³ Slovenia - Occupational Exposure Limits OEL TWA 270 mg/m³	OEL STEL	100 ppm (indicative limit value)	
OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] 50 ppm NPHV (OEL C) 540 mg/m³ Slovenia - Occupational Exposure Limits OEL TWA 270 mg/m³	Romania - Occupational Exposure Limits		
OEL STEL 540 mg/m³ OEL STEL 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] 50 ppm NPHV (OEL C) 540 mg/m³ Slovenia - Occupational Exposure Limits OEL TWA 270 mg/m³	OEL TWA	270 mg/m³	
OEL STEL 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] 50 ppm NPHV (OEL C) 540 mg/m³ Slovenia - Occupational Exposure Limits 270 mg/m³	OEL TWA	50 ppm	
Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] 50 ppm NPHV (OEL C) 540 mg/m³ Slovenia - Occupational Exposure Limits OEL TWA 270 mg/m³	OEL STEL	540 mg/m³	
NPHV (OEL TWA) [1] 270 mg/m³ NPHV (OEL TWA) [2] 50 ppm NPHV (OEL C) 540 mg/m³ Slovenia - Occupational Exposure Limits OEL TWA 270 mg/m³	OEL STEL	100 ppm	
NPHV (OEL TWA) [2] 50 ppm NPHV (OEL C) 540 mg/m³ Slovenia - Occupational Exposure Limits OEL TWA 270 mg/m³	Slovakia - Occupational Exposure Limits		
NPHV (OEL C) 540 mg/m³ Slovenia - Occupational Exposure Limits OEL TWA 270 mg/m³	NPHV (OEL TWA) [1]	270 mg/m³	
Slovenia - Occupational Exposure Limits OEL TWA 270 mg/m³	NPHV (OEL TWA) [2]	50 ppm	
OEL TWA 270 mg/m³	NPHV (OEL C)	540 mg/m³	
	Slovenia - Occupational Exposure Limits		
OEL TWA 50 ppm	OEL TWA	270 mg/m³	
	OEL TWA	50 ppm	





OEL STEL 540 mg/m² OEL STEL 100 ppm Spain - Occupational Exposure Limits VLA-ED (OEL TWA) [1] VLA-ED (OEL TWA) [2] 50 ppm (indicative limit value) VLA-ED (OEL STEL) 540 mg/m² VLA-EC (OEL STEL) [ppm] 100 ppm Sweden - Occupational Exposure Limits NGV (OEL TWA) [ppm] NGV (OEL TWA) [ppm] 50 ppm (Pentyl acetates) KTV (OEL STEL) [ppm] 50 ppm (Pentyl acetates) KTV (OEL STEL) [ppm] 100 ppm (Pentyl acetates) Norway - Occupational Exposure Limits Cereseverdi (OEL TWA) [1] Cereseverdi (OEL TWA) [2] 50 ppm Kontridsverdi (OEL STEL) [ppm] 226 mg/m² Cereseverdi (OEL TWA) [2] 50 ppm Kontridsverdi (OEL STEL) [ppm] 50 ppm (Pentyl acetate, all isomers) USA - ACGIH - Occupational Exposure Limits ACGIH OEL STEL [ppm] USA - ACGIH - Occupational Exposure Limits OEL TWA [ppm] Belgium - Occupational Exposure Limits 62 mg/m² OEL TWA [1] 61 mg/m² OEL TWA [2] 10 ppm OEL TWA [2] 10 ppm OEL STEL [2] 10 ppm <th colspan="3">isopentyl acetate (123-92-2)</th>	isopentyl acetate (123-92-2)		
Spain - Occupational Exposure Limits	OEL STEL	540 mg/m³	
VLA-ED (OEL TWA) [1] 270 mg/m² (indicative limit value)	OEL STEL	100 ppm	
VIA.=E0 (OEL TWA) [2] 50 ppm (indicative limit value) VIA.=E0 (OEL STEL) (ppm) 100 ppm Sweden - Occupational Exposure Limits NGV (OEL TWA) (ppm) 50 ppm (Pentyl acetates) NGV (OEL TWA) (ppm) 50 ppm (Pentyl acetates) KTV (OEL STEL) 540 mg/m² (Pentyl acetates) Kortidsverdi (OEL TWA) [2] 59 ppm (Pentyl acetate, all isomers) Kortidsverdi (OEL STEL) 540 ppm (Pentyl acetate, all isomers) KOGIH OEL STEL 150 mg/m² (Pentyl acetate, all isomers) KOGIH OEL STEL 540 mg/m² (Pentyl acetate, all isomers) KOGIH OEL STEL 540 mg/m² (Pentyl acetate, all isomers) KOGIH OEL STEL 540 mg/m² (Pentyl acetate, all isomers) KOGIH OEL STEL 540 mg/m² (Pentyl acetate, all isomers) KOGIH OEL STEL 540 mg/m² (Pentyl acetate, all isomers) KOGIH OEL STEL 540 mg/m² (Pentyl acetate, all isomers) KOGIH OEL STEL 540 mg/m² (Pentyl acetate, all isomers) KOGIH OEL STEL 540 mg/m² (Pentyl acetate, all isomers) KOGIH OEL STEL 540 mg/m² (Pentyl acetate, all isomers) KOGIH OEL STEL 540 mg/m² (Pentyl acetate, all isomers) KOGIH OEL STEL 540 mg/m² (Pentyl acetate, all isomers) KOGIH OEL STEL 540 mg/m² (Pentyl acetate, all isomers) KOGIH OEL STEL 540 mg/m² (Pentyl acetate, all isomers) KOGIH OEL STEL 540 mg/m² (Pentyl acetate, all isomers) KOGIH OEL STEL 540 mg/m² (Pentyl acetate, all isomers) K			
VLA-EC (OEL STEL) ppm 100 ppm	VLA-ED (OEL TWA) [1]	270 mg/m³ (indicative limit value)	
VLA-EC (OEL STEL) ppm 100 ppm	VLA-ED (OEL TWA) [2]	50 ppm (indicative limit value)	
Swedon - Occupational Exposure Limits NGV (OEL TWA) 270 mg/m³ (Pentyl acetates) NGV (OEL TWA) 50 ppm 50 ppm (Pentyl acetates) KTV (OEL STEL) 540 mg/m³ (Pentyl acetates) KTV (OEL STEL) 540 mg/m³ (Pentyl acetates) KTV (OEL STEL) 100 ppm (Pentyl acetates) KTV (OEL STEL) 100 ppm (Pentyl acetates) KTV (OEL STEL) 260 mg/m³ Grenseverdi (OEL TWA) [1] 260 mg/m³ Grenseverdi (OEL TWA) [2] 50 ppm Kortidosverdi (OEL STEL) 325 mg/m³ (value calculated) Kortidosverdi (OEL STEL) 325 mg/m³ (value calculated) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA [5pm] 50 ppm (Pentyl acetate, all isomers) ACGIH OEL STEL [5pm] 100 ppm (Pentyl acetate, all isomers) Benzyl acetate (140-11-4) Belgium - Occupational Exposure Limits OEL TWA 10 ppm Denmark - Occupational Exposure Limits OEL TWA 10 ppm Denmark - Occupational Exposure Limits OEL TWA 10 ppm OEL STEL 122 mg/m³ OEL STEL 20 ppm Ireland - Occupational Exposure Limits OEL TWA 5 mg/m³ OEL STEL 30 ppm (calculated) Latvia - Occupational Exposure Limits OEL TWA 5 mg/m³ Lithuania - Occupational Exposure Limits OEL TWA 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	VLA-EC (OEL STEL)	540 mg/m³	
NGV (OEL TWA) 270 mg/m² (Pentyl acetates)	VLA-EC (OEL STEL) [ppm]	100 ppm	
NGV (OEL TWA) [ppm] 50 ppm (Pentyl acetates)	Sweden - Occupational Exposure Limits		
KTV (OEL STEL) 540 mg/m³ (Pentyl acetates) KTV (OEL STEL) [ppm] 100 ppm (Pentyl acetates) Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) [1] 260 mg/m³ Grenseverdi (OEL TWA) [2] 50 ppm Kortidsverdi (OEL STEL) 325 mg/m³ (value calculated) Kortidsverdi (OEL STEL) [ppm] 75 ppm (value calculated) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA [ppm] 50 ppm (Pentyl acetate, all isomers) ACGIH OEL STEL [ppm] 100 ppm (Pentyl acetate, all isomers) Benzyl acetate (140-11-4) Belgium - Occupational Exposure Limits OEL TWA 05 ppm Denmark - Occupational Exposure Limits OEL TWA [1] 61 mg/m³ OEL TWA [2] 10 ppm OEL STEL 122 mg/m² OEL STEL 20 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 10 ppm OEL STEL 30 ppm CEL TWA [2] 10 ppm OEL STEL 30 ppm (calculated) Latvia - Occupational Exposure Limits OEL TWA [5 mg/m² Lithuania - Occupational Exposure Limits OEL TWA 5 mg/m² Lithuania - Occupational Exposure Limits OPL TWA 5 mg/m² Lithuania - Occupational Exposure Limits OPL TWA 5 mg/m² Lithuania - Occupational Exposure Limits OPL TWA 5 mg/m² Lithuania - Occupational Exposure Limits OPL TWA 5 mg/m² Lithuania - Occupational Exposure Limits OPL TWA 5 mg/m² Lithuania - Occupational Exposure Limits OPL TWA 5 mg/m² Lithuania - Occupational Exposure Limits OPL TWA 5 mg/m² Lithuania - Occupational Exposure Limits OPL TWA 5 mg/m² Lithuania - Occupational Exposure Limits OPL TWA 10 ppm	NGV (OEL TWA)	270 mg/m³ (Pentyl acetates)	
Norway - Occupational Exposure Limits	NGV (OEL TWA) [ppm]	50 ppm (Pentyl acetates)	
Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) [1] 260 mg/m³ Grenseverdi (OEL TWA) [2] 50 ppm Korttidsverdi (OEL STEL) 325 mg/m³ (value calculated) Korttidsverdi (OEL STEL) [ppm] 75 ppm (value calculated) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA [ppm] 50 ppm (Pentyl acetate, all isomers) ACGIH OEL STEL [ppm] 100 ppm (Pentyl acetate, all isomers) Benzyl acetate (140-11-4) Belgium - Occupational Exposure Limits OEL TWA 62 mg/m³ OEL TWA 10 ppm Denmark - Occupational Exposure Limits OEL TWA [1] 61 mg/m³ OEL TWA [2] 10 ppm OEL STEL 122 mg/m³ OEL STEL 20 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 10 ppm OEL STEL 30 ppm Letand - Occupational Exposure Limits OEL TWA [2] 5 mg/m³ OEL TWA [2] 10 ppm OEL STEL 5 mg/m³ OEL STEL 5 mg/m³ OEL TWA [2] 5 mg/m³ OEL TWA [3] 5 mg/m³ Lithuania - Occupational Exposure Limits OEL TWA 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 5 mg/m³ Portugal - Occupational Exposure Limits	KTV (OEL STEL)	540 mg/m³ (Pentyl acetates)	
Grenseverdi (OEL TWA) [1] 260 mg/m³ Grenseverdi (OEL STEL) 50 ppm Kortiidsverdi (OEL STEL) 325 mg/m³ (value calculated) Kortiidsverdi (OEL STEL) [ppm] 75 ppm (value calculated) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA [ppm] 50 ppm (Pentyl acetate, all isomers) ACGIH OEL STEL [ppm] 100 ppm (Pentyl acetate, all isomers) Benzyl acetate (140-11-4) Belgium - Occupational Exposure Limits OEL TWA 62 mg/m³ OEL TWA 10 ppm Denmark - Occupational Exposure Limits OEL TWA [1] 61 mg/m³ OEL TWA [2] 10 ppm OEL STEL 122 mg/m³ OEL STEL 20 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 10 ppm OEL STEL 30 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 5 mg/m³ OEL TWA [3] 5 mg/m³ Littuania - Occupational Exposure Limits OEL TWA [4] 5 mg/m³ Littuania - Occupational Exposure Limits OEL TWA 5 mg/m³ Littuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	KTV (OEL STEL) [ppm]	100 ppm (Pentyl acetates)	
Grenseverdi (OEL TWA) [2] 50 ppm Korttidsverdi (OEL STEL) 325 mg/m³ (value calculated) Korttidsverdi (OEL STEL) [ppm] 75 ppm (value calculated) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA [ppm] 50 ppm (Pentyl acetate, all isomers) ACGIH OEL STEL [ppm] 100 ppm (Pentyl acetate, all isomers) Benzyl acetate (140-11-4) Belgium - Occupational Exposure Limits OEL TWA 62 mg/m³ OEL TWA 10 ppm Denmark - Occupational Exposure Limits OEL TWA [1] 61 mg/m³ OEL TWA [2] 10 ppm OEL STEL 122 mg/m³ OEL STEL 20 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 10 ppm OEL STEL 30 ppm (calculated) Latvia - Occupational Exposure Limits OEL TWA 5 mg/m³ Littuania - Occupational Exposure Limits PRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA	Norway - Occupational Exposure Limits		
Korttidsverdi (OEL STEL) 325 mg/m³ (value calculated) Korttidsverdi (OEL STEL) [ppm] 75 ppm (value calculated) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA [ppm] 50 ppm (Pentyl acetate, all isomers) ACGIH OEL STEL [ppm] 100 ppm (Pentyl acetate, all isomers) Benzyl acetate (140-11-4) Belgium - Occupational Exposure Limits OEL TWA 62 mg/m³ OEL TWA 10 ppm Denmark - Occupational Exposure Limits OEL TWA [1] 61 mg/m³ OEL TWA [2] 10 ppm OEL STEL 122 mg/m² OEL STEL 20 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 10 ppm OEL STEL 30 ppm CEL TWA [2] 10 ppm OEL STEL 5 mg/m³ OEL TWA [2] 5 mg/m³ Lithuania - Occupational Exposure Limits OEL TWA 5 mg/m³ Lithuania - Occupational Exposure Limits OFL TWA 5 mg/m³ Portugal - Occupational Exposure Limits OFL TWA 5 mg/m³ Portugal - Occupational Exposure Limits OFL TWA 10 ppm	Grenseverdi (OEL TWA) [1]	260 mg/m³	
Kortidsverdi (OEL STEL) [ppm] 75 ppm (value calculated) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA [ppm] 50 ppm (Pentyl acetate, all isomers) ACGIH OEL STEL [ppm] 100 ppm (Pentyl acetate, all isomers) Benzyl acetate (140-11-4) Belgium - Occupational Exposure Limits OEL TWA 62 mg/m² OEL TWA 10 ppm Denmark - Occupational Exposure Limits OEL TWA [1] 61 mg/m² OEL TWA [2] 10 ppm OEL STEL 122 mg/m² OEL STEL 20 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 10 ppm OEL STEL 30 ppm (calculated) Latvia - Occupational Exposure Limits OEL TWA [3] 5 mg/m³ Lithuania - Occupational Exposure Limits OEL TWA 5 mg/m³ Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA [3] 5 mg/m³ Portugal - Occupational Exposure Limits	Grenseverdi (OEL TWA) [2]	50 ppm	
USA - ACGIH OCCUpational Exposure Limits ACGIH OEL TWA [ppm] 50 ppm (Pentyl acetate, all isomers) ACGIH OEL STEL [ppm] 100 ppm (Pentyl acetate, all isomers) Benzyl acetate (140-11-4) Belgium - Occupational Exposure Limits OEL TWA 62 mg/m³ OEL TWA 10 ppm Denmark - Occupational Exposure Limits OEL TWA [1] 61 mg/m³ OEL TWA [2] 10 ppm OEL STEL 122 mg/m³ OEL STEL 20 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 10 ppm OEL STEL 30 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 5 mg/m³ OEL TWA [3] 5 mg/m³ Lithuania - Occupational Exposure Limits OEL TWA 5 mg/m³ Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	Korttidsverdi (OEL STEL)	325 mg/m³ (value calculated)	
ACGIH OEL TWA [ppm] 50 ppm (Pentyl acetate, all isomers) Benzyl acetate (140-11-4) Belgium - Occupational Exposure Limits OEL TWA 62 mg/m³ OEL TWA 10 ppm Denmark - Occupational Exposure Limits OEL TWA [1] 61 mg/m³ OEL TWA [2] 10 ppm OEL STEL 122 mg/m³ OEL STEL 20 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 10 ppm OEL STEL 30 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 5 mg/m³ OEL STEL 5 mg/m³ OEL STEL 5 mg/m³ OEL STEL 5 mg/m³ OEL TWA [2] 5 mg/m³ Ireland - Occupational Exposure Limits OEL TWA [2] 5 mg/m³ DEL STEL 5 mg/m³ OEL STEL 5 mg/m³ DEL STEL 5 mg/m³ OEL STEL 5 mg/m³ DEL TWA 5 mg/m³ Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	Korttidsverdi (OEL STEL) [ppm]	75 ppm (value calculated)	
Benzyl acetate (140-11-4) Belgium - Occupational Exposure Limits OEL TWA 62 mg/m³ OEL TWA 10 ppm Denmark - Occupational Exposure Limits OEL TWA [1] 61 mg/m³ OEL TWA [2] 10 ppm OEL STEL 122 mg/m³ OEL STEL 20 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 10 ppm OEL STEL 5 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 5 mg/m³ OEL STEL 5 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 5 mg/m³ OEL STEL 5 ppm Ireland - Occupational Exposure Limits OEL TWA 5 mg/m³ Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	USA - ACGIH - Occupational Exposure Limits		
Benzyl acetate (140-11-4) Belgium - Occupational Exposure Limits OEL TWA 62 mg/m³ OEL TWA 10 ppm Denmark - Occupational Exposure Limits OEL TWA [1] 61 mg/m³ OEL TWA [2] 10 ppm OEL STEL 122 mg/m³ OEL STEL 20 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 10 ppm OEL STEL 30 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 5 mg/m³ OEL STEL 5 mg/m³ Lithuania - Occupational Exposure Limits OEL TWA 5 mg/m³ Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	ACGIH OEL TWA [ppm]	50 ppm (Pentyl acetate, all isomers)	
Belgium - Occupational Exposure Limits OEL TWA 62 mg/m³ OEL TWA 10 ppm Denmark - Occupational Exposure Limits OEL TWA [1] 61 mg/m³ OEL TWA [2] 10 ppm OEL STEL 122 mg/m³ OEL STEL 20 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 10 ppm OEL STEL 30 ppm Lireland - Occupational Exposure Limits OEL TWA [2] 5 mg/m³ Lithuania - Occupational Exposure Limits OEL TWA 5 mg/m³ Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	ACGIH OEL STEL [ppm]	100 ppm (Pentyl acetate, all isomers)	
OEL TWA 62 mg/m³ OEL TWA 10 ppm Denmark - Occupational Exposure Limits 61 mg/m³ OEL TWA [1] 61 mg/m³ OEL TWA [2] 10 ppm OEL STEL 122 mg/m³ OEL STEL 20 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 10 ppm OEL STEL 30 ppm (calculated) Latvia - Occupational Exposure Limits OEL TWA 5 mg/m³ Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	Benzyl acetate (140-11-4)		
DEL TWA 10 ppm Denmark - Occupational Exposure Limits OEL TWA [1] 61 mg/m³ OEL TWA [2] 10 ppm OEL STEL 122 mg/m³ OEL STEL 20 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 10 ppm OEL STEL 30 ppm DEL STEL 30 ppm CEL TWA [2] 5 mg/m³ DEL STEL 5 mg/m³ Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	Belgium - Occupational Exposure Limits		
Denmark - Occupational Exposure Limits OEL TWA [1] 61 mg/m³ OEL TWA [2] 10 ppm OEL STEL 122 mg/m³ OEL STEL 20 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 10 ppm OEL STEL 30 ppm DEL STEL 30 ppm CEL STEL 30 ppm OEL STEL 50 ppm Latvia - Occupational Exposure Limits OEL TWA 5 mg/m³ Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	OEL TWA	62 mg/m³	
OEL TWA [1] 61 mg/m³ OEL TWA [2] 10 ppm OEL STEL 122 mg/m³ OEL STEL 20 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 10 ppm OEL STEL 30 ppm (calculated) Latvia - Occupational Exposure Limits OEL TWA 5 mg/m³ Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	OEL TWA	10 ppm	
OEL TWA [2] 10 ppm OEL STEL 122 mg/m³ OEL STEL 20 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 10 ppm OEL STEL 30 ppm (calculated) Latvia - Occupational Exposure Limits OEL TWA 5 mg/m³ Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	Denmark - Occupational Exposure Limits		
OEL STEL 122 mg/m³ OEL STEL 20 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 10 ppm OEL STEL 30 ppm (calculated) Latvia - Occupational Exposure Limits OEL TWA 5 mg/m³ Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	OEL TWA [1]	61 mg/m³	
OEL STEL 10 ppm Ireland - Occupational Exposure Limits OEL TWA [2] 10 ppm OEL STEL 30 ppm (calculated) Latvia - Occupational Exposure Limits OEL TWA 5 mg/m³ Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	OEL TWA [2]	10 ppm	
Ireland - Occupational Exposure Limits 10 ppm	OEL STEL	122 mg/m³	
OEL TWA [2] 10 ppm OEL STEL 30 ppm (calculated) Latvia - Occupational Exposure Limits OEL TWA 5 mg/m³ Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	OEL STEL	20 ppm	
OEL STEL 30 ppm (calculated) Latvia - Occupational Exposure Limits OEL TWA 5 mg/m³ Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	Ireland - Occupational Exposure Limits		
Latvia - Occupational Exposure Limits OEL TWA 5 mg/m³ Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	OEL TWA [2]	10 ppm	
OEL TWA 5 mg/m³ Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	OEL STEL	30 ppm (calculated)	
Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	Latvia - Occupational Exposure Limits		
IPRV (OEL TWA) 5 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 10 ppm	OEL TWA	5 mg/m³	
Portugal - Occupational Exposure Limits OEL TWA 10 ppm	Lithuania - Occupational Exposure Limits		
OEL TWA 10 ppm	IPRV (OEL TWA)	5 mg/m³	
· ··	Portugal - Occupational Exposure Limits		
OEL chemical category A4 - Not Classifiable as a Human Carcinogen	OEL TWA	10 ppm	
	OEL chemical category	A4 - Not Classifiable as a Human Carcinogen	

Safety Data Sheet





Benzyl acetate (140-11-4)		
Romania - Occupational Exposure Limits		
OEL TWA	50 mg/m³	
OEL TWA	8 ppm	
OEL STEL	80 mg/m³	
OEL STEL	13 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	62 mg/m³	
VLA-ED (OEL TWA) [2]	10 ppm	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	10 ppm	
ACGIH chemical category	Not Classifiable as a Human Carcinogen	
citral (5392-40-5)		
Belgium - Occupational Exposure Limits		
OEL TWA	32 mg/m³ (vapor and aerosol)	
OEL TWA	5 ppm (vapor and aerosol)	
OEL chemical category	Skin	
Ireland - Occupational Exposure Limits		
OEL TWA [2]	5 ppm	
OEL STEL	15 ppm (calculated)	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	27 mg/m³	
NDSCh (OEL STEL)	54 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	5 ppm (inhalable fraction; vapor)	
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [2]	5 ppm (inhalable fraction and vapor)	
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	5 ppm (inhalable fraction and vapor)	
ACGIH chemical category	Not Classifiable as a Human Carcinogen, Skin - potential significant contribution to overall exposure by the cutaneous route, dermal sensitizer	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):





8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : Standard. light yellow. amber. Conforms to standard.

Odor characteristic. : Not available Odor threshold Melting point : Not applicable Freezing point : Not available Not available Boiling point Flammability Non flammable. Lower explosion limit Not available Upper explosion limit Not available > 93 °C Flash point Auto-ignition temperature Not available Decomposition temperature Not available рΗ Not available Viscosity, kinematic : Not available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878





Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available : Not available Vapor pressure Not available Vapor pressure at 50°C Density Not available Relative density Not available Relative vapor density at 20°C : Not available Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

Benzyl salicylate (118-58-1)	
LD50 oral rat	2227 mg/kg (Source: NLM_CIP)
LD50 oral	2200 mg/kg body weight
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)
Benzyl acetate (140-11-4)	
LD50 oral rat	2490 mg/kg (Source: JAPAN_GHS)
LD50 oral	2490 mg/kg body weight
LD50 dermal rabbit	> 5000 mg/kg (Source: JAPAN_GHS)

Safety Data Sheet





citral (5392-40-5)	
LD50 oral rat	4960 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	2250 mg/kg (Source: NLM_CIP)
Lavandin abrialis oil (8022-15-9)	
LD50 oral rat	> 5 g/kg (Source: NLM_CIP)
Linalyl acetate (115-95-7)	
LD50 oral rat	14550 mg/kg (Source: EPA_HPV)
LD50 dermal rabbit	> 5000 mg/kg (Source: EPA_HPV)
Linalool (78-70-6)	
LD50 oral	2790 mg/kg body weight
benzyl benzoate (120-51-4)	
LD50 oral rat	500 mg/kg (Source: NLM_CIP)
LD50 oral	1160 mg/kg body weight
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)
Skin corrosion/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Benzyl acetate (140-11-4)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified
Additional information	: Based on available data, the classification criteria are not met
benzyl benzoate (120-51-4)	
Viscosity, kinematic	7.456 mm²/s
	I

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

: Not classified

Hazardous to the aquatic environment, short-term

(acute)

Hazardous to the aquatic environment, long-term

: Harmful to aquatic life with long lasting effects.

(chronic)

Benzyl salicylate (118-58-1)	
LC50 - Fish [1]	1.03 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
citral (5392-40-5)	
EC50 - Crustacea [1]	7 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	16 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [1]	19 mg/l (Species: Desmodesmus subspicatus)
Linalyl acetate (115-95-7)	
LC50 - Fish [1]	11 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [flow-through] Source: ECHA)
Linalool (78-70-6)	
EC50 96h - Algae [1]	88.3 mg/l (Species: Desmodesmus subspicatus)
benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
NOEC (chronic)	0.168 mg/l

12.2. Persistence and degradability

LAVENDER GELATO CC-16354 10% in DPG	
Persistence and degradability	Not established.
benzyl benzoate (120-51-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

LAVENDER GELATO CC-16354 10% in DPG		
Bioaccumulative potential	Not established.	
Benzyl salicylate (118-58-1)		
Partition coefficient n-octanol/water (Log Pow)	4	
isopentyl acetate (123-92-2)		
Partition coefficient n-octanol/water (Log Pow)	2.7 (at 35 °C)	
Benzyl acetate (140-11-4)		
Partition coefficient n-octanol/water (Log Pow)	1.96 (at 25 °C (at pH 7)	
citral (5392-40-5)		
Partition coefficient n-octanol/water (Log Pow)	2.76 (at 25 °C)	
Linalyl acetate (115-95-7)		
Partition coefficient n-octanol/water (Log Pow)	3.9 (at 25 °C)	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



benzyl benzoate (120-51-4)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods Product/Packaging disposal recommendations Ecology - waste materials HP code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Dispose in a safe manner in accordance with local/national regulations.
- : Avoid release to the environment.
- : HP3 "Flammable:"
- flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
- flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
 flammable solid waste: solid waste which is readily combustible or may cause or
- contribute to fire through friction;
- flammable gaseous waste: gaseous waste which is flammable in air at 20 $^{\circ}\text{C}$ and a standard pressure of 101.3 kPa;
- water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
- other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shippin	14.2. UN proper shipping name			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



ADR	IMDG	IATA	ADN	RID
14.5. Environmental hazards				
Not applicable Not applicable Not applicable Not applicable Not applicable				
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)			
Reference code	Applicable on	Entry title or description	
3(a)	isopentyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	
3(b)	LAVENDER GELATO CC-16354 10% in DPG; Benzyl salicylate; citral; Iso E Super; Lavandin abrialis oil; Linalyl acetate; Linalool; benzyl benzoate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	
3(c)	LAVENDER GELATO CC-16354 10% in DPG; Benzyl salicylate; Benzyl acetate; Iso E Super; Lavandin abrialis oil; benzyl benzoate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	
40.	isopentyl acetate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



REACH Annex XIV (Authorisation List)

Contains no REACH Annex XIV substances.

REACH Candidate List (SVHC)

Contains no REACH candidate substance

PIC Regulation (Prior Informed Consent)

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Ozone Regulation (1005/2009)

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

Explosives Precursors Regulation (2019/1148)

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Drug Precursors Regulation (273/2004)

Contains no substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

15.1.2. National regulations

Germany

Joint storage table

Water hazard class (WGK) : WGK 2, significant hazardous to water (Classification according to AwSV, Annex 1).

Storage class (LGK, TRGS 510) : LGK 12 - Non-combustible liquids.

:	LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
	LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
	LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
	LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
	LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for : LGK 1, LGK 6.2, LGK 7.

Joint storage with restrictions permitted for : LGK 4.1A, LGK 4.3, LGK 5.1C.

Joint storage permitted for : LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A,

LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK

10-13.

Hazardous Incident Ordinance (12. BlmSchV) : Is not subject of the Hazardous Incident Ordinance (12. BlmSchV)

Netherlands

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic

environment

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – : None of the components are listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Switzerland

Storage class (LK) : LK 10/12 - Liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and

amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-phrases:		
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard Category 3	
Asp. Tox. 1	Aspiration hazard Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 3	Flammable liquids Category 3	
H226	Flammable liquid and vapor.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Skin Irrit. 2	Skin corrosion/irritation Category 2	
Skin Sens. 1	Skin sensitization, Category 1	
Skin Sens. 1B	Skin sensitization, Category 1B	

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.