Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : LAVENDER GELATO CC-16354 25% in DPG

Product code : CC-16354_25%

Type of product : Perfumes, Fragrances

Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use,Industrial use

Industrial/Professional use spec : Industrial

For professional use only : Perfumes, Fragrances

Use of the substance/mixture : Perfumes, Frag Function or use category : Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Candle Craft Weiherwiese 10 65510 Idstein - Germany T 49-6126-9363 -0

info@candlecraft.de - www.candlecraft.de

1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731;

Brazil: +0-800-591-6042; India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitization, Category 1 H317 Hazardous to the aquatic environment – Chronic Hazard H411

Category 2

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS07

GHS09

Signal word (CLP) : Warning

Contains : Benzyl salicylate; Heliotropine; Citral; Iso E Super; Eucalyptus oil; Patchouli oil; Lavandin


abrialis oil; Linalyl acetate; Linalool

Hazard statements (CLP) : H317 - May cause an allergic skin reaction.

H411 - Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

ANDLECRAFT

protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P321 - Specific treatment (see supplemental first aid instruction on this label).

Extra phrases : Restricted to professional users.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371- 33	5.425 – 10.85	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Iso E Super	CAS-No.: 54464-57-2 EC-No.: 259-174-3 REACH-no: 01-2119489989- 04	1.25 – 2.5	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 1, H410
Ethylene brassylate	CAS-No.: 105-95-3 EC-No.: 203-347-8 REACH-no: 01-2119976314- 33	1.175 – 2.3375	Aquatic Chronic 2, H411
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016-	0.625 – 1.25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Benzyl salicylate	CAS-No.: 118-58-1 EC-No.: 204-262-9 EC Index-No.: 607-754-00-5 REACH-no: 01-2119969442- 31	0.25 – 0.5	Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Benzyl acetate substance with national workplace exposure limit(s) (BE, DK, ES, IE, LT, LV, PT, RO)	CAS-No.: 140-11-4 EC-No.: 205-399-7 REACH-no: 01-2119638272- 42	0.25 – 0.5	Aquatic Chronic 3, H412

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Lavandin abrialis oil	CAS-No.: 8022-15-9 EC-No.: 617-009-6	0.125 – 0.25	Eye Irrit. 2, H319 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Linalyl acetate	CAS-No.: 115-95-7 EC-No.: 204-116-4 REACH-no: 01-2119454789- 19	0.125 – 0.25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Heliotropine	CAS-No.: 120-57-0 EC-No.: 204-409-7 REACH-no: 01-2119983608- 21	0.075 – 0.1625	Skin Sens. 1B, H317
Eucalyptus oil	CAS-No.: 8000-48-4 EC-No.: 283-406-2 REACH-no: 01-2119978250- 37	0.075 – 0.125	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Patchouli oil	CAS-No.: 8014-09-3 EC Index-No.: 616-944-7	0.075 – 0.125	Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
isopentyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, DE, DK, EE, ES, FI, FR, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, TR); substance with a Community workplace exposure limit	CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2 REACH-no: 01-2119548408- 32	0.05 – 0.1125	Flam. Liq. 3, H226
citral substance with national workplace exposure limit(s) (BE, ES, IE, PL, PT)	CAS-No.: 5392-40-5 EC-No.: 226-394-6 EC Index-No.: 605-019-00-3 REACH-no: 01-2119462829- 23	0.05 – 0.1125	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Allow affected person to

breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact

: Remove affected clothing and wash all exposed skin area with mild soap and water,

followed by warm water rinse. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes.

Avoid breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew

with proper protection. For further information refer to section 8: "Exposure

controls/personal protection".

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or

diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash

contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep

container closed when not in use. Store in a well-ventilated place. Keep cool.

Incompatible products : Strong bases. Strong acids. Incompatible materials

: Sources of ignition. Direct sunlight.

Storage temperature 25 °C

Storage area Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container. Packaging materials : Do not store in corrodable metal.

7.3. Specific end use(s)


No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters


8.1.1 National occupational exposure and biological limit values

isopentyl acetate (123-92-2)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	270 mg/m³	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	540 mg/m³	
IOEL STEL [ppm]	100 ppm	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	270 mg/m³ (Pentyl acetate (all isomers))	
MAK (OEL TWA) [ppm]	50 ppm (Pentyl acetate (all isomers))	
MAK (OEL STEL)	540 mg/m³ (Pentylacetate)	
MAK (OEL STEL) [ppm]	100 ppm (Pentylacetate)	
Belgium - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Bulgaria - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA) [1]	270 mg/m³	
GVI (OEL TWA) [2]	50 ppm	
KGVI (OEL STEL)	540 mg/m³	
KGVI (OEL STEL) [ppm]	100 ppm	






	isopentyl acetate (123-92-2)		
Cyprus - Occupational Exposure Limits			
OEL TWA	270 mg/m³		
OEL TWA	50 ppm		
OEL STEL	540 mg/m³		
OEL STEL	100 ppm		
Denmark - Occupational Exposure Limits			
OEL TWA [1]	271 mg/m³ (Amyl acetate, all isomers)		
OEL TWA [2]	50 ppm (Amyl acetate, all isomers)		
OEL STEL	540 mg/m³		
OEL STEL	100 ppm		
Estonia - Occupational Exposure Limits			
OEL TWA	270 mg/m³		
OEL TWA	50 ppm		
OEL STEL	540 mg/m³		
OEL STEL	100 ppm		
Finland - Occupational Exposure Limits			
HTP (OEL TWA) [1]	270 mg/m³ (Pentyl acetate)		
HTP (OEL TWA) [2]	50 ppm (Pentyl acetate)		
HTP (OEL STEL)	540 mg/m³		
HTP (OEL STEL) [ppm]	100 ppm		
France - Occupational Exposure Limits			
VME (OEL TWA)	270 mg/m³ (restrictive limit)		
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)		
VLE (OEL C/STEL)	540 mg/m³ (restrictive limit)		
VLE (OEL C/STEL) [ppm]	100 ppm (restrictive limit)		
Germany - Occupational Exposure Limits (TRGS 90	00)		
AGW (OEL TWA) [1]	270 mg/m³		
AGW (OEL TWA) [2]	50 ppm		
Gibraltar - Occupational Exposure Limits			
OEL TWA	270 mg/m³		
OEL TWA	50 ppm		
OEL STEL	540 mg/m³		
OEL STEL	100 ppm		
Greece - Occupational Exposure Limits			
OEL TWA	530 mg/m³		
OEL TWA	100 ppm		
OEL STEL	800 mg/m³		
OEL STEL	150 ppm		






Hungary - Occupational Exposure Limits	isopentyl acetate (123-92-2)		
CK (OEL STEL) S40 mg/m²	Hungary - Occupational Exposure Limits		
Ireland - Occupational Exposure Limits	AK (OEL TWA)	270 mg/m³	
OEL TWA [1] 260 mg/m² OEL TWA [2] 50 ppm OEL STEL 520 mg/m² OEL STEL 100 ppm Italy - Occupational Exposure Limits OEL TWA OEL TWA 270 mg/m² OEL STEL 540 mg/m² OEL STEL 540 mg/m² OEL STEL 540 mg/m² OEL TWA 270 mg/m² OEL TWA 50 ppm Lithuania - Occupational Exposure Limits 100 ppm Lithuania - Occupational Exposure Limits 270 mg/m² PPRV (OEL TWA) [5pm] 50 ppm TPRV (OEL STEL) [5pm] 100 ppm Luxembourg - Occupational Exposure Limits 270 mg/m² OEL TWA 270 mg/m² OEL STEL 540 mg/m² OEL STEL 100 ppm Malta - Occupational Exposure Limits 270 mg/m² OEL TWA 50 ppm OEL STEL 540 mg/m²	CK (OEL STEL)	540 mg/m³	
OEL TWA [2] 50 ppm OEL STEL 520 mg/m³ OEL STEL 100 ppm Italy - Occupational Exposure Limits CEL TWA OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Latvia - Occupational Exposure Limits 270 mg/m³ OEL TWA 270 mg/m³ OEL TWA 50 ppm Lithuania - Occupational Exposure Limits IPRV (OEL TWA) [5pm] IPRV (OEL TWA) [5pm] 50 ppm TPRV (OEL STEL) [5pm] 100 ppm Luxembourg - Occupational Exposure Limits CEL TWA OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ OEL TWA 270 mg/m³ OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL TWA 50 ppm OEL TWA 50 ppm OEL TWA 50 ppm OEL STEL 540 mg/m³	Ireland - Occupational Exposure Limits		
OEL STEL 520 mg/m² OEL STEL 100 ppm Italy - Occupational Exposure Limits 270 mg/m² OEL TWA 50 ppm OEL STEL 540 mg/m² OEL STEL 100 ppm Latvia - Occupational Exposure Limits 270 mg/m² OEL TWA 50 ppm Ulthuania - Occupational Exposure Limits 1PRV (OEL TWA) IPRV (OEL TWA) [ppm] 50 ppm TPRV (OEL STEL) [ppm] 100 ppm Luxembourg - Occupational Exposure Limits 270 mg/m² OEL TWA 50 ppm OEL TWA 50 ppm OEL STEL 540 mg/m² OEL STEL 540 mg/m² OEL STEL 100 ppm Mata - Occupational Exposure Limits 270 mg/m² OEL STEL 540 mg/m² <td< td=""><td>OEL TWA [1]</td><td>260 mg/m³</td></td<>	OEL TWA [1]	260 mg/m³	
OEL STEL 100 ppm Italy - Occupational Exposure Limits 270 mg/m² OEL TWA 50 ppm OEL STEL 540 mg/m² OEL STEL 100 ppm Latvia - Occupational Exposure Limits EVENTAR OEL TWA 50 ppm Lithuania - Occupational Exposure Limits EVENTAR IPRV (OEL TWA) [ppm] 50 ppm IPRV (OEL TWA) [ppm] 50 ppm TPRV (OEL STEL) [ppm] 100 ppm Luxembourg - Occupational Exposure Limits OEL TWA OEL TWA 50 ppm OEL STEL 540 mg/m² OEL STEL 50 ppm OEL STEL 50 ppm OEL TWA 50 ppm OEL TWA 50 ppm OEL STEL 100 ppm Noterlands - Occupational Exposure Limits 50 mg/m² OEL STEL 500 mg/m² NDS (OEL STEL) [ppm]	OEL TWA [2]	50 ppm	
Italy - Occupational Exposure Limits	OEL STEL	520 mg/m³	
OEL TWA 270 mg/m³ OEL STEL 540 mg/m³ OEL STEL 100 ppm Latvia - Occupational Exposure Limits 270 mg/m³ OEL TWA 270 mg/m³ OEL TWA 270 mg/m³ UPRY (OEL TWA) 270 mg/m³ IPRY (OEL TWA) [ppm] 50 ppm TPRY (OEL STEL) 540 mg/m³ TPRY (OEL STEL) [ppm] 100 ppm Luxembourg - Occupational Exposure Limits 0EL TWA OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Mata - Occupational Exposure Limits 0EL TWA OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ OEL STEL 550 mg/m³ NEtherlands - Occupational Exposure Limits 100 ppm Netherlands - Occupational Exposure Limits 100 ppm NDS (OEL STEL) [ppm] 98.1 ppm </td <td>OEL STEL</td> <td>100 ppm</td>	OEL STEL	100 ppm	
OEL TWA 50 ppm OEL STEL \$40 mg/m³ OEL STEL 100 ppm Latvia - Occupational Exposure Limits 270 mg/m³ OEL TWA 270 mg/m³ OEL TWA 50 ppm Lithuania - Occupational Exposure Limits IPRV (OEL TWA) IPRV (OEL TWA) [ppm] 50 ppm TPRV (OEL STEL) \$40 mg/m³ TPRV (OEL STEL) [ppm] 100 ppm Luxembourg - Occupational Exposure Limits OEL TWA OEL TWA 50 ppm OEL STEL \$40 mg/m³ OEL STEL \$40 mg/m³ OEL STEL \$40 mg/m³ OEL TWA 270 mg/m³ OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL TWA 50 ppm OEL STEL \$40 mg/m³ OEL STEL \$50 ppm OEL STEL \$50 mg/m³ OEL STEL \$50 mg/m³ OEL STEL \$50 mg/m³ NB Tymin (OEL STEL) [ppm] \$8.1 pm Poland - Occupational Exposure Limits NDS Ch (OEL STEL) \$5	Italy - Occupational Exposure Limits		
OEL STEL 540 mg/m³ OEL STEL 100 ppm Latvia - Occupational Exposure Limits 270 mg/m³ OEL TWA 270 mg/m³ OEL TWA 50 ppm Lithuania - Occupational Exposure Limits 1PRV (OEL TWA) [ppm] IPRV (OEL TWA) [ppm] 50 ppm TPRV (OEL STEL) 540 mg/m³ TPRV (OEL STEL) [ppm] 100 ppm Luxembourg - Occupational Exposure Limits 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Malta - Occupational Exposure Limits 270 mg/m³ OEL TWA 270 mg/m³ OEL STEL 540 mg/m³ OEL STEL 530 mg/m³ TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDS (OEL STEL) 500 mg/m³	OEL TWA	270 mg/m³	
DEL STEL	OEL TWA	50 ppm	
Latvia - Occupational Exposure Limits OEL TWA 270 mg/m³ OEL TWA 50 ppm Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 270 mg/m³ IPRV (OEL TWA) 50 ppm TPRV (OEL STEL) 540 mg/m³ TPRV (OEL STEL) 540 mg/m³ TPRV (OEL STEL) 540 mg/m³ OEL TWA 270 mg/m³ OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ OEL STEL 100 ppm Malta - Occupational Exposure Limits OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Malta - Occupational Exposure Limits OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Malta - Occupational Exposure Limits TGG-15min (OEL STEL) 530 mg/m³ OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ OEL STEL 550 mg/m³	OEL STEL	540 mg/m³	
OEL TWA 270 mg/m³ OEL TWA 50 ppm Lithuania - Occupational Exposure Limits 1PRV (OEL TWA) IPRV (OEL TWA) [ppm] 50 ppm TPRV (OEL STEL) 540 mg/m³ TPRV (OEL STEL) [ppm] 100 ppm Luxembourg - Occupational Exposure Limits OEL TWA OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Malta - Occupational Exposure Limits OEL TWA OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ OEL STEL 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDS (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits 500 mg/m³	OEL STEL	100 ppm	
DEL TWA	Latvia - Occupational Exposure Limits		
Lithuania - Occupational Exposure Limits IPRV (OEL TWA)	OEL TWA	270 mg/m³	
IPRV (OEL TWA)	OEL TWA	50 ppm	
PRV (OEL TWA) [ppm]	Lithuania - Occupational Exposure Limits		
TPRV (OEL STEL) 540 mg/m³ TPRV (OEL STEL) [ppm] 100 ppm Luxembourg - Occupational Exposure Limits 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Malta - Occupational Exposure Limits 270 mg/m³ OEL TWA 270 mg/m³ OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ OEL STEL 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) TGG-15min (OEL STEL) 530 mg/m³ TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits	IPRV (OEL TWA)	270 mg/m³	
TPRV (OEL STEL) [ppm] 100 ppm	IPRV (OEL TWA) [ppm]	50 ppm	
Luxembourg - Occupational Exposure Limits OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Malta - Occupational Exposure Limits 270 mg/m³ OEL TWA 270 mg/m³ OEL STEL 540 mg/m³ OEL STEL 100 ppm Netherlands - Occupational Exposure Limits 100 ppm Netherlands - Occupational Exposure Limits 530 mg/m³ TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits 500 mg/m³	TPRV (OEL STEL)	540 mg/m³	
OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Malta - Occupational Exposure Limits OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Netherlands - Occupational Exposure Limits 530 mg/m³ TGG-15min (OEL STEL) 530 mg/m³ Poland - Occupational Exposure Limits NDS (OEL TWA) NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits	TPRV (OEL STEL) [ppm]	100 ppm	
OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Malta - Occupational Exposure Limits OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits	Luxembourg - Occupational Exposure Limits		
OEL STEL 540 mg/m³ OEL STEL 100 ppm Malta - Occupational Exposure Limits 270 mg/m³ OEL TWA 270 mg/m³ OEL STEL 540 mg/m³ OEL STEL 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits	OEL TWA	270 mg/m³	
OEL STEL 100 ppm Malta - Occupational Exposure Limits 270 mg/m³ OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) 530 mg/m³ TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits	OEL TWA	50 ppm	
Malta - Occupational Exposure Limits OEL TWA 270 mg/m³ OEL STEL 540 mg/m³ OEL STEL 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) 530 mg/m³ TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits	OEL STEL	540 mg/m³	
OEL TWA 270 mg/m³ OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) 530 mg/m³ TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits	OEL STEL	100 ppm	
OEL TWA 50 ppm OEL STEL 540 mg/m³ OEL STEL 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) 530 mg/m³ TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits	Malta - Occupational Exposure Limits		
OEL STEL OEL STEL 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) TGG-15min (OEL STEL) [ppm] Poland - Occupational Exposure Limits NDS (OEL TWA) NDSCh (OEL STEL) Portugal - Occupational Exposure Limits	OEL TWA	270 mg/m³	
OEL STEL 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) 530 mg/m³ TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits	OEL TWA	50 ppm	
Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) 530 mg/m³ TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits	OEL STEL	540 mg/m³	
TGG-15min (OEL STEL) 530 mg/m³ TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits	OEL STEL	100 ppm	
TGG-15min (OEL STEL) [ppm] 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits	Netherlands - Occupational Exposure Limits		
Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits	TGG-15min (OEL STEL)	530 mg/m³	
NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits	TGG-15min (OEL STEL) [ppm]	98.1 ppm	
NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits	Poland - Occupational Exposure Limits		
Portugal - Occupational Exposure Limits	NDS (OEL TWA)	250 mg/m³	
	NDSCh (OEL STEL)	500 mg/m³	
OEL TWA 270 mg/m³ (indicative limit value)	Portugal - Occupational Exposure Limits		
	OEL TWA	270 mg/m³ (indicative limit value)	





isopentyl acetate (123-92-2)		
OEL TWA	50 ppm (indicative limit value (Pentyl acetate, all isomers)	
OEL STEL	540 mg/m³ (indicative limit value)	
OEL STEL	100 ppm (indicative limit value)	
Romania - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA) [1]	270 mg/m³	
NPHV (OEL TWA) [2]	50 ppm	
NPHV (OEL C)	540 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	270 mg/m³ (indicative limit value)	
VLA-ED (OEL TWA) [2]	50 ppm (indicative limit value)	
VLA-EC (OEL STEL)	540 mg/m³	
VLA-EC (OEL STEL) [ppm]	100 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	270 mg/m³ (Pentyl acetates)	
NGV (OEL TWA) [ppm]	50 ppm (Pentyl acetates)	
KTV (OEL STEL)	540 mg/m³ (Pentyl acetates)	
KTV (OEL STEL) [ppm]	100 ppm (Pentyl acetates)	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	260 mg/m³	
Grenseverdi (OEL TWA) [2]	50 ppm	
Korttidsverdi (OEL STEL)	325 mg/m³ (value calculated)	
Korttidsverdi (OEL STEL) [ppm]	75 ppm (value calculated)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	50 ppm (Pentyl acetate, all isomers)	
ACGIH OEL STEL [ppm]	100 ppm (Pentyl acetate, all isomers)	
Benzyl acetate (140-11-4)		
Belgium - Occupational Exposure Limits		
OEL TWA	62 mg/m³	
OEL TWA	10 ppm	





Benzyl acetate (140-11-4)		
Denmark - Occupational Exposure Limits		
OEL TWA [1]	61 mg/m³	
OEL TWA [2]	10 ppm	
OEL STEL	122 mg/m³	
OEL STEL	20 ppm	
Ireland - Occupational Exposure Limits		
OEL TWA [2]	10 ppm	
OEL STEL	30 ppm (calculated)	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	10 ppm	
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen	
Romania - Occupational Exposure Limits		
OEL TWA	50 mg/m³	
OEL TWA	8 ppm	
OEL STEL	80 mg/m³	
OEL STEL	13 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	62 mg/m³	
VLA-ED (OEL TWA) [2]	10 ppm	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	10 ppm	
ACGIH chemical category	Not Classifiable as a Human Carcinogen	
citral (5392-40-5)	citral (5392-40-5)	
Belgium - Occupational Exposure Limits		
OEL TWA	32 mg/m³ (vapor and aerosol)	
OEL TWA	5 ppm (vapor and aerosol)	
OEL chemical category	Skin	
Ireland - Occupational Exposure Limits		
OEL TWA [2]	5 ppm	
OEL STEL	15 ppm (calculated)	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	27 mg/m³	
NDSCh (OEL STEL)	54 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	5 ppm (inhalable fraction; vapor)	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



citral (5392-40-5)		
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [2]	5 ppm (inhalable fraction and vapor)	
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	5 ppm (inhalable fraction and vapor)	
ACGIH chemical category	Not Classifiable as a Human Carcinogen, Skin - potential significant contribution to overall exposure by the cutaneous route, dermal sensitizer	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):





8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : Standard. light yellow. amber. Conforms to standard.

: Not applicable

Odor : characteristic. Odor threshold : Not available : Not applicable Melting point Freezing point : Not available Boiling point : Not available Flammability : Non flammable. Lower explosion limit : Not available Upper explosion limit : Not available Flash point : > 93 °C Auto-ignition temperature : Not available Decomposition temperature : Not available рΗ Not available Viscosity, kinematic Not available Solubility Not available Partition coefficient n-octanol/water (Log Kow) : Not available Vapor pressure Not available Vapor pressure at 50°C : Not available Density : Not available Relative density : Not available Relative vapor density at 20°C : Not available

9.2. Other information

Particle characteristics

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.


SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (inhalation) : Not classified		
Ethylene brassylate (105-95-3)		
LD50 oral rat	> 5000 mg/kg (Source: ECHA)	
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA)	
Benzyl salicylate (118-58-1)		
LD50 oral rat	2227 mg/kg (Source: NLM_CIP)	
LD50 oral	2200 mg/kg body weight	
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)	
Heliotropine (120-57-0)		
LD50 oral rat	2700 mg/kg (Source: NLM_CIP)	
LD50 oral	2700 mg/kg body weight	
LD50 dermal rat	> 5000 mg/kg (Source: ECHA_API)	
Benzyl acetate (140-11-4)		
LD50 oral rat	2490 mg/kg (Source: JAPAN_GHS)	
LD50 oral	2490 mg/kg body weight	
LD50 dermal rabbit	> 5000 mg/kg (Source: JAPAN_GHS)	
citral (5392-40-5)		
LD50 oral rat	4960 mg/kg (Source: NLM_CIP)	
LD50 dermal rabbit	2250 mg/kg (Source: NLM_CIP)	
Eucalyptus oil (8000-48-4)		
LD50 oral rat	2480 mg/kg (Source: NLM_CIP)	
Patchouli oil (8014-09-3)		
LD50 oral rat	> 5 g/kg (Source: NLM_CIP)	
Lavandin abrialis oil (8022-15-9)		
LD50 oral rat	> 5 g/kg (Source: NLM_CIP)	
Linalyl acetate (115-95-7)		
LD50 oral rat	14550 mg/kg (Source: EPA_HPV)	
LD50 dermal rabbit	> 5000 mg/kg (Source: EPA_HPV)	
Linalool (78-70-6)		
LD50 oral	2790 mg/kg body weight	
benzyl benzoate (120-51-4)		
LD50 oral rat	500 mg/kg (Source: NLM_CIP)	

Safety Data Sheet





benzyl benzoate (120-51-4)	
LD50 oral	1160 mg/kg body weight
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)
Skin corrosion/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Benzyl acetate (140-11-4)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Heliotropine (120-57-0)	
Viscosity, kinematic	Not applicable
benzyl benzoate (120-51-4)	
Viscosity, kinematic	7.456 mm²/s

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Not classified


acute

Hazardous to the aquatic environment, long-term : Toxic to aquatic life with long lasting effects.

(chronic)

	(Gill Gill Gill)	
	Benzyl salicylate (118-58-1)	
LC50 - Fish [1] 1.03 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)		1.03 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
Heliotropine (120-57-0) LC50 - Fish [1] 2.5 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static] Source: ECHA)		
		2.5 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static] Source: ECHA)

Safety Data Sheet





citral (5392-40-5)	5392-40-5)	
EC50 - Crustacea [1]	7 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 72h - Algae [1]	16 mg/l (Species: Desmodesmus subspicatus)	
EC50 96h - Algae [1]	19 mg/l (Species: Desmodesmus subspicatus)	
Linalyl acetate (115-95-7)		
LC50 - Fish [1]	11 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [flow-through] Source: ECHA)	
Linalool (78-70-6)		
EC50 96h - Algae [1]	88.3 mg/l (Species: Desmodesmus subspicatus)	
benzyl benzoate (120-51-4)		
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)	
NOEC (chronic)	0.168 mg/l	

12.2. Persistence and degradability

LAVENDER GELATO CC-16354 25% in DPG		
Persistence and degradability Not established.		
Eucalyptus oil (8000-48-4)		
Persistence and degradability Not established.		
benzyl benzoate (120-51-4)		
Persistence and degradability	May cause long-term adverse effects in the environment.	

12.3. Bioaccumulative potential

LAVENDER GELATO CC-16354 25% in DPG			
Bioaccumulative potential	Not established.		
Ethylene brassylate (105-95-3)			
Partition coefficient n-octanol/water (Log Pow)	4.3 (at 25 °C (at pH 6.4-7)		
Benzyl salicylate (118-58-1)			
Partition coefficient n-octanol/water (Log Pow)	4		
Heliotropine (120-57-0)			
Partition coefficient n-octanol/water (Log Pow)	1.2 (at 35 °C)		
isopentyl acetate (123-92-2)			
Partition coefficient n-octanol/water (Log Pow)	2.7 (at 35 °C)		
Benzyl acetate (140-11-4)			
Partition coefficient n-octanol/water (Log Pow)	1.96 (at 25 °C (at pH 7)		
citral (5392-40-5)			
Partition coefficient n-octanol/water (Log Pow)	2.76 (at 25 °C)		
Eucalyptus oil (8000-48-4)			
Bioaccumulative potential	Not established.		

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



Linalyl acetate (115-95-7)		
Partition coefficient n-octanol/water (Log Pow) 3.9 (at 25 °C)		
benzyl benzoate (120-51-4)		
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)	
Bioaccumulative potential	Not established.	

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods Product/Packaging disposal recommendations Ecology - waste materials HP code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Dispose in a safe manner in accordance with local/national regulations.
- : Avoid release to the environment.
- : HP3 "Flammable:"
 - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
 - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
 - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
 - flammable gaseous waste: gaseous waste which is flammable in air at 20 $^{\circ}\text{C}$ and a standard pressure of 101.3 kPa;
 - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
 - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	14.1. UN number or ID number			
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shippin	14.2. UN proper shipping name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER)	Environmentally hazardous substance, liquid, n.o.s. (ISO E SUPER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



ADR	IMDG	IATA	ADN	RID
Transport document descr	Transport document description			
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (ISO E SUPER), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER), 9,	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER), 9,
14.3. Transport hazard	class(es)			
9	9	9	9	9
**************************************	**************************************	**************************************	**************************************	**************************************
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : M6

Special provision (ADR) : 274, 335, 375, 601

Limited quantities (ADR) : 5I Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions : TP1, TP29

(ADR)

Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading : CV13

and handling (ADR)

Hazard identification number (Kemler No.) : 90

Orange plates :

90 3082

Tunnel restriction code (ADR)

EAC : •3Z

Transport by sea

Special provision (IMDG) : 274, 335, 969

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : LP01, P001

Packing provisions (IMDG) : PP1

IBC packing instructions (IMDG) : IBC03

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-F
Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L

Special provision (IATA) : A97, A158, A197, A215

ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M6

Special provision (ADN) : 274, 335, 375, 601

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Carriage permitted (ADN) : T

Equipment required (ADN) : PP

Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : M6

Special provision (RID) : 274, 335, 375, 601

Limited quantities (RID) : 5L Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions : TP1, TP29

(RID)

Tank codes for RID tanks (RID) : LGBV

Transport category (RID) : 3

Special provisions for carriage – Packages (RID) : W12

Special provisions for carriage - Loading, unloading : CW13, CW31

and handling (RID)

Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	isopentyl acetate ; Eucalyptus oil	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	LAVENDER GELATO CC-16354 25% in DPG; Benzyl salicylate; citral; Iso E Super; Eucalyptus oil; Patchouli oil; Lavandin abrialis oil; Linalyl acetate; Linalool; benzyl benzoate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	LAVENDER GELATO CC-16354 25% in DPG; Ethylene brassylate; Benzyl salicylate; Benzyl acetate; Iso E Super; Eucalyptus oil; Patchouli oil; Lavandin abrialis oil; benzyl benzoate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	isopentyl acetate ; Eucalyptus oil	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

REACH Annex XIV (Authorisation List)

Contains no REACH Annex XIV substances.

REACH Candidate List (SVHC)

Contains no REACH candidate substance

PIC Regulation (Prior Informed Consent)

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Ozone Regulation (1005/2009)

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

Explosives Precursors Regulation (2019/1148)

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Drug Precursors Regulation (273/2004)

Contains no substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



15.1.2. National regulations

Germany

Water hazard class (WGK) : WGK 2, significant hazardous to water (Classification according to AwSV, Annex 1).

Storage class (LGK, TRGS 510) : LGK 12 - Non-combustible liquids.

Joint storage table : LGK 2A LGK 2B

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for

Joint storage with restrictions permitted for

Joint storage permitted for

: LGK 1, LGK 6.2, LGK 7. : LGK 4.1A, LGK 4.3, LGK 5.1C.

: LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK

10-13.

Hazardous Incident Ordinance (12. BlmSchV)

ImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic

environment

SZW-lijst van kankerverwekkende stoffen

SZW-lijst van mutagene stoffen

SZW-lijst van reprotoxische stoffen - Borstvoeding

SZW-lijst van reprotoxische stoffen -

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling

: Eucalyptus oil is listed

: Eucalyptus oil is listed

: None of the components are listed: None of the components are listed

: None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Switzerland

Storage class (LK) : LK 10/12 - Liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and

amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-phrases:		
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard Category 3	
Asp. Tox. 1	Aspiration hazard Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 3	Flammable liquids Category 3	

Safety Data Sheet





Full text of H- and EUH-phrases:		
H226	Flammable liquid and vapor.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Skin Irrit. 2	Skin corrosion/irritation Category 2	
Skin Sens. 1	Skin sensitization, Category 1	
Skin Sens. 1B	Skin sensitization, Category 1B	

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.