Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Issue date: 27.11.2023 Version: 1.0



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

: LAVENDER GELATO CC-16354 Trade name UFI : 9E1M-WCT0-5009-XHU8

Product code : CC-16354

Type of product : Perfumes, fragrances Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use.Industrial use

Industrial/Professional use spec : Industrial

> For professional use only : Perfumes, fragrances

Function or use category : Odour agents

1.2.2. Uses advised against

Use of the substance/mixture

No additional information available

1.3. Details of the supplier of the safety data sheet

Candle Craft Weiherwiese 10 65510 Idstein - Germany T 49-6126-9363 -0

info@candlecraft.de - www.candlecraft.de

1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731;

Brazil: +0-800-591-6042; India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H302 Skin corrosion/irritation, Category 2 H315 Serious eye damage/eye irritation, Category 2 H319 Skin sensitisation, Category 1 H317 Hazardous to the aquatic environment - Acute Hazard, H400 Category 1

Hazardous to the aquatic environment - Chronic Hazard,

H411

Category 2

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS07

: Warning

Signal word (CLP)

Contains : Benzyl benzoate; Iso E Super; Linalool; Benzyl salicylate; Ethyl maltol; Heliotropine; 2-

Buten-1-one, 1-(2,6,6-trimethyl-2-cyclohexen-1-yl)-, (E)-; Citral; Allyl ionone; Eucalyptus oil;

Patchouli oil; Lavandin abrialis oil; Linalyl acetate

Hazard statements (CLP) : H302 - Harmful if swallowed.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H410 - Very toxic to aquatic life with long lasting effects. : P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

Extra phrases : For professional users only.

2.3. Other hazards

Precautionary statements (CLP)

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371- 33	21,7 – 43,4	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Iso E Super	CAS-No.: 54464-57-2 EC-No.: 259-174-3 REACH-no: 01-2119489989- 04	5 – 10	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 1, H410
Ethylene brassylate	CAS-No.: 105-95-3 EC-No.: 203-347-8 REACH-no: 01-2119976314- 33	4,7 – 9,35	Aquatic Chronic 2, H411

Safety Data Sheet

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016-	2,5 – 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Vanillin	CAS-No.: 121-33-5 EC-No.: 204-465-2 REACH-no: 01-2119516040- 60	1,5 – 3	Eye Irrit. 2, H319
Benzyl salicylate	CAS-No.: 118-58-1 EC-No.: 204-262-9 EC Index-No.: 607-754-00-5 REACH-no: 01-2119969442- 31	1-2	Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Benzyl acetate substance with national workplace exposure limit(s) (BE, DK, ES, IE, LT, LV, PT, RO)	CAS-No.: 140-11-4 EC-No.: 205-399-7 REACH-no: 01-2119638272- 42	1 – 2	Aquatic Chronic 3, H412
Anisic aldehyde	CAS-No.: 123-11-5 EC-No.: 204-602-6 REACH-no: 01-2119977101- 43	0,7 – 1,4	Aquatic Chronic 3, H412
Ethyl vanillin	CAS-No.: 121-32-4 EC-No.: 204-464-7 REACH-no: 01-211958961-24	0,7 – 1,3	Eye Irrit. 2, H319
Ethyl maltol	CAS-No.: 4940-11-8 EC-No.: 225-582-5	0,5 – 1	Acute Tox. 4 (Oral), H302
gamma-Heptalactone	CAS-No.: 105-21-5 EC-No.: 203-279-9	0,5 – 1	Skin Irrit. 2, H315
Lavandin abrialis oil	CAS-No.: 8022-15-9 EC-No.: 617-009-6	0,5 – 1	Eye Irrit. 2, H319 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Linalyl acetate	CAS-No.: 115-95-7 EC-No.: 204-116-4 REACH-no: 01-2119454789- 19	0,5 – 1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Heliotropine	CAS-No.: 120-57-0 EC-No.: 204-409-7 REACH-no: 01-2119983608- 21	0,3 – 0,65	Skin Sens. 1B, H317
Eucalyptus oil	CAS-No.: 8000-48-4 EC-No.: 283-406-2 REACH-no: 01-2119978250- 37	0,3 – 0,5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Patchouli oil	CAS-No.: 8014-09-3 EC Index-No.: 616-944-7	0,3 – 0,5	Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
isopentyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, DE, DK, EE, ES, FI, FR, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, TR); substance with a Community workplace exposure limit	CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2 REACH-no: 01-2119548408- 32	0,2 – 0,45	Flam. Liq. 3, H226
citral substance with national workplace exposure limit(s) (BE, ES, IE, PL, PT)	CAS-No.: 5392-40-5 EC-No.: 226-394-6 EC Index-No.: 605-019-00-3 REACH-no: 01-2119462829- 23	0,2 – 0,45	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Allyl amyl glycolate	CAS-No.: 67634-00-8 EC-No.: 266-803-5	0,1 – 0,25	Acute Tox. 4 (Oral), H302 Acute Tox. 2 (Inhalation), H330 Aquatic Chronic 1, H410
2-Buten-1-one, 1-(2,6,6-trimethyl-2-cyclohexen-1-yl)-, (E)-	CAS-No.: 24720-09-0 EC-No.: 246-430-4	0,1 – 0,2	Acute Tox. 4 (Oral), H302 Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Allyl ionone	CAS-No.: 79-78-7 EC-No.: 201-225-9	0,1 – 0,2	Aquatic Chronic 2, H411 Skin Sens. 1B, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water,

followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact

: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion

: Do NOT induce vomiting. Obtain emergency medical attention. Rinse mouth. Call a poison

: Do NOT induce vomiting. Obtain emergency medical attention. Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew

with proper protection. For further information refer to section 8: "Exposure

controls/personal protection".

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or

diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always

wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep

container closed when not in use. Store in a well-ventilated place. Keep cool.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

Storage temperature : 25 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container.
Packaging materials : Do not store in corrodable metal.

27.11.2023 (Issue date) EN (English) 5/22

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

o National cooupational exposure and biological			
Benzyl acetate (140-11-4)	Benzyl acetate (140-11-4)		
Belgium - Occupational Exposure Limits			
OEL TWA	62 mg/m³		
OEL TWA	10 ppm		
Denmark - Occupational Exposure Limits			
OEL TWA [1]	61 mg/m³		
OEL TWA [2]	10 ppm		
OEL STEL	122 mg/m³		
OEL STEL	20 ppm		
Ireland - Occupational Exposure Limits			
OEL TWA [2]	10 ppm		
OEL STEL	30 ppm (calculated)		
Latvia - Occupational Exposure Limits			
OEL TWA	5 mg/m³		
Lithuania - Occupational Exposure Limits			
IPRV (OEL TWA)	5 mg/m³		
Portugal - Occupational Exposure Limits			
OEL TWA	10 ppm		
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen		
Romania - Occupational Exposure Limits			
OEL TWA	50 mg/m³		
OEL TWA	8 ppm		
OEL STEL	80 mg/m³		
OEL STEL	13 ppm		
Spain - Occupational Exposure Limits			
VLA-ED (OEL TWA) [1]	62 mg/m³		
VLA-ED (OEL TWA) [2]	10 ppm		
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA [ppm]	10 ppm		
ACGIH chemical category	Not Classifiable as a Human Carcinogen		
isopentyl acetate (123-92-2)			
EU - Indicative Occupational Exposure Limit (IOEL)			
IOEL TWA	270 mg/m³		

Safety Data Sheet

	50 ppm	
OFI STEL		
OEL STEL 54	540 mg/m³	
OEL STEL [ppm] 10	00 ppm	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	270 mg/m³ (Pentyl acetate (all isomers))	
MAK (OEL TWA) [ppm] 50	50 ppm (Pentyl acetate (all isomers))	
MAK (OEL STEL) 54	540 mg/m³ (Pentylacetate)	
MAK (OEL STEL) [ppm] 10	00 ppm (Pentylacetate)	
Belgium - Occupational Exposure Limits		
DEL TWA 2	270 mg/m³	
DEL TWA 50	50 ppm	
DEL STEL 54	540 mg/m³	
DEL STEL 10	00 ppm	
Bulgaria - Occupational Exposure Limits		
DEL TWA 2	270 mg/m³	
DEL TWA 50	50 ppm	
DEL STEL 54	540 mg/m³	
DEL STEL 10	00 ppm	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA) [1] 2	270 mg/m³	
GVI (OEL TWA) [2] 50	50 ppm	
(GVI (OEL STEL) 54	540 mg/m³	
(GVI (OEL STEL) [ppm] 10	00 ppm	
Cyprus - Occupational Exposure Limits		
DEL TWA 2	270 mg/m³	
DEL TWA 50	50 ppm	
DEL STEL 5-	540 mg/m³	
DEL STEL 10	00 ppm	
Denmark - Occupational Exposure Limits		
DEL TWA [1] 2	271 mg/m³ (Amyl acetate, all isomers)	
DEL TWA [2] 50	50 ppm (Amyl acetate, all isomers)	
DEL STEL 54	540 mg/m³	
DEL STEL 10	00 ppm	
Estonia - Occupational Exposure Limits		
DEL TWA 2	270 mg/m³	
DEL TWA 50	50 ppm	
DEL STEL 5-	540 mg/m³	
DEL STEL 10	00 ppm	

Safety Data Sheet

isopentyl acetate (123-92-2)			
Finland - Occupational Exposure Limits	Finland - Occupational Exposure Limits		
HTP (OEL TWA) [1]	270 mg/m³ (Pentyl acetate)		
HTP (OEL TWA) [2]	50 ppm (Pentyl acetate)		
HTP (OEL STEL)	540 mg/m³		
HTP (OEL STEL) [ppm]	100 ppm		
France - Occupational Exposure Limits			
VME (OEL TWA)	270 mg/m³ (restrictive limit)		
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)		
VLE (OEL C/STEL)	540 mg/m³ (restrictive limit)		
VLE (OEL C/STEL) [ppm]	100 ppm (restrictive limit)		
Germany - Occupational Exposure Limits (TRGS 90	0)		
AGW (OEL TWA) [1]	270 mg/m³		
AGW (OEL TWA) [2]	50 ppm		
Gibraltar - Occupational Exposure Limits			
OEL TWA	270 mg/m³		
OEL TWA	50 ppm		
OEL STEL	540 mg/m³		
OEL STEL	100 ppm		
Greece - Occupational Exposure Limits			
OEL TWA	530 mg/m³		
OEL TWA	100 ppm		
OEL STEL	800 mg/m³		
OEL STEL	150 ppm		
Hungary - Occupational Exposure Limits			
AK (OEL TWA)	270 mg/m³		
CK (OEL STEL)	540 mg/m³		
Ireland - Occupational Exposure Limits			
OEL TWA [1]	260 mg/m³		
OEL TWA [2]	50 ppm		
OEL STEL	520 mg/m³		
OEL STEL	100 ppm		
Italy - Occupational Exposure Limits			
OEL TWA	270 mg/m³		
OEL TWA	50 ppm		
OEL STEL	540 mg/m³		
OEL STEL	100 ppm		
Latvia - Occupational Exposure Limits			
OEL TWA	270 mg/m³		
OEL TWA	50 ppm		

Safety Data Sheet

isopentyl acetate (123-92-2)		
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	270 mg/m³	
IPRV (OEL TWA) [ppm]	50 ppm	
TPRV (OEL STEL)	540 mg/m³	
TPRV (OEL STEL) [ppm]	100 ppm	
Luxembourg - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Malta - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Netherlands - Occupational Exposure Limits		
TGG-15min (OEL STEL)	530 mg/m³	
TGG-15min (OEL STEL) [ppm]	98,1 ppm	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	250 mg/m³	
NDSCh (OEL STEL)	500 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	270 mg/m³ (indicative limit value)	
OEL TWA	50 ppm (indicative limit value (Pentyl acetate, all isomers)	
OEL STEL	540 mg/m³ (indicative limit value)	
OEL STEL	100 ppm (indicative limit value)	
Romania - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA) [1]	270 mg/m³	
NPHV (OEL TWA) [2]	50 ppm	
NPHV (OEL C)	540 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	

Safety Data Sheet

isopentyl acetate (123-92-2)		
OEL STEL	100 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	270 mg/m³ (indicative limit value)	
VLA-ED (OEL TWA) [2]	50 ppm (indicative limit value)	
VLA-EC (OEL STEL)	540 mg/m³	
VLA-EC (OEL STEL) [ppm]	100 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	270 mg/m³ (Pentyl acetates)	
NGV (OEL TWA) [ppm]	50 ppm (Pentyl acetates)	
KTV (OEL STEL)	540 mg/m³ (Pentyl acetates)	
KTV (OEL STEL) [ppm]	100 ppm (Pentyl acetates)	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	260 mg/m³	
Grenseverdi (OEL TWA) [2]	50 ppm	
Korttidsverdi (OEL STEL)	325 mg/m³ (value calculated)	
Korttidsverdi (OEL STEL) [ppm]	75 ppm (value calculated)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	50 ppm (Pentyl acetate, all isomers)	
ACGIH OEL STEL [ppm]	100 ppm (Pentyl acetate, all isomers)	
citral (5392-40-5)		
Belgium - Occupational Exposure Limits		
OEL TWA	32 mg/m³ (vapor and aerosol)	
OEL TWA	5 ppm (vapor and aerosol)	
OEL chemical category	Skin	
Ireland - Occupational Exposure Limits		
OEL TWA [2]	5 ppm	
OEL STEL	15 ppm (calculated)	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	27 mg/m³	
NDSCh (OEL STEL)	54 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	5 ppm (inhalable fraction; vapor)	
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [2]	5 ppm (inhalable fraction and vapor)	
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	5 ppm (inhalable fraction and vapor)	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

citral	(5392-40-5)
Gillai	JJJZ-40-J

ACGIH chemical category

Not Classifiable as a Human Carcinogen, Skin - potential significant contribution to overall exposure by the cutaneous route, dermal sensitizer

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):





8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Colour : light yellow, amber. Conforms to standard.

: Not available

: Not applicable

Odour : characteristic. Odour threshold : Not available Melting point : Not applicable Freezing point : Not available **Boiling point** : Not available Flammability : Not applicable Lower explosion limit : Not available : Not available Upper explosion limit : > 93 °C Flash point Auto-ignition temperature : Not available Decomposition temperature : Not available рΗ : Not available : Not available Viscosity, kinematic : Not available Solubility Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : Not available Vapour pressure at 50°C : Not available Density : Not available Relative density : Not available

9.2. Other information

Particle characteristics

Relative vapour density at 20°C

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Safety Data Sheet

LAVENDER GELATO CC-16354			
ATE CLP (oral)	1140,647 mg/kg bodyweight		
benzyl benzoate (120-51-4)			
LD50 oral rat	500 mg/kg (Source: NLM_CIP)		
LD50 oral	1160 mg/kg bodyweight		
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)		
Ethylene brassylate (105-95-3)			
LD50 oral rat	> 5000 mg/kg (Source: ECHA)		
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA)		
Vanillin (121-33-5)			
LD50 dermal rabbit	> 5010 mg/kg (Source: OECD_SIDS)		
LD50 dermal	2600 mg/kg bodyweight		
Linalool (78-70-6)			
LD50 oral	2790 mg/kg bodyweight		
Benzyl salicylate (118-58-1)			
LD50 oral rat	2227 mg/kg (Source: NLM_CIP)		
LD50 oral	2200 mg/kg bodyweight		
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)		
Ethyl vanillin (121-32-4)			
LD50 oral rat	1590 mg/kg (Source: NLM_CIP)		
LD50 oral	3000 mg/kg bodyweight		
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)		
Anisic aldehyde (123-11-5)			
LD50 oral rat	> 2000 mg/kg (Source: OECD_SIDS)		
LD50 oral	3210 mg/kg bodyweight		
LD50 dermal rabbit	> 5000 mg/kg (Source: EPA_HPV)		
LC50 Inhalation - Rat	> 0,32 mg/l (Exposure time: 7 h Source: OECD_SIDS)		
Benzyl acetate (140-11-4)			
LD50 oral rat	2490 mg/kg (Source: JAPAN_GHS)		
LD50 oral	2490 mg/kg bodyweight		
LD50 dermal rabbit	> 5000 mg/kg (Source: JAPAN_GHS)		
Ethyl maltol (4940-11-8)			
LD50 oral rat	1150 mg/kg (Source: NLM_CIP)		
LD50 oral	1200 mg/kg bodyweight		
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)		
gamma-Heptalactone (105-21-5)			
LD50 oral rat	> 5 g/kg (Source: NLM_CIP)		

Safety Data Sheet

Heliotropine (120-57-0)		
LD50 oral rat	2700 mg/kg (Source: NLM_CIP)	
LD50 oral	2700 mg/kg bodyweight	
LD50 dermal rat	> 5000 mg/kg (Source: ECHA_API)	
2-Buten-1-one, 1-(2,6,6-trimethyl-2-cyclohexer	n-1-yl)-, (E)- (24720-09-0)	
LD50 oral	1670 mg/kg bodyweight	
LD50 dermal rat	2150 – 2780 mg/kg (Source: ECHA_API)	
LD50 dermal	2900 mg/kg bodyweight	
citral (5392-40-5)		
LD50 oral rat	4960 mg/kg (Source: NLM_CIP)	
LD50 dermal rabbit	2250 mg/kg (Source: NLM_CIP)	
Allyl amyl glycolate (67634-00-8)		
LD50 oral	500 mg/kg bodyweight	
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)	
LC50 Inhalation - Rat	0,43 mg/l/4h	
LC50 Inhalation - Rat (Dust/Mist)	0,5 mg/l/4h	
Eucalyptus oil (8000-48-4)		
LD50 oral rat	2480 mg/kg (Source: NLM_CIP)	
Patchouli oil (8014-09-3)		
LD50 oral rat	> 5 g/kg (Source: NLM_CIP)	
Lavandin abrialis oil (8022-15-9)		
LD50 oral rat	> 5 g/kg (Source: NLM_CIP)	
Linalyl acetate (115-95-7)		
LD50 oral rat	14550 mg/kg (Source: EPA_HPV)	
LD50 dermal rabbit	> 5000 mg/kg (Source: EPA_HPV)	
Skin corrosion/irritation : 0	Causes skin irritation.	
, ,	Causes serious eye irritation.	
	May cause an allergic skin reaction.	
3	Not classified	
Carcinogenicity :	Not classified	
Benzyl acetate (140-11-4)		
IARC group	3 - Not classifiable	
	Not classified	
3 1 1 1 1 1	Not classified	
	Not classified	
'	Not classified	
benzyl benzoate (120-51-4)	7.45020	
Viscosity, kinematic	7,456 mm²/s	
Heliotropine (120-57-0)		
Viscosity, kinematic	Not applicable	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term

(acute)

Hazardous to the aquatic environment, long–term : Toxic to aquatic life with long lasting effects.

: Very toxic to aquatic life.

(chronic)

(chronic)	
benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2,32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
NOEC (chronic)	0,168 mg/l
Vanillin (121-33-5)	
LC50 - Fish [1]	53 – 61,3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
NOEC (acute)	10000 mg/kg (Exposure time: 42 Days - Species: Eisenia foetida [soil dry weight])
Linalool (78-70-6)	
EC50 96h - Algae [1]	88,3 mg/l (Species: Desmodesmus subspicatus)
Benzyl salicylate (118-58-1)	
LC50 - Fish [1]	1,03 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
Ethyl vanillin (121-32-4)	
LC50 - Fish [1]	81,4 – 94,3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
Ethyl maltol (4940-11-8)	
LC50 - Fish [1]	> 85 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: ECHA)
Heliotropine (120-57-0)	
LC50 - Fish [1]	2,5 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static] Source: ECHA)
citral (5392-40-5)	
EC50 - Crustacea [1]	7 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	16 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [1]	19 mg/l (Species: Desmodesmus subspicatus)
Linalyl acetate (115-95-7)	
LC50 - Fish [1]	11 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [flow-through] Source: ECHA)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.2. Persistence and degradability

LAVENDER GELATO CC-16354	
Persistence and degradability	Not established.
benzyl benzoate (120-51-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.
Eucalyptus oil (8000-48-4)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

LAVENDER GELATO CC-16354	
Bioaccumulative potential	Not established.
benzyl benzoate (120-51-4)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)
Bioaccumulative potential	Not established.
Ethylene brassylate (105-95-3)	
Partition coefficient n-octanol/water (Log Pow)	4,3 (at 25 °C (at pH 6.4-7)
Vanillin (121-33-5)	,,, (a. 25 5 (a. p. 1 5 . 1 .)
Partition coefficient n-octanol/water (Log Pow)	1,23 (at 22 °C)
Benzyl salicylate (118-58-1)	1,20 (dt 22 0)
Partition coefficient n-octanol/water (Log Pow)	4
	*
Ethyl vanillin (121-32-4)	4.04 (44.05.90)
Partition coefficient n-octanol/water (Log Pow)	1,61 (at 25 °C)
Anisic aldehyde (123-11-5)	1.50 (1.50 (1.11) 5.0 (1.11)
Partition coefficient n-octanol/water (Log Pow)	1,56 (at 25 °C (at pH >7.9-<8.25)
Benzyl acetate (140-11-4)	
Partition coefficient n-octanol/water (Log Pow)	1,96 (at 25 °C (at pH 7)
Ethyl maltol (4940-11-8)	
Partition coefficient n-octanol/water (Log Pow)	2,9 (at 25 °C)
gamma-Heptalactone (105-21-5)	
Partition coefficient n-octanol/water (Log Pow)	1 (at 20 °C (at pH 6.5)
Heliotropine (120-57-0)	
Partition coefficient n-octanol/water (Log Pow)	1,2 (at 35 °C)
isopentyl acetate (123-92-2)	
Partition coefficient n-octanol/water (Log Pow)	2,7 (at 35 °C)
2-Buten-1-one, 1-(2,6,6-trimethyl-2-cyclohexen-1-yl)-, (E)- (24720-09-0)	
BCF - Fish [1]	(>8.4 - <20)
Partition coefficient n-octanol/water (Log Pow)	3,66 (at 25 °C (at pH 5.82)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

citral (5392-40-5)	
Partition coefficient n-octanol/water (Log Pow)	2,76 (at 25 °C)
Allyl amyl glycolate (67634-00-8)	
Partition coefficient n-octanol/water (Log Pow)	1,96 (at 25 °C (at pH 2.3)
Eucalyptus oil (8000-48-4)	
Bioaccumulative potential	Not established.
Linalyl acetate (115-95-7)	
Partition coefficient n-octanol/water (Log Pow)	3,9 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information

: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods Product/Packaging disposal recommendations Ecology - waste materials

HP Code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Dispose in a safe manner in accordance with local/national regulations.
- : Avoid release to the environment.
- : HP3 "Flammable:"
 - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
 - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
 - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
 - flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
 - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
 - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
 - HP6 "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.
 - HP13 "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs.
 - HP14 "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID number					
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082	
14.2. UN proper shippin	14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Iso E Super)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Iso E Super)	Environmentally hazardous substance, liquid, n.o.s. (Iso E Super)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Iso E Super)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Iso E Super)	
Transport document descr	iption				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Iso E Super), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Iso E Super), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Iso E Super), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Iso E Super), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Iso E Super), 9, III	
14.3. Transport hazard o	class(es)				
9	9	9	9	9	
**************************************	**************************************	**************************************	**************************************	**************************************	
14.4. Packing group					
III	III	III	III	III	
14.5. Environmental hazards					
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	
No supplementary information	n available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : M6

Special provisions (ADR) : 274, 335, 375, 601

Limited quantities (ADR) : 5I Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4

Portable tank and bulk container special provisions : TP1, TP29

(ADR)

Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading : CV13

and handling (ADR)

Hazard identification number (Kemler No.) : 90

Orange plates :



Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Tunnel restriction code (ADR) EAC code : •3Z

Transport by sea

: 274, 335, 969 Special provisions (IMDG)

Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1 : LP01, P001 Packing instructions (IMDG) : PP1 Special packing provisions (IMDG) IBC packing instructions (IMDG) : IBC03 Tank instructions (IMDG) : T4 : TP1. TP29 Tank special provisions (IMDG) EmS-No. (Fire) : F-A : S-F EmS-No. (Spillage)

Air transport

Stowage category (IMDG)

PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) : Y964 PCA limited quantity max net quantity (IATA) : 30kgG PCA packing instructions (IATA) : 964 : 450L PCA max net quantity (IATA) CAO packing instructions (IATA) : 964 : 450L CAO max net quantity (IATA)

: A97, A158, A197, A215 Special provisions (IATA)

: A

ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M6

Special provisions (ADN) : 274, 335, 375, 601

Limited quantities (ADN) : 5 L Excepted quantities (ADN) : E1 Carriage permitted (ADN) : T Equipment required (ADN) : PP Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : M6

Special provisions (RID) : 274, 335, 375, 601

Limited quantities (RID) : 5L Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1 Mixed packing provisions (RID) : MP19 Portable tank and bulk container instructions (RID) : T4 Portable tank and bulk container special provisions : TP1, TP29

(RID)

Tank codes for RID tanks (RID) : LGBV Transport category (RID) : 3 Special provisions for carriage – Packages (RID) : W12 : CW13, CW31

Special provisions for carriage - Loading, unloading

and handling (RID)

Colis express (express parcels) (RID) : CE8 : 90 Hazard identification number (RID)

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description	
3(a)	isopentyl acetate ; Eucalyptus oil	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	
3(b)	LAVENDER GELATO CC-16354; benzyl benzoate; Iso E Super; Linalool; Benzyl salicylate; gamma-Heptalactone; 2-Buten-1-one, 1-(2,6,6- trimethyl-2-cyclohexen-1- yl)-, (E)-; citral; Allyl amyl glycolate; Allyl ionone; Eucalyptus oil; Patchouli oil; Lavandin abrialis oil; Linalyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	
3(c)	LAVENDER GELATO CC-16354; benzyl benzoate; Iso E Super; Ethylene brassylate; Benzyl salicylate; Anisic aldehyde; Benzyl acetate ; 2-Buten-1-one, 1-(2,6,6- trimethyl-2-cyclohexen-1- yl)-, (E)-; Allyl amyl glycolate; Allyl ionone; Eucalyptus oil; Patchouli oil; Lavandin abrialis oil	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	
40.	isopentyl acetate ; Eucalyptus oil	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Storage class (LGK, TRGS 510) : LGK 12 - Non-combustible liquids.

Joint storage table LGK 3 LGK 4.1A .GK 1 LGK 2A LGK 2B LGK 4.3 LGK 4.1B LGK 5.1B LGK 4.2 LGK 5.1A LGK 6.1C LGK 5.1C LGK 5.2 LGK 6.1A LGK 6.1B LGK 6.1D LGK 6.2 LGK 7 LGK 8A LGK 8B LGK 10 LGK 11 LGK 12 **LGK 13** LGK 10-13

Joint storage not permitted for : LGK 1, LGK 6.2, LGK 7.

Joint storage with restrictions permitted for : LGK 4.1A, LGK 4.3, LGK 5.1C.

Joint storage permitted for : LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A,

LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 3.1A, LGK 3.1B, LGK 5.2, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK

10-13.

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(1) - highly toxic for aquatic organisms, may have longterm hazardous effects in aquatic

environment

SZW-lijst van kankerverwekkende stoffen : Allyl amyl glycolate,Eucalyptus oil are listed SZW-lijst van mutagene stoffen : Allyl amyl glycolate,Eucalyptus oil are listed

SZW-ijst van mutagene stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – : None of the components are listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Switzerland

Storage class (LK) : LK 10/12 - Liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.