Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 3/23/2021 Revision date: 2/5/2025 Supersedes version of: 9/23/2024 Version: 5.0



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : BAKERY SHOP CC-16400 UFI : RCYN-6CK2-X00Q-PTK9

Product code : CC-16400

Type of product : Perfumes, fragrances
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use,Industrial use Industrial/Professional use spec : For professional use only

Industrial

Use of the substance/mixture : Perfumes, fragrances Function or use category : Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Candle Craft
Weiherwiese 10
65510 Idstein - Germany
T 49-6126-9363 -0

info@candlecraft.de - www.candlecraft.de

1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731;

Brazil: +0-800-591-6042; India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Reproductive toxicity, Category 2 H361
Hazardous to the aquatic environment – Chronic Hazard, H411

Category 2

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Suspected of damaging fertility or the unborn child. Causes skin irritation. Causes serious eye irritation. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

GHS07 GHS08 GHS09

Signal word (CLP) : Warning

Hazard statements (CLP) : H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.

H361 - Suspected of damaging fertility or the unborn child. H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

Extra phrases : For professional users only.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1-Butanol, 3-methoxy-3-methyl-	CAS-No.: 56539-66-3 EC-No.: 260-252-4 REACH-no: 01-2119976333- 33	10.8 – 21.6	Eye Irrit. 2, H319
Ethyl vanillin	CAS-No.: 121-32-4 EC-No.: 204-464-7 REACH-no: 01-211958961-24	3.303228 – 6.505649	Eye Irrit. 2, H319
Citrus medica limonum (Lemon) peel oil	CAS-No.: 8008-56-8 EC-No.: 284-515-8	2 – 4	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Orange Oil	CAS-No.: 8028-48-6 EC-No.: 232-433-8	2 – 4	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Lime oil distilled	CAS-No.: 8008-26-2 EC-No.: 290-010-3 REACH-no: 01-2120138646- 51	1.5 – 3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Repr. 2, H361 Asp. Tox. 1, H304 Aquatic Chronic 1, H410

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016- 42	1.5 – 3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Ethyl maltol	CAS-No.: 4940-11-8 EC-No.: 225-582-5	1 – 2	Acute Tox. 4 (Oral), H302
Anisic aldehyde	CAS-No.: 123-11-5 EC-No.: 204-602-6 REACH-no: 01-2119977101- 43	0.556 – 1.098	Aquatic Chronic 3, H412
Litsea cubeba oil	CAS-No.: 68855-99-2 EC-No.: 290-018-7	0.4 – 0.75	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
citral substance with national workplace exposure limit(s) (BE, ES, IE, PL, PT)	CAS-No.: 5392-40-5 EC-No.: 226-394-6 EC Index-No.: 605-019-00-3 REACH-no: 01-2119462829- 23	0.3 – 0.5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	0.000508 – 0.000889	Not classified
Toluene substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3	≤ 0.0000105	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

First-aid measures after inhalation

First-aid measures after skin contact

First-aid measures after eye contact

- Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible).
- : Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
- : Wash with plenty of water/.... Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label). If skin irritation or rash occurs: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
- : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. If eye irritation persists: Get medical advice/attention.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after ingestion

: Immediately call a POISON CENTER/doctor. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects

: Suspected of damaging fertility or the unborn child. Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after inhalation

: May cause an allergic skin reaction.

Symptoms/effects after skin contact Symptoms/effects after eye contact : Causes skin irritation. Irritation. May cause an allergic skin reaction.

: Causes serious eye irritation. Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions

: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting

: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures

: Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure

controls/personal protection".

Emergency procedures

: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment

Methods for cleaning up

: Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Notify authorities if product enters sewers or public waters.

Other information

: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

2/5/2025 (Revision date) EN (English) 4/28

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid breathing

dust/fume/gas/mist/vapours/spray. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and

eyes.

Hygiene measures : Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or

smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Keep in fireproof place. Store locked up. Store in a well-

ventilated place. Keep cool.
: Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Storage temperature : 25 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container.
Packaging materials : Do not store in corrodable metal.

Switzerland

Incompatible products

Storage class (LK) : LK 6.1 - Toxic materials

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

citral (5392-40-5)		
Belgium - Occupational Exposure Limits		
OEL TWA	32 mg/m³ (vapor and aerosol)	
	5 ppm (vapor and aerosol)	
OEL chemical category	Skin	
Ireland - Occupational Exposure Limits		
OEL TWA	5 ppm	
OEL STEL	15 ppm (calculated)	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	27 mg/m³	
NDSCh (OEL STEL)	54 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	5 ppm (inhalable fraction; vapor)	
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure	

Safety Data Sheet

OEL chemical category Sens USA - ACGIH - Occupational Exposure Limits	m (inhalable fraction and vapor)	
OEL chemical category Sens USA - ACGIH - Occupational Exposure Limits		
USA - ACGIH - Occupational Exposure Limits		
	itizer, skin - potential for cutaneous absorption	
ı		
ACGIH OEL TWA 5 ppr	m (inhalable fraction and vapor)	
	Classifiable as a Human Carcinogen, Skin - potential significant contribution to overall sure by the cutaneous route, dermal sensitizer	
Toluene (108-88-3)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA 192 r	ng/m³	
50 pp	om	
IOEL STEL 384 r	ng/m³	
100 p	орт	
Remark Poss	ibility of significant uptake through the skin	
Austria - Occupational Exposure Limits		
MAK (OEL TWA) 190 r	ng/m³	
50 pp	om	
MAK (OEL STEL) 380 r	ng/m³	
100 p	ppm	
OEL chemical category Skin	notation	
Belgium - Occupational Exposure Limits		
OEL TWA 77 m	g/m³	
20 рр	om	
OEL STEL 384 r	ng/m³	
100 p	орт	
OEL chemical category Skin,	Skin notation	
Bulgaria - Occupational Exposure Limits		
OEL TWA 192 r	ng/m³	
50 pp	om	
OEL STEL 384 r	ng/m³	
100 p	ppm	
Bulgaria - Biological limit values		
	nmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at nd of exposure or end of work shift	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA)	mg/m³	
50 pp	om	
KGVI (OEL STEL) 384 r	ng/m³	
100 բ	opm	

Safety Data Sheet

Toluene (108-88-3)	
OEL chemical category	Skin notation
Croatia - Biological limit values	
BLV	1 mg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of the work shift 20 ppm Parameter: Toluene - Medium: final exhaled air - Sampling time: during exposure 2.5 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine) 1 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine)
Cyprus - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	200 mg/m³
OEL chemical category	Potential for cutaneous absorption
Czech Republic - Biological limit values	
BLV	1.6 μmol/mmol Creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1000 μmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.) 1.5 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1600 mg/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.)
Denmark - Occupational Exposure Limits	
OEL TWA	94 mg/m³
	25 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin notation

Safety Data Sheet

Toluene (108-88-3)	
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	81 mg/m³
	25 ppm
HTP (OEL STEL)	380 mg/m³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Finland - Biological limit values	
BLV	500 nmol/L Parameter: Toluene - Medium: blood - Sampling time: in the morning after a working day
France - Occupational Exposure Limits	
VME (OEL TWA)	76.8 mg/m³ (restrictive limit)
	20 ppm (restrictive limit)
VLE (OEL C/STEL)	384 mg/m³ (restrictive limit)
	100 ppm (restrictive limit)
OEL chemical category	Reproductive Toxin category 2, Risk of cutaneous absorption
France - Biological limit values	
BLV	20 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of workweek (Semi- quantitative (ambiguous interpretation)) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (per the Authority, the values for this substance must be decided and/or determined on a case by case basis. Guidance for the calculation of and interpretation of values is provided in the source)
Germany - Occupational Exposure Limits (TRGS 90	00)
AGW (OEL TWA)	190 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	50 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	Skin notation
Germany - Biological limit values (TRGS 903)	
Biological limit value	600 μg/l Parameter: Toluene - Medium: whole blood - Sampling time: immediately after exposure 75 μg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: for long-term exposures: at the end of the shift after several shifts 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: end of shift
Gibraltar - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
Greece - Occupational Exposure Limits	
OEL TWA	192 mg/m³

Safety Data Sheet

Toluene (108-88-3)		
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	190 mg/m³	
CK (OEL STEL)	384 mg/m³	
OEL chemical category	Potential for cutaneous absorption	
Ireland - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Potential for cutaneous absorption	
Italy - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Latvia - Occupational Exposure Limits		
OEL TWA	50 mg/m³	
	14 ppm	
OEL chemical category	skin - potential for cutaneous exposure	
Latvia - Biological Exposure Indices		
BEI	1.6 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: end of shift	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	192 mg/m³	
	50 ppm	
TPRV (OEL STEL)	384 mg/m³	
	100 ppm	
OEL chemical category	Reproductive toxin, Skin notation	
Luxembourg - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Possibility of significant uptake through the skin	
Malta - Occupational Exposure Limits		
OEL TWA	192 mg/m³	

Safety Data Sheet

Toluene (108-88-3)	
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	150 mg/m³
	39 ppm
TGG-15min (OEL STEL)	384 mg/m³
	100 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	100 mg/m³
NDSCh (OEL STEL)	200 mg/m³
Portugal - Occupational Exposure Limits	
OEL TWA	192 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)
OEL STEL	384 mg/m³ (indicative limit value)
	100 ppm (indicative limit value)
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
Romania - Biological limit values	
BLV	2 g/l Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 3 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	192 mg/m³
	50 ppm
NPHV (OEL C)	384 mg/m³ (also biological monitoring considered)
OEL chemical category	Potential for cutaneous absorption
Slovakia - Biological limit values	
BLV	600 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of exposure or work shift 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: after all work shifts (for long-term exposure) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of exposure or work shift 2401 mg/g creatinine Parameter: Hippuric acid - Sampling time: end of exposure or work shift

Safety Data Sheet

Toluene (108-88-3)		
Slovenia - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Category 2, Potential for cutaneous absorption	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	192 mg/m³ (indicative limit value)	
	50 ppm (indicative limit value)	
VLA-EC (OEL STEL)	384 mg/m³	
	100 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Spain - Biological limit values		
BLV	0.6 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift 0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: start of last shift of workweek 0.08 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	192 mg/m³	
	50 ppm	
KGV (OEL STEL)	384 mg/m³	
	100 ppm	
OEL chemical category	Skin notation	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	191 mg/m³	
	50 ppm	
WEL STEL (OEL STEL)	384 mg/m³	
	100 ppm	
WEL chemical category	Potential for cutaneous absorption	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA)	94 mg/m³	
	25 ppm	
Korttidsverdi (OEL STEL)	141 mg/m³ (value calculated)	
	37.5 ppm (value calculated)	
OEL chemical category	Skin notation	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	190 mg/m³	
	50 ppm	
KZGW (OEL STEL)	760 mg/m³	
	200 ppm	

Safety Data Sheet

Toluene (108-88-3)	
OEL chemical category	Skin notation, Category 2 reproductive toxin
Switzerland - BAT	
BAT	600 μg/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 6.48 μmol/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 2 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 0.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 4.62 μmol/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 75 μg/l Parameter: Toluol - Medium: urine - Sampling time: end of shift
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	20 ppm
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 0.3 mg/g creatinine Parameter: o-Cresol with hydrolysis - Medium: urine - Sampling time: end of shift (background)
Dipropylene glycol monomethyl ether (34590-	94-8)
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	308 mg/m³
	50 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	307 mg/m³ (mixed isomers)
	50 ppm (mixed isomers)
MAK (OEL STEL)	614 mg/m³ (isomers mixtures)
	100 ppm (isomers mixtures)
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Skin, Skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	308 mg/m³
	50 ppm
OEL chemical category	Skin notation

Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)		
Cyprus - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
	50 ppm	
OEL chemical category	Skin-potential for cutaneous absorption	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	270 mg/m³	
OEL chemical category	Potential for cutaneous absorption	
Denmark - Occupational Exposure Limits		
OEL TWA	309 mg/m³	
	50 ppm	
OEL STEL	618 mg/m³	
	100 ppm	
OEL chemical category	Potential for cutaneous absorption	
Estonia - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
	50 ppm	
OEL chemical category	Skin notation	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	310 mg/m³	
	50 ppm	
OEL chemical category	Potential for cutaneous absorption	
France - Occupational Exposure Limits		
VME (OEL TWA)	308 mg/m³ (restrictive limit)	
	50 ppm (restrictive limit)	
OEL chemical category	Risk of cutaneous absorption	
Germany - Occupational Exposure Limits (TRGS 90	00)	
AGW (OEL TWA)	310 mg/m³ (isomer mixture)	
	50 ppm (isomer mixture)	
Gibraltar - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
	50 ppm	
OEL chemical category	Skin notation	
Greece - Occupational Exposure Limits		
OEL TWA	600 mg/m³	
	100 ppm	
OEL STEL	900 mg/m³	
	150 ppm	
OEL chemical category	skin - potential for cutaneous absorption	

Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)		
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	308 mg/m³	
Ireland - Occupational Exposure Limits		
OEL TWA	308 mg/m³ ((2-Methoxymethylethoxy)propanol)	
	50 ppm ((2-Methoxymethylethoxy)propanol)	
OEL STEL	924 mg/m³ (calculated (2-(2-Methoxypropoxy)-1-propanol)	
	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)	
OEL chemical category	Potential for cutaneous absorption	
Italy - Occupational Exposure Limits		
OEL TWA	308 mg/m³ (1-(3-Methoxypropoxy)propan-1-ol)	
	50 ppm (1-(3-Methoxypropoxy)propan-1-ol)	
OEL chemical category	skin - potential for cutaneous absorption	
Latvia - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
	50 ppm	
OEL chemical category	skin - potential for cutaneous exposure	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	300 mg/m³ (2-(2-Methoxypropoxy)-propanol)	
	50 ppm (2-(2-Methoxypropoxy)-propanol)	
TPRV (OEL STEL)	450 mg/m³ (2-(2-Methoxypropoxy)-propanol)	
	75 ppm (2-(2-Methoxypropoxy)-propanol)	
OEL chemical category	Skin notation	
Luxembourg - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
	50 ppm	
OEL chemical category	Possibility of significant uptake through the skin	
Malta - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
	50 ppm	
OEL chemical category	Possibility of significant uptake through the skin	
Netherlands - Occupational Exposure Limits		
TGG-8u (OEL TWA)	300 mg/m³	
	48.7 ppm	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-1-ol)	
NDSCh (OEL STEL)	480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)	
Portugal - Occupational Exposure Limits		
OEL TWA	308 mg/m³ (indicative limit value)	

Safety Data Sheet

OEL STEL 150 ppm OEL Chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits 308 mg/m³ OEL Chemical category \$ no notation Slovakia - Occupational Exposure Limits Very pm NPHY (OEL TWA) 308 mg/m³ 50 ppm 50 ppm OEL Chemical category Potential category OEL Chemical category Potential Category OEL TWA 308 mg/m³ 50 ppm 50 ppm OEL STEL 308 mg/m³ 50 ppm Potential for cutaneous absorption OEL chemical category Potential for cutaneous absorption Spain - Occupational Exposure Limits VLA-ED (OEL TWA) OEL chemical category 308 mg/m³ (indicative limit value) OEL chemical category 308 mg/m² (indicative limit value) OEL chemical category 300 mg/m² Sweden - Occupational Exposure Limits Very (OEL TWA) KGY (OEL TWA) 300 mg/m² KGY (OEL STEL) 400 mg/m² For pm OEL chemical category Soin notation	Dipropylene glycol monomethyl ether (34590-94-8)		
OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits 308 mg/m³ OEL chemical category \$kin notation Silovakia - Occupational Exposure Limits Why (OEL TWA) 308 mg/m³ Silovania - Occupational Exposure Limits 50 ppm OEL chemical category Potential for cutaneous absorption Silovania - Occupational Exposure Limits OEL STEL 308 mg/m³ 50 ppm OEL chemical category Potential for cutaneous absorption Spain - Occupational Exposure Limits VLA-EB (OEL TWA) Spain - Occupational Exposure Limits VLA-EB (OEL TWA) 308 mg/m³ (indicative limit value) OEL chemical category 8 kin - potential for cutaneous absorption Sweden - Occupational Exposure Limits NGY (OEL TWA) 300 mg/m³ 50 ppm VEX. (OEL TWA) 300 mg/m³ 50 ppm VEX. (OEL TWA) 308 mg/m³ Value Kingdom - Occupational Exposure Limits WEL STEL (OEL STEL) 924 mg/m³ (calculated) WEL STEL (OEL STEL) 924 mg/m³ (calculated) <th></th> <th colspan="2">50 ppm (indicative limit value)</th>		50 ppm (indicative limit value)	
Romania - Occupational Exposure Limits 308 mg/m³ OEL chemical category Skin notation Slovakia - Occupational Exposure Limits **** NPHY (OEL TWA)**	OEL STEL	150 ppm	
QEL chemical category Skin notation Slovakia - Occupational Exposure Limits 308 mg/m³ PMFW (QEL TWA) 308 mg/m³ Slovakia - Occupational Exposure Limits 50 ppm OEL chemical category Potential for cutaneous absorption Slovenia - Occupational Exposure Limits 50 ppm OEL TWA 308 mg/m³ 50 ppm 50 ppm OEL chemical category Potential for cutaneous absorption Spain - Occupational Exposure Limits 50 ppm VLA-ED (OEL TWA) 308 mg/m³ (indicative limit value) Spain - Occupational Exposure Limits 50 ppm (indicative limit value) VLA-ED (OEL TWA) 308 mg/m³ (indicative limit value) Sweden - Occupational Exposure Limits 50 ppm (indicative limit value) Sweden - Occupational Exposure Limits 50 ppm KGY (OEL STEL) 450 mg/m³ KGY (OEL STEL) 50 ppm WEL chemical category Skin notation United Kingdom - Occupational Exposure Limits 50 ppm WEL STEL (OEL STEL) 924 mg/m² (calculated) 150 ppm (calculated) 150 ppm (calculated) WEL L	OEL chemical category	skin - potential for cutaneous exposure indicative limit value	
S0 pm	Romania - Occupational Exposure Limits		
OEL chemical category Skin notation Slovakia - Occupational Exposure Limits NPHV (OEL TWA) 308 mg/m³ 50 ppm Potential for cutaneous absorption Slovania - Occupational Exposure Limits Potential for cutaneous absorption OEL TWA 308 mg/m³ 50 ppm 90 mg/m³ OEL STEL 308 mg/m³ OEL chemical category Potential for cutaneous absorption Spain - Occupational Exposure Limits VLA-ED (OEL TWA) VLA-ED (OEL TWA) 308 mg/m³ (indicative limit value) OEL chemical category skin - potential for cutaneous absorption Sweden - Occupational Exposure Limits Sweden - Occupational Exposure Limits NGV (OEL TWA) 300 mg/m³ 50 ppm 50 ppm KGV (OEL STEL) 450 mg/m³ VINIted Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) WEL TWA (OEL TWA) 308 mg/m³ 50 ppm 50 ppm WEL STEL (OEL STEL) 924 mg/m² (calculated) WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits 50 ppm (calculated)	OEL TWA	308 mg/m³	
Siovakia - Occupational Exposure Limits So ppm Potential for cutaneous absorption		50 ppm	
NPHV (OEL TWA) 308 mg/m² 50 ppm 50 ppm OEL chemical category Potential for cutaneous absorption Siovenia - Occupational Exposure Limits 308 mg/m² 50 ppm 50 ppm OEL STEL 308 mg/m² 50 ppm 50 ppm OEL chemical category Potential for cutaneous absorption Spain - Occupational Exposure Limits 308 mg/m² (indicative limit value) 50 ppm (indicative limit value) 50 ppm (indicative limit value) OEL chemical category skin - potential for cutaneous absorption Sweden - Occupational Exposure Limits 450 mg/m² KGV (OEL TWA) 450 mg/m² 50 ppm 450 mg/m² 75 ppm 50 ppm WEL STEL (OEL STEL) 308 mg/m² WEL TWA (OEL TWA) 308 mg/m² 50 ppm 50 ppm WEL chemical category 924 mg/m² (calculated) WEL STEL (OEL STEL) 924 mg/m² (calculated) WEL STEL (OEL STEL) 90 ppm (calculated) WEL chemical category Potential for cutaneous absorption <t< td=""><td>OEL chemical category</td><td>Skin notation</td></t<>	OEL chemical category	Skin notation	
OEL chemical category Potential for cutaneous absorption Slovenia - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm 50 ppm OEL STEL 308 mg/m³ OEL chemical category Petential for cutaneous absorption Spain - Occupational Exposure Limits 308 mg/m³ (indicative limit value) VLA-ED (OEL TWA) 308 mg/m³ (indicative limit value) OEL chemical category skin - potential for cutaneous absorption Sweden - Occupational Exposure Limits 300 mg/m³ MGV (OEL TWA) 300 mg/m³ MGV (OEL STEL) 450 mg/m³ MGV (OEL STEL) 450 mg/m³ OEL chemical category Skin notation United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) 308 mg/m³ 50 ppm WEL STEL (OEL STEL) 924 mg/m³ (calculated) WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits Well chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits	Slovakia - Occupational Exposure Limits		
OEL chemical category Petential for cutaneous absorption Slovenia - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm 50 ppm OEL STEL 308 mg/m³ 50 ppm 50 ppm OEL chemical category Potential for cutaneous absorption Spain - Occupational Exposure Limits VLA-ED (OEL TWA) 308 mg/m³ (indicative limit value) 50 ppm (indicative limit value) 60 ppm (indicative limit value) Sweden - Occupational Exposure Limits NGV (OEL TWA) 300 mg/m³ 50 ppm 50 ppm KGV (OEL STEL) 450 mg/m³ 60 ppm 50 ppm OEL chemical category Skin notation United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) 308 mg/m³ Oppm WEL STEL (OEL STEL) 224 mg/m³ (calculated) (a) ppm (calculated) Norway - Occupational Exposure Limits	NPHV (OEL TWA)	308 mg/m³	
Slovenia - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm 50 ppm OEL STEL 308 mg/m³ 60 ppm Potential for cutaneous absorption Spain - Occupational Exposure Limits VLA-ED (OEL TWA) 308 mg/m³ (indicative limit value) So ppm (indicative limit value) Sweden - Occupational Exposure Limits NGY (OEL TWA) 300 mg/m³ 50 ppm 50 ppm KGV (OEL STEL) 450 mg/m³ 75 ppm 0EL chemical category Winter TWA (OEL TWA) United Kingdom - Occupational Exposure Limits WEL STEL (OEL STEL) WEL STEL (OEL STEL) 308 mg/m³ 50 ppm WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm Kortiidsverdi (OEL STEL) 300 mg/m³ 50 ppm		50 ppm	
OEL TWA 308 mg/m³ 50 ppm 50 ppm OEL STEL 308 mg/m³ 50 ppm 50 ppm OEL chemical category Potential for cutaneous absorption Spain - Occupational Exposure Limits 308 mg/m³ (indicative limit value) VLA-ED (OEL TWA) 308 mg/m³ (indicative limit value) OEL chemical category skin - potential for cutaneous absorption Sweden - Occupational Exposure Limits 300 mg/m³ KGV (OEL TWA) 450 mg/m³ 650 ppm 75 ppm OEL chemical category 8kin notation United Kingdom - Occupational Exposure Limits 8kin notation United Kingdom - Occupational Exposure Limits 50 ppm WEL STEL (OEL STEL) 924 mg/m³ (calculated) WEL STEL (OEL STEL) 924 mg/m³ (calculated) WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits 50 ppm Korttidsverdi (OEL TWA) 300 mg/m³ (value calculated) Fop ppm (value calculated) 75 ppm (value calculated)	OEL chemical category	Potential for cutaneous absorption	
OEL STEL 308 mg/m³ OEL chemical category Potential for cutaneous absorption Spain - Occupational Exposure Limits VLA-ED (OEL TWA) 308 mg/m³ (indicative limit value) OEL chemical category skin - potential for cutaneous absorption Sweden - Occupational Exposure Limits NGY (OEL TWA) 300 mg/m³ 50 ppm 450 mg/m³ KGV (OEL STEL) 450 mg/m³ OEL chemical category 8 kin notation United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) 308 mg/m³ 50 ppm WEL STEL (OEL STEL) 924 mg/m³ (calculated) WEL STEL (OEL STEL) 924 mg/m³ (calculated) WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm Kortidisverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated) 75 ppm (value calculated)	Slovenia - Occupational Exposure Limits		
OEL STEL 308 mg/m³ 50 ppm Potentical category Potential for cutaneous absorption Spain - Occupational Exposure Limits VLA-ED (OEL TWA) 308 mg/m³ (indicative limit value) 50 ppm (indicative limit value) 50 ppm (indicative limit value) OEL chemical category skin - potential for cutaneous absorption Sweden - Occupational Exposure Limits NGY (OEL TWA) 300 mg/m³ 50 ppm 50 ppm KGV (OEL STEL) 450 mg/m³ 75 ppm 75 ppm OEL chemical category Skin notation United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) 308 mg/m³ 50 ppm 924 mg/m³ (calculated) WEL STEL (OEL STEL) 924 mg/m³ (calculated) WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm 50 ppm Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm <td>OEL TWA</td> <td>308 mg/m³</td>	OEL TWA	308 mg/m³	
OEL chemical category Potential for cutaneous absorption Spain - Occupational Exposure Limits VLA-ED (OEL TWA) 308 mg/m³ (indicative limit value) OEL chemical category skin - potential for cutaneous absorption Sweden - Occupational Exposure Limits NGV (OEL TWA) 300 mg/m³ 50 ppm KGV (OEL STEL) 450 mg/m² 75 ppm OEL chemical category skin notation United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) 308 mg/m³ 50 ppm WEL STEL (OEL STEL) 924 mg/m³ (calculated) WEL STEL (OEL STEL) 910 mg/m³ 50 ppm WEL STEL (OEL STEL) 924 mg/m³ (calculated) T50 ppm (calculated) WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits Kentidsverdi (OEL TWA) 300 mg/m³ 50 ppm Kortlidsverdi (OEL STEL) 300 mg/m³ 50 ppm		50 ppm	
OEL chemical category Potential for cutaneous absorption Spain - Occupational Exposure Limits VLA-ED (OEL TWA) 308 mg/m³ (indicative limit value) OEL chemical category skin - potential for cutaneous absorption Sweden - Occupational Exposure Limits NGV (OEL TWA) 300 mg/m³ 50 ppm 50 ppm KGV (OEL STEL) 450 mg/m³ 75 ppm OEL chemical category United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) 308 mg/m³ 50 ppm WEL STEL (OEL STEL) 924 mg/m³ (calculated) WEL schemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm Kortidsverdi (OEL STEL) 375 mg/m³ (value calculated) Kortidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)	OEL STEL	308 mg/m³	
Spain - Occupational Exposure Limits VLA-ED (OEL TWA) 308 mg/m³ (indicative limit value) 50 ppm (indicative limit value) 60 ppm (indicative limit value) OEL chemical category skin - potential for cutaneous absorption Sweden - Occupational Exposure Limits NGV (OEL STEL) 300 mg/m³ 450 mg/m³ 75 ppm OEL chemical category Skin notation United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) 308 mg/m³ 50 ppm 50 ppm WEL STEL (OEL STEL) 924 mg/m³ (calculated) WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)		50 ppm	
VLA-ED (OEL TWA) 308 mg/m³ (indicative limit value) OEL chemical category skin - potential for cutaneous absorption Sweden - Occupational Exposure Limits NGV (OEL TWA) 300 mg/m³ 50 ppm KGV (OEL STEL) 450 mg/m³ 75 ppm OEL chemical category Skin notation United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) 308 mg/m³ 50 ppm WEL STEL (OEL STEL) 924 mg/m³ (calculated) 150 ppm (calculated) WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits Fenseverdi (OEL TWA) 300 mg/m³ 50 ppm Norway - Occupational Exposure Limits Kortidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated) 75 ppm (value calculated)	OEL chemical category	Potential for cutaneous absorption	
So ppm (indicative limit value) OEL chemical category skin - potential for cutaneous absorption Sweden - Occupational Exposure Limits NGV (OEL TWA) 300 mg/m³ 50 ppm KGV (OEL STEL) 450 mg/m³ 75 ppm OEL chemical category skin notation United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) 308 mg/m³ 50 ppm WEL STEL (OEL STEL) 924 mg/m³ (calculated) 150 ppm (calculated) WEL chemical category potential for cutaneous absorption Norway - Occupational Exposure Limits Fenseverdi (OEL TWA) 300 mg/m³ 50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)	Spain - Occupational Exposure Limits		
Sweden - Occupational Exposure Limits NGV (OEL TWA) 300 mg/m³ 50 ppm KGV (OEL STEL) 450 mg/m³ 75 ppm OEL chemical category Skin notation United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) 308 mg/m³ 50 ppm WEL STEL (OEL STEL) 924 mg/m³ (calculated) 150 ppm (calculated) WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 309 mg/m³ 50 ppm Source Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm Source Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)	VLA-ED (OEL TWA)	308 mg/m³ (indicative limit value)	
NGV (OEL TWA) 300 mg/m³ 50 ppm KGV (OEL STEL) 450 mg/m³ 75 ppm OEL chemical category Skin notation United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) 308 mg/m³ 50 ppm WEL STEL (OEL STEL) 924 mg/m³ (calculated) 150 ppm (calculated) WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 308 mg/m³ 50 ppm 924 mg/m³ (calculated) 150 ppm (calculated) Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)		50 ppm (indicative limit value)	
NGV (OEL TWA) 300 mg/m³ 50 ppm 50 ppm KGV (OEL STEL) 450 mg/m³ 75 ppm 75 ppm United Kingdom - Occupational Exposure Limits Skin notation WEL TWA (OEL TWA) 308 mg/m³ 50 ppm WEL STEL (OEL STEL) 924 mg/m³ (calculated) WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits To ppm (calculated) Genseverdi (OEL TWA) 300 mg/m³ 50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)	OEL chemical category	skin - potential for cutaneous absorption	
50 ppm KGV (OEL STEL) 450 mg/m³ 75 ppm 75 ppm OEL chemical category Skin notation United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) 308 mg/m³ 50 ppm 50 ppm WEL STEL (OEL STEL) 924 mg/m³ (calculated) 150 ppm (calculated) 150 ppm (calculated) Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm 50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated) 75 ppm (value calculated)	Sweden - Occupational Exposure Limits		
KGV (OEL STEL) 450 mg/m³ 75 ppm 75 ppm OEL chemical category Skin notation United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) 308 mg/m³ 50 ppm 50 ppm WEL STEL (OEL STEL) 924 mg/m³ (calculated) WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated) 75 ppm (value calculated)	NGV (OEL TWA)	300 mg/m³	
OEL chemical category Skin notation United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) 308 mg/m³ 50 ppm WEL STEL (OEL STEL) 924 mg/m³ (calculated) 150 ppm (calculated) WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)		50 ppm	
OEL chemical category Well TWA (OEL TWA) Well STEL (OEL STEL) Well chemical category Well chemical category Well chemical category Well chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)	KGV (OEL STEL)	450 mg/m³	
WEL TWA (OEL TWA) 308 mg/m³ 50 ppm WEL STEL (OEL STEL) 924 mg/m³ (calculated) 150 ppm (calculated) WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)		75 ppm	
WEL TWA (OEL TWA) 308 mg/m³ 50 ppm WEL STEL (OEL STEL) 924 mg/m³ (calculated) 150 ppm (calculated) WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)	OEL chemical category	Skin notation	
WEL STEL (OEL STEL) 924 mg/m³ (calculated) 150 ppm (calculated) WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)	United Kingdom - Occupational Exposure Limit	is	
WEL STEL (OEL STEL) 924 mg/m³ (calculated) 150 ppm (calculated) WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)	WEL TWA (OEL TWA)	308 mg/m³	
WEL chemical category Potential for cutaneous absorption Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)		50 ppm	
WEL chemical category Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)	WEL STEL (OEL STEL)	924 mg/m³ (calculated)	
Norway - Occupational Exposure Limits Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)		150 ppm (calculated)	
Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)	WEL chemical category	Potential for cutaneous absorption	
50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)	Norway - Occupational Exposure Limits		
Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)	Grenseverdi (OEL TWA)	300 mg/m³	
75 ppm (value calculated)		50 ppm	
	Korttidsverdi (OEL STEL)	375 mg/m³ (value calculated)	
OEL chemical category Skin notation		75 ppm (value calculated)	
	OEL chemical category	Skin notation	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) 300 mg/m³ (aerosol, vapour)	
	50 ppm (aerosol, vapour)
KZGW (OEL STEL)	300 mg/m³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	50 ppm (Dipropylene glycol methyl ether)

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):





8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection. Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : light yellow. amber. Conforms to standard.

Odour : characteristic.
Odour threshold : Not available
Melting point : Not applicable
Freezing point : Not available
Boiling point : Not available

Flammability : Not applicable, Combustible liquid

Lower explosion limit : Not available : Not available Upper explosion limit Flash point Auto-ignition temperature : Not available Decomposition temperature : Not available : Not available Viscosity, kinematic : 20.5 mm²/s Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available

Vapour pressure : 0.007298366 mm Hg (calculated value)

Vapour pressure at 50° C: Not availableDensity: Not availableRelative density: ≈ 0.93 Relative vapour density at 20° C: Not availableParticle characteristics: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 35.9527545 % (calculated value)(CARB VOC) (%w/w)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Combustible liquid. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

2/5/2025 (Revision date) EN (English) 17/28

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (inhalation) :	Not classified	
1-Butanol, 3-methoxy-3-methyl- (56539-66-3)		
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)	
LC50 Inhalation - Rat	> 5 mg/l/4h	
Ethyl vanillin (121-32-4)		
LD50 oral rat	1590 mg/kg (Source: NLM_CIP)	
LD50 oral	3000 mg/kg bodyweight	
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)	
Citrus medica limonum (Lemon) peel oil (800	8-56-8)	
LD50 oral rat	2840 mg/kg (Source: NLM_CIP)	
Orange Oil (8028-48-6)		
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)	
Lime oil distilled (8008-26-2)		
LD50 oral rat	5600 mg/kg	
LD50 dermal rabbit	> 5000 mg/kg	
Linalool (78-70-6)		
LD50 oral	2790 mg/kg	
Ethyl maltol (4940-11-8)		
LD50 oral rat	1150 mg/kg (Source: NLM_CIP)	
LD50 oral	1200 mg/kg bodyweight	
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)	
Anisic aldehyde (123-11-5)		
LD50 oral rat	3210 mg/kg (Source: ECHA)	
LD50 oral	3210 mg/kg bodyweight	
LD50 dermal rabbit	> 5000 mg/kg (Source: EPA_HPV)	
LC50 Inhalation - Rat	> 0.32 mg/l (Exposure time: 7 h Source: ECHA)	
Litsea cubeba oil (68855-99-2)		
LD50 oral rat	> 5 g/kg (Source: NLM_CIP)	
LD50 dermal	4800 mg/kg bodyweight	
citral (5392-40-5)		
LD50 oral rat	4960 mg/kg (Source: NLM_CIP)	
LD50 dermal rabbit	2250 mg/kg (Source: NLM_CIP)	
Toluene (108-88-3)		
LD50 oral rat	2600 mg/kg (Source: JAPAN_GHS)	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
LD50 dermal rabbit	12000 mg/kg (Source: JAPAN_GHS)
LC50 Inhalation - Rat	12.5 mg/l/4h
Dipropylene glycol monomethyl ether (3459)	0-94-8)
LD50 oral rat	5.35 g/kg (Source: NLM_HSDB)
LD50 dermal rabbit	9500 mg/kg (Source: NLM_CIP)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
• •	: Based on available data, the classification criteria are not met
Toluene (108-88-3)	
IARC group	3 - Not classifiable
Reproductive toxicity	Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Toluene (108-88-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not classified
Additional information	: Based on available data, the classification criteria are not met
BAKERY SHOP CC-16400	
Viscosity, kinematic	20.5 mm²/s
Toluene (108-88-3)	
Hydrocarbon	Yes

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and symptoms

: Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Ecology - water : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Toxic to a

(chronic)

: Toxic to aquatic life with long lasting effects.

2/5/2025 (Revision date) EN (English) 19/28

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1-Butanol, 3-methoxy-3-methyl- (56539-66-3) LC50 - Fish [1] > 1	100 mg/l (Exposure time: 96 h - Species: Oryzias latipes [semi-static] Source: ECHA)	
LC50 - Fish [1] > 1	100 mg/l (Exposure time: 06 h. Species: Onyzins latines (semi static) Source: ECHA)	
	100 mg/r (Exposure time: 90 m - Species: Oryzias latipes [semi-static] Source: EGHA)	
Ethyl vanillin (121-32-4)		
	.4 – 94.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] urce: EPA)	
Linalool (78-70-6)		
EC50 96h - Algae [1] 88.	.3 mg/l (Species: Desmodesmus subspicatus)	
Ethyl maltol (4940-11-8)		
LC50 - Fish [1] > 8	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: ECHA)	
citral (5392-40-5)		
EC50 - Crustacea [1] 7 m	ng/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 72h - Algae [1] 16	mg/l (Species: Desmodesmus subspicatus)	
EC50 96h - Algae [1] 19	mg/l (Species: Desmodesmus subspicatus)	
Toluene (108-88-3)		
	.22 – 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] urce: EPA)	
LC50 - Fish [2] 12.	.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)	
EC50 - Crustacea [1] 5.4	16 – 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
EC50 - Crustacea [2] 11.	.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 72h - Algae [1] 12.	.5 mg/l (Species: Pseudokirchneriella subcapitata [static])	
EC50 96h - Algae [1] > 4	133 mg/l (Species: Pseudokirchneriella subcapitata)	
Dipropylene glycol monomethyl ether (34590-94-8)		
LC50 - Fish [1] > 1	10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 - Crustacea [1] 191	19 mg/l (Exposure time: 48 h - Species: Daphnia magna)	

12.2. Persistence and degradability

BAKERY SHOP CC-16400		
Persistence and degradability May cause long-term adverse effects in the environment. Not established.		
1-Butanol, 3-methoxy-3-methyl- (56539-66-3)		
Persistence and degradability	Not established.	
Ethyl vanillin (121-32-4)		
Persistence and degradability	Rapidly degradable	
Citrus medica limonum (Lemon) peel oil (800	8-56-8)	
Persistence and degradability Rapidly degradable		
Orange Oil (8028-48-6)		
Persistence and degradability Rapidly degradable		
Lime oil distilled (8008-26-2)		
Persistence and degradability	Rapidly degradable	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Linalool (78-70-6)		
Persistence and degradability	Rapidly degradable	
Ethyl maltol (4940-11-8)		
Persistence and degradability	Rapidly degradable	
Anisic aldehyde (123-11-5)		
Persistence and degradability Rapidly degradable		
Litsea cubeba oil (68855-99-2)		
Persistence and degradability	Rapidly degradable	
citral (5392-40-5)		
Persistence and degradability	Rapidly degradable	
Toluene (108-88-3)		
Persistence and degradability Rapidly degradable		
Dipropylene glycol monomethyl ether (34590-94-8)		
Persistence and degradability	Rapidly degradable	

12.3. Bioaccumulative potential

BAKERY SHOP CC-16400		
Bioaccumulative potential	Not established.	
1-Butanol, 3-methoxy-3-methyl- (56539-66-3)		
Partition coefficient n-octanol/water (Log Pow)	0.18 (at 24.8 °C (at pH 6.4)	
Bioaccumulative potential	Not established.	
Ethyl vanillin (121-32-4)		
Partition coefficient n-octanol/water (Log Pow)	1.61 (at 25 °C)	
Ethyl maltol (4940-11-8)		
Partition coefficient n-octanol/water (Log Pow)	2.9 (at 25 °C)	
Anisic aldehyde (123-11-5)		
Partition coefficient n-octanol/water (Log Pow)	1.56 (at 25 °C (at pH >7.9-<8.25)	
citral (5392-40-5)		
Partition coefficient n-octanol/water (Log Pow)	2.76 (at 25 °C)	
Toluene (108-88-3)		
Partition coefficient n-octanol/water (Log Pow)	2.73 (at 20 °C (at pH 7)	
Dipropylene glycol monomethyl ether (34590-94-8)		
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7)	

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information

: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods
Product/Packaging disposal recommendations

Ecological information HP Code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with local/national laws and regulations.
- : Avoid release to the environment. Hazardous waste due to toxicity.
- : HP4 "Irritant skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

HP10 - "Toxic for reproduction:" waste which has adverse effects on sexual function and fertility in adult males and females, as well as developmental toxicity in the offspring.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID n	14.1. UN number or ID number				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082	
14.2. UN proper shipping	g name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Lime Oil Distilled)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Lime Oil Distilled)	Environmentally hazardous substance, liquid, n.o.s. (Lime Oil Distilled)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Lime Oil Distilled)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Lime Oil Distilled)	
Transport document descr	iption				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Lime Oil Distilled), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Lime Oil Distilled), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Lime Oil Distilled), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Lime Oil Distilled), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Lime Oil Distilled), 9, III	
14.3. Transport hazard o	class(es)				
9	9	9	9	9	
**************************************	9	**************************************	**************************************	**************************************	
14.4. Packing group					
III	III	III	Ш	III	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.5. Environmental hazards				
Dangerous for the environment: Yes environment: Yes environment: Yes				
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : M6

Special provisions (ADR) : 274, 335, 375, 601

Limited quantities (ADR) : 5I Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4

Portable tank and bulk container special provisions : TP1, TP29

(ADR)

Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading : CV13

and handling (ADR)

Hazard identification number (Kemler No.) : 90

Orange plates : **F**

90 3082

Tunnel restriction code (ADR) : -

EAC code : •3Z

Transport by sea

Special provisions (IMDG) : 274, 335, 969

Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1 Packing instructions (IMDG) : LP01, P001 Special packing provisions (IMDG) : PP1 IBC packing instructions (IMDG) : IBC03 Tank instructions (IMDG) : T4 Tank special provisions (IMDG) : TP1, TP29 EmS-No. (Fire) : F-A EmS-No. (Spillage) : S-F Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L

Special provisions (IATA) : A97, A158, A197, A215

ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M6

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Special provisions (ADN) : 274, 335, 375, 601

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Carriage permitted (ADN) : T

Equipment required (ADN) : PP

Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : M6

Special provisions (RID) : 274, 335, 375, 601

Limited quantities (RID) : 5L Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions : TP1, TP29

(RID)

Tank codes for RID tanks (RID) : LGBV
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12

Special provisions for carriage - Loading, unloading : CW13, CW31

and handling (RID)

Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Citrus medica limonum (Lemon) peel oil ; Orange Oil ; Lime oil distilled ; Toluene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	BAKERY SHOP CC- 16400; 1-Butanol,3- methoxy-3-methyl-; Citrus medica limonum (Lemon) peel oil; Orange Oil; Lime oil distilled; Linalool; Litsea cubeba oil; citral; Toluene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	BAKERY SHOP CC-16400 ; Citrus medica limonum (Lemon) peel oil ; Orange Oil ; Lime oil distilled ; Anisic aldehyde ; Litsea cubeba oil	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
40.	Citrus medica limonum (Lemon) peel oil ; Orange Oil ; Lime oil distilled ; Toluene	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.
48.	Toluene	Toluene

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 35.9527545 % (calculated value)(CARB VOC) (%w/w)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.		Category, Subcategory	Threshold	Annex
Toluene		108-88-3	2902 30 00	Category 3		Annex I

15.1.2. National regulations

France

Occupational diseases	cupational diseases		
Code	Description		
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them		
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide		

Germany

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).

Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment

 2/5/2025 (Revision date)
 EN (English)
 25/28

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SZW-lijst van kankerverwekkende stoffen

SZW-lijst van mutagene stoffen

SZW-lijst van reprotoxische stoffen – Borstvoeding

SZW-lijst van reprotoxische stoffen -

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen - Ontwikkeling

: Lemon oil ,Orange Oil are listed: None of the components are listed: None of the components are listed

: Lemon oil ,Orange Oil are listed

: Toluene is listed

Denmark

Class for fire hazard : Class III-1 Store unit : 50 liter

Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines

for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:		
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disrupting properties	

Other information : None.

Full text of H- and EUH-statements:		
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
H361	Suspected of damaging fertility or the unborn child.	
H361d	Suspected of damaging the unborn child.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Repr. 2	Reproductive toxicity, Category 2	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUF	ull text of H- and EUH-statements:		
Skin Sens. 1 Skin sensitisation, Category 1			
Skin Sens. 1B	Skin sensitisation, category 1B		
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2		
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis		

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.