Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 8/16/2024 Revision date: 3/28/2022 Version: 1.0



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : COCONUT CANDY CC-16401 UFI : A86R-S15N-000V-T3MJ

Product code : CC-16401

Type of product : Perfumes, fragrances Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

: Industrial use, Professional use Main use category Industrial/Professional use spec : For professional use only

Industrial

Use of the substance/mixture : Perfumes, fragrances : Odour agents Function or use category

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Candle Craft Weiherwiese 10 65510 Idstein - Germany T 49-6126-9363 -0

info@candlecraft.de - www.candlecraft.de

1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731;

Brazil: +0-800-591-6042: India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H302 Acute toxicity (dermal), Category 4 H312 Acute toxicity (inhalation:dust,mist) Category 4 H332 Skin sensitisation, Category 1 H317 H400 Hazardous to the aquatic environment – Acute Hazard,

Category 1

Hazardous to the aquatic environment - Chronic Hazard, H411

Category 2

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful to aquatic life with long lasting effects. Harmful in contact with skin. Harmful if inhaled. Harmful if swallowed. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS07

GHS

Signal word (CLP)

: Warning

Contains

: benzyl benzoate; COUMARIN; Triplal (Vertocitral)

Hazard statements (CLP)

: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled.

H317 - May cause an allergic skin reaction.

H410 - Very toxic to aquatic life with long lasting effects.

: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

Precautionary statements (CLP)

P261 - Avoid breatning dustrume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

Extra phrases

: For professional users only.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371- 33	17 – 34	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Resin acids and Rosin acids, hydrogenated, methyl esters	CAS-No.: 8050-15-5 EC-No.: 232-476-2	15 – 30	Aquatic Chronic 3, H412
COUMARIN	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756- 26	8.8 – 17.5	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Ethyl vanillin	CAS-No.: 121-32-4 EC-No.: 204-464-7 REACH-no: 01-211958961-24	0.7 – 1.4	Eye Irrit. 2, H319

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
isopentyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, DE, DK, EE, ES, FI, FR, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2 REACH-no: 01-2119548408- 32	0.5 – 1	Flam. Liq. 3, H226
Triplal (Vertocitral)	CAS-No.: 68039-49-6 EC-No.: 268-264-1	0.1 – 0.1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest. Call a poison center or a doctor if you feel unwell.

First-aid measures after skin contact

: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash with plenty of water/.... If skin irritation or rash occurs:

Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label). Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.

First-aid measures after ingestion : Do NOT induce vomiting. Obtain emergency medical attention. Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after inhalation : May cause an allergic skin reaction. Symptoms/effects after skin contact : May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

3/28/2022 (Revision date) EN (English) 3/18

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Protection during firefighting

: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures

: Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure

controls/personal protection".

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment

Other information

: Collect spillage.

Methods for cleaning up

: Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Do not get in eyes, on skin, or on clothing. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures

: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep only in the original container in a cool, well ventilated place away from : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Store in a well-ventilated place. Keep cool.

Incompatible products Incompatible materials

: Strong bases. Strong acids.: Sources of ignition. Direct sunlight.

Storage temperature

: 25 °C

Storage area

: Store in a well-ventilated place. Store away from heat.

Special rules on packaging Packaging materials

Store in a closed container.Do not store in corrodable metal.

Switzerland

Storage class (LK) : LK 10/12 - Liquids

7.3. Specific end use(s)

No additional information available

3/28/2022 (Revision date) EN (English) 4/18

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

isopentyl acetate (123-92-2)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	270 mg/m³	
	50 ppm	
IOEL STEL	540 mg/m³	
	100 ppm	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	270 mg/m³ (Pentyl acetate (all isomers))	
	50 ppm (Pentyl acetate (all isomers))	
MAK (OEL STEL)	540 mg/m³ (Pentylacetate)	
	100 ppm (Pentylacetate)	
Belgium - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Bulgaria - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA)	270 mg/m³	
	50 ppm	
KGVI (OEL STEL)	540 mg/m³	
	100 ppm	
Cyprus - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Denmark - Occupational Exposure Limits		
OEL TWA	271 mg/m³ (Amyl acetate, all isomers)	
	50 ppm (Amyl acetate, all isomers)	
OEL STEL	540 mg/m³	
	100 ppm	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

OEL TWA 270 mg/m³ 58 ppm 58 ppm OEL STEL 540 mg/m³ 100 ppm 100 ppm Finland - Occupational Exposure Limits HTP (OEL TWA) 270 mg/m³ (Pentyl acetate) 540 mg/m³ 50 ppm (Pentyl acetate) HTP (OEL STEL) 540 mg/m³ France - Occupational Exposure Limits VME (OEL TWA) 270 mg/m³ (restrictive limit) So ppm (restrictive limit) Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) 270 mg/m³ Gibraltar - Occupational Exposure Limits OEL TWA 270 mg/m³ Go ppm OEL STEL 540 mg/m³ 50 ppm OEL TWA 530 mg/m³ OEL TWA 500 ppm OEL STEL 800 mg/m³ OEL STEL 800 mg/m³ OEL STEL 800 mg/m³ OEL STEL 540 mg/m³ OEL TWA 260 mg/m³ <th colspan="3">isopentyl acetate (123-92-2)</th>	isopentyl acetate (123-92-2)		
SO ppm	Estonia - Occupational Exposure Limits		
OEL STEL 540 mg/m² 100 ppm Finland - Occupational Exposure Limits HTP (OEL TWA) 270 mg/m² (Pentyl acetate) 50 ppm (Pentyl acetate) 100 ppm France - Occupational Exposure Limits VME (OEL TWA) 270 mg/m² (restrictive limit) 50 ppm (restrictive limit) 50 ppm (restrictive limit) VLE (OEL C/STEL) 540 mg/m² (restrictive limit) 6Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) AGW (OEL TWA) 270 mg/m² 6Jbraltar - Occupational Exposure Limits 270 mg/m² OEL TWA 270 mg/m² 6Gerece - Occupational Exposure Limits 50 ppm OEL STEL 540 mg/m² 100 ppm 100 ppm OEL TWA 530 mg/m² 150 ppm 100 ppm OEL STEL 800 mg/m² K (OEL TWA) 270 mg/m² K (OEL TWA) 270 mg/m² CK (OEL STEL) 540 mg/m² L TWA 260 mg/m² OEL TWA 260 mg/m² OEL STEL 500 ppm	OEL TWA	270 mg/m³	
100 ppm		50 ppm	
Finland - Occupational Exposure Limits 270 mg/m³ (Pentyl acetate) HTP (OEL TWA) 50 ppm (Pentyl acetate) HTP (OEL STEL) 540 mg/m³ 100 ppm 100 ppm France - Occupational Exposure Limits 270 mg/m³ (restrictive limit) VME (OEL TWA) 270 mg/m³ (restrictive limit) VLE (OEL C/STEL) 540 mg/m³ (restrictive limit) MC OEL TWA) 270 mg/m³ (restrictive limit) Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) Gibraltar - Occupational Exposure Limits 270 mg/m³ OEL TWA 270 mg/m³ OEL STEL 540 mg/m³ OEL TWA 530 mg/m³ Greece - Occupational Exposure Limits 330 mg/m³ OEL STEL 800 mg/m³ Hungary - Occupational Exposure Limits 270 mg/m³ K (OEL TWA) 270 mg/m³ CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits 260 mg/m³ OEL STEL 50 ppm OEL STEL 50 ppm OEL STEL 50 ppm	OEL STEL	540 mg/m³	
HTP (OEL TWA) 270 mg/m² (Pentyl acetate) 50 ppm (Pentyl acetate) 100 ppm France - Occupational Exposure Limits VME (OEL TWA) 50 ppm (restrictive limit) VLE (OEL C/STEL) 540 mg/m² (restrictive limit) AGW (OEL TWA) 270 mg/m² 50 ppm Gibraltar - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) 270 mg/m² 50 ppm OEL STEL 540 mg/m² 100 ppm Greece - Occupational Exposure Limits OEL TWA 530 mg/m² 100 ppm OEL STEL 640 mg/m² 100 ppm OEL STEL 650 pm OEL STEL 600 mg/m² 150 ppm Hungary - Occupational Exposure Limits XK (OEL TWA) 270 mg/m² 150 ppm Hungary - Occupational Exposure Limits XK (OEL TWA) 270 mg/m² 150 ppm Hungary - Occupational Exposure Limits XK (OEL TWA) 270 mg/m² 150 ppm OEL STEL 640 mg/m² 150 ppm OEL STEL 650 mg/m² 150 ppm		100 ppm	
FO ppm (Pentyl acetate) 50 ppm (Pentyl acetate) 540 mg/m³ 100 ppm	Finland - Occupational Exposure Limits		
HTP (OEL STEL)	HTP (OEL TWA)	270 mg/m³ (Pentyl acetate)	
France - Occupational Exposure Limits VME (OEL C/STEL) 40 ppm (restrictive limit) 50 ppm (restrictive limit) 50 ppm (restrictive limit) 70 ppm (restrictive limit) 60 ppm 60 ppm		50 ppm (Pentyl acetate)	
France - Occupational Exposure Limits VME (OEL TWA) 270 mg/m³ (restrictive limit) VLE (OEL C/STEL) 540 mg/m³ (restrictive limit) Support (restrictive limit) Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) 270 mg/m³ 50 ppm Gibraltar - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm 50 ppm OEL STEL 540 mg/m³ 6 ppm OEL TWA 530 mg/m³ 100 ppm OEL STEL 800 mg/m³ Mungary - Occupational Exposure Limits Hungary - Occupational Exposure Limits AK (OEL STEL) 540 mg/m³ 10 ppm OEL TWA) 270 mg/m³ OEL TWA 260 mg/m³ OEL TWA 260 mg/m³ OEL TWA 260 mg/m³ 0 ppm OEL STEL 520 mg/m³ 0 ppm	HTP (OEL STEL)	540 mg/m³	
VME (OEL TWA)		100 ppm	
S0 ppm (restrictive limit) S40 mg/m³ (restrictive limit) 100 ppm 100	France - Occupational Exposure Limits		
VLE (OEL C/STEL) 540 mg/m³ (restrictive limit) Germany - Occupational Exposure Limits (TRGS 900) 270 mg/m³ AGW (OEL TWA) 270 mg/m³ Gibraltar - Occupational Exposure Limits 270 mg/m³ OEL TWA 270 mg/m³ 50 ppm 50 ppm OEL STEL 540 mg/m³ 100 ppm 60 ppm Greece - Occupational Exposure Limits 530 mg/m³ OEL TWA 530 mg/m³ 100 ppm 60 ppm OEL STEL 800 mg/m³ Hungary - Occupational Exposure Limits 800 mg/m³ K (OEL TWA) 270 mg/m³ CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits 50 ppm OEL TWA 260 mg/m³ 50 ppm 50 ppm OEL STEL 520 mg/m³ 100 ppm 100 ppm	VME (OEL TWA)	270 mg/m³ (restrictive limit)	
100 ppm (restrictive limit)		50 ppm (restrictive limit)	
Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) 270 mg/m³ 50 ppm 50 ppm OEL TWA 270 mg/m³ 50 ppm 50 ppm OEL STEL 540 mg/m³ Greece - Occupational Exposure Limits OEL TWA 530 mg/m³ 100 ppm 100 ppm OEL STEL 800 mg/m³ Hungary - Occupational Exposure Limits AK (OEL TWA) 270 mg/m³ CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits OEL TWA 260 mg/m³ OEL STEL 520 mg/m³ OEL STEL 520 mg/m³ 100 ppm OEL STEL 520 mg/m³ OEL STEL 520 mg/m³ OEL STEL 520 mg/m³ OEL STEL 520 mg/m³	VLE (OEL C/STEL)	540 mg/m³ (restrictive limit)	
AGW (OEL TWA) 270 mg/m³ 50 ppm CEL TWA 270 mg/m³ 50 ppm CEL TWA 270 mg/m³ 50 ppm CEL STEL 540 mg/m³ 100 ppm CEL TWA 530 mg/m³ 100 ppm CEL TWA 530 mg/m³ 100 ppm CEL STEL 800 mg/m³ 100 ppm CEL STEL 800 mg/m³ 150 ppm CEL STEL 800 mg/m³ 150 ppm CEL STEL 800 mg/m³ 150 ppm CEL STEL CEL TWA 270 mg/m³ 50 ppm CEL STEL CEL TWA 270 mg/m³ 50 ppm CEL STEL 540 mg/m³ 50 ppm CEL STEL 520 mg/m³ 50 ppm		100 ppm (restrictive limit)	
S0 ppm	Germany - Occupational Exposure Limits (TRGS 90	00)	
Gibraltar - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm 50 ppm OEL STEL 540 mg/m³ Greece - Occupational Exposure Limits OEL TWA 530 mg/m³ 100 ppm OEL STEL 800 mg/m³ Hungary - Occupational Exposure Limits AK (OEL TWA) 270 mg/m³ CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits 260 mg/m³ OEL TWA 260 mg/m³ OEL STEL 520 mg/m³ Include the proposure Limits 520 mg/m³ OEL STEL 520 mg/m³ Italy - Occupational Exposure Limits 100 ppm	AGW (OEL TWA)	270 mg/m³	
OEL TWA 270 mg/m³ 50 ppm 50 ppm OEL STEL 540 mg/m³ 100 ppm 100 ppm OEL TWA 530 mg/m³ 100 ppm OEL STEL 800 mg/m³ 150 ppm Hungary - Occupational Exposure Limits AK (OEL TWA) 270 mg/m³ CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits OEL TWA 260 mg/m³ 50 ppm OEL STEL 520 mg/m³ 100 ppm Italy - Occupational Exposure Limits		50 ppm	
S0 ppm S40 mg/m³ 100 ppm S50 mg/m³ 150 ppm S50 ppm S50 ppm S60 mg/m³	Gibraltar - Occupational Exposure Limits		
OEL STEL 540 mg/m³ 100 ppm Greece - Occupational Exposure Limits OEL TWA 530 mg/m³ 100 ppm OEL STEL 800 mg/m³ 150 ppm Hungary - Occupational Exposure Limits AK (OEL TWA) 270 mg/m³ CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits OEL TWA 260 mg/m³ 50 ppm OEL STEL 520 mg/m³ 100 ppm	OEL TWA	270 mg/m³	
100 ppm		50 ppm	
Greece - Occupational Exposure Limits OEL TWA 530 mg/m³ 100 ppm 100 ppm OEL STEL 800 mg/m³ 150 ppm Hungary - Occupational Exposure Limits AK (OEL TWA) 270 mg/m³ CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits OEL TWA 260 mg/m³ 50 ppm OEL STEL 520 mg/m³ 100 ppm Italy - Occupational Exposure Limits	OEL STEL	540 mg/m³	
OEL TWA 530 mg/m³ 100 ppm 100 ppm OEL STEL 800 mg/m³ 150 ppm 150 ppm Hungary - Occupational Exposure Limits AK (OEL TWA) 270 mg/m³ CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits OEL TWA 260 mg/m³ 50 ppm OEL STEL 520 mg/m³ 100 ppm Italy - Occupational Exposure Limits		100 ppm	
100 ppm 100 ppm	Greece - Occupational Exposure Limits		
OEL STEL 800 mg/m³ Hungary - Occupational Exposure Limits AK (OEL TWA) 270 mg/m³ CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits OEL TWA 260 mg/m³ 50 ppm 50 ppm OEL STEL 520 mg/m³ Italy - Occupational Exposure Limits	OEL TWA	530 mg/m³	
150 ppm		100 ppm	
Hungary - Occupational Exposure Limits AK (OEL TWA) CK (OEL STEL) Ireland - Occupational Exposure Limits OEL TWA 260 mg/m³ 50 ppm OEL STEL 520 mg/m³ 100 ppm Italy - Occupational Exposure Limits	OEL STEL	800 mg/m³	
AK (OEL TWA) 270 mg/m³ CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits OEL TWA 260 mg/m³ 50 ppm OEL STEL 520 mg/m³ 100 ppm Italy - Occupational Exposure Limits		150 ppm	
CK (OEL STEL) 540 mg/m³ Ireland - Occupational Exposure Limits OEL TWA 260 mg/m³ 50 ppm OEL STEL 520 mg/m³ 100 ppm Italy - Occupational Exposure Limits	Hungary - Occupational Exposure Limits		
Ireland - Occupational Exposure Limits OEL TWA 260 mg/m³ 50 ppm OEL STEL 520 mg/m³ 100 ppm Italy - Occupational Exposure Limits	AK (OEL TWA)	270 mg/m³	
OEL TWA 260 mg/m³ 50 ppm 50 ppm OEL STEL 520 mg/m³ 100 ppm Italy - Occupational Exposure Limits	CK (OEL STEL)	540 mg/m³	
50 ppm	Ireland - Occupational Exposure Limits		
OEL STEL 520 mg/m³ 100 ppm Italy - Occupational Exposure Limits	OEL TWA	260 mg/m³	
100 ppm Italy - Occupational Exposure Limits		50 ppm	
Italy - Occupational Exposure Limits	OEL STEL	520 mg/m³	
		100 ppm	
OFI TWA 270 mg/m³	Italy - Occupational Exposure Limits		
2 ····	OEL TWA	270 mg/m³	
50 ppm		50 ppm	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

OEL STEL 540 mg/m² Latvia - Occupational Exposure Limits 270 mg/m² DEL TWA 270 mg/m² 50 ppm 50 ppm Lithuania - Occupational Exposure Limits 270 mg/m² TPRY (OEL TWA) 270 mg/m² 540 mg/m² 100 ppm Luxembourg - Occupational Exposure Limits 270 mg/m² CEL TWA 270 mg/m² 50 ppm 50 ppm OEL STEL 540 mg/m² 100 ppm 100 ppm Mata - Occupational Exposure Limits 270 mg/m² OEL TWA 50 ppm Networkands - Occupational Exposure Limits TO ppm Networkands - Occupational Exposure Limits 500 mg/m² NBS (OEL TWA) 500 mg/m² NBS (DEL TWA) 500 mg/m² NBS (DEL TWA) 500 mg/m² OEL STEL 500 mg/m² OEL STEL 500 mg/m² OEL STEL 540 mg/m² (indicative lim	isopentyl acetate (123-92-2)		
Latvia - Occupational Exposure Limits DEL TWA 270 mg/m³ 50 ppm 50 ppm Lithwania - Occupational Exposure Limits Lithwania - Occupational Exposure Limits TPRY (OEL STEL) 270 mg/m³ 50 ppm 50 ppm CEL TWA 270 mg/m³ 50 ppm 50 ppm OEL STEL 540 mg/m³ 50 ppm 50 ppm OEL TWA 270 mg/m³ Matta - Occupational Exposure Limits OEL STEL 270 mg/m³ 50 ppm 50 ppm OEL STEL 540 mg/m³ 50 ppm 50 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) 550 mg/m³ 58.1 ppm 58.1 ppm Polaria (Occupational Exposure Limits NDS (OEL TWA) 50 ppm (indicative limit value) 50 ppm (indicative limit value) 50 ppm (indicative limit value) 60 ppm (indicative limit value) 50 ppm (indicative limit value) 60	OEL STEL	540 mg/m³	
QET TWA 270 mg/m² Lithuania - Occupational Exposure Limits 270 mg/m² 1PRY (OEL TWA) 270 mg/m² 50 ppm 50 ppm TPRV (OEL STEL) 540 mg/m² 100 ppm 100 ppm Luxembourg - Occupational Exposure Limits 270 mg/m² 60 ppm 50 ppm OEL TWA 540 mg/m² 640 mg/m² 100 ppm Malta - Occupational Exposure Limits 270 mg/m² OEL TWA 540 mg/m² 640 mg/m² 100 ppm Netherlands - Occupational Exposure Limits 270 mg/m² Netherlands - Occupational Exposure Limits 540 mg/m² NDS (OEL STEL) 550 mg/m² 98 n ppm 9 Poland - Occupational Exposure Limits V NDS (OEL TWA) 250 mg/m² 90 mg/m² 9 Portugal - Occupational Exposure Limits V Portugal - Occupational Exposure Limits 00 mg/m² OEL TWA 270 mg/m² (indicative limit value) 0EL TWA 100 ppm (indicative limit value) 0EL TWA <t< td=""><td></td><td>100 ppm</td></t<>		100 ppm	
Lithuania - Occupational Exposure Limits IPRY (OEL TWA) 270 mg/m² 50 pm 500 pm TPRY (OEL STEL) 540 mg/m² 100 ppm 100 ppm Luxembourg - Occupational Exposure Limits 270 mg/m² CEL TWA 540 mg/m² DEL STEL 540 mg/m² 100 ppm 100 ppm Matra - Occupational Exposure Limits 270 mg/m³ 50 pm 50 pm OEL STEL 540 mg/m³ 60 pm 50 pm OEL STEL 540 mg/m³ 100 ppm 100 ppm Netherlands - Occupational Exposure Limits 550 mg/m³ 7G-15min (OEL STEL) 550 mg/m³ 98.1 ppm 90 mg/m³ 90.1 ppm 90 mg/m³ NDS (OEL STEL) 500 mg/m³ NDS (OEL STEL) 500 mg/m³ NDS (OEL STEL) 500 mg/m³ (indicative limit value) Portugal - Occupational Exposure Limits 100 ppm (indicative limit value) (Pentyl acctate, all isomers) OEL STEL 500 mg/m³ (indicative limit value) 100 ppm (indic	Latvia - Occupational Exposure Limits		
Lithuania - Occupational Exposure Limits 270 mg/m³ IPRY (OEL TWA) 270 mg/m³ 50 ppm 50 ppm TERY (OEL STEL) 540 mg/m³ 100 ppm 100 ppm CEL TWA 270 mg/m³ 50 ppm 50 ppm OEL STEL 540 mg/m³ 50 ppm 70 ppm OEL STEL 540 mg/m³ 50 ppm 70 ppm OEL STEL 540 mg/m³ 50 ppm 70 ppm Netherlands - Occupational Exposure Limits 70 ppm Poland - Occupational Exposure Limits 70 ppm Poland - Occupational Exposure Limits 70 ppm/m³ NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits 70 mg/m³ (indicative limit value) OEL STEL 540 mg/m² (indicative limit value) 100 ppm (indicative limit value) 70 ppm (indicative limit value) Romania - Occupational Exposure Limits 70 ppm (indicative limit value) OEL STEL 540 mg/m² <td>OEL TWA</td> <td>270 mg/m³</td>	OEL TWA	270 mg/m³	
IPRY (OEL TWA) 270 mg/m² 50 ppm TPRY (OEL STEL) 540 mg/m² Luxembourg - Occupational Exposure Limits 270 mg/m² CEL TWA 270 mg/m³ OEL STEL 540 mg/m³ 0EL STEL 540 mg/m³ 0EL TWA 270 mg/m³ 0EL TWA 270 mg/m³ 0EL TWA 50 ppm 0EL STEL 540 mg/m³ 0EL STEL 550 mg/m³ 0EL STEL 550 mg/m³ 0EL STEL 550 mg/m³ NDS (OEL STEL) 550 mg/m³ NDS (OEL TWA) 250 mg/m³ (indicative limit value) OEL STEL 260 mg/m³ (indicative limit value) 100 ppm (indicative limit value) 100 p		50 ppm	
Part	Lithuania - Occupational Exposure Limits		
TPRV (OEL STEL)	IPRV (OEL TWA)	270 mg/m³	
DOD pm		50 ppm	
Luxembourg - Occupational Exposure Limits 270 mg/m³ OEL STEL 540 mg/m³ 50 ppm 50 ppm OEL STEL 540 mg/m³ 100 ppm 100 ppm Malta - Occupational Exposure Limits 270 mg/m³ OEL STEL 540 mg/m³ 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) 530 mg/m³ 98.1 ppm 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits 270 mg/m³ (indicative limit value) OEL TWA 270 mg/m³ (indicative limit value) (Pentyl acetate, all isomers) OEL STEL 540 mg/m³ (indicative limit value) 100 ppm (indicative limit value) 100 ppm (indicative limit value) OEL TWA 270 mg/m³ OEL STEL 540 mg/m³ OEL TWA 270 mg/m³ OEL TWA 270 mg/m³ OEL TWA 270 mg/m³ OEL TWA 270 mg/m³ OCCUpational Exposure Limits 100 ppm <td>TPRV (OEL STEL)</td> <td>540 mg/m³</td>	TPRV (OEL STEL)	540 mg/m³	
OEL TWA 270 mg/m³ 50 ppm 50 ppm OEL STEL \$40 mg/m³ Malta - Occupational Exposure Limits 270 mg/m³ OEL TWA 270 mg/m³ 50 ppm 50 ppm Netherlands - Occupational Exposure Limits 540 mg/m³ Netherlands - Occupational Exposure Limits 530 mg/m³ Poland - Occupational Exposure Limits 530 mg/m³ NDS (OEL TWA) 250 mg/m³ NDS (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits 270 mg/m³ (indicative limit value) OEL TWA 270 mg/m³ (indicative limit value (Pentyl acetate, all isomers) OEL STEL 540 mg/m³ (indicative limit value) Romania - Occupational Exposure Limits 270 mg/m³ (indicative limit value) OEL TWA 270 mg/m³ (indicative limit value) OEL TWA 270 mg/m³ (indicative limit value) OEL TWA 50 ppm OEL TWA 270 mg/m³ (indicative limit value) OEL TWA 270 mg/m³ (indicative limit value) OEL TWA 270 mg/m³ (indicative limit value) OEL TWA 270 mg/m³ (indicative limit value) <td></td> <td>100 ppm</td>		100 ppm	
S0 ppm	Luxembourg - Occupational Exposure Limits		
OEL STEL 540 mg/m³ Malta - Occupational Exposure Limits 270 mg/m³ OEL TWA 270 mg/m³ OEL STEL 540 mg/m³ 0EL STEL 540 mg/m³ Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) TGG-15min (OEL STEL) 530 mg/m³ 98.1 ppm 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDS (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits 270 mg/m³ (indicative limit value) OEL TWA 270 mg/m³ (indicative limit value) OEL STEL 540 mg/m³ (indicative limit value) Romania - Occupational Exposure Limits 270 mg/m³ OEL TWA 270 mg/m³ OEL STEL 540 mg/m³ 50 ppm 00 ppm Slovakia - Occupational Exposure Limits NPHY (OEL TWA) NPHY (OEL TWA) 270 mg/m³	OEL TWA	270 mg/m³	
Malta - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) 530 mg/m³ 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) 50 ppm (indicative limit value) OEL STEL 540 mg/m³ (indicative limit value) 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm (indicative limit value) 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) 270 mg/m³ 100 ppm		50 ppm	
Malta - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm 540 mg/m³ 100 ppm 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) 530 mg/m³ 98.1 ppm 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDS (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) 50 ppm (indicative limit value) 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ 50 ppm 50 ppm OEL STEL 540 mg/m³ 50 ppm 50 ppm OEL STEL 540 mg/m³ 50 ppm 100 ppm Slovakia - Occupational Exposure Limits 270 mg/m³ NPHY (OEL TWA) 270 mg/m³	OEL STEL	540 mg/m³	
OEL TWA 270 mg/m³ 50 ppm 540 mg/m³ OEL STEL 540 mg/m³ Netherlands - Occupational Exposure Limits 530 mg/m³ TGG-15min (OEL STEL) 530 mg/m³ 98.1 ppm 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) 50 ppm (indicative limit value) 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm 50 ppm OEL STEL 540 mg/m³ 50 ppm 70 ppm OEL STEL 270 mg/m³		100 ppm	
S0 ppm S40 mg/m³ 100 ppm S40 mg/m³ S40 m	Malta - Occupational Exposure Limits		
OEL STEL 540 mg/m³ 100 ppm Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) 530 mg/m³ 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) 50 ppm (indicative limit value) (Pentyl acetate, all isomers) OEL STEL 540 mg/m³ (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ OEL STEL 540 mg/m³ Slovakia - Occupational Exposure Limits NPHV (OEL TWA)	OEL TWA	270 mg/m³	
Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) 530 mg/m³ 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) 50 ppm (indicative limit value) (Pentyl acetate, all isomers) OEL STEL 540 mg/m³ (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) 50 ppm (indicative limit value) 50 ppm (indicative limit value) 50 ppm (indicative limit value) 80 ppm (indicative limit value) SUBJECT (STEL) 540 mg/m³ 540 mg/m³ 100 ppm SIovakia - Occupational Exposure Limits NPHV (OEL TWA) 270 mg/m³		50 ppm	
Netherlands - Occupational Exposure Limits TGG-15min (OEL STEL) 530 mg/m³ 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) 50 ppm (indicative limit value) 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ 100 ppm	OEL STEL	540 mg/m³	
TGG-15min (OEL STEL) 530 mg/m³ 98.1 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 250 mg/m³ NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) 50 ppm (indicative limit value) 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) 270 mg/m³		100 ppm	
Poland - Occupational Exposure Limits NDS (OEL TWA) DSCh (OEL STEL) Portugal - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) 50 ppm (indicative limit value) 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) 270 mg/m³ 270 mg/m³ 270 mg/m³	Netherlands - Occupational Exposure Limits		
Poland - Occupational Exposure Limits NDS (OEL TWA) DSCh (OEL STEL) Portugal - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) 50 ppm (indicative limit value) (Pentyl acetate, all isomers) OEL STEL 540 mg/m³ (indicative limit value) 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) 270 mg/m³ 270 mg/m³ 300 ppm	TGG-15min (OEL STEL)	530 mg/m³	
NDS (OEL TWA) NDSCh (OEL STEL) 500 mg/m³ Portugal - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) 50 ppm (indicative limit value) (Pentyl acetate, all isomers) OEL STEL 540 mg/m³ (indicative limit value) 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) 270 mg/m³ 270 mg/m³ 270 mg/m³ 3		98.1 ppm	
NDSCh (OEL STEL) Portugal - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) 50 ppm (indicative limit value (Pentyl acetate, all isomers) OEL STEL 540 mg/m³ (indicative limit value) 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) 270 mg/m³ 270 mg/m³ 270 mg/m³	Poland - Occupational Exposure Limits		
Portugal - Occupational Exposure Limits OEL TWA 270 mg/m³ (indicative limit value) 50 ppm (indicative limit value (Pentyl acetate, all isomers) OEL STEL 540 mg/m³ (indicative limit value) 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) 270 mg/m³ 270 mg/m³	NDS (OEL TWA)	250 mg/m³	
OEL TWA 270 mg/m³ (indicative limit value) 50 ppm (indicative limit value (Pentyl acetate, all isomers) OEL STEL 540 mg/m³ (indicative limit value) 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) 270 mg/m³ 270 mg/m³ 100 ppm	NDSCh (OEL STEL)	500 mg/m³	
50 ppm (indicative limit value (Pentyl acetate, all isomers) OEL STEL 540 mg/m³ (indicative limit value) 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) 270 mg/m³ 270 mg/m³	Portugal - Occupational Exposure Limits		
OEL STEL 540 mg/m³ (indicative limit value) 100 ppm (indicative limit value) Romania - Occupational Exposure Limits OEL TWA 270 mg/m³ 50 ppm OEL STEL 540 mg/m³ 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) 270 mg/m³ 270 mg/m³ 270 mg/m³	OEL TWA	270 mg/m³ (indicative limit value)	
100 ppm (indicative limit value) Romania - Occupational Exposure Limits 270 mg/m³ 50 ppm		50 ppm (indicative limit value (Pentyl acetate, all isomers)	
Romania - Occupational Exposure Limits 270 mg/m³ 50 ppm	OEL STEL	540 mg/m³ (indicative limit value)	
OEL TWA 270 mg/m³ 50 ppm 50 ppm OEL STEL 540 mg/m³ 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) 270 mg/m³		100 ppm (indicative limit value)	
50 ppm 50 ppm 540 mg/m³ 100 ppm	Romania - Occupational Exposure Limits		
OEL STEL 540 mg/m³ 100 ppm Slovakia - Occupational Exposure Limits NPHV (OEL TWA) 270 mg/m³	OEL TWA	270 mg/m³	
Slovakia - Occupational Exposure Limits NPHV (OEL TWA) 270 mg/m³		50 ppm	
Slovakia - Occupational Exposure Limits NPHV (OEL TWA) 270 mg/m³	OEL STEL	540 mg/m³	
NPHV (OEL TWA) 270 mg/m³		100 ppm	
	Slovakia - Occupational Exposure Limits		
50 ppm	NPHV (OEL TWA)	270 mg/m³	
		50 ppm	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

isopentyl acetate (123-92-2)		
NPHV (OEL C)	540 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	270 mg/m³ (indicative limit value)	
	50 ppm (indicative limit value)	
VLA-EC (OEL STEL)	540 mg/m³	
	100 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	270 mg/m³ (Pentyl acetates)	
	50 ppm (Pentyl acetates)	
KGV (OEL STEL)	540 mg/m³ (Pentyl acetates)	
	100 ppm (Pentyl acetates)	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA)	260 mg/m³	
	50 ppm	
Korttidsverdi (OEL STEL)	325 mg/m³ (value calculated)	
	75 ppm (value calculated)	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	260 mg/m³ (Pentyl acetate all isomers)	
	50 ppm (Pentyl acetate all isomers)	
KZGW (OEL STEL)	260 mg/m³ (Pentyl acetate all isomers)	
	50 ppm (Pentyl acetate all isomers)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	50 ppm (Pentyl acetate, all isomers)	
ACGIH OEL STEL	100 ppm (Pentyl acetate, all isomers)	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):





8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask. [In case of inadequate ventilation] wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : light yellow. amber. Conforms to standard.

Odour : characteristic. characteristic.

Odour threshold : Not available Melting point : Not applicable Freezing point : Not available : Not available Boiling point Flammability : Not applicable Lower explosion limit : Not available Upper explosion limit : Not available Flash point : 93 °C Auto-ignition temperature : Not available

Decomposition temperature : Not available pH : Not available Viscosity, kinematic : Not available Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Vapour pressure : 0.004366566 mm Hg (calculated value)

Vapour pressure at 50°C : Not available Density : Not available

Relative density : ≈ 1

Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 1.3 % (calculated value)(CARB VOC) (%w/w)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.

Acute toxicity (dermal) : Harmful in contact with skin.

Acute toxicity (inhalation) : Inhalation:dust,mist: Harmful if inhaled.

,	The state of the s	
COCONUT CANDY CC-16401		
ATE CLP (oral)	411.523 mg/kg bodyweight	
ATE CLP (dermal)	1674.286 mg/kg bodyweight	
ATE CLP (dust,mist)	2.857 mg/l/4h	
benzyl benzoate (120-51-4)		
LD50 oral rat	500 mg/kg (Source: NLM_CIP)	
LD50 oral	1160 mg/kg bodyweight	
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)	
Resin acids and Rosin acids, hydrogenated, methyl esters (8050-15-5)		
LD50 oral rat	> 2000 mg/kg (Source: CHEMVIEW)	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Resin acids and Rosin acids, hydrogenated, methyl esters (8050-15-5)		
LD50 dermal rabbit	> 10000 mg/kg (Source: ECHA_API)	
COUMARIN (91-64-5)		
LD50 oral rat	> 5000 mg/kg (Source: JAPAN_GHS)	
LD50 dermal rat	293 mg/kg (Source: ECHA_API)	
Ethyl vanillin (121-32-4)		
LD50 oral rat	1590 mg/kg (Source: NLM_CIP)	
LD50 oral	3000 mg/kg bodyweight	
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)	
Triplal (Vertocitral) (68039-49-6)		
LD50 oral	2330 mg/kg	
Skin corrosion/irritation	: Not classified	
Serious eye damage/irritation	: Not classified	
Respiratory or skin sensitisation	: May cause an allergic skin reaction.	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
COUMARIN (91-64-5)		
IARC group	3 - Not classifiable	
Reproductive toxicity	: Not classified	
STOT-single exposure	: Not classified	
STOT-repeated exposure	: Not classified	
Aspiration hazard	: Not classified	
benzyl benzoate (120-51-4)		
Viscosity, kinematic	7.456 mm²/s	
	· · · · · · · · · · · · · · · · · · ·	

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects. Very toxic to aquatic life. Toxic to aquatic life

> with long lasting effects. : Very toxic to aquatic life.

Ecology - water Hazardous to the aquatic environment, short-term

(acute)

: Very toxic to aquatic life.

Hazardous to the aquatic environment, long-term : Toxic to aquatic life with long lasting effects.

(chronic)

(critorile)	
benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
NOEC (chronic)	0.168 mg/l

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethyl vanillin (121-32-4)	
	81.4 – 94.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)

12.2. Persistence and degradability

COCONUT CANDY CC-16401		
Persistence and degradability	Not established.	
benzyl benzoate (120-51-4)		
Persistence and degradability	May cause long-term adverse effects in the environment.	
Resin acids and Rosin acids, hydrogenated, n	nethyl esters (8050-15-5)	
Persistence and degradability	Rapidly degradable	
COUMARIN (91-64-5)		
Persistence and degradability	Rapidly degradable	
Ethyl vanillin (121-32-4)		
Persistence and degradability	Rapidly degradable	
isopentyl acetate (123-92-2)		
Persistence and degradability	Rapidly degradable	
Triplal (Vertocitral) (68039-49-6)		
Persistence and degradability	Rapidly degradable	

12.3. Bioaccumulative potential

COCONUT CANDY CC-16401		
Bioaccumulative potential	Not established.	
benzyl benzoate (120-51-4)		
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)	
Bioaccumulative potential	Not established.	
Resin acids and Rosin acids, hydrogenated, methyl esters (8050-15-5)		
Partition coefficient n-octanol/water (Log Pow)	6.4 – 7.6 (at pH 6)	
Ethyl vanillin (121-32-4)		
Partition coefficient n-octanol/water (Log Pow)	1.61 (at 25 °C)	
isopentyl acetate (123-92-2)		
Partition coefficient n-octanol/water (Log Pow)	2.7 (at 35 °C)	

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.7. Other adverse effects

Additional information

: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

Product/Packaging disposal recommendations

Ecological information HP Code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Dispose of contents/container in accordance with local/national laws and regulations. Dispose in a safe manner in accordance with local/national regulations.
- : Avoid release to the environment.
- : HP6 "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.

 $\mbox{HP4}$ - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shippin	g name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	Environmentally hazardous substance, liquid, n.o.s. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)
Transport document descr	iption			
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Benzyl Benzoate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III
14.3. Transport hazard o	class(es)			
9	9	9	9	9
	9			9
14.4. Packing group				
III	III	Ш	Ш	III
14.5. Environmental haz	zards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : M6

Special provisions (ADR) : 274, 335, 375, 601

Limited quantities (ADR) : 5I Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4

Portable tank and bulk container special provisions : TP1, TP29

(ADR)

Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading : CV13

and handling (ADR)

Hazard identification number (Kemler No.) : 90

Orange plates :

90 3082

Tunnel restriction code (ADR) : -EAC code : •3Z

Transport by sea

Special provisions (IMDG) : 274, 335, 969

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : LP01, P001

Special packing provisions (IMDG) : PP1

IBC packing instructions (IMDG) : IBC03

Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP1, TP29

EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-F
Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1

PCA Limited quantities (IATA) : Y964

PCA limited quantity max net quantity (IATA) : 30kgG

PCA packing instructions (IATA) : 964

PCA max net quantity (IATA) : 450L

CAO packing instructions (IATA) : 964

CAO max net quantity (IATA) : 450L

Special provisions (IATA) : A97, A158, A197, A215

ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M6

Special provisions (ADN) : 274, 335, 375, 601

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Carriage permitted (ADN) : T

Equipment required (ADN) : PP

Number of blue cones/lights (ADN) : 0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Rail transport

Classification code (RID) : M6

Special provisions (RID) : 274, 335, 375, 601

Limited quantities (RID) : 5L Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions : TP1, TP29

(RID)

Tank codes for RID tanks (RID) : LGBV
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12

Special provisions for carriage - Loading, unloading : CW13, CW31

and handling (RID)

Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	isopentyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	COCONUT CANDY CC-16401 ; benzyl benzoate ; Triplal (Vertocitral)	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	COCONUT CANDY CC-16401; benzyl benzoate; Resin acids and Rosin acids, hydrogenated, methyl esters; Triplal (Vertocitral)	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	isopentyl acetate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

VOC Directive (2004/42)

VOC content : 1.3 % (calculated value)(CARB VOC) (%w/w)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases		
Code	Description	
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide	

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(1) - highly toxic for aquatic organisms, may have longterm hazardous effects in aquatic

environment

SZW-lijst van kankerverwekkende stoffen : Resin acids and Rosin acids, hydrogenated, methyl esters, Triplal (Vertocitral) are listed

SZW-lijst van mutagene stoffen : Resin acids and Rosin acids, hydrogenated, methyl esters, Triplal (Vertocitral) are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed SZW-lijst van reprotoxische stoffen – : None of the components are listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Class for fire hazard : Class III-1 Store unit : 50 liter

Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines

for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

3/28/2022 (Revision date) EN (English) 16/18

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 16: Other information

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disrupting properties	

Other information : None.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
H226	Flammable liquid and vapour.	
H301	Toxic if swallowed.	
H302	Harmful if swallowed.	
H311	Toxic in contact with skin.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H331	Toxic if inhaled.	
H332	Harmful if inhaled.	
H400	Very toxic to aquatic life.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.