Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Issue date: 1/2/2024



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : BIRTHDAY CAKE CC-16438 UFI : DCXX-08S0-K00Y-TQGR

Product code : CC-16438

Type of product : Perfumes, fragrances Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

: Professional use,Industrial use Main use category

Industrial/Professional use spec : Industrial

> For professional use only : Perfumes, fragrances : Odour agents

Function or use category

1.2.2. Uses advised against No additional information available

Use of the substance/mixture

1.3. Details of the supplier of the safety data sheet

Candle Craft Weiherwiese 10 65510 Idstein - Germany T 49-6126-9363 -0

info@candlecraft.de - www.candlecraft.de

1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731;

Brazil: +0-800-591-6042: India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H302 Skin corrosion/irritation, Category 2 H315 Serious eye damage/eye irritation, Category 2 H319 Skin sensitisation, Category 1 H317 H412 Hazardous to the aquatic environment - Chronic Hazard,

Category 3

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Safety Data Sheet

Precautionary statements (CLP)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

GHS07

Signal word (CLP) : Warning

Contains : Vertenex; benzyl alcohol; Hexyl cinnamic aldehyde; benzyl benzoate; COUMARIN; Linalool;

Ethyl maltol; Acetyl Propionyl; Heliotropine; 1,2-Cyclopentanedione, 3-methyl-

Hazard statements (CLP) : H302 - Harmful if swallowed.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.

H412 - Harmful to aquatic life with long lasting effects.

: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

Extra phrases : For professional users only.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Vertenex	CAS-No.: 32210-23-4 EC-No.: 250-954-9 REACH-no: 01-2119976286- 24	5.5 – 11	Skin Sens. 1B, H317
benzyl alcohol substance with national workplace exposure limit(s) (BG, CZ, DE, FI, LT, LV, PL, SI, CH)	CAS-No.: 100-51-6 EC-No.: 202-859-9 EC Index-No.: 603-057-00-5 REACH-no: 01-2119492630-	5 – 9.99	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Bis(2-ethylhexyl) adipate substance with national workplace exposure limit(s) (PL)	CAS-No.: 103-23-1 EC-No.: 203-090-1 REACH-no: 01-2119439699-	5 – 9.99	Not classified
Hexyl cinnamic aldehyde	CAS-No.: 101-86-0 EC-No.: 202-983-3 REACH-no: 01-2119533092- 50	5 – 9.99	Skin Sens. 1, H317 Aquatic Chronic 2, H411
benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371- 33	1.6 – 3.141	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
COUMARIN	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756- 26	1.3 – 2.5	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Anisic aldehyde	CAS-No.: 123-11-5 EC-No.: 204-602-6 REACH-no: 01-2119977101- 43	1.3 – 2.5	Aquatic Chronic 3, H412
Vanillin	CAS-No.: 121-33-5 EC-No.: 204-465-2 REACH-no: 01-2119516040- 60	1.3 – 2.5	Eye Irrit. 2, H319
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016- 42	1.3 – 2.5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Ethyl maltol	CAS-No.: 4940-11-8 EC-No.: 225-582-5	1 – 2	Acute Tox. 4 (Oral), H302
Acetyl Propionyl substance with national workplace exposure limit(s) (DE, SI, CH)	CAS-No.: 600-14-6 EC-No.: 209-984-8	0.3 – 0.5	Flam. Liq. 2, H225 Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT RE 2, H373
Heliotropine	CAS-No.: 120-57-0 EC-No.: 204-409-7 REACH-no: 01-2119983608- 21	0.1 – 0.249	Skin Sens. 1B, H317
ethyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-	0.1 – 0.2	Flam. Liq. 1, H224 Eye Irrit. 2, H319 STOT SE 3, H336
1,2-Cyclopentanedione, 3-methyl-	CAS-No.: 765-70-8 EC-No.: 212-154-8	0.1 – 0.1	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash

occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

1/2/2024 (Issue date) EN (English) 3/20

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing

dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear

personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always

wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

Storage temperature : 25 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container.
Packaging materials : Do not store in corrodable metal.

1/2/2024 (Issue date) EN (English) 4/20

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Germany

Storage class (LGK, TRGS 510)

Joint storage table

: LGK 10 - Combustible liquids

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for

Joint storage with restrictions permitted for

Joint storage permitted for

: LGK 1, LGK 2A, LGK 5.1A, LGK 6.2, LGK 7

: LGK 4.1A, LGK 4.2, LGK 4.3, LGK 5.1B, LGK 5.1C, LGK 5.2

 $: \mathsf{LGK}\,\mathsf{2B}, \mathsf{LGK}\,\mathsf{3}, \mathsf{LGK}\,\mathsf{4.1B}, \mathsf{LGK}\,\mathsf{6.1A}, \mathsf{LGK}\,\mathsf{6.1B}, \mathsf{LGK}\,\mathsf{6.1C}, \mathsf{LGK}\,\mathsf{6.1D}, \mathsf{LGK}\,\mathsf{8A}, \mathsf{LGK}\,\mathsf{8B},$

LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13

Switzerland

Storage class (LK) : LK 10/12 - Liquids

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

benzyl alcohol (100-51-6)		
Bulgaria - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	40 mg/m³	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	45 mg/m³	
	10 ppm	
Germany - Occupational Exposure Limits (TRGS 90	0)	
AGW (OEL TWA)	22 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Chemical category	Skin notation	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
OEL chemical category	Skin notation	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	240 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	22 mg/m³	

Safety Data Sheet

benzyl alcohol (100-51-6)		
	5 ppm	
OEL STEL	44 mg/m³	
	10 ppm	
OEL chemical category	Potential for cutaneous absorption	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	22 mg/m³ (aerosol, vapour)	
	5 ppm (aerosol, vapour)	
OEL chemical category	Skin notation	
Bis(2-ethylhexyl) adipate (103-23-1)		
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	400 mg/m³	
Acetyl Propionyl (600-14-6)		
Germany - Occupational Exposure Limits (TRGS 90	00)	
AGW (OEL TWA)	0.083 mg/m³	
	0.02 ppm	
Chemical category	Skin notation, Skin sensitization	
Slovenia - Occupational Exposure Limits		
OEL TWA	0.083 mg/m³	
	0.02 ppm	
OEL STEL	0.083 mg/m³	
	0.02 ppm	
OEL chemical category	Potential for cutaneous absorption	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	0.08 mg/m³	
	0.02 ppm	
KZGW (OEL STEL)	0.16 mg/m³	
	0.04 ppm	
OEL chemical category	Sensitizer, Skin notation	
ethyl acetate (141-78-6)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	734 mg/m³	
	200 ppm	
IOEL STEL	1468 mg/m³	
	400 ppm	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	734 mg/m³	
	200 ppm	
MAK (OEL STEL)	1468 mg/m³	

Safety Data Sheet

Mod ppm	ethyl acetate (141-78-6)		
OEL TWIA 754 mg/m³ OEL STEL 468 mg/m³ 0b pm 400 ppm Butgaria - Occupational Exposure Limits 754 mg/m³ 200 ppm 200 ppm OEL STEL 468 mg/m³ 200 ppm 200 ppm Croatia - Occupational Exposure Limits 734 mg/m³ 6VI (OEL TWA) 734 mg/m³ 200 ppm 468 mg/m³ 400 ppm 400 ppm Cyprus - Occupational Exposure Limits 734 mg/m³ OEL TWA 734 mg/m³ 200 ppm 468 mg/m³ 400 ppm 400 ppm Czech Republic - Occupational Exposure Limits 744 mg/m³ Czech Republic - Occupational Exposure Limits 750 mg/m³ Denmark - Occupational Exposure Limits 750 mg/m³ Denmark - Occupational Exposure Limits 750 mg/m³ Det TWA 540 mg/m³ 400 ppm 450 ppm Det TWA 550 mg/m³ 550 mg/m³ 550 ppm		400 ppm	
DEL STEL 1468 mg/m³ Bulgaria - Occupational Exposure Limits 734 mg/m³ DEL STEL 1468 mg/m³ DEL TWA 734 mg/m³ 200 ppm 700 ppm Croatia - Occupational Exposure Limits 734 mg/m³ CYI (OEL TWA) 734 mg/m³ 200 ppm KGYI (OEL STEL) 1468 mg/m³ 400 ppm CYPTUS - Occupational Exposure Limits CYPTUS - OCCUpational Exposure Limits CEL TWA 734 mg/m³ 400 ppm CEL STEL 1468 mg/m³ 400 ppm CEL STEL 700 mg/m³ DEL (CEL TWA) 700 mg/m³ DEL (CEL TWA) 700 mg/m³ DEL TWA 540 mg/m³ 150 ppm OEL STEL 150 ppm OEL STEL 1468 mg/m³ 400 ppm DEL STEL 150 ppm 0EL STEL 150 ppm 0EL STEL 150 ppm	Belgium - Occupational Exposure Limits	·	
QEL STEL 1468 mg/m³ Bulgaria - Occupational Exposure Limits 734 mg/m³ QEL TWA 734 mg/m³ 200 ppm 400 ppm CTOSALE - OCCUPATIONAL EXPOSURE LIMITS 1468 mg/m³ 200 ppm 200 ppm KEYI (OEL TWA) 734 mg/m³ 200 ppm 400 ppm CYPTUS - OCCUPATIONAL EXPOSURE LIMITS 1468 mg/m³ 200 ppm 200 ppm CEL TWA 734 mg/m³ 200 ppm 200 ppm CEL STEL 1468 mg/m³ 400 ppm 400 ppm CECCENTREQUISIONAL EXPOSURE LIMITS 700 mg/m³ DEL (DEL TWA) 700 mg/m³ DEL TWA 540 mg/m³ 150 ppm OEL STEL 150 ppm OEL STEL 1468 mg/m³ 400 ppm 400 ppm DEL STEL 1468 mg/m³ 150 ppm 400 ppm DEL STEL 1468 mg/m³ 150 ppm 400 ppm DEL STEL	OEL TWA	734 mg/m³	
Bulgaria - Occupational Exposure Limits		200 ppm	
Bulgaria - Occupational Exposure Limits	OEL STEL	1468 mg/m³	
OEL TWA 734 mg/m³ 200 ppm 200 ppm OEL STEL 1468 mg/m³ 400 ppm 400 ppm Croatia - Occupational Exposure Limits 734 mg/m³ 200 ppm 200 ppm KGVI (OEL STEL) 1468 mg/m³ 400 ppm 400 ppm Cyprus - Occupational Exposure Limits 734 mg/m³ 200 ppm 200 ppm OEL TWA 1468 mg/m³ 400 ppm 400 ppm Czech Republic - Occupational Exposure Limits 700 mg/m³ Denmark - Occupational Exposure Limits 540 mg/m³ OEL TWA 540 mg/m³ 150 ppm 400 ppm Estonia - Occupational Exposure Limits 500 mg/m³ OEL TWA 500 mg/m³ 150 ppm 1500 mg/m³		400 ppm	
200 ppm OEL STEL 1468 mg/m³ 400 ppm Creatia - Occupational Exposure Limits GYI (OEL TWA) 734 mg/m³ 200 ppm KGVI (OEL STEL) 1468 mg/m³ 400 ppm Cyprus - Occupational Exposure Limits CPL TWA 60 ppm CPL TWA 734 mg/m³ 200 ppm Cech Republic - Occupational Exposure Limits PEL (OEL TWA) 700 mg/m³ Denmark - Occupational Exposure Limits OEL TWA 540 mg/m³ 150 ppm OEL STEL 0EL STEL 1468 mg/m³ 400 ppm Estonia - Occupational Exposure Limits OEL STEL 0E TWA 540 mg/m³ 400 ppm Estonia - Occupational Exposure Limits OEL TWA 0 ppm Estonia - Occupational Exposure Limits 0 ppm Estonia - Occupational Exposure Limits Occupational Ex	Bulgaria - Occupational Exposure Limits	<u>'</u>	
QEL STEL 1468 mg/m³ 400 ppm Croatia - Occupational Exposure Limits GVI (OEL TWA) 734 mg/m³ 200 ppm KGVI (OEL STEL) 1468 mg/m³ 0 pm Cyprus - Occupational Exposure Limits CPL TWA 734 mg/m³ 200 ppm CPL STEL 1468 mg/m³ 400 ppm Czech Republic - Occupational Exposure Limits PEL (OEL TWA) 700 mg/m³ Denmark - Occupational Exposure Limits DEL TWA 540 mg/m³ 150 ppm OEL STEL 1468 mg/m³ 168 mg/m³ 400 ppm 400 ppm Estonia - Occupational Exposure Limits DEL TWA 500 mg/m³ 500 mg/m³ 150 ppm 500 mg/m³ 150 ppm 500 mg/m³	OEL TWA	734 mg/m³	
A00 ppm		200 ppm	
Croatia - Occupational Exposure Limits GVI (OEL TWA) 734 mg/m³ / 200 ppm KGVI (OEL STEL) 1468 mg/m³ / 400 ppm Cyprus - Occupational Exposure Limits OEL TWA 734 mg/m³ / 200 ppm OEL STEL 1468 mg/m³ / 400 ppm Czech Republic - Occupational Exposure Limits 700 mg/m³ PEL (OEL TWA) 700 mg/m³ Denmark - Occupational Exposure Limits 540 mg/m³ / 150 ppm OEL STEL 1468 mg/m³ / 400 ppm Estonia - Occupational Exposure Limits 500 mg/m³ / 150 ppm DEL TWA 500 mg/m³ / 150 ppm	OEL STEL	1468 mg/m³	
T34 mg/m³ 200 ppm 20		400 ppm	
KGVI (OEL STEL) 200 ppm Cyprus - Occupational Exposure Limits OEL TWA 734 mg/m³ 200 ppm OEL STEL 1468 mg/m³ 400 ppm Czech Republic - Occupational Exposure Limits PEL (OEL TWA) 700 mg/m³ Denmark - Occupational Exposure Limits OEL TWA 540 mg/m³ 150 ppm OEL STEL 1468 mg/m³ 400 ppm Estonia - Occupational Exposure Limits OEL TWA 500 mg/m³ 150 ppm	Croatia - Occupational Exposure Limits	<u>'</u>	
KGVI (OEL STEL) 1468 mg/m³ Cyprus - Occupational Exposure Limits OEL TWA 734 mg/m³ 200 ppm 200 ppm OEL STEL 1468 mg/m³ 400 ppm 400 ppm Czech Republic - Occupational Exposure Limits PEL (OEL TWA) 700 mg/m³ Denmark - Occupational Exposure Limits OEL TWA 540 mg/m³ 150 ppm OEL STEL 1468 mg/m³ 400 ppm Estonia - Occupational Exposure Limits OEL TWA 500 mg/m³ 150 ppm	GVI (OEL TWA)	734 mg/m³	
Cyprus - Occupational Exposure Limits OEL TWA 734 mg/m³ 200 ppm OEL STEL 1468 mg/m³ 400 ppm Czech Republic - Occupational Exposure Limits PEL (OEL TWA) 700 mg/m³ Denmark - Occupational Exposure Limits OEL TWA 540 mg/m³ 150 ppm OEL STEL 1468 mg/m³ 400 ppm Estonia - Occupational Exposure Limits OEL TWA 5500 mg/m³ 150 ppm		200 ppm	
Cyprus - Occupational Exposure Limits OEL TWA 734 mg/m³ 200 ppm 1468 mg/m³ 400 ppm 400 ppm Czech Republic - Occupational Exposure Limits PEL (OEL TWA) 700 mg/m³ Denmark - Occupational Exposure Limits OEL TWA 540 mg/m³ 150 ppm 00 ppm Estonia - Occupational Exposure Limits OEL TWA 500 mg/m³ 150 ppm 150 ppm	KGVI (OEL STEL)	1468 mg/m³	
OEL TWA 734 mg/m³ 200 ppm 200 ppm OEL STEL 1468 mg/m³ 400 ppm 400 ppm Czech Republic - Occupational Exposure Limits PEL (OEL TWA) 700 mg/m³ Denmark - Occupational Exposure Limits OEL TWA 540 mg/m³ 150 ppm OEL STEL 1468 mg/m³ 400 ppm Estonia - Occupational Exposure Limits OEL TWA 500 mg/m³ 150 ppm		400 ppm	
200 ppm 200	Cyprus - Occupational Exposure Limits		
OEL STEL 1468 mg/m³ 400 ppm Czech Republic - Occupational Exposure Limits PEL (OEL TWA) 700 mg/m³ Denmark - Occupational Exposure Limits OEL TWA 540 mg/m³ 150 ppm 150 ppm Estonia - Occupational Exposure Limits OEL TWA 500 mg/m³ 150 ppm	OEL TWA	734 mg/m³	
A00 ppm		200 ppm	
Czech Republic - Occupational Exposure Limits PEL (OEL TWA) 700 mg/m³ Denmark - Occupational Exposure Limits OEL TWA 540 mg/m³ 150 ppm OEL STEL 1468 mg/m³ 400 ppm Estonia - Occupational Exposure Limits OEL TWA 500 mg/m³ 150 ppm	OEL STEL	1468 mg/m³	
PEL (OEL TWA) 700 mg/m³ Denmark - Occupational Exposure Limits OEL TWA 540 mg/m³ 150 ppm OEL STEL 1468 mg/m³ 400 ppm Estonia - Occupational Exposure Limits OEL TWA 500 mg/m³ 150 ppm		400 ppm	
Denmark - Occupational Exposure Limits OEL TWA 540 mg/m³ 150 ppm 1468 mg/m³ 400 ppm 400 ppm Estonia - Occupational Exposure Limits OEL TWA 500 mg/m³ 150 ppm	Czech Republic - Occupational Exposure Limit	ts	
OEL TWA 540 mg/m³ 150 ppm OEL STEL 1468 mg/m³ 400 ppm Estonia - Occupational Exposure Limits OEL TWA 500 mg/m³ 150 ppm	PEL (OEL TWA)	700 mg/m³	
150 ppm	Denmark - Occupational Exposure Limits		
OEL STEL 1468 mg/m³ 400 ppm Estonia - Occupational Exposure Limits OEL TWA 500 mg/m³ 150 ppm	OEL TWA	540 mg/m³	
Estonia - Occupational Exposure Limits OEL TWA 500 mg/m³ 150 ppm		150 ppm	
Estonia - Occupational Exposure Limits OEL TWA 500 mg/m³ 150 ppm	OEL STEL	1468 mg/m³	
OEL TWA 500 mg/m³ 150 ppm		400 ppm	
150 ppm	Estonia - Occupational Exposure Limits		
	OEL TWA	500 mg/m³	
OEL STEL 1100 mg/m³		150 ppm	
	OEL STEL	1100 mg/m³	
300 ppm		300 ppm	
Finland - Occupational Exposure Limits	Finland - Occupational Exposure Limits	•	
HTP (OEL TWA) 730 mg/m³	HTP (OEL TWA)	730 mg/m³	
200 ppm		200 ppm	
HTP (OEL STEL) 1470 mg/m³	HTP (OEL STEL)	1470 mg/m³	
400 ppm		400 ppm	

Safety Data Sheet

ethyl acetate (141-78-6)		
France - Occupational Exposure Limits		
VME (OEL TWA)	734 mg/m³	
	200 ppm	
VLE (OEL C/STEL)	1468 mg/m³ (restrictive limit)	
	400 ppm (restrictive limit)	
Germany - Occupational Exposure Limits (TRGS	5 900)	
AGW (OEL TWA)	730 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
	200 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Gibraltar - Occupational Exposure Limits		
OEL TWA	200 mg/m³	
	734 ppm	
OEL STEL	400 mg/m³	
	1468 ppm	
Greece - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
	200 ppm	
OEL STEL	1468 mg/m³	
	400 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	734 mg/m³	
CK (OEL STEL)	1468 mg/m³	
OEL chemical category	Sensitizer	
Ireland - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
	200 ppm	
OEL STEL	1468 mg/m³	
	400 ppm	
Italy - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
	200 ppm	
OEL STEL	1468 mg/m³	
	400 ppm	
Latvia - Occupational Exposure Limits		
OEL TWA	200 mg/m³	
	54 ppm	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA) 500 mg/m³		
	150 ppm	
	<u> </u>	

Safety Data Sheet

ethyl acetate (141-78-6)		
NRV (OEL C)	1100 mg/m³	
	300 ppm	
Luxembourg - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
	200 ppm	
OEL STEL	1468 mg/m³	
	400 ppm	
Malta - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
	200 ppm	
OEL STEL	1468 mg/m³	
	400 ppm	
Netherlands - Occupational Exposure Limits		
TGG-8u (OEL TWA)	734 mg/m³	
	200 ppm	
TGG-15min (OEL STEL)	1468 mg/m³	
	400 ppm	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	734 mg/m³	
NDSCh (OEL STEL)	1468 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	734 mg/m³ (indicative limit value)	
	200 ppm (indicative limit value)	
OEL STEL	1468 mg/m³ (indicative limit value)	
	400 ppm (indicative limit value)	
Romania - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
	200 ppm	
OEL STEL	1468 mg/m³	
	400 ppm	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA)	734 mg/m³	
	200 ppm	
NPHV (OEL C)	1100 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
	200 ppm	
OEL STEL	1468 mg/m³	
	400 ppm	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethyl acetate (141-78-6)		
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	734 mg/m³	
	200 ppm	
VLA-EC (OEL STEL)	1468 mg/m³	
	400 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	550 mg/m³	
	150 ppm	
KTV (OEL STEL)	1100 mg/m³	
	300 ppm	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	734 mg/m³	
	200 ppm	
WEL STEL (OEL STEL)	1468 mg/m³	
	400 ppm	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA)	734 mg/m³	
	200 ppm	
Korttidsverdi (OEL STEL)	1468 mg/m³ (value from the regulation)	
	400 ppm (value from the regulation)	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	730 mg/m³	
	200 ppm	
KZGW (OEL STEL)	1460 mg/m³	
	400 ppm	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	400 ppm	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):







8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : light yellow. amber. Conforms to standard.

Odour : characteristic. Odour threshold : Not available Melting point : Not applicable : Not available Freezing point : Not available Boiling point : Not available Flammability : Not available Lower explosion limit Upper explosion limit : Not available

Flash point : 92 °C
Auto-ignition temperature : Not available

: Not available Decomposition temperature : Not available рΗ : Not available Viscosity, kinematic : Not available Solubility Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : Not available Vapour pressure at 50°C : Not available Density : Not available Relative density : Not available Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

BIRTHDAY CAKE CC-16438	
ATE CLP (oral)	1886.752 mg/kg bodyweight
Vertenex (32210-23-4)	
LD50 oral rat	5 g/kg (Source: NLM_CIP)
LD50 oral	3370 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)
benzyl alcohol (100-51-6)	
LD50 oral rat	1230 mg/kg (Source: NLM_CIP)
LD50 oral	1620 mg/kg bodyweight
LD50 dermal	2500 mg/kg bodyweight
Bis(2-ethylhexyl) adipate (103-23-1)	
LD50 oral rat	5600 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	8410 mg/kg (Source: NLM_CIP)
LC50 Inhalation - Rat	> 5.7 mg/l/4h
Hexyl cinnamic aldehyde (101-86-0)	
LD50 oral rat	3100 mg/kg (Source: NLM_CIP)
LD50 oral	3100 mg/kg bodyweight

1/2/2024 (Issue date) EN (English) 12/20

Safety Data Sheet

Hexyl cinnamic aldehyde (101-86-0)	
LD50 dermal rabbit	> 3000 mg/kg (Source: EPA_HPV)
LC50 Inhalation - Rat	> 5 mg/l/4h
benzyl benzoate (120-51-4)	
LD50 oral rat	500 mg/kg (Source: NLM_CIP)
LD50 oral	1160 mg/kg bodyweight
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)
COUMARIN (91-64-5)	
LD50 oral rat	> 5000 mg/kg (Source: JAPAN_GHS)
LD50 oral	290 mg/kg bodyweight
LD50 dermal rat	293 mg/kg (Source: ECHA_API)
Anisic aldehyde (123-11-5)	
LD50 oral rat	> 2000 mg/kg (Source: OECD_SIDS)
LD50 oral	3210 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: EPA_HPV)
LC50 Inhalation - Rat	> 0.32 mg/l (Exposure time: 7 h Source: OECD_SIDS)
Vanillin (121-33-5)	
LD50 dermal rabbit	> 5010 mg/kg (Source: OECD_SIDS)
LD50 dermal	2600 mg/kg bodyweight
Linalool (78-70-6)	
LD50 oral	2790 mg/kg bodyweight
Ethyl maltol (4940-11-8)	
LD50 oral rat	1150 mg/kg (Source: NLM_CIP)
LD50 oral	1200 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)
Acetyl Propionyl (600-14-6)	
LD50 oral rat	3 g/kg (Source: NLM_CIP)
LD50 oral	3000 mg/kg bodyweight
LD50 dermal rabbit	> 2000 mg/kg (Source: NIOSH)
LD50 dermal	2500 mg/kg bodyweight
Heliotropine (120-57-0)	
LD50 oral rat	2700 mg/kg (Source: NLM_CIP)
LD50 oral	2700 mg/kg bodyweight
LD50 dermal rat	> 5000 mg/kg (Source: ECHA_API)
ethyl acetate (141-78-6)	
LD50 oral rat	5620 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 18000 mg/kg (Source: JAPAN_GHS)
LC50 Inhalation - Rat [ppm]	4000 ppm/4h

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1,2-Cyclopentanedione, 3-methyl- (7	(65-70-8)
LD50 oral	1067 mg/kg bodyweight
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Bis(2-ethylhexyl) adipate (103-23-1)	
IARC group	3 - Not classifiable
COUMARIN (91-64-5)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Acetyl Propionyl (600-14-6)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
benzyl benzoate (120-51-4)	
Viscosity, kinematic	7.456 mm ² /s
Heliotropine (120-57-0)	
Viscosity, kinematic	Not applicable
44.0 Information on other bounds	

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Harmful to aquatic life with long lasting effects.

(chronic)

(CHIOTIC)	
Vertenex (32210-23-4)	
LC50 - Fish [1]	8.6 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static] Source: ECHA)
benzyl alcohol (100-51-6)	
LC50 - Fish [1]	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
LC50 - Fish [2]	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
EC50 - Crustacea [1]	23 mg/l (Exposure time: 48 h - Species: water flea)
Bis(2-ethylhexyl) adipate (103-23-1)	
LC50 - Fish [1]	0.48 – 0.85 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Bis(2-ethylhexyl) adipate (103-23-1)	
LC50 - Fish [2]	0.48 – 0.85 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
EC50 - Crustacea [1]	> 1.6 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	> 500 mg/l (Species: Desmodesmus subspicatus)
benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
NOEC (chronic)	0.168 mg/l
Vanillin (121-33-5)	
LC50 - Fish [1]	53 – 61.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
NOEC (acute)	10000 mg/kg (Exposure time: 42 Days - Species: Eisenia foetida [soil dry weight])
Linalool (78-70-6)	
EC50 96h - Algae [1]	88.3 mg/l (Species: Desmodesmus subspicatus)
Ethyl maltol (4940-11-8)	
LC50 - Fish [1]	> 85 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: ECHA)
Heliotropine (120-57-0)	
LC50 - Fish [1]	2.5 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static] Source: ECHA)
ethyl acetate (141-78-6)	
LC50 - Fish [1]	220 – 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: IUCLID)
EC50 - Crustacea [1]	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

12.2. Persistence and degradability

BIRTHDAY CAKE CC-16438				
Persistence and degradability	Rapidly degradable			
Vertenex (32210-23-4)				
Persistence and degradability	Rapidly degradable			
benzyl alcohol (100-51-6)				
Persistence and degradability	Rapidly degradable			
Bis(2-ethylhexyl) adipate (103-23-1)				
Persistence and degradability	Rapidly degradable			
Hexyl cinnamic aldehyde (101-86-0)				
Persistence and degradability	Rapidly degradable			
benzyl benzoate (120-51-4)				
Persistence and degradability	May cause long-term adverse effects in the environment.			

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

COUMARIN (91-64-5)	
Persistence and degradability	Rapidly degradable
Anisic aldehyde (123-11-5)	
Persistence and degradability	Rapidly degradable
Vanillin (121-33-5)	
Persistence and degradability	Rapidly degradable
Linalool (78-70-6)	
Persistence and degradability	Rapidly degradable
Ethyl maltol (4940-11-8)	
Persistence and degradability	Rapidly degradable
Acetyl Propionyl (600-14-6)	
Persistence and degradability	Rapidly degradable
Heliotropine (120-57-0)	
Persistence and degradability	Rapidly degradable
ethyl acetate (141-78-6)	
Persistence and degradability	Rapidly degradable
1,2-Cyclopentanedione, 3-methyl- (765-70-8)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

Vertenex (32210-23-4)				
Partition coefficient n-octanol/water (Log Pow)	4.8 (at 25 °C)			
benzyl alcohol (100-51-6)				
Partition coefficient n-octanol/water (Log Pow)	1.05			
Bis(2-ethylhexyl) adipate (103-23-1)				
BCF - Fish [1]	(27 dimensionless)			
Partition coefficient n-octanol/water (Log Pow)	8.94 (at 25 °C)			
benzyl benzoate (120-51-4)				
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)			
Bioaccumulative potential	Not established.			
Anisic aldehyde (123-11-5)				
Partition coefficient n-octanol/water (Log Pow)	1.56 (at 25 °C (at pH >7.9-<8.25)			
Vanillin (121-33-5)				
Partition coefficient n-octanol/water (Log Pow)	1.23 (at 22 °C)			
Ethyl maltol (4940-11-8)				
Partition coefficient n-octanol/water (Log Pow)	2.9 (at 25 °C)			

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Heliotropine (120-57-0)		
Partition coefficient n-octanol/water (Log Pow)	1.2 (at 35 °C)	
ethyl acetate (141-78-6)		
BCF - Fish [1]	(30 dimensionless)	
Partition coefficient n-octanol/water (Log Pow)	0.73 (at 20 °C (at pH 7)	

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods HP Code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : HP4 "Irritant skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
4.1. UN number or ID n	umber			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
4.2. UN proper shippin	g name			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
4.3. Transport hazard o	class(es)			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
4.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
4.5. Environmental haz	zards			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)				
Reference code	Applicable on	Entry title or description		
3(a)	Acetyl Propionyl; ethyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F		
3(b)	BIRTHDAY CAKE CC-16438; Vertenex; benzyl alcohol; Hexyl cinnamic aldehyde; benzyl benzoate; Linalool; Acetyl Propionyl; ethyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10		
3(c)	BIRTHDAY CAKE CC-16438; Hexyl cinnamic aldehyde; benzyl benzoate; Anisic aldehyde	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1		
40.	Acetyl Propionyl; ethyl acetate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.		

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.		Category, Subcategory	Threshold	Annex
Piperonal		120-57-0	2932 93 00	Category 1		Annex I

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic

environment

SZW-lijst van kankerverwekkende stoffen : None of the components are listed SZW-lijst van mutagene stoffen : None of the components are listed SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed : None of the components are listed

SZW-lijst van reprotoxische stoffen -

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen - Ontwikkeling

: None of the components are listed

Denmark

Class for fire hazard : Class III-1 Store unit : 50 liter

Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines

for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

1/2/2024 (Issue date) EN (English) 19/20

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 16: Other information

Full text of H- and EUH	H-statements:
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
	i .

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.