Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 9/25/2024



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : VANILLA BEAN CC-16439
UFI : 3QQN-5C4R-P00P-TEQJ

Product code : CC-16439

Type of product : Perfumes, fragrances
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use,Industrial use

Industrial/Professional use spec : Industrial

For professional use only : Perfumes, fragrances

Use of the substance/mixture : Perfumes, fragran Function or use category : Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Candle Craft Weiherwiese 10 65510 Idstein - Germany T 49-6126-9363 -0

info@candlecraft.de - www.candlecraft.de

1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China: +400-120-0751; Mexico: +01-800-099-0731;

Brazil: +0-800-591-6042; India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H302
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment – Acute Hazard,

Category 1

Hazardous to the aquatic environment – Chronic Hazard, H411

Category 2

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS07

GHS09

Signal word (CLP)

: Warning

Contains

: benzyl benzoate; benzyl alcohol; Heliotropine

Hazard statements (CLP)

: H302 - Harmful if swallowed.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.

H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371- 33	32.8 – 65.6	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
benzyl alcohol substance with national workplace exposure limit(s) (BG, CZ, DE, FI, LT, LV, PL, SI, CH)	CAS-No.: 100-51-6 EC-No.: 202-859-9 EC Index-No.: 603-057-00-5 REACH-no: 01-2119492630- 38	5.3 – 10.5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Ethyl vanillin	CAS-No.: 121-32-4 EC-No.: 204-464-7 REACH-no: 01-211958961-24	5 – 10	Eye Irrit. 2, H319
Vanillin	CAS-No.: 121-33-5 EC-No.: 204-465-2 REACH-no: 01-2119516040- 60	2 – 4	Eye Irrit. 2, H319

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Anisic aldehyde	CAS-No.: 123-11-5 EC-No.: 204-602-6 REACH-no: 01-2119977101- 43	1.3 – 2.5	Aquatic Chronic 3, H412
Heliotropine	CAS-No.: 120-57-0 EC-No.: 204-409-7 REACH-no: 01-2119983608- 21	0.6 – 1.25	Skin Sens. 1B, H317
Ethyl acetoacetate substance with national workplace exposure limit(s) (RO)	CAS-No.: 141-97-9 EC-No.: 205-516-1	0.3 – 0.5	Not classified
benzaldehyde substance with national workplace exposure limit(s) (BG, FI, HU, LT, LV, PL)	CAS-No.: 100-52-7 EC-No.: 202-860-4 EC Index-No.: 605-012-00-5 REACH-no: 01-2119455540-	0.1 – 0.2	Acute Tox. 4 (Oral), H302
butyric acid substance with national workplace exposure limit(s) (BG, LT, LV, RO)	CAS-No.: 107-92-6 EC-No.: 203-532-3 EC Index-No.: 607-135-00-X	0.1 – 0.1	Skin Corr. 1B, H314

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. D	escription)	of first aid	measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Allow affected person to

breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water,

followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated

clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Obtain emergency medical attention. Rinse mouth. Call a poison

center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

9/25/2024 (Issue date) EN (English) 3/17

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions

: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting

: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures

: Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure

controls/personal protection". : Ventilate area.

Emergency procedures

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment

: Collect spillage.

Methods for cleaning up

: Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information

: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures

: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep only in the original container in a cool, well ventilated place away from : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Store in a well-ventilated place. Keep cool.

Incompatible products Incompatible materials

: Sources of ignition. Direct sunlight.

: Strong bases. Strong acids.

Storage temperature

: Store in a well-ventilated place. Store away from heat. Storage area

Special rules on packaging : Store in a closed container. Packaging materials : Do not store in corrodable metal.

9/25/2024 (Issue date) EN (English) 4/17

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Germany

Storage class (LGK, TRGS 510)

Joint storage table

: LGK 12 - Non-combustible liquids

:	LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
	LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
	LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
	LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
	LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for

Joint storage with restrictions permitted for

Joint storage permitted for

: LGK 1, LGK 6.2, LGK 7

: LGK 4.1A, LGK 4.3, LGK 5.1C

: LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13

Switzerland

Storage class (LK) : LK 10/12 - Liquids

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

benzyl alcohol (100-51-6)		
Bulgaria - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	40 mg/m³	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	45 mg/m³	
	10 ppm	
Germany - Occupational Exposure Limits (TRGS 900)		
AGW (OEL TWA)	22 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Chemical category	Skin notation	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
OEL chemical category	Skin notation	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	240 mg/m³	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

benzyl alcohol (100-51-6)		
Slovenia - Occupational Exposure Limits		
OEL TWA	22 mg/m³	
	5 ppm	
OEL STEL	44 mg/m³	
	10 ppm	
OEL chemical category	Potential for cutaneous absorption	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	22 mg/m³ (aerosol, vapour)	
	5 ppm (aerosol, vapour)	
OEL chemical category	Skin notation	
Ethyl acetoacetate (141-97-9)		
Romania - Occupational Exposure Limits		
OEL TWA	100 mg/m³	
	19 ppm	
OEL STEL	200 mg/m³	
	38 ppm	
benzaldehyde (100-52-7)		
Bulgaria - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	4.4 mg/m³	
	1 ppm	
HTP (OEL C)	17.4 mg/m³	
	4 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³	
CK (OEL STEL)	10 mg/m³	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	10 mg/m³	
NDSCh (OEL STEL)	40 mg/m³	
butyric acid (107-92-6)		
Bulgaria - Occupational Exposure Limits		
OEL TWA	10 mg/m³	
	<u> </u>	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

butyric acid (107-92-6)		
Latvia - Occupational Exposure Limits		
OEL TWA	10 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	10 mg/m³	
Romania - Occupational Exposure Limits		
OEL TWA	15 mg/m³	
	4 ppm	
OEL STEL	30 mg/m³	
	8 ppm	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):





8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Conforms to standard. : characteristic. Odour : Not available Odour threshold : Not applicable Melting point : Not available Freezing point : Not available **Boiling point** : Not applicable Flammability Lower explosion limit : Not available Upper explosion limit : Not available Flash point : > 93 °C

Auto-ignition temperature : Not available
Decomposition temperature : Not available
pH : Not available
Viscosity, kinematic : Not available
Solubility : Not available
Partition coefficient n-octanol/water (Log Kow) : Not available

Vapour pressure : 0.005477216 mm Hg (calculated value)

Vapour pressure at 50°C : Not available
Density : Not available
Relative density : Not available
Relative vapour density at 20°C : Not available
Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 1.9 % (calculated value)(CARB VOC) (%w/w)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (inhalation) :	Not classified
VANILLA BEAN CC-16439	
ATE CLP (oral)	657.03 mg/kg bodyweight
benzyl benzoate (120-51-4)	
LD50 oral rat	> 2000 mg/kg (Source: ECHA_API)
LD50 oral	1160 mg/kg bodyweight
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)
benzyl alcohol (100-51-6)	
LD50 oral rat	1230 mg/kg (Source: NLM_CIP)
LD50 oral	1570 mg/kg
Ethyl vanillin (121-32-4)	
LD50 oral rat	1590 mg/kg (Source: NLM_CIP)
LD50 oral	3000 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)
Vanillin (121-33-5)	
LD50 dermal rabbit	> 5010 mg/kg (Source: OECD_SIDS)
LD50 dermal	2600 mg/kg bodyweight
Anisic aldehyde (123-11-5)	
LD50 oral rat	3210 mg/kg (Source: ECHA)
LD50 oral	3210 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: EPA_HPV)
LC50 Inhalation - Rat	> 0.32 mg/l (Exposure time: 7 h Source: ECHA)
Heliotropine (120-57-0)	
LD50 oral rat	2700 mg/kg (Source: NLM_CIP)
LD50 oral	2700 mg/kg bodyweight
LD50 dermal rat	> 5000 mg/kg (Source: ECHA_API)
Ethyl acetoacetate (141-97-9)	
LD50 oral rat	3980 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 5000 mg/kg (Source: NLM_CIP)
benzaldehyde (100-52-7)	
LD50 oral rat	1292 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	> 1250 mg/kg (Source: JAPAN_GHS)

9/25/2024 (Issue date) EN (English) 9/17

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

benzaldehyde (100-52-7)		
LC50 Inhalation - Rat	< 5 mg/l/4h	
butyric acid (107-92-6)		
LD50 oral rat	2 g/kg (Source: NLM_CIP)	
LD50 oral	1630 mg/kg bodyweight	
LD50 dermal rabbit	530 mg/kg (Source: NLM_HSDB)	
Skin corrosion/irritation : 0	Causes skin irritation.	
Serious eye damage/irritation : 0	Causes serious eye irritation.	
Respiratory or skin sensitisation : 1	May cause an allergic skin reaction.	
Germ cell mutagenicity :	Not classified	
Carcinogenicity :	Not classified	
Reproductive toxicity :	Not classified	
STOT-single exposure :	Not classified	
STOT-repeated exposure :	Not classified	
Aspiration hazard :	Not classified	
benzyl benzoate (120-51-4)		
Viscosity, kinematic	7.456 mm²/s	
Heliotropine (120-57-0)		
Viscosity, kinematic	Not applicable	

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Very toxic to aquatic life.

acute)

Hazardous to the aquatic environment, long-term : Toxic to aquatic life with long lasting effects.

(chronic)

hronic)		
benzyl benzoate (120-51-4)		
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)	
NOEC (chronic)	0.168 mg/l	
benzyl alcohol (100-51-6)		
LC50 - Fish [1]	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)	
LC50 - Fish [2]	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)	
EC50 - Crustacea [1]	23 mg/l (Exposure time: 48 h - Species: water flea)	
Ethyl vanillin (121-32-4)		
LC50 - Fish [1]	81.4 – 94.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Vanillin (121-33-5)		
LC50 - Fish [1]	53 – 61.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
LC50 - Fish [2]	88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)	
NOEC (acute)	10000 mg/kg (Exposure time: 42 Days - Species: Eisenia foetida [soil dry weight])	
Heliotropine (120-57-0)		
LC50 - Fish [1]	2.5 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static] Source: ECHA)	
Ethyl acetoacetate (141-97-9)		
LC50 - Fish [1]	298 mg/l (Exposure time: 96 h - Species: Pimephales promelas Source: IUCLID)	
LC50 - Fish [2]	290 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: IUCLID)	
EC50 - Crustacea [1]	646 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 72h - Algae [1]	> 500 mg/l (Species: Desmodesmus subspicatus)	
benzaldehyde (100-52-7)		
LC50 - Fish [1]	10.6 – 11.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: EPA)	
LC50 - Fish [2]	12.69 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: IUCLID)	
butyric acid (107-92-6)		
EC50 72h - Algae [1]	46.7 mg/l (Species: Desmodesmus subspicatus)	

12.2. Persistence and degradability

VANILLA BEAN CC-16439		
Persistence and degradability	Not established.	
benzyl benzoate (120-51-4)		
Persistence and degradability	May cause long-term adverse effects in the environment.	
benzyl alcohol (100-51-6)		
Persistence and degradability	Rapidly degradable	
Ethyl vanillin (121-32-4)		
Persistence and degradability	Rapidly degradable	
Vanillin (121-33-5)		
Persistence and degradability	Rapidly degradable	
Anisic aldehyde (123-11-5)		
Persistence and degradability	Rapidly degradable	
Heliotropine (120-57-0)		
Persistence and degradability	Rapidly degradable	
Ethyl acetoacetate (141-97-9)		
Persistence and degradability	Rapidly degradable	
benzaldehyde (100-52-7)		
Persistence and degradability	Rapidly degradable	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

butyric acid (107-92-6)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

VANILLA BEAN CC-16439			
Bioaccumulative potential	Not established.		
benzyl benzoate (120-51-4)			
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)		
Bioaccumulative potential	Not established.		
benzyl alcohol (100-51-6)			
Partition coefficient n-octanol/water (Log Pow)	1.05		
Ethyl vanillin (121-32-4)			
Partition coefficient n-octanol/water (Log Pow)	1.61 (at 25 °C)		
Vanillin (121-33-5)			
Partition coefficient n-octanol/water (Log Pow)	1.23 (at 22 °C)		
Anisic aldehyde (123-11-5)			
Partition coefficient n-octanol/water (Log Pow)	1.56 (at 25 °C (at pH >7.9-<8.25)		
Heliotropine (120-57-0)			
Partition coefficient n-octanol/water (Log Pow)	1.2 (at 35 °C)		
Ethyl acetoacetate (141-97-9)			
Partition coefficient n-octanol/water (Log Pow)	0.8 (at 20 °C)		
benzaldehyde (100-52-7)			
BCF - Fish [1]	(no significant bioaccumulation)		
Partition coefficient n-octanol/water (Log Pow)	1.4 (at 25 °C)		
butyric acid (107-92-6)	butyric acid (107-92-6)		
Partition coefficient n-octanol/water (Log Pow)	1.1 (at 25 °C (at pH 3)		

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information

: Avoid release to the environment.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

Product/Packaging disposal recommendations

Ecological information

HP Code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Dispose in a safe manner in accordance with local/national regulations.
- : Avoid release to the environment.
- : HP6 "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.

HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID		
14.1. UN number or ID number						
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082		
14.2. UN proper shipping name						
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	Environmentally hazardous substance, liquid, n.o.s. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)		
Transport document descr	iption					
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Benzyl Benzoate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III		
14.3. Transport hazard o	class(es)					
9	9	9	9	9		
***************************************			***************************************	***************************************		
14.4. Packing group						
III	III	III	III	III		
14.5. Environmental haz	ards					
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes		
No supplementary information	n available					

14.6. Special precautions for user

Overland transport

Classification code (ADR) : M6

9/25/2024 (Issue date) EN (English) 13/17

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Special provisions (ADR) : 274, 335, 375, 601

Limited quantities (ADR) : 5I Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4

Portable tank and bulk container special provisions : TP1, TP29

(ADR)

Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading : CV13

and handling (ADR)

Hazard identification number (Kemler No.) : 90

Orange plates :

90 3082

Tunnel restriction code (ADR) : -

EAC code : •3Z

Transport by sea

Special provisions (IMDG) : 274, 335, 969 Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1 Packing instructions (IMDG) : LP01, P001 Special packing provisions (IMDG) : PP1 IBC packing instructions (IMDG) : IBC03 Tank instructions (IMDG) : T4 Tank special provisions (IMDG) : TP1, TP29

EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-F
Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L

Special provisions (IATA) : A97, A158, A197, A215

ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M6

Special provisions (ADN) : 274, 335, 375, 601

 Limited quantities (ADN)
 : 5 L

 Excepted quantities (ADN)
 : E1

 Carriage permitted (ADN)
 : T

 Equipment required (ADN)
 : PP

 Number of blue cones/lights (ADN)
 : 0

Rail transport

Classification code (RID) : M6

Special provisions (RID) : 274, 335, 375, 601

Limited quantities (RID) : 5L Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions : TP1, TP29

(RID)

Tank codes for RID tanks (RID) : LGBV
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12

Special provisions for carriage - Loading, unloading : CW13, CW31

and handling (RID)

Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	VANILLA BEAN CC CC-16439 ; benzyl benzoate ; benzyl alcohol ; benzaldehyde ; butyric acid	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	VANILLA BEAN CC CC-16439 ; benzyl benzoate ; Anisic aldehyde	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 1.9 % (calculated value)(CARB VOC) (%w/w)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.		Category, Subcategory	Threshold	Annex
Piperonal		120-57-0	2932 93 00	Category 1		Annex I

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Hazardous Incident Ordinance (12. BlmSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(1) - highly toxic for aquatic organisms, may have longterm hazardous effects in aquatic

environment

SZW-lijst van kankerverwekkende stoffen : None of the components are listed SZW-lijst van mutagene stoffen : None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen -: None of the components are listed Vruchtbaarheid

SZW-lijst van reprotoxische stoffen - Ontwikkeling : None of the components are listed

Denmark

: Emergency management guidelines for the storage of flammable liquids must be followed Classification remarks

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Other information : None.

Full text of H- and EUH-statements:		
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
H302	Harmful if swallowed.	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H400	Very toxic to aquatic life.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
Skin Sens. 1B	Skin sensitisation, category 1B	

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.